KING TONY

• Service • Assurance • Responsibility • Satisfaction

2012

The brand you trust for life

KING TONY

2010
TAIWAN SUPERIOR BRANDS
2011
NATIONAL BRAND YUSHAN AWARD

For over 25 years, KING TONY has been specializing in professional tools and serving as the “Tool expert with the best service". In addition to creating effective marketing strategies with the concept of “customer first” in mind, KING TONY has been focusing on international brand marketing, while developing other potential markets and setting up branch offices in France, Germany, Mexico, America, and China. With sales distribution channels in over 110 countries around the world, KING TONY has successfully established its own brand wordlwide. In the future, KING TONY continues to commit itself in enhancing its R&D and strict quality inspection in order to provide end-users with superior quality tools to boost their working efficiency and productivity.

Create to improve,
protect where we live,
balance environment and human.

ISO 14001

In 1976, amidst a lack of capital and technology in Taiwan, Mr. Charles Lai & Mr. Tony Lin founded a hot forge factory specializing in making hand tools for the DIY market. Eight years later, many other companies had followed their lead and although the market grew quickly, quality suffered. With pricing, costs and quality nearing a state of chaos it became clear to King Tony's founders that they needed to seek a new direction.

Mr. Lai & Mr. Lin found their new direction; making professional quality hand tools built to compete with the best in the world. They set their standards high and in the years since, have consistently exceeded the requirements of the world's toughest standards. King Tony tools don't just meet the DIN (German) standard and the ANSI (U.S.A.) standard, they routinely exceed them. In fact, we test every torque make to a standard 30% higher than that prescribed by DIN and our pneumatic impact tools to a 50% higher standard. That's true commitment to quality!

To further underscore our determination to compete with the best in the world we have achieved certification with ISO on three separate standards. First, in January 1998, ISO 9002, followed by ISO 9001 and more recently we have qualified for the environmental safety standard, ISO 14001. We believe that is our responsibility to the world and we will always dedicate to reduce the harm to the earth during our manufacturing process in the future.

You might sense that King Tony Tools is about much more than a world-class tool. The ideals of King Tony's management are fulfilled daily by our hundreds of employee's at our branches and offices around the world. You will find King Tony Tools and its branches in: France, Germany, Spain, Mexico, U.S.A, China. Each of our local branch offices is tasked with insuring that you, our customer, are happy not just with our quality but with the experience of being a King Tony customer. That is how King Tony became known as; "The brand you trust for life."

BRANCHES :

- **France** :
  3 Rue des imprimeurs, ZI République Nord,
  86000 POITIERS, France
- **Germany** :
  Wilhelmstrasse 11 D-69115 Heidelberg
- **Spain** :
  Paseo de la Castellana, 241-4°B 28046 Madrid Espana
- **U.S.A.** :
  2432 Peck Rd , City of industry CA 90601, U.S.A.
- **Mexico** :
  Av San Jose No. 15-A.Col. , Zona Industiral La Presa,
  C.P. 54187 Tlalnepantla, Edo. De Mexico
- **China** :
  No. 3 Building.No.285 Jingmao Rd.,
  Industrial Park of Suzhou, Suzhou, Jiangsu, China

KING TONY®
www.kingtony.com

The Brand You Trust for Life

sales department e-mail:sales@kingtony.com.tw
customer service e-mail:service@kingtony.com.tw
Tel:886-4-2335-3567 Fax:886-4-2335-3642

Service Assurance Responsibility Satisfaction

Intellectual Property

New Registered Trade Mark

Please recognize King Tony's official registered trademark.

Trademark Worldwide Registration

Algeria Australia Austria Belarus Belgium Bolivia Brazil
Bulgaria Chile China Cyprus Czech Denmark Dominicana
Egypt Estonia Ethiopia Finland France Germany Ghana
Greece Guatemala Hungary Indonesia Iran Ireland Israel
Italy Japan Kazakhstan Laos Latvia Lebanon Libya
Lithuania Luxembourg Malta Mexico Morocco Malaysia
Netherlands New Zealand North Korea Portugal Poland Peru
Romania Russian Federation Saudi Arabia Singapore Slovakia
Slovenia South Korea South Africa Spain Sweden Switzerland
Syria Taiwan Thailand Tunisia U.S.A. U.A.E. United Kingdom
Ukraine Vietnam Yemen Yugoslavia

Certificate

Sectional Drawing of Grain Flow Line

O GOOD GRAIN FLOW LINE KING TONY

Metric Size

X BAD GRAIN FLOW LINE OTHER BRAND

Imperial Size

Production process

Production process.....

Hot Forge

Grinding

Drilling

Heat Treatment

Vibrating

Plating

Marking

Lathing

De-Burring

Lathe Machining

Punching & Broaching

Sand Blast

Phosphate Sunk

Silk Printing

Inspection Equipment

Strict and precise production as well as professional inspection and testing equipment are the key point to guaranty the satisfaction of customers.

Inspection equipment.....

Environmental Simulation Test of Temperature & Humidity

Spectrometer

Insulated Test

Overhead Projector

Tension Tester

Tension Tester

Thickness Test of Plating

Grinding & Polish Machine

Product Gauge

Carton Busting Strength Tester

Hardness Tester

Micro Torque Tester

Salt-water Spray Tester

Micro Hardness Tester

Precise Cutting Machine

Mounting Press Machine

The Pliers Class Measure & Tester

2.5D Vision Measuring Machine

Innovation

Style / Torque (min) / Size	Hexagon		Hexagon with ball point
	DIN	KING TONY	KING TONY
1.5mm	8.36	8.6	5.5
2mm	19.4	21.0	14.1
2.5mm	38.8	46.0	31.0
3mm	67.3	77.0	54.0
4mm	163.0	192.0	154.0
5mm	306.0	392.0	255.0
6mm	530.0	694.0	418.0
7mm	795.0	1074.0	685.0
8mm	1224.0	1664.0	1021.0
10mm	2243.0	3059.0	1635.0
12mm	3773.0	4980.0	
14mm	6016.0	7821.0	

K.T standard screwdriver

K.T heavy Duty screwscrewdriver

Hand socket

Impact socket

- Insert a bolt/nut fully into the deepest position of a socket opening.
- Use a right size socket, whose opening fits a bolt/nut correctly.
- Wear safety goggles and a hearing protection aid while using an impact wrench.
- Do not touch a spinning impact tool.
- Do not combine several extensions, weld handles, or alter the surface of any tools.

Offset Extension Bar

The offset extension bar bears less torque than normal extension bar. Do not use it as a normal extension bar.

offset extension bar

extension bar

One-way usage: flexible extension bar angled at 15°.

Safety instruction

Electronic Torque Wrench

Electronic Torque Adapter

CE

Torque Screwdriver

- Tolerance of torque within ±5% quality meets DIN ISO 6789 & ASME B107.14M-2004

Torque Multiplier

- Torque multiplication with 1:5, accuracy guaranteed better than ± 5 %.

Set contents:

Open-Side Speed Wrench

Innovation

1.FAST

The special ratcheting open end design will not slip off the screw when torque is applied.

2.ASSEMBLE

The special curve design would not hurt the screw.

3.EASY

The wider design is easy to fit of the screw.

4.SAFE

The special rack design that easy to lock the screw and more safe.

5.To protect rack without iron chippings damage.

6.HIGH TORQUE:
The standard of torque is 30% higher than ANSI.

Gift CLASSIC

Leather Wallet
For Business Card
ZS105
Size - 8.5 x11 cm

Leather Male Wallet
ZS104
Size - 11 x 9 cm

Briefcase (Leather)
ZS107
Size - 40 x 29.5 x 8 cm

Briefcase (Nylon)
ZS106
Size - 43 x 32 x 9 cm

Case for business card
ZS113
Size - 9.5 x 6.1 x 12 cm

Leather Belt (Male)
ZS108

Watch
ZS203

Ball-Bearing Pen
ZS405

Ballpoint Pen
ZS403

Ballpoint Pen
ZS402

Gift WORK

Work Clothing

ZS109 - L	165 cm
ZS109 - XL	173 cm
ZS109 - 2L	180 cm
ZS109 - 3L	190 cm

Back

Front

Polo Shirt

ZS111- S	145~155 cm
ZS111- M	155~165 cm
ZS111- L	165~175 cm
ZS111- XL	175~185 cm
ZS111- XXL	185~190 cm

Overall	Waist. (inch)	Hip (inch)
ZS112 - L	36"	44"
ZS112 - XL	40"	48"
ZS112 - 2L	44"	52"
ZS112 - 3L	48"	56"

Necktie
ZS520

Work Hat
ZS110

Necktie Clip
ZS521

Gift
SALES SUPPORT

Key Ring
ZS533

Key Ring
ZS526

Key Ring
ZS522

Key Ring
ZS524

Kingtony Big Flag
- 930 x 1430 mm
ADFLAG1

Display Card ADVT
Ø - 452 mm

Sticker ADSTK-H
Ø - 150 mm

Display Card ADVT-T
Ø - 452 mm

Sticker ADSTK-T
Ø - 150 mm

Kingtony Small Flag
- 25.4 x 16 cm
ADFLAG

Display Card ADVT-P
Ø - 452 mm

Sticker ADSTK-P
Ø - 150 mm

Display Card ADVT-A
Ø - 452 mm

Sticker ADSTK-A
Ø - 150 mm

Gift SALES SUPPORT

Paper Cup
ZS511

Paperweight
ZS531

Notepaper
ZS510

Hand Pressing
Flash Light
ZS208

Sticker
Size - 99 x 44 cm CPSTK-G1
Size - 50 x 22 cm CPSTK-G2
Size - 20 x 9.4 cm CPSTK-G3

Note Book
ZS512

Handbag
HANDBAG

Sticker / Length - 25 cm
ADHSTK-KT

Paper Clip Of
Dr.Q Toy Figure
ZS529

Card Holder Of
Dr.Q Toy Figure
ZS535

Photo Frame Of
Dr.Q Toy Figure
ZS534

SIGN LIST

- Internal Hexagon
- External Hexagon
- Bi - Hexagon
- Spline Head
- Spline Head - Tamper Resistant
- Internal Torx
- External Torx
- External Torx - Tamper Resistant
- Double square
- Impact Socket
- Ribe Bit Socket
- Phillips Head
- POZIDRIV
- Slotted Head
- Internal Square
- External Square
- Accessory
- Impact Accessory
- Pin
- Tray
- Gear Puller
- Wrench
- Pliers
- Snips
- Hammer
- Tube Cutter
- Tool Box
- ISO
- CE Certificate
- G.S. Approval
- VDE Certificate
- Other
- Q'ty / Carton
- Q'ty / Box
- Weight (g)
- Insulated (1000V)
- Diameter
- Capacity of open Jaw (mm)
- External Circlip
- Internal Circlip
- Circlip Pliers Head Size

Tool Storage

Tool Display ..... 1 ~ 6
Tool Trolley & Acessory ..... 7 ~ 21
Tool Chest ..... 22 ~ 23
Tool Box ..... 23 ~ 24
Tool Chest Set ..... 25 ~ 26
Tool Box Set ..... 27 ~ 29
Tool Set Content ..... 30 ~ 42
Tool Box Set Content ..... 42 ~ 46

Socket & Accessory

1/4" (6.35) Drive — Socket, Ratchet, Accessory, Socket Set — 47 ~ 60
3/8" (9.53) Drive — Socket, Ratc het, Accessory, Bit Holder, Socket Set — 61 ~ 75
1/2" (12.7) Drive — Socket, Ratchet, Accessory, Socket Set — 76 ~ 99
3/4" (19.05) Drive — Socket, Ratchet & Accessory, Socket Set — 100 ~ 104
1" (25.4) Drive — Socket, Accessory & Socket Set — 105 ~ 106
Combination Socket Set — 107 ~ 110

Impact Socket & Accessory

1/4" (6.35) Drive — Socket — 119
3/8" (9.53) Drive — Socket, Accessory, Socket Set — 120~123
1/2" (12.7) Drive — Socket, Bit Socket, Accessory, Socket Set — 124~138
3/4" (19.05) Drive — Socket, Bit Socket, Accessory, Socket Set — 139~147
1" (25.4) Drive — Socket, Accessory, Socket Set — 148~154
1-1/2" (38.1) Drive — Impact Socket & Accessory — 155
#5 Spline Drive — 156

Pneumatic Tools

Impact Wrench — Impact Wrench, Composite Impact Wrench, Air Ratchet Wrench, Impact Screwdriver, Socket & Wrench Set — 157~174

Torque Tools

Torque Wrench & Set — 175~186
Torque Screwdriver & Torque Angle Gauge & Torque Multiplier & Torque Teater — 187~190

Wrench

Wrench & Special Purpose Wrench — 191~216
T-shaped Driver & T-type Spark Plug Sockel — 217~219
T-type Universal Joint & Socket Wrench — 220~222

INDEX

Pliers

- Pliers 223~229
- Insulated Pliers 230~231
- Lock-Grip Pliers 232~233
- Crimping Tools 234

Snips & Cutter

- Snips 235~239
- Cutter 240~241
- Bolt Cutter 242
- Tubing Cutter 243

Screwdriver & Key & Bit

- Screwdriver 245~259
- Bit 260~269
- Key 270~278

Other Tools

- Punch 279~282
- File 283~284
- Puller 285
- Hammer 285~286
- Saw 287
- Riveter 287~288
- Measuring 289~292
- Others 293~294

Automotive Tools

- Engine Series 297~302
- Undercar Series 303~311
- Body Series 310~314
- Battery & Electrical 315
- General Tools 316~324

Notes

Tool Storage

- Tool Display
- Tool Trolley
- Tool Chest
- Tool Box
- Tool Chest Set
- Tool Box Set
- Tool Set

KING TONY

KING TONY

Tool display

87301

Display Hook

87301-494 4" x Ø 4 mm
87301-496 6" x Ø 5.2 mm
87301-498 8" x Ø 5.2 mm

87203

Display Board

Wall hanging type
30 pcs hooks attached
Overall Size -
W 725 x D 14 x H 900 mm
Weight - 11.5 Kg
Cuft - 0.328

Screwdriver Shelf

Overall Size -
W 600 x D 240 x H 210 mm
Weight - 3.38 Kg
Cuft - 1.086

87105 / 87110 / 87111

Reference:

87105 (31416MR 253)
(31516MR 253)
87110 (31512MR 253)
87111 (31519MR 253)

91431

Hammer Hook

Overall Size -
W 40 x D 210 x H 240 mm
Weight - 411.6 g
Cuft - 0.072

Display Stand

Overall Size -
W 950 x D 500 x H 2230 mm
Attachment-
1 pc lamp case
2 pcs angled steel frames
2 pcs shelves
4 pcs steel plate with holes
40 pcs hooks

87106

Individual pack
Finger - safe design socket insert
Housing material - PP
Lock pin is optional

Impact wrench display stand

Applied for 1/2"drive & 3/4"drive impact wrench
Steel plate with chrome plated
Air hose adapter attached

Applied Item

8772KT	30 x 63 mm	(1/4" drive socket)
8773KT	30 x 65 mm	(3/8" drive socket)
8774KT	44 x 85 mm	(1/2" drive socket)
8776KT	60 x 108 mm	(3/4" drive socket)

Pliers Hook

91421-01

Overall Size -
W 75 x D 130 x H 60 mm
Weight - 100 g
Cuft - 0.021

91421-11 Overall Size -
W 822 x D 130 x H 60 mm
Weight - 922 g
Cuft - 0.230

8711B

Metal Holder

Overall Size -
W 600 x D 240 x H 60 mm
Weight - 6.2 Kg
Cuft - 0.9

Reference:

1090PR1 284

87352

Bit Display Box

Overall Size -
W 318 x D 235 x H 183 mm
Weight - 1.3 Kg
Cuft - 0.4

(Example)

87103

Socket Shelf

Width can be adjustable offering to display multiple socket series
Single serial socket size tab attached
Overall Size -
W 427 x D 282 x H 297 mm
Weight - 8.1 Kg
Cuft - 1.866

Reference:

4072MR / 4572MR	91
4072SR / 4572SR	91
4066MR / 4566MR	91
4066SR	91
4472MP/4472SP	137
4466MP/4466SP	137

Socket Hook

Special design in display stand (87301)
Zinc finishing

91403 (applied to 3/8" drive socket)
91404 (applied to 1/2" drive socket)
91406 (applied to 3/4" drive socket)
91408 (applied to 1" drive socket)

Holder For Other Tools

Tool display

Applied Item

8781007KT (applied to 1/4" Ratchet ,Slideing T- handle,Wrenches 6~12mm)
8781012KT (applied to 3/8" Ratchet ,Slideing T- handle,Wrenches 13~23mm)
8781013KT (applied to 1/2" Ratchet ,Slideing T- handle,Wrenches 13~23mm)
8781032KT (applied to 3/4" Ratchet ,Slideing T- handle,Wrenches 24~32mm)

Tool display

(Example)

Torque Wrench Display Stand

NEW

Overall Size -
W 725 x D 14 x H 900 mm

87151

Site	Square driver	Model	Overall Length (mm)	Applied to torque wrench				
A	3/8" 1/2"		435	34362-2CG	34362-2DG	34362-2EG	34422-3GG	
			521	34462-1CG	34462-1DG	34462-1EG	34462-1FG	34422-1GG
			613	34462-2CG	34462-2DG	34462-2EG	34462-2FG	
	3/8" 1/2"		430	3436A-2DG	3436A-2EG			
			490	3446A-1DG	3446A-1EG			
			590	3446A-2DG	3446A-2EG			
	9x12mm 14x18mm		430	34512-3CG	34512-3DG	34512-3EG	34512-3FG	
			430	34522-1CG	34522-1DG	34522-1EG	34522-1FG	
			485	34522-2CG	34522-2DG	34522-2EG	34522-2FG	
			580	34522-3CG	34522-3DG	34522-3EG	34522-3FG	
	3/8" 1/2"		450	34423-1A	34423-1B	34423-1C		
			570	34423-2A	34423-2B			
	3/8" 1/2"		460	34367-2AG	34387-2AG			
			530	34467-1AG	34487-1AG			
B	1/4" 3/8"		281	34262-2DG				
			324	34262-1CG	34262-1DG	34262-1EG	34262-3DG	
				34362-1CG	34362-1DG	34362-1EG	34362-3DG	
	1/4"		285	3426A-1DG	3426A-1EG			
			325	3426A-2DG	3426A-2EG			
	9 x 12 mm		261	34512-1CG	34512-1DG	34512-1EG	34512-1FG	
			306	34512-2CG	34512-2DG	34512-2EG	34512-2FG	34512-4CG
	1/4" 3/8"		280	34223-1A	34223-1B			
			370	34223-1C	34323-1A	34323-1B	34323-2A	34323-2B
	1/4"		180	34111-1DG	34111-1EG			
C	1/4" 3/8"		280	34223-1A	34223-1B			
			370	34223-1C	34323-1A	34323-1B	34323-2A	34323-2B
	3/4"		L110xW56 mm	34607-1A				
D	1/4" 3/8"		210	3426C-1DF	3436C-1DF			
			248	3426C-2DF	3436C-2DF			
	1/4" 3/8" 1/2"		L75xW45 mm	34207-1A	34307-1A	34407-1A		
E	1/4"		248	34111-2DG	34111-2EG			

Tool display

87160

(Example)

NEW

DISPLAY RACK

Overall Size -
W 400 x D 600 x H 2070 mm

Tool Trolley

87432-5B
87434-7B
87438-3B NEW

- 26 inch roll-wagon (with bulk storage compartment)
- Frame constructed with one piece steel sheet for integral strength
- 4 industrial casters can be loaded 300 kgs grossly (size: 5" x 1-1/4")
- Useful tool tray / special side handle for easy moving tool trolley
- Drawer slides type - ball bearing
- Grooved full width drawer pulls add strength and offer to list contents of drawer
- Central locking system
- 10mm Top mat
- Powder coating finish
- Overall size (mm) - 670(W) x 460(D) x 812(H)

87432-5B

87434-7B

87438-3B

	Spec.	Drawer Size (mm) Width x Depth x Height	category	kg	CUFT
87432-5B	5 Drawer	4-576 x 380 x 75 1-576 x 380 x 154 bulk-603 x 404 x 234	B3 B3	56	12.24
87434-7B	7 Drawer	5-576x380x75 2-576x380x154	B3 B3	64.0	
87438-3B	3 Drawer 2 Door	3-576 x 380 x 75 1-610 x 395 x 500	B3	48.5	

⚠ 87432-5G
⚠ 87434-7G

Risk - Free System (Only One Drawer Can Be Opened At One Time)

- 26 inch roll-wagon (with bulk storage compartment)
- Frame constructed with one piece steel sheet for integral strength
- 4 industrial casters can be loaded 495 kgs grossly (size: 5" x 2")
- Useful tool tray / special side handle for easy moving tool trolley.
- Drawer slides type - ball bearing
- Grooved full width drawer pulls add strength and offer to list contents of drawer
- Central locking system
- 10mm Top mat
- Powder coating finish
- Overall size (mm) - 670(W) x 460(D) x 812(H)

87432-5G

87434-7G

	Spec.	Drawer Size (mm) Width x Depth x Height	category	kg	CUFT
87432-5G	5 Drawer	4-576 x 380 x 75 1-576 x 380 x 154 bulk-603 x 404 x 234	B3 B3	56	12.24
87434-7G	7 Drawer	5-576x380x75 2-576x380x154	B3 B3	64.0	

- Only open one drawer to prevent dump when moving the cabinet.
- Open one drawer, the other drawer are locked.

Tool Trolley

87441-1B

- 1 drawer trolley
- Two 3.5" deep trays are positioned for convenience

	Spec.	Drawer Size (mm) Width x Depth x Height	kg	CUFT
87441-1B	overall	720 x 410 x 750	24.6	2.7
	overall + 3" Casters	720 x 410 x 853		
	1 Drawer	572 x 275 x 65		

87441-1B

87441-3B

- 3 drawer trolley (ball bearing slide)
- 2 PC. protective mat for top and bottom shelves
- 3 PC. protective drawer liners

	Spec.	Drawer Size (mm) Width x Depth x Height	kg	CUFT
87441-3B	overall	720 x 410 x 750	33.0	3.94
	overall + 3" x 1-1/4" Casters	720 x 410 x 853		
	1 Drawer	572 x 275 x 65		
	2 Drawer	572 x 275 x 41		

87441-3B

Accessory

87432

- Drawer divider for cabinet :
  size : 570mm(W) x 380mm(D) x 45mm(H)

	Material	Drawer Divider Size (mm) Width x Depth x Height
87432-22	Steel	574 x 368 x 40
87432-23		568 x 265 x 40
87432-24	Plastic	570 x 370 x 40
87432-26		570 x 270 x 40

87432-22 / 87432-23

87432-24 / 87432-26

87432-15

- Plastic tray of parts for tool trolley 87432-5B
- Overall size (mm)
  - 920(W) x 490(D) x 50(H)

87432-15

87432-52

- Paper holder :
  size : 45mm(H) x 290mm(L) x 65mm(D)

87432-52

Workbench

87502

- Workstation - 3 drawer chest
  Ball bearing slide
  2 wall cabinets

	Spec.	Width x Depth x Height (mm)	kg	CUFT
87502	overall	1525 x 700 x 1520	104.2	13.4
	3 Drawer chest	660 x 307 x 251		
	2 Drawer	569 x 275 x 50		
	1 Drawer	569 x 275 x 75		
	Wall cabinet	400 x 200 x 500		

Work bench excludes cutting board & tool holder

87502

Workbench

87502P90

- 2 wall cabinets

	Spec.	Width x Depth x Height (mm)	kg	CUFT
87502P90	overall	1525 x 700 x 1520	73	-

87502P91

- Workstation-3 drawer chest
- Ball bearing slide

	Spec.	Width x Depth x Height (mm)	kg	CUFT
87502P91	overall	1525 x 700 x 800	61	9.2

87502P01

	Spec.	Width x Depth x Height (mm)	kg	CUFT
87502P01	overall	1525 x 700 x 1520	59	6.5

87502P011

- Workbench
  (without drawer)

	Spec.	Width x Depth x Height (mm)	kg	CUFT
87502P011	overall	1525 x 700 x 800	48	6.5

87502P012

- Wall cabinet

	Spec.	Width x Depth x Height (mm)	kg	CUFT
87502P012	overall	400 x 200 x 500	13.5	2.7

Wall Mounted Type Tool Cabine

87201

- With 20 PC. hooks.
  - 5PC. 87502-050 U shape hook
  - 10PC. 87502-051 1" single hook
  - 5PC. 87502-061 1" double hook
- Heavy duty design for storage heavy duty tool.
- Powder coating finishing.
- Full opened door with 2 aluminum alloy handles.
- 4 holes on the back of cabinet to be fixed on the wall.
- Double wall door panel design, peg hole at inside wall of door.

87502-050

87502-051

87502-061

Steel thickness: body : 1.0 mm

	Spec.	Width x Depth x Height (cm)	kg	CUFT
87201	overall	820 x 250 x 900	26	8

Accessory

87501P02

- Drawer for workbench

x2

87501P02

87502P03

- 2 PC. wall cabinets

87502P03

Accessory

87502-11

Cutting board

- Oil-resistant, acid-resistant, moisture-resistant and anti-static
- Cutting board is adjustable on the workbench

87502-11

87502-12

4 PC. of adjusting device

- Included adjustable bolt & adjustable pad

87502-12

Tool holder excluded pliers, wrenches & screwdrivers

87502-01

- Tool holder 500mm, L

87502-01

87502-05

- 87502-050 U Shape hook
  87502-051 1" Shape hook
  87502-054 4" Shape hook
  87502-058 8" Shape hook

87502-05

87502-02

- Magnetic tool holder for workbench backpanel
  Size: 475 x 52 x 17mm

87502-02

87502-06

- 87502-061 1" Double hook
  87502-064 4" Double hook
  87502-068 8" Double hook

87502-06

Tool Trolley & Set

Drawer slides type - ball bearing

ABS worktop matching tool chests

Floor brake

Drawer locking system
Central locking system

Useful tool tray /special side handle for easy moving tool trolley

The Way To Fill Your Drawer

HOW TO COMPLETE YOUR TOOL CHEST SET AND TOOL TROLLEY SET

The drawer of tool chest and tool trolley includes one top drawer and different size

Drawer A1 (646x290 mm)

Drawer B1 (172x275 mm)

Drawer B2 (572x275 mm)

Drawer B3 (579x380 mm)

P* : Tray for parts

CAUTION

- Do not move the tool unit unless you have closed the cover and locked the drawers.
- Never open more than one loaded drawer at the same time.
- Watch for sharp edges, we suggest to put on gloves before you lift the unit.

Tool Trolley Set

941-000 MR

- 172 PC. tool trolley set
  Tool trolley:

941-000MR

87411-6B 22

87421-3B 22

87432-5B 7

Tray No.	Set	Use Drawer
Tray #1	642 x 286 mm 9-4526MR 30	 A1
Tray #4	375 x 265 mm 9-3523MR 37 9-1711MR 35 9-1216MR 34 9-90103PP 36 9-22108MR 35 9-22308PR 35	 B2 B2 B3
Tray #5	265 x 185 mm 9-2526MR 39 9-4128FR 39 9-4119PR 39 9-4120PR 39 9-1303MR 39 9-20110MR 39 9-31106MR 39 9-40103GP 40 Tray for parts (375 x 30 mm) x 4 84700612B	 B2 B2 B3

	Spec.	kg	CUFT
941-000MR-A	87411-6B	28.4	3.97
941-000MR-B	87421-3B	17.5	2.71
941-000MR-C	87432-5B	63.5	11.84
941-000MR-D	172 PC. trolley contents	28.4	2.93

Tool Trolley Set

932-000 MR

- 173 PC. tool trolley set

932-000MR

Tray No.	Set	Use Drawer
Tray #4	375 x 265 mm 9-4333MR 32 9-7540MR 33 9-1711MR 35 9-1216MR01 34 9-90103PP 36 9-40207GP 36 9-22108MR 35 9-22308PR 35 9-31110MR 36 9-90131MR 37	 B3
	 1006PR 282 Tray for parts (375 x 30 mm) x 8 84700612B	

Tool trolley:

87432-5B 7

	Spec.	kg	CUFT
932-000MR-A	87432-5B	63.5	11.84
932-000MR-D	173 PC. trolley contents	24.7	1.97

Tool Trolley Set

932-008 MR

- 179 PC. tool trolley set

932-008MR

Tray No.	Set	Use Drawer
Tray # 4	375 x 265 mm 9-4522MR 33 9-3523MR 37 9-90315MR 34 9-1219MR01 34 9-31909PR 38 9-91120MR 35 9-40207GP 36 9-90103PP01 36	 B3
Tray # 5	265 x 185 mm 9-2526MR 39 9-4119PR 39 9-4120PR 39 9-31106MR 39	 B3
	1010PR 282 9DC23 315 Tray for parts (375 x 30 mm) x 5 84700612B	

Tool trolley:

87432-5B 7

	Spec.	kg	CUFT
932-008MR-A	87432-5B	63.5	11.84
932-008MR-D	179 PC. trolley contents	20.5	1.97

Tool Trolley Set

934-001 MR

- 197 PC. tool trolley set

934-001MR

Tray No.	Set	Use Drawer
Tray #6	532 x 375 mm 9-90408TQ 42	B3
Tray #4	375 x 265 mm 9-4516MR 32 9-5575MR 33 9-90310MR 36 9-90106SR 38 9-90205GN01 37 9-1218MR 34 9-1711MR 35 9-22108MR 35 9-31909PR 38	B3
Tray #5	265 x 185 mm 9-4128FR 39 9-40103GP 40 42114GP 229	B3

2121-18 319

14210212
14226512 249

7962-04 265

7963-04 285

1108MR 198

9DC23 315

Tray for parts (375 x 30 mm)
x 5
84700612B

Tool trolley:

87434-7B 7

	Spec.	kg	CUFT
934-001MR-A	87434-7B	64.0	12.24
934-001MR-D	197 PC. trolley contents	28.7	1.97

Tool Trolley Set

932-010 MR

- 144 PC. tool trolley set

932-010MR

Tray No.	Set	Use Drawer
Tray #4	375 x 265 mm 9-4328MR 32 9-5575MR 33 9-1216MR01 34 9-1709MR 35 9-90106SR 38	 B3
Tray #5	265 x 185 mm 9-31106MR 39 9-40103GP 40	 B3
	 34423-1A 184 84700612B	

Tool trolley:

87432-5B 7

	Spec.	kg	CUFT
932-010MR-A	87432-5B	63.5	11.84
932-010MR-D	144 PC. trolley contents	17.5	1.97

Tool Trolley Set

932-009 MR

- 101 PC. tool trolley set

932-009MR

Tray No.	Set	Use Drawer
Tray # 4	375 x 265 mm 9-4333MR 32 9-1711MR 35 9-1219MR01 34 9-90106SR 38	 B3
Tray # 5	265 x 185 mm 9-4120PR 39 9-4119PR 39 9-40103GP 40	 B3
	 34423-1A 184	 1110MR 190
		 Tray for parts (375 x 30 mm) x 3 84700612B

Tool trolley:

87432-5B 7

	Spec.	kg	CUFT
932-009MR-A	87432-5B	63.5	11.84
932-009MR-D	98 PC. trolley contents	19.8	1.97

Tool Trolley Set

938-001 MR

- 77 PC. tool trolley set

938-001MR

Tray No.	Set	Use Drawer
Tray #4	375 x 265 mm 9-1219MR01 34 9-1711MR 35 9-40207GP 36 9-22308PR 35 9-31110MR 36 9-4522MR 33	 B3

Tool trolley:

87438-3B 7

	Spec.	kg	CUFT
938-001MR-A	87438-3B	50	12.03
938-001MR-D	77 PC. trolley contents	12.24	1.64

Tool Chest

87411-6B

- 6 drawer chest
- Heavy gauge steel
- Drawer slides type-ball bearing
- Grooved full width drawer pulls add strength and offer to list contents of drawer
- Fold down locking system
- Powder coating finish
- With drawer liners and 4 bottom rubber mats
- Overall size (mm)- 660(W) x 305(D) x 380(H)

87411-6B

ball bearing slides

steel ball

bottom rubber mats to avoid slipping

Carrying handle

Handle

KING TONY	Drawer Size (mm) Width x Depth x Height	Category	kg	CUFT
87411-6B	TOP -646 x 290 x 60 3-172 x 275 x 41 2-572 x 275 x 41 1-572 x 275 x 65	A1 B1 B2 B2	25.4	3.97'

87411-9B

- 9 drawer chest
- Heavy gauge steel
- Drawer slides type-ball bearing
- Grooved full width drawer pulls add strength and offer to list contents of drawer
- Fold down locking system
- Powder coating finish
- With drawer liners and 4 bottom rubber mats
- Overall size (mm)- 660(W) x 307(D) x 427(H)

87411-9B

ball bearing slides

steel ball

bottom rubber mats to avoid slipping

Carrying handle

Handle

KING TONY	Drawer Size (mm) Width x Depth x Height	Category	kg	CUFT
87411-9B	TOP -646 x 290 x 60 6-170 x 275 x 50 2-569 x 275 x 50 1-569 x 275 x 75	A1 B1 B2 B2	30.2	4.3'

87421-3B

- 3 drawer chest
- Intermediate type
- Heavy gauge steel
- Drawer slides type-ball bearing
- Grooved full width drawer pulls add strength and offer to list contents of drawer
- Central locking system
- 10mm Top mat
- Powder coating finish
- 4 pins on the middle chest corners to tie in with top chest for extra security
- Overall size (mm) - 660(W) x 305(D) x 250(H)

87421-3B

ball bearing slides

steel ball

KING TONY	Drawer Size (mm) Width x Depth x Height	Category	kg	CUFT
87421-3B	2-572 x 275 x 41 1-572 x 275 x 65	B2	15.2	2.60'

Portable Tool Chest

87401

- Heavy gauge steel plus flange reinforced design
- Cover closing synchronously locks all of the drawer
- Powder coating
- Overall size (mm) - 535(W) x 220(D) x 290(H)

87401-2

87401-3

KING TONY	Spec.	Drawer Size (mm) Width x Depth x Height	kg	CUFT
87401-2	2 drawer	505 x 195 x 65	8.8	2.05
87401-3	3 drawer	505 x 195 x 45	10.21	
87401-3H	3 drawer	504 x 195 x 52	11.2	

87401-3H

internal lock system

ball bearing slides

steel ball

Tool Box

87402

- 3 section fold up type
- Tubular handle, curved hinge
- Shaped pressing on flat surface to reinforced steel strength
- Adjustable handle

KING TONY	Spec.	Drawer Size (mm) Width x Depth x Height	kg	CUFT
87402	5 compartments	470 x 220 x 260	5.60	1.22

87404

- Meterial : PP
- Multi-function box, extra space for tools and parts
- Light weight
- Durable design for tool storage

Specification.	Overall size (mm)	kg	CUFT
2 Compartments	560(W) x 278(D) x 270(H)	2.4	1.75

Tool Box

87407

- Meterial : PP
- Multi-function box, extra space for tools and parts
- Light weight
- Durable design for tool storage

Specification.	Overall size (mm)	kg	CUFT
2 compartments	445(W) x 240(D) x 206(H)	1.74	0.79

87407

Fabric Tool Box

87711C

- Waterproof 1200D Nylon Oxford
- Light weight stainless bar & comfortable EVA handle
- Velcro cover for easy access & quickly take out tools
- Adjustable ambi-bag with soft padded shoulder strap
- 39 inner pockets for multiple-tools storage
- 50% Light Weight compare with metal box

KING TONY	Overall size (mm)	kg	
87711C	550(W)x285(D)x370(H)	3	1 / 1

Tool Chest Set

911-000 CR
911-000 CR01
911-000 CR02

- 219 PC. tool chest set

Tray No.	Set		Use Drawer
Tray #1	500 x 195 mm 9-7069CR 30 (911-000CR use)	 9-7069CR01 30 [911-000CR01 911-000CR02 use]	 A1
Tray #2	172 x 257 mm 9-42114GP 31 9-40102GP 31 9-2548CR 30 (911-000CR 911-000CR01 use) 9-2548CR01 30 911-000CR02 use		 B1
Tray #3	554 x 260 mm 9-90128SR 31 9-90129CR 31 9-90138CR 32		 B2
	 7911-12 287		

Tool Chest:

87411-6B 122

	Spec.	kg	CUFT
911-000CR-A	87411-6B	24.8	3.97
911-000CR-D	219 PC. trolley contents	23.3	1.69
911-000CR01-A	87411-6B	24.8	3.97
911-000CR01-D	219 PC. trolley contents	23.3	1.69
911-000CR02-A	87411-6B	24.8	3.97
911-000CR02-D	219 PC. trolley contents	23.3	1.69

Tool Chest Set

901-068 MR
901-069 MR

- 69 PC. tool chest set

Tray No.	Set	Use Drawer
Tray # 1	500 x 195 mm 9-4338MR 42 (901-068MR use) 9-4338MR01 42 (901-069MR use)	 A1
Tray # 3	554 x 260 mm 9-90121MR 43 9-90104GP 43 9-31006MR 43	 B2

901-073 MR

- 74 PC. tool chest set

Tray No.	Set	Use Drawer
Tray # 1	500 x 195 mm 9-4338MR03 42	 A1
Tray # 3	554 x 260 mm 9-90126MR 43 9-90104GP 43 9-31006MR 43	 B2

Tool chest:

87401-3 22

	Drawer Size (mm) Width x Depth x Height	kg	CUFT
901-068MR	505 x 195 x 65	18.8	1.98
901-069MR		18.4	
901-073MR		19.5	

Tool Box Set

902-062 MR

- 62 PC. tool box set

KING TONY	Contents
902-062MR	9-4116FR 44 9-1217MR 44 9-90120MR 45 9-30206MR 45 9-4319MR 44 9-40203GP 45

kg	CUFT	Overall size (mm)
15.9	1.22	470(W) x 220(D) x 255(H)

902-065 MR
902-065 MR04

- 65 PC. tool box set

KING TONY	Contents	
902-065MR	9-4116FR 44 9-4319MR 44	9-90115MR01 45 9-1716MR 44
902-065MR04	⊕ 1421 No.1 x 80 No.2 x 38 No.3 x 150 ⊖ 1422 5.5 x 100 6.5 x 38 8 x 175 3611-08P 6111-07 6311-06 6511-10A 76104-05 76217-06 76223-08 76403-05 76404-06 76405-65 76406-07 7811-16	9-1606MR01 44 9-90125MR 45

kg	CUFT	Overall size (mm)
14.7	1.22	470(W) x 220(D) x 255(H)

Tool Box Set

902-068 MR

- 68 PC. tool box set

KING TONY	Contents
902-068MR	9-4116FR 44
	9-4319MR01 44
	1060: 8 10 11 12 13 14 15 16 17 18 19 21 22 24
	1120M: 1.5 2 2.5 3 4 5 6 8 10
	1421 ⊕ NO. 1 X 80 NO. 2 X 38 NO. 3 X 150
	1422 ⊖ 5.5 x 100 6.5 x 38 8 x 175
	6111-07 6311-06 6511-10A 3611-12P 7821-30
	7911-12 76104-05 76217-06 76223-08
	76403-05 76405-65 76404-06 76406-07

kg	CUFT	Overall size (mm)
15.9	1.22	470(W) x 220(D) x 255(H)

902-089 MR01

- 88 PC. tool box set

KING TONY	Contents
902-089MR01	9-4116FR 44
	9-4319MR01 44
	1812MR 213
	1060: 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 24
	1120M: 1.5 2 2.5 3 4 5 6 8 10
	1147: T10 T15 T20 T25 T27 T30 T40
	1900: 6x7 8x10 11x13 12x13 17x19 22x24
	1421 ⊕ NO. 2 X 38 NO. 3 X 150
	1422 ⊖ 3 x 75 5 x 100
	6111-07 6311-06 6516-10 3611-08R 7821-80
	7911-12

kg	CUFT	Overall size (mm)
17.7	1.22	470(W) x 220(D) x 255(H)

Tool Box Set

902-103 MR

- 103 PC. tool box set

KING TONY	Contents
902-103MR	9-4116FR 44 9-4319MR01 44 1812MR 213 1060: 8 9 10 11 12 13 14 15 16 17 18 19 21 22 23 24 27 30 32 1120M: 1.5 2 2.5 3 4 5 6 8 10 1147: T10 T15 T20 T25 T27 T30 T40 1421 ⊕: NO. 0 X 60 NO. 1 X 100 NO. 2 X 100 NO. 3 X 150 1422 ⊖: 3 X 75 4 X 100 5 X 75 5.5 X 125 6.5 X 150 8 X 175 6111-07 6311-06 6231-08 6516-10 6431-10 6011-10R 3611-12R 7821-80 7911-12 79083-03C 76220-07 76226-12 76402-45 76404-06 76406-07 76412-09 76403-05 76405-65 76408-08 76414-10

kg	CUFT	Overall size (mm)
25.5	1.22	470(W) x 220(D) x 255(H)

Tool Set Content

Tray category #1 (642 x 286mm)

Drawer A1(646x290)

9-4526 MR

	Contents	kg	
9-4526MR	4335M: 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 27 30 32 463521 4768-10F 4452-15F 4251-05 4251-10 4572-12	4.6	5

9-4526MR

9-7069 CR / CR01

	Contents	kg	
9-7069CR	3330M: 6 7 8 9 10 11 12 13 14 15 16 17 19 20 21 22 3330S: 3/8 7/16 1/2 9/16 5/8 11/16 3/4 13/16 4330M: 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 27 30 32 4330S: 3/8 7/16 1/2 9/16 5/8 11/16 3/4 13/16 7/8 15/16 1 3779-08G 4779-10G	8.8	4
9-7069CR01	463521 463516 3792 4791 3812 4813 3452-08F 4452-15F 3769-08P 3221-03 3221-06 4251-05 4251-10 3571-08 4572-10 4768-10P 7911-12	8.8	

9-7069CR

9-7069CR01

Tray category #2 (163 x 263mm)

Drawer B1(172x275)

9-2548 CR / CR01

	Contents	kg	
9-2548CR	2235M: 4 5 5.5 6 7 8 9 10 11 12 13 2235S: 5/32 3/16 7/32 1/4 9/32 5/16 11/32 3/8 7/16 1/2 2335M: 4 4.5 5 5.5 6 7 8 9 10 11 12 13 2779-55G	1.28	10
9-2548CR01	2335S: 5/32 3/16 7/32 1/4 9/32 5/16 11/32 3/8 7/16 1/2 2792 2813 2221-02 2221-04 2769-55P	1.28	

9-2548CR

9-2548CR01

Tool Set Content

Tray category #2 (163 x 263mm)

Drawer B1(172x275)

9-40102 GP

	Contents		kg	
9-40102GP	6011-10R	6511-10A	1.0	10

9-40102GP

9-42114 GP

	Contents		kg	
9-42114GP	68SS-07	68HS-07	0.6	10
	68SB-07	68HB-07		

9-42114GP

Tray category #3 (554 x 260mm)

Drawer B2(572x275)

9-90128 SR

	Contents			
9-90128SR	5060 1/4 5/16 3/8 7/16 1/2 9/16 5/8 11/16 3/4 13/16 7/8 1	76105-06	76215-05 76217-06 76220-07 76224-10	76404-06 76406-07 76408-08
	5970 1/4 x 5/16 3/8 x 7/16 1/2 x 9/16 5/8 x 11/16 3/4 x 7/8 15/16 x 1 1-1/16 x 1-1/8	7811-16		

9-90128SR

kg	
4.8	4

9-90129 CR

	Contents			
9-90129CR	1421 No.0x60 No.1x80 No.2x38 No.2x100 No.3x150			
	1422 3x75 6.5x38 6.5x100 6.5x150 8x175	6111-07	6231-07	6311-06
	1130S 3/32 1/8 5/32 3/16 1/4 5/16 3/8			
	1120M 1.5 2 2.5 3 4 5 6 8 10			

9-90129CR

kg	
2.5	4

Tool Set Content

Tray category #4 (375 x 265mm)

9-90138 CR

	Contents
9-90138CR	1060 6 7 8 9 10 11 12 13 14 15 16 17 19 20 21 1900 8x9 10x11 12x13 14x15 18x19 1970 6x7 8x9 10x11 12x13 14x15 16x17 18x19 1930 10x11 12x14 14x17 5900 1/4x5/16 3/8x7/16 7/16x1/2 9/16x5/8 11/16x3/4 13/16x7/8 3611-08P 3611-12P

9-90138CR

kg	
4.8	4

9-4328 MR

	Contents	kg	
9-4328MR	4335M 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 27 29 32 4027 T55 T60 4791 4768-10F 4251-05 4251-10 4452-15 4572-10	4.6	6

9-4328MR

9-4333 MR

	Contents	kg	
9-4333MR	4335M 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 32 463516 463521 4791 4251-03 4251-05 4251-10 4452-15F 4572-12 4755-10G	5.4	6

9-4333MR

9-4516 MR

	Contents	kg	
9-4516MR	4335M 8 10 11 12 13 14 17 19 21 23 24 4791 4768-10F 4452-15F 4251-05 4251-10	3.12	10

9-4516MR

Tool Set Content

Tray category #4 (375 x 265mm)

Drawer B3(579x380)

9-4522 MR

	Contents	kg	
9-4522MR	4335M 8 10 11 12 13 14 15 16 17 18 19 20 21 22 24 4791 4768-10F 4251-03 4251-05 4251-10 463516 463521	2.96	5

9-4522MR

9-5575 MR

	Contents	
9-5575MR	2335M 4 4.5 5 5.5 6 7 8 9 10 11 12 13	3235M 8 10 12 14 17
	3335M 6 7 8 9 10 11 12 13 14 15 16 17 18 19 21 22	2335S 1/4 3/8 1/2
		3027M T40 T45 T50
	2375M E4 E5 E6 E7 E8	2037M T10 T15 T20 T25 T27 T30
	3375M E10 E12 E14 E16 E18	2033M T20 T25 T30 T40
	366516 2792 2769-55F 3769-08F 2571-45 3789-11F 3221-03	
	366521 3792 2452-05F 3452-08F 3571-08 2221-02 2221-04 3221-06 3221-16	

9-5575MR

kg	
4.15	6

9-7540 MR

	Contents	kg	
9-7540MR	2335M 4 4.5 5 5.5 6 7 8 9 10 11 12 13		
	2375M E4 E5 E6 E7 E8		
	4375M E10 E12 E14 E16 E18 E20		
	4435M 10 11 12 13 14 17 19 21 22 24	3.50	5
	2792 2755-55G 2571-45		
	2452-05F 2177DF 2221-02 / 2221-04		

9-7540MR

Tool Set Content

Tray category #4 (375 x 265mm)

9-1216 MR 9-1216 MR01
9-1218 MR 9-1219 MR01

		Contents	kg	
9-1216MR	1060	6 8 10 12 13 14 16 17 19 21 22 24 26 27 29 32	3.20	6
9-1216MR01	1060	6 8 10 11 13 14 16 17 18 19 21 22 24 27 30 32	3.20	6
9-1218MR	1060 1930	6 7 8 10 11 12 13 14 15 16 17 18 19 21 22 24 8 x 10 9 x 11	2.12	6
9-1219MR01	1060	6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24	2.25	6

9-1216MR

9-1216MR01

9-1218MR

9-1219MR01

9-1272 MR NEW

		Contents	kg	
9-1272MR	1063	6 7 8 9 10 11 12 13 14 17 19 22	1.45	5

9-1272MR

9-1608 MR NEW

		Contents	kg	
9-1608MR	1960	6x7, 8x9, 10x11, 12x13, 14x15, 16x17, 18x19, 20x22	1.5	5

9-1608MR

9-90315 MR

		Contents	kg	
9-90315MR	1900 1970	8x10, 10x12, 12x14, 14x17, 17x19, 21x23, 22x24 8x10, 10x12, 12x14, 14x17, 17x19, 21x23 22x24 79083-05C	2.6	6

9-90315MR

Tool Set Content

Tray category #4 (375 x 265mm)

Drawer B2(572x275)

Drawer B3(579x380)

9-1709 MR 9-1711 MR

	Contents	kg	
9-1709MR	1970: 8 x 9, 10 x 12, 11 x 13, 12 x 14, 14 x 17, 17 x 19, 19 x 21, 22 x 24, 23 x 26	2.38	6
9-1711MR	1970: 6 x 7, 8 x 9, 10 x 11, 12 x 13, 14 x 15, 16 x 17, 18 x 19, 20 x 22, 21 x 23, 24 x 27, 30 x 32	2.60	6

9-1709MR

9-1711MR

9-90109 MN

	Contents	kg	
9-90109MN	1970: 8x10, 10x12, 11x13, 12x14, 14x17, 17x19 6011-10N 3611-12R	2.28	6

9-90109MN

9-91120 MR

	Contents	kg	
9-91120MR	1120: 1.5 2 2.5 3 4 5 6 8 10 1930: 8x10 10x12 11x13 14x17 3731: 8 10 12 13 14 3611-12R 6011-10N	2.40	6

9-91120MR

9-22108 MR 9-22308 PR

	Contents	kg	
9-22108MR	1160: 2 2.5 3 4 5 6 8 10	1.10	10
9-22308PR	1163: T10 T15 T20 T25 T30 T40 T45 T50	1.10	10

9-22108MR

9-22308PR

9-30110 CR NEW

	Contents	kg	
9-30110CR	1450: 6 7 8 9 10 11 12 13 5450: 1/4 5/16	1.4	6

9-30110CR

Tool Set Content

Tray category #4 (375 x 265mm)

Drawer B2(572x275)

Drawer B3(579x380)

9-31110 MR

	Contents	kg	
9-31110MR	1421 NO. 1 X 80 NO. 2 X 38 NO. 2 X 100 NO.3 X 150 1422 3 X 75 4 X 100 5.5 X 125 6.5 X 35 6.5X150 8 X 175	1.0	10

9-31110MR

9-90310 MR

	Contents	kg	
9-90310MR	1411 NO.1x100 NO.2x100 NO.3x150 1412 5.5x100 6.5x100 8.0x150 76220-07 9CJ2120 14324003 24110214	1.08	6

9-90310MR

9-40207 GP

	Contents	kg	
9-40207GP	6111-08 6211-06 6311-06 68HS-07 68HB-07 68SS-07 68SB-07	1.5	10

9-40207GP

9-40207 GP01

	Contents	kg	
9-40207GP01	6211-06 6311-06 6463-08 67HS-07 67HB-07 67SS-07 67SB-07	1.5	6

9-40207GP01

9-90103 PP 9-90103 PP01

	Contents	kg	
9-90103PP	3611-12P 6511-10A 7821-30	2.3	5
9-90103PP01	3611-12P 6511-10A 7811-16	2.3	5

9-90103PP

9-90103PP01

Tool Set Content

Tray category #4 (375 x 265mm)

Drawer B2(572x275)

Drawer B3(579x380)

9-90131 MR

	Contents		kg	
9-90131MR	4033	T20 T25 T27 T30 T40 T45 T50 T55 T60	3.1	10
	4035	4 5 6 7 8 10 12 14 17		
	1120M	1.5 2 2.5 3 4 5 6 8 10		
	1930	10 X 11 12 X 14 14 X 17		
		3204 (Ø 60 ~ 140)		

9-90131MR

9-3523 MR

	Contents		kg	
9-3523MR	3335M	3769-08F, 3571-08	1.38	10
	6 7 8 9 10 11 12 13 14 15 16 17 19 20 21 22	3221-03, 3221-06, 3792, 3452-08F		

9-3523MR

9-90205 GN / GN01

	Contents			kg	
9-90205GN	6011-10N	6111-07	6313-06	1.98	6
9-90205GN01	74410	6463-08	6311-06		

9-90205GN

9-90205GN01

9-40604 GP

	Contents		kg	
9-40604GP	6116-07A	6216-06A	1.53	8
	6318-08A	6516-10A		

9-40604GP

Tool Set Content

Tray category #4 (375 x 265mm)

Drawer B2(572x275)

Drawer B3(579x380)

9-42144 GP

	Contents	kg	
9-42144GP	6011-10N, 6111-08, 6211-06, 6311-06	1.63	8

9-42144GP

9-1609 MR

	Contents	kg	
9-1609MR	1960 8 x 9, 10 x 12, 11 x 13, 12 x 14, 14 x 17, 17 x 19, 19 x 21, 22 x 24, 23 x 26	1.93	6

9-1609MR

9-31909 PR

	Contents	kg	
9-31909PR	1427 T8x75, T9x75, T10x75, T15x75, T20x100, T25x100, T27x100, T30x125, T40x150	0.65	6

9-31909PR

9-90106 SR

	Contents	kg	
9-90106SR	76404-06, 76405-65, 76406-07, 7822-30, 7842-35, 76105-06	2.05	4

9-90106SR

Tool Set Content

Tray category #5 (265 x 185mm)

Drawer B2(579x270)

Drawer B3(579x380)

9-2526 MR

	Contents		kg	
9-2526MR	2335M	4 4.5 5 5.5 6 7 8 9 10 11 13	0.80	10
	2235M	4 5 5.5 6 7 8 9 10 11 13		
	2779-55G, 2813, 2792, 2221-02, 2221-04			

9-2526MR

9-4119 PR 9-4120 PR

	Contents		kg	
9-4119PR	4033	T20 T25 T27 T30 T40 T45 T50 T55 T60	1.10	10
9-4120PR	4035	4 5 6 7 8 10 12 14 17	1.30	10

9-4119PR

9-4120PR

9-4128 FR 9-1303 MR

	Contents		kg	
9-4128FR	1836S	9 11	1.70	10
	1880S	8 10		
	1836P	2 3		
	1880P	2 3		
	4112, 414810S			
9-1303MR	1930	10 X 11 12 X 14 14 X 17	0.50	10

9-4128FR

9-1303MR

9-20110 MR 9-31106 MR

	Contents		kg	
9-20110MR	1120M	1.5 2 2.5 3 4 5 6 8 10	1.10	10
	3204 (Ø 60 ~ 140)			
9-31106MR	1421	NO. 0 X 60 NO. 1 X 80 NO. 2 X 100	0.60	10
	1422	3 X 75 5.5 X 100 6.5 X 150		

9-20110MR

9-31106MR

Tool Set Content

Tray category #5 (265 x 185mm)

Drawer B2(579x270)

Drawer B3(579x380)

9-40103 GP

	Contents			kg	
9-40103GP	6111-07	6211-06	6311-06	0.81	1.0

9-40103GP

9-1905 MR

	Contents		kg	
9-1905MR		10 x 12 11 x 13 14 x 17 16 x 18 19 x 22	0.82	1 / 10

9-1905MR

9-10112 MR 9-10212 MR

	Contents		kg	
9-10112MR 3731	10 11 12 13 14 15 16 17 19	373202R 373203R 373204R	12.25	10
9-10212MR 3732				

9-10112MR

9-10115 MR 9-10215 MR

	Contents		kg	
9-10115MR 3731	8 9 10 11 12 13 14 15 16 17 19 22	373202R 373203R 373204R	17.3	10
9-10215MR 3732				

9-10115MR

Tool Set Content

Tray category #5 (265 x 185mm)

9-1282 MR NEW

	Contents		kg	
9-1282MR	10D0	8 9 10 11 12 13 14 15 16 17 18 19	1.05	5

9-1282MR

9-1C08 MR NEW

	Contents		kg	
9-1C08MR	19C0	8x10, 10x12, 12x14, 14x17, 17x19, 21x23, 22x24	0.91	5

9-1C08MR

Tool Set Content

Drawer B3(579x380)

Tray category #6 (570 x 375mm)

9-31919 MR

	Contents	kg	
9-31919MR	1411 NO.0x75 NO.2x38; 1412 3x75 6.5x38; 1421 NO.2x300; 1422 6.5x300; 43280212; 1481 NO.2x100 NO.3x150; 1482 6.5x100 8x150; 1427 T8x75 T10x75 T15x75 T20x100 T25x100 T27x100 T30x125; 2121-18	2.67	5

9-31919MR

9-90408 TQ

	Contents	kg	
9-90408TQ	75102-08G; 75202-08G; 75302-08G; 79083-05C; 75402-08G; 75502-08G; 79061-12; 7911-12	2.06	5

9-90408TQ

Tool Box Set Content

- Tray size 500 x 195 mm : for 87401-2 / 87401-3 / 87401-3H 17

9-4338 MR
9-4338 MR 01 For top drawer only
9-4338 MR 03

	Contents				
9-4338MR	4335M 23	10 11 12 13 14 15 16 17 18 19 20 21 22 24 27 30 32	4021 NO.2 NO.3; 4022 8 10; 4023 T25 T27 T30 T40; 4025 4 5 6 8 10 12	4768-10F; 4755-10G	4251-05 4251-10; 4572-12; 463521; 4791
9-4338MR01					
9-4338MR03	8				

9-4338MR

9-4338MR01

9-4338MR03

kg	
5.96	5

Tool Box Set Content

- Tray size 500 x 195 mm : for 87401-2 / 87401-3 18

9-90104 GP

	Contents			
9-90104GP	3611-08P	6511-10A	6111-07	6311-06

kg	
1.36	5

9-90104GP

9-90121 MR

	Contents	
9-90121MR	1900	6 x 7 8 x 10 11 x 13 12 x 13 17 x 19 22 x 24
	1970	8 x 9 10 x 11 12 x 13 14 x 15 16 x 17 18 x 19
	1120M	1.5 2 2.5 3 4 5 6 8 10

kg	
2.1	5

9-90121MR

9-31006 MR

	Contents	
9-31006MR	1421	NO. 1 X 80 NO. 2 X 38 NO. 3 X 150
	1422	6.5 X 38 5.5 X 100 8 X 175

kg	
0.74	5

9-31006MR

9-90126 MR

	Contents	
9-90126MR	1060	6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22
	1120M	1.5 2 2.5 3 4 5 6 8 10

kg	
2.38	5

9-90126MR

Tool Box Set Content

- Tray size 470 x 110 mm : For 87402 only 17

9-4319 MR
9-4319 MR 01

	Contents			
9-4319MR	4335M	10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 27 30 32	4791	4768-10F
9-4319MR01				4755-10G

9-4319MR

9-4319MR01

kg	
2.5	8

9-4116 FR

	Contents				
9-4116FR	463521	4452-18F	4251-05 4251-10	4223-02	4572-12

9-4116FR

kg	
2.2	8

9-1217 MR

	Contents	
9-1217MR	1060	17 18 19 20 21 22 24

9-1217MR

kg	
1.5	8

9-1716 MR

	Contents	
9-1716MR	1970	8 x 9 10 x 11 12 x 13 14 x 15 16 x 17 18 x 19

9-1716MR

kg	
1.1	8

9-1606 MR
9-1606 MR 01

	Contents	
9-1606MR	1960	10 x 12 12 x 14 14 x 17 17 x 19 19 x 21 23 x 26
9-1606MR01		8 x 10 10 x 12 12 x 14 14 x 17 17 x 19 22 x 24

9-1606MR01

kg	
1.1	8

Tool Box Set Content

9-30106 MR

	Contents	
9-30106MR	1421	NO. 1 X 80 NO. 2 X 100 NO. 3 X 150
	1422	5.5 X 100 6.5 X 150 8 X 175

kg	
1.0	8

9-30106MR

9-30206 MR

	Contents	
9-30206MR	1461	NO. 1 X 75 NO. 2 X 100 NO. 3 X 150
	1462	5.5 X 100 6.5 X 150 8 X 175

kg	
1.1	8

9-30206MR

- Tray size 470 x 110 mm : for 87402 only B29

9-40203 GP

	Contents		
9-40203GP	6111-07	6211-06	6311-06

kg	
0.8	8

9-40203GP

9-90115 MR

	Contents	
9-90115MR	1900	6x7 8x10 11x13 12x13 17x19 22x24
	1120M	1.5 2 2.5 3 4 5 6 8 10

kg	
1.2	8

9-90115MR

9-90120 MR

	Contents	
9-90120MR	1060	6 7 8 9 10 11 12 13 14 15 16
	1120M	1.5 2 2.5 3 4 5 6 8 10

kg	
1.5	8

9-90120MR

9-90125 MR

	Contents	
9-90125MR	1900	8x10 10x12 12x14 14x17 17x19 22x24
	1120M	1.5 2 2.5 3 4 5 6 8 10

kg	
1.2	8

9-90125MR

Notes

Socket & Accessory

■ Standard Socket ■ Deep Socket ■ Square Socket ■ Double Square Socket
■ Star Socket ■ Bit Socket ■ Ribe Bit Socket ■ Spark Plug Socket ■ Ratchet
■ Extension Bar ■ Extension Bar Set ■ Flexible Handle ■ Sliding Handle
■ Universal Joint ■ Speed Brace ■ Adapter ■ Socket & Wrench Set
■ Socket Rail Set ■ Socket Shelf Set

KT Socket			1/4"		3/8"		1/2"		3/4"		1"	
			mm	inch	mm	inch	mm	inch	mm	inch	mm	inch
Standard Socket	6PT		2335M	2335S	3335M	3335S	4335M	4335S	6335M			
	12PT		2330M	2330S	3330M	3330S	4330M	4330S	6330M	6330S	8330M	8330S
Deep Socket	6PT	Regular	2235M	2235S	3235M	3235S	4235M	4235S	6235M			
		Thin Wall (65L)			3215M							
		Thin Wall (90L)					4245M					
		Thin Wall (120L)					4255M					
	12PT				3230M	3230S	4230M	4230S				
Star Socket			2375M		3375M		4375M					
	Long Type		2275M		3275M		4275M					
Bit Socket	Phillips		2031		3021		4021					
	Slotted		2032		3022		4022					
	Hexagon		2035		3025		4025					
	Hexagon Long Type						4035					
	12PT (Spline)	60L					4026					
		80L					4036					
		100L					404108					
		120L					402616					
	Torx		2033		3023		4023					
		80L					4033					
		Torx Plus Tamper			302D							
		Tamper Resitant Type	2037		3027		4027					
		Tamper Resitant Type(80L)					4037					
	Ribe				3039		4049					
Spark Plug Socket	6PT	Rubber			3635		4635					
		Magnet			3665		4665					
	12PT	Rubber			3630		4630					
		Magnet			3660		4660					
Square Socket							4014M					
Double Square Socket			2310M	2310S								
Bit Holder					3148		4148					

Standard Socket

- Chrome vanadium alloy steel, polished, chrome plated.
- 4 ball retaining grooves.

2335 M

- 1/4" drive
- 6 points
- Metric size
- Thin walled design on square driving side
- DIN 3124 ,ISO 2725-1

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
233532M	3.2	5.7	11.8	3.5	24	9	20 / 600
233504M	4	6.8	11.8	4	24	10	20 / 600
233545M	4.5	7.4	11.8	5	24	10	20 / 600
233505M	5	8.0	11.8	6	24	11	20 / 600
233555M	5.5	8.7	11.8	6	24	11	20 / 600
233506M	6	9.2	11.8	7	24	11	20 / 600
233507M	7	10.3	11.8	7	24	11	20 / 600
233508M	8	11.4	11.8	8	24	11	20 / 600
233509M	9	12.8	12.0	8	24	15	20 / 600
233510M	10	14.3	13.0	9	24	14	12 / 360
233511M	11	15.8	14.2	9	24	20	12 / 360
233512M	12	16.8	15.5	9	24	22	12 / 360
233513M	13	17.8	16.5	9	24	24	12 / 360
233514M	14	19.6	18.5	9	24	30	10 / 300

2335 S

- 1/4" drive
- 6 points
- Inch size
- Thin walled design on square driving side
- ANSI/ASME B107.1

KING TONY	inch	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
233505S	5/32	6.8	11.8	4	24	10	20 / 600
233506S	3/16	7.9	11.8	6	24	10	20 / 600
233507S	7/32	8.7	11.8	6	24	11	20 / 600
233508S	1/4	9.5	11.8	7	24	11	20 / 600
233509S	9/32	10.3	11.8	7	24	11	20 / 600
233510S	5/16	11.4	11.8	8	24	11	20 / 600
233511S	11/32	13.7	12.2	8	24	13	20 / 600
233512S	3/8	14.2	13.0	8	24	14	12 / 360
233514S	7/16	15.8	14.2	9	24	19	12 / 360
233515S	15/32	16.8	15.5	9	24	22	12 / 360
233516S	1/2	17.6	16.5	9	24	24	12 / 360

2330 M

- 1/4" drive
- 12 points
- Metric size
- Thin walled design on square driving side
- DIN 3124 ,ISO 2725-1

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
233004M	4	6.8	11.8	4	24	10	20 / 600
233045M	4.5	7.4	11.8	5	24	10	20 / 600
233005M	5	8.0	11.8	6	24	11	20 / 600
233055M	5.5	8.7	11.8	6	24	11	20 / 600
233006M	6	9.2	11.8	7	24	11	20 / 600
233007M	7	10.3	11.8	7	24	11	20 / 600
233008M	8	11.4	11.8	8	24	11	20 / 600
233009M	9	12.8	12.0	8	24	15	20 / 600
233010M	10	14.3	13.0	9	24	14	12 / 360
233011M	11	15.8	14.2	9	24	20	12 / 360
233012M	12	16.8	15.5	9	24	22	12 / 360
233013M	13	17.8	16.5	9	24	24	12 / 360
233014M	14	19.6	18.5	9	24	30	10 / 300

2330 S

- 1/4" drive
- 12 points
- Inch size
- Thin walled design on square driving side
- ANSI/ASME B107.1

KING TONY	inch	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
233005S	5/32	6.8	11.8	4	24	10	20 / 600
233006S	3/16	7.9	11.8	6	24	10	20 / 600
233007S	7/32	8.7	11.8	6	24	11	20 / 600
233008S	1/4	9.5	11.8	7	24	11	20 / 600
233009S	9/32	10.3	11.8	7	24	11	20 / 600
233010S	5/16	11.4	11.8	8	24	11	20 / 600
233011S	11/32	13.7	12.2	8	24	13	20 / 600
233012S	3/8	14.2	13.0	8	24	14	12 / 360
233014S	7/16	15.8	14.2	9	24	19	12 / 360
233015S	15/32	16.8	15.5	9	24	22	12 / 360
233016S	1/2	17.6	16.5	9	24	24	12 / 360

Deep Socket

2235 M

- 1/4" drive
- 6 points
- Metric size
- DIN 3124 ,ISO 2725-1

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
223504M	4	6.8	11.8	6	50	20	30 / 480
223545M	4.5	7.4	11.8	7	50	21	30 / 480
223505M	5	8.0	11.8	7	50	21	30 / 480
223555M	5.5	8.7	11.8	9	50	21	30 / 480
223506M	6	9.2	11.8	9	50	23	30 / 480
223507M	7	10.3	11.8	15	50	23	30 / 480
223508M	8	11.8	11.8	15	50	24	30 / 480
223509M	9	13.0	13.0	15	50	29	16 / 256
223510M	10	14.5	14.5	15	50	38	16 / 256
223511M	11	15.8	15.8	21	50	44	14 / 224
223512M	12	16.8	16.8	21	50	53	14 / 224
223513M	13	17.8	17.8	21	50	51	16 / 320
223514M	14	19.8	19.8	21	50	68	14 / 280

2235 S

- 1/4" drive
- 6 points
- Inch size
- Thin walled design on square driving side
- ANSI/ASME B107.1

KING TONY	inch	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
223505S	5/32	6.8	11.8	6	50	24	30 / 480
223506S	3/16	7.9	11.8	7	50	24	30 / 480
223507S	7/32	8.7	11.8	9	50	25	30 / 480
223508S	1/4	9.5	11.8	9	50	25	30 / 480
223509S	9/32	10.3	11.8	15	50	25	30 / 480
223510S	5/16	11.8	11.8	15	50	24	30 / 480
223511S	11/32	13.0	13.0	15	50	31	16 / 256
223512S	3/8	14.5	14.5	15	50	34	16 / 256
223514S	7/16	15.8	15.8	21	50	46	14 / 224
223516S	1/2	17.6	17.6	21	50	56	16 / 320

Double Square Socket

2310 M

- 1/4" drive
- 8 points
- Metric size
- Thin walled design on square driving side
- DIN 3120

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
231008M	8	14.3	13.0	9	24	14	12 / 360
231010M	10	17.6	16.5	9	24	14	12 / 360

2310 S

- 1/4" drive
- 8 points
- Inch size
- Thin walled design on square driving side
- ANSI/ASME B107.1

KING TONY	inch	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
231010S	5 / 16	14.3	13.0	9	24	14	12 / 360
231012S	3 / 8	17.6	16.5	9	24	14	12 / 360

Star Socket

2375 M

- 1/4" drive star socket
- For torx external screws
- Chrome vanadium steel Polished, chrome plated
- DIN 3120

KING TONY	SIZE	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
237504M	E4	6.0	11.8	3.6	24	15	20 / 360
237505M	E5	7.0	11.8	4.0	24	16	20 / 360
237506M	E6	8.0	11.8	6.0	24	16	20 / 360
237507M	E7	8.5	11.8	7.0	24	17	20 / 360
237508M	E8	9.8	11.8	8.0	24	20	20 / 360

2275 M

- 1/4" drive star socket
- Long type

KING TONY	SIZE	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
227504M	E4	6.0	11.8	3.6	50	22	30 / 480
227505M	E5	7.0	11.8	4.0	50	22	30 / 480
227506M	E6	8.0	11.8	6.0	50	23	30 / 480
227507M	E7	8.5	11.8	7.0	50	24	30 / 480
227508M	E8	9.8	11.8	8.0	50	26	30 / 480

Bit Socket

- Socket made from chrome vanadium alloy steel
- Bit made from silicon alloy steel (S2)
- Polished, chrome plated.

CAUTION In order to get normal life of bit socket, Always use within limited torque to bits.

2031

- 1/4" drive bit socket
- Phillips head
- DIN ISO 8764-1

KING TONY	No.	Overall Length (mm)	g	
203101	1	37	14	20 / 600
203102	2	37	14	20 / 600
203103	3	37	15	20 / 600
203104	4	37	16	20 / 600

2032

- 1/4" drive bit socket
- Slotted head
- DIN ISO 8764-1

KING TONY	Tip Width (mm)	Tip thickness (mm)	Overall Length (mm)	g	
203235	3.5	0.5	37	14	20 / 600
203204	4	0.8	37	14	20 / 600
203255	5.5	1.0	37	15	20 / 600
203265	6.5	1.2	37	15	20 / 600
203208	8	1.2	37	16	20 / 600
203210	10	1.6	37	17	20 / 600

2033

- 1/4" drive bit socket
- For Torx internal screws
- DIN 3120

KING TONY	SIZE	Overall Length (mm)	g	
203308	T8	37	12	20 / 600
203309	T9	37	12	20 / 600
203310	T10	37	13	20 / 600
203315	T15	37	14	20 / 600
203320	T20	37	14	20 / 600
203325	T25	37	14	20 / 600
203327	T27	37	14	20 / 600
203330	T30	37	15	20 / 600
203340	T40	37	16	20 / 600

2035

- 1/4" drive bit socket
- Hexagon head
- DIN 7422/3120

KING TONY	mm	Overall Length (mm)	g	
203503	3	37	13	20 / 600
203504	4	37	15	20 / 600
203505	5	37	15	20 / 600
203506	6	37	15	20 / 600
203507	7	37	16	20 / 600
203508	8	37	17	20 / 600
203510	10	37	21	20 / 600

2037

- 1/4" drive bit socket
- For tamper resistant torx screws
- DIN 3120

KING TONY	SIZE	Overall Length (mm)	g	
203708	T8	37	12	20 / 600
203709	T9	37	12	20 / 600
203710	T10	37	13	20 / 600
203715	T15	37	14	20 / 600
203720	T20	37	14	20 / 600
203725	T25	37	14	20 / 600
203727	T27	37	14	20 / 600
203730	T30	37	15	20 / 600
203740	T40	37	16	20 / 600

Ratchet

- MATERIAL
  - handle of chrome vanadium alloy steel
  - (gear) driver of chrome molybdenum steel
- FINISHING
  - polished, chrome plated
  - black driver by phosphate sunk

2755

DIN 3122

1/4" drive reversible ratchet
5° gear action degree (72 teeth)

	Overall (inch)	Length (mm)		
2755-55G	5-1/2	140	120.0	5 / 90
2755DK	renewal kits		-	-

2755-55G

2755DK

8781007KT

2752

NEW

- 1/4" swivel head reversible quick release ratchet
- 5° gear action degree (72 teeth)
- Multi-angle design for difficult-to-reach fasteners

	Overall (inch)	Length (mm)		
2752-06P	6	150	141	6 / 108
2752-06G	6	150	140	6 / 108
2752DK	renewal kits		-	-

2752-06P

2752-06G

2752DK

2761

DIN 3122

- 1/4" drive reversible ratchet quick-release
- 15° gear action degree (24 teeth)
- Two teeth pawl action

	Overall (inch)	Length (mm)		
2761-55F	5-1/2	140	169.0	6 / 108
2761-55P	5-1/2	140	158.0	6 / 108
2761DK	renewal kits		-	-

2761-55F

2761-55P

2761DK

8781007KT

2769

DIN 3122

- 1/4" drive reversible ratchet
- 15° gear action degree (24 teeth)
- Two teeth pawl action

	Overall (inch)	Length (mm)		
2769-55F	5-1/2	140	126.0	6 / 108
2769-55P	5-1/2	140	125.0	6 / 108
2769DK	renewal kits		-	-

2769-55F

2769-55P

2769DK

8781007KT

Ratchet

- MATERIAL
  - handle of chrome vanadium alloy steel
  - (gear) driver of chrome molybdenum steel
- FINISHING
  - polished, chrome plated
  - black driver by phosphate sunk

2771 DIN 3122

- 1/4" drive reversible ratchet quick-release
- 15° gear action degree (24 teeth)
- Two teeth pawl action

KING TONY	Total Length (inch)	(mm)	g	
2771-55F	5-1/8	130	140	6 / 108
2771-55G	5-1/8	130	122	6 / 108
2771DK	renewal kits		-	-

2771-55F

2771-55G

2771DK

8781007KT

2779 DIN 3122

- 1/4" drive reversible ratchet
- 15° gear action degree (24 teeth)
- Two teeth pawl action

KING TONY	Total Length (inch)	(mm)	g	
2779-55F	5 - 1/8	130	146	6 / 108
2779-55G	5 - 1/8	130	126	6 / 108
2779DK	renewal kits		-	-

2779-55F

2779-55G

2779DK

8781007KT

2781 DIN 3122

- 1/4" drive reversible ratchet quick-release
- 15° gear action degree (24 teeth)
- Two teeth pawl action

KING TONY	Total Length (inch)	(mm)	g	
2781-06F	6	150	155	6 / 108
2781-06P	6	150	148	6 / 108
2781DK	renewal kits		-	-

2781-06F

2781-06P

2781DK

8781007KT

2789 DIN 3122

- 1/4" drive reversible ratchet
- 15° gear action degree (24 teeth)
- Two teeth pawl action

KING TONY	Total Length (inch)	(mm)	g	
2789-06F	6	150	140	6 / 108
2789-06P	6	150	140	6 / 108
2789DK	renewal kits		-	-

2789-06F

2789-06P

2789DK

8781007KT

2760 DIN 3122

- 1/4" drive mini reversible ratchet
- 11° gear action degree (32 teeth)
- Two teeth pawl action

KING TONY	Overall Length (inch)	(mm)	g	
2760-04	4	100	73.4	8 / 128
2760DK	renewal kits		-	-

2760-04

2760DK

8781007KT

Ratchet

- MATERIAL
  - handle of chrome vanadium alloy steel
  - (gear) driver of chrome molybdenum steel
- FINISHING
  - polished, chrome plated
  - black driver by phosphate sunk

2765 & 276A NEW

- 1/4" mini bit holder ratchet
- 5° gear action degree (72 teeth)
- Two teeth pawl action

MINI RATCHET

KING TONY	A (mm)	D (mm)	L (mm)	H (mm)	g	kg /
2765-04G	18.5	26	108	20	111	6 / 108
276A-04G	23	26	108	20	111	6 / 108
2765DK			renewal kits			
276ADK			renewal kits			

2765-04G

276A-04G

2765-04G (top, side, back)

276A-04G (top, side, back)

2765DK

276ADK

87A1007KT

1001MR NEW

- 10 PC. 1/4" bit and mini ratchet set
- 5° gear action degree (72 teeth)
- Two teeth pawl action

	Contents		
1001MR	1025P	NO.1 NO.2	2765-04G
	1025T	T10 T15 T20	
	1025H	H3 H4 H5 H6	

1001MR

kg	/
0.19	6 / 36

2515MR NEW

- 15 PC. 1/4" bit socket and mini ratchet set
- 5° gear action degree (72 teeth)
- Two teeth pawl action

	Contents		
2515MR	2335M	5 5.5 6 7 8	276A-04G
	1025P	NO.1 NO.2	
	1025T	T10 T15 T20	
	1025H	H3 H4 H5 H6	

2515MR

kg	/
0.26	6 / 36

Accessory

- MATERIAL - chrome vanadium alloy steel
- FINISHING - polished, chrome plated

2221 DIN 3123

- 1/4" drive extension bar

KINGTONY	Total Length (inch)	(mm)	g	
2221-02	2	55	24	30 / 480
2221-03	3	75	37	20 / 400
2221-04	4	100	45	15 / 240
2221-06	6	150	67	15 / 300
2221-10	10	254	108	15 / 240
2221-12	12	305	130	15 / 240

2221

8772KT

2223 DIN 3123

- 1/4" drive offset extension bar
- Max. torque 35 Nm

KINGTONY	Total Length (inch)	(mm)	g	
2223-02	2	55	23	30 / 480
2223-04	4	100	45	15 / 240

2223

8772KT

2293 DIN 3123

- 1/4" drive munti-function of extention bar and offset extension bar.
- Hex key is applicable to the hex shank.

KINGTONY	Total Length (inch)	(mm)	g	
2293-02	2	55	25	30 / 480
2293-04	4	100	45	15 / 240
2293-06	6	150	140	15 / 300

2293

1.offset extension bar

or

2.extension bar

8772KT

2311 DIN 3120

- 1/4" drive flexible extension bar

KINGTONY	Total Length (inch)	(mm)	g	
2311-06	6	150	68	12 / 240
2311-12	12	300	92	12 / 120
2311-18	18	450	120	20 / 200

2311

8772KT

2792 DIN 3123

- 1/4" drive universal joint

KINGTONY	Total Length (inch)	(mm)	g	
2792	1 - 1/2	36	29	24 / 384

2792

8772KT

2813 DIN 3123

- 1/4" drive adapter
- Convertimg to 3/8" drive

KINGTONY	Spec.	g	
2813	1/4" F x 3/8"M	20	12 / 360

3/8" drive (M) ← 1/4" drive (F)

8772KT

Accessory

- MATERIAL - chrome vanadium alloy steel
- FINISHING - polished, chrome plated & black phosphate sunk

2133DF DIN 3126

- 1/4" drive screwdriver driver

KING TONY	Total Length (inch)	(mm)	g	
213312DF	12	300	132	2 / 40

213312DF

2177DF DIN 3122

- 1/4" drive spinner handle

KING TONY	Total Length (inch)	(mm)	g	
2177DF	12 - 1/4	310	126	2 / 40

2177DF

2178AE DIN 3122
2178DF DIN 3122

- 1/4" drive driving handle

KING TONY	Total Length (inch)	(mm)	g	
2178AE	6	150	76	6 / 120
2178DF	6	150	71	6 / 120

2178AE (Polycarbonates)

2178DF (PP + TPR)

2452 DIN 3122

- 1/4" drive flexible handle
- Action degree -180°

KING TONY	Total Length (inch)	(mm)	g	
2452-05F	5	130	88	15 / 270
2452DK	renewal kits		-	-

2452-05F

2452DK

2571 DIN 3122

- 1/4" drive sliding T-handle

KING TONY	Total Length (inch)	(mm)	g	
2571-45	4-1/2	115	41	12 / 192

2571-45

Socket Set

2510 SR (10 PC.)
2511 MR (11 PC.)

- 1/4" drive socket set

	Contents	
2510SR	2235S	5/32 3/16 7/32 1/4 9/32 5/16 11/32 3/8 7/16 1/2
2511MR	2235M	4 5 5.5 6 7 8 9 10 11 12 13

2510SR

2511MR

	kg		Metal case size (mm)
2510SR	0.62	30	223 x 65 x 32 (0.016 cuft)
2511MR	0.67		

2516 MR SR

- 16 PC. 1/4" drive socket wrench set

	Contents			
2516MR	2335M	4 4.5 5 5.5 6 7 8 9 10 11 13	2779-55G	2221-04
2516SR	2335S	5/32 3/16 7/32 1/4 9/32 5/16 11/32 3/8 7/16 15/32 1/2	2178AE, 2571-45	2792

2516MR

2516SR

kg		Metal case size (mm)
1.10	18	244 x 118 x 37 (0.038 cuft)

2519 MR SR
2019 MR SR

- 18 PC. 1/4" drive socket wrench set

	Contents			
2519MR	2335M	4 4.5 5 6 7 8 9 10 11 12	2310M 8 10	2769-55P, 2452-05F, 2221-02, 2221-04, 2571-45, 2792
2019MR	2330M			
2519SR	2335S	5/32 3/16 7/32 1/4 9/32 5/16 11/32 3/8 7/16 1/2	2310S 5/16 3/8	
2019SR	2330S			

kg		Metal case size (mm)
0.92	20	198 x 105 x 32 (0.023 cuft)

2521 MR
2021 MR

- 19 PC. 1/4" drive socket wrench set

	Contents		
2521MR	2335M	4 4.5 5 5.5 6 7 8 9 10 11 12 13	2779-55G; 2452-05F, 2571-45, 2221-02, 2221-04, 2792, 2141
2021MR	2330M		

kg		Metal case size (mm)
0.87	20	198 x 105 x 32 (0.023 cuft)

Socket Set

2526 MR SR

- 26 PC. 1/4" drive socket wrench set

	Contents		
2526MR	2335M	4 4.5 5 5.5 6 7 8 9 10 11 13	2779-55G, 2792
	2235M	4 5 5.5 6 7 8 9 10 11 13	
2526SR	2335S	5/32 3/16 7/32 1/4 9/32 5/16 11/32 3/8 7/16 15/32 1/2	2221-02, 2221-04, 2813
	2235S	5/32 3/16 7/32 1/4 9/32 5/16 11/32 3/8 7/16 1/2	

2526MR

2526SR

kg		Metal case size (mm)
1.30	18	244 x 118 x 37 (0.038 cuft)

2530 CR
2030 CR

- 30 PC. 1/4" drive socket wrench set

	Contents			
2530CR	2335M	4 4.5 5 6 7 8 9 10 11 12	2310M 8 10	2769-55F, 2571-45, 2452-05F, 2221-02, 2221-04, 2792
	2335S	5/32 3/16 7/32 1/4 9/32 5/16 11/32 3/8 7/16 1/2	2310S 5/16 3/8	
2030CR	2330M	4 4.5 5 6 7 8 9 10 11 12		
	2330S	5/32 3/16 7/32 1/4 9/32 5/16 11/32 3/8 7/16 1/2		

kg		Metal case size (mm)
1.30	18	244 x 118 x 37 (0.038 cuft)

2531 MR
2031 MR

- 31 PC. 1/4" drive socket wrench set

	Contents			
2531MR	2335M	4 4.5 5 6 7 8 9 10 11 12 13	2033 T8 T9 T10 T15 T20 T25 T27 T30	2779-55G, 2221-03, 2221-06, 2178AE, 2571-45, 2792
2031MR	2330M		2035 3 4 5 6 8 10	

kg		Metal case size (mm)
1.60	15	280 x 130 x 41 (0.053 cuft)

Socket Set

2539 MR

- 39 PC. 1/4" drive socket wrench set

Contents			
2539MR	2335M	4 4.5 5 5.5 6 7 8 9 10 11 12 13	2779-55G, 2178AE, 2571-45, 2792, 2221-02, 2221-04
	2033	T8 T9 T10 T15 T20 T25 T27 T30 T40	
	2035	3 4 5 6 7 8 10	
	2375	E4 E5 E6 E7 E8	

kg		Metal case size (mm)
1.52	15	280 x 130 x 41 (0.053 cuft)

2540 MR

- 39 PC.1/4" drive socket wrench set

Contents			
2540MR	2335M	4 4.5 5 5.5 6 7 8 9 10 11 12 13	2779-55G, 2452-05F, 2571-45, 2133DF, 2221-02, 2221-06, 2792, 2141
	1025S	4 5.5 7	
	1025P	0 1 2 3	
	1025H	3 4 5 6 7 8	
	1025T	T10 T15 T20 T25 T30 T40	

kg		Metal case size (mm)
1.36	12	316 x 104 x 40 (0.047 cuft)

2526 CR

- 26 PC. 1/4" drive socket wrench set

Contents			
2526CR	2335M	4 4.5 5 5.5 6 7 8 9 10 11 12 13 14	2779-55G, 2452-05F, 2571-45, 2221-02, 2221-04, 2792
	2335S	1/4 3/8 1/2	
	2033	T20 T25 T30 T40	

kg		Metal case size (mm)
0.68	10	280 x 130 x 41 (0.053 cuft)

2575 MR

- 45 PC. 1/4" drive socket wrench set

Contents			
2575MR	2335M	4 5 5.5 6 7 8 9 10 11 12 13 14	2755-55G, 2311, 2178AE, 2792, 2223, 2142
	1025S	4.0 6.5 7.0 8.0	
	1025P	1 2 3	
	1025H	2.5 3 4 5 6 7 8 10	
	1025U	T8 T9 T10 T15 T20 T25 T27 T30 T40	
	1025Z	PZ1 PZ2 PZ3	

kg		Metal case size (mm)
1.24	1 / 18	244 x 118 x 37

Socket Set

■ 2551 MR

- 51 PC. 1/4" drive socket wrench set

	Contents		
2551MR	○ 2335M: 4 5 5.5 6 7 8 9 10 11 12 13 14		
	⊖ 1025S: 3.0 4.0 5.0 6.0	2755-55G	2792
	⊕ 1025P: PH1 PH2 x 2 PH3	2178DF	7702-25
	⊛ 1025Z: PZ1 PZ2 x 2 PZ3	2223-02 2223-04	753-63
	✱ 1025T: T10 T15 T20 T25 T27 T30 T40		
	◉ 1025H: H3 H4 H5 H6	2142	2813
	✪ 1025U: T10 T15 T20 T25 T27 T30 T40		

kg		Metal case size (mm)
1.3	1 / 18	244 x 118 x 37

Socket Rail Set

■ 2509 MR SR

- 9 PC. 1/4" drive socket set
- Socket rail 150mm L
  - Rail with 9 PC. 1/4" drive clips

	Contents	
2509MR	○ 2335M: 4 5 6 7 8 9 10 11 13	8720609
2509SR	○ 2335S: 5/32 3/16 1/4 9/32 5/16 11/32 3/8 7/16 1/2	

kg	
0.20	50

■ 2127 PR

- 7 PC. 1/4" drive bit socket set
  - Socket rail 130 mm L
  - Rail with 7 PC. 1/4" drive clip

	Contents	
2127PR	◉ 2035: H3 H4 H5 H6 H7 H8 H10	8720507

kg	
0.15	50

Socket Rail

○ 872

- 1/4" drive socket rail
- Rail length from 160 mm to 560 mm

KING TONY	CLIP	L (mm)	g	
870406	-	160	-	-
870208	-	200	-	-
870422	-	560	-	-
8720	-	-	-	-

Customer Selected

Standard Socket

- Chrome vanadium alloy steel, polished, chrome plated.
- 4 ball retaining grooves.

○ 3330 M

- 3/8" drive
- 12 points
- Metric size
- Thin walled design on square driving side
- DIN 3124 ,ISO 2725-1

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
333006M	6	9.9	17.8	7.0	27	24	12 / 360
333007M	7	10.8	17.8	7.0	27	24	12 / 360
333008M	8	12.0	17.8	7.0	27	25	12 / 360
333009M	9	13.2	17.8	7.0	27	25	12 / 360
333010M	10	14.5	17.8	9.0	27	26	12 / 360
333011M	11	15.8	17.8	9.0	27	27	12 / 360
333012M	12	16.8	17.8	9.0	27	27	12 / 360
333013M	13	17.8	16.8	9.0	27	30	12 / 360
333014M	14	19.7	18.0	11.0	29	33	10 / 300
333015M	15	20.8	18.0	11.0	29	40	10 / 300
333016M	16	21.8	20.0	11.0	29	39	10 / 300
333017M	17	23.8	20.0	11.0	29	52	10 / 200
333018M	18	24.7	21.0	13.0	29	58	10 / 200
333019M	19	25.8	21.0	13.0	29	62	10 / 200
333020M	20	27.1	25.0	13.0	32	73	10 / 160
333021M	21	27.8	25.0	13.0	32	82	10 / 160
333022M	22	29.7	26.0	15.0	32	87	10 / 160
333024M	24	31.8	26.0	17.0	32	78	8 / 160

○ 3330 S

- 3/8" drive
- 12 points
- Inch size
- Thin walled design on square driving side
- ANSI/ASME B107.1

KING TONY	inch	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
333008S	1/4	10.0	17.8	7.0	27	25	12 / 360
333010S	5/16	12.0	17.8	7.0	27	22	12 / 360
333011S	11/32	13.2	17.8	7.0	27	25	12 / 360
333012S	3/8	14.0	17.8	9.0	27	26	12 / 360
333014S	7/16	15.8	17.8	9.0	27	27	12 / 360
333015S	15/32	16.8	17.8	9.0	27	25	12 / 360
333016S	1/2	17.8	16.8	9.0	27	30	12 / 360
333018S	9/16	19.7	18.0	11.0	29	33	10 / 300
333019S	19/32	20.8	18.0	11.0	29	41	10 / 300
333020S	5/8	21.8	20.0	11.0	29	43	10 / 300
333022S	11/16	23.8	20.0	11.0	29	52	10 / 200
333024S	3/4	25.7	21.0	13.0	29	62	10 / 200
333026S	13/16	27.8	25.0	13.0	32	77	10 / 160
333028S	7/8	29.6	26.0	15.0	32	87	10 / 160

○ 3335 M

- 3/8" drive
- 6 points
- Metric size
- Thin walled design on square driving side
- DIN 3124 ,ISO 2725-1

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
333506M	6	9.9	17.8	7.0	27	25	12 / 360
333507M	7	10.8	17.8	7.0	27	24	12 / 360
333508M	8	12.0	17.8	7.0	27	25	12 / 360
333509M	9	13.2	17.8	7.0	27	25	12 / 360
333510M	10	14.5	17.8	9.0	27	27	12 / 360
333511M	11	15.8	17.8	9.0	27	28	12 / 360
333512M	12	16.8	17.8	9.0	27	28	12 / 360
333513M	13	17.8	16.8	9.0	27	31	12 / 360
333514M	14	19.7	18.0	11.0	29	34	10 / 300
333515M	15	20.8	18.0	11.0	29	47	10 / 300
333516M	16	21.8	20.0	11.0	29	45	10 / 300
333517M	17	23.8	20.0	11.0	29	53	10 / 200
333518M	18	24.7	21.0	13.0	29	58	10 / 200
333519M	19	25.8	21.0	13.0	29	64	10 / 200
333520M	20	27.1	25.0	13.0	32	73	10 / 160
333521M	21	27.8	25.0	13.0	32	82	10 / 160
333522M	22	29.7	26.0	15.0	32	87	10 / 160
333523M	23	29.7	26.0	15.0	32	80	10 / 160
333524M	24	31.8	26.0	17.0	32	78	8 / 160

Standard Socket

- Chrome vanadium alloy steel, polished, chrome plated.
- 4 ball retaining grooves.

○ 3335 S

- 3/8" drive
- 6 points
- Inch size
- Thin walled design on square driving side
- ANSI/ASME B107.1

KING TONY	inch	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
333508S	1/4	10.0	17.8	7.0	27	25	12 / 360
333510S	5/16	12.0	17.8	7.0	27	22	12 / 360
333511S	11/32	13.2	17.8	7.0	27	25	12 / 360
333512S	3/8	14.0	17.8	9.0	27	26	12 / 360
333514S	7/16	15.8	17.8	9.0	27	27	12 / 360
333515S	15/32	16.8	17.8	9.0	27	25	12 / 360
333516S	1/2	17.8	16.8	9.0	27	30	12 / 360
333518S	9/16	19.7	18.0	11.0	29	33	10 / 300
333519S	19/32	20.8	18.0	11.0	29	41	10 / 300
333520S	5/8	21.8	20.0	11.0	29	43	10 / 300
333522S	11/16	23.8	20.0	11.0	29	52	10 / 200
333524S	3/4	25.7	21.0	13.0	29	62	10 / 200
333526S	13/16	27.8	25.0	13.0	32	77	10 / 160
333528S	7/8	29.6	26.0	15.0	32	87	10 / 160
333530S	15/16	31.8	26.0	17.0	34	80	8 / 160
333532S	1	33.8	26.0	17.0	34	100	8 / 160

Deep Socket

- Chrome vanadium alloy steel, polished, chrome plated.
- 4 ball retaining grooves.

○ 3230 M

- 3/8" drive
- 12 points
- Metric size
- Thin walled design on square driving side
- DIN 3124 ,ISO 2725-1

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
323007M	7	10.8	17.8	10.0	63	54	20 / 320
323008M	8	12.0	17.8	12.0	63	54	18 / 288
323009M	9	13.2	17.8	12.0	63	59	18 / 288
323010M	10	14.5	17.8	12.0	63	56	15 / 240
323011M	11	15.8	17.8	15.0	63	63	15 / 240
323012M	12	16.8	17.8	15.0	63	58	15 / 240
323013M	13	17.8	16.8	15.0	63	61	15 / 240
323014M	14	19.7	18.0	16.0	63	71	12 / 192
323015M	15	20.8	18.0	18.0	63	92	10 / 160
323016M	16	21.8	20.0	18.0	63	88	8 / 128
323017M	17	23.8	20.0	18.0	63	97	8 / 128
323018M	18	24.7	21.0	20.0	63	136	6 / 96
323019M	19	25.8	21.0	20.0	63	110	6 / 96
323021M	21	27.8	25.0	20.0	63	127	6 / 96
323022M	22	29.7	26.0	20.0	63	164	6 / 96
323024M	24	31.8	26.0	25.0	63	182	3 / 48

○ 3230 S

- 3/8" drive
- 12 points
- Inch size
- Thin walled design on square driving side
- ANSI/ASME B107.1

KING TONY	inch	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
323010S	5/16	12.0	17.8	12.0	63	52	18 / 288
323012S	3/8	14.0	17.8	12.0	63	60	15 / 240
323014S	7/16	15.8	17.8	15.0	63	68	15 / 240
323016S	1/2	17.8	16.8	15.0	63	68	15 / 240
323018S	9/16	19.7	18.0	16.0	63	72	12 / 192
323020S	5/8	21.8	20.0	18.0	63	88	8 / 128
323022S	11/16	23.8	20.0	18.0	63	112	8 / 128
323024S	3/4	25.8	21.0	20.0	63	126	6 / 96
323026S	13/16	27.8	25.0	20.0	63	126	6 / 96

Deep Socket

- Chrome vanadium alloy steel, polished, chrome plated.
- 4 ball retaining grooves.

3235 M

- 3/8" drive
- 6 points
- Metric size
- Thin walled design on square driving side
- DIN 3124 ,ISO 2725-1

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
323507M	7	10.8	17.8	10.0	63	52	20 / 320
323508M	8	12.0	17.8	12.0	63	52	18 / 288
323509M	9	13.2	17.8	12.0	63	56	18 / 288
323510M	10	14.5	17.8	12.0	63	60	15 / 240
323511M	11	15.8	17.8	15.0	63	68	15 / 240
323512M	12	16.8	17.8	15.0	63	68	15 / 240
323513M	13	17.8	16.8	15.0	63	64	15 / 240
323514M	14	19.7	18.0	16.0	63	72	12 / 192
323515M	15	20.8	18.0	18.0	63	88	10 / 160
323516M	16	21.8	19.0	18.0	63	88	8 / 128
323517M	17	23.8	20.0	18.0	63	112	8 / 128
323518M	18	24.7	21.0	20.0	63	126	6 / 96
323519M	19	25.8	21.0	20.0	63	124	6 / 96
323521M	21	27.8	25.0	20.0	63	126	6 / 96
323522M	22	29.7	26.0	20.0	63	128	6 / 96
323524M	24	31.8	26.0	25.0	63	155	3 / 48

3235 S

- 3/8" drive
- 6 points
- Inch size
- Thin walled design on square driving side
- ANSI/ASME B107.1

KING TONY	inch	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
323510S	5/16	12.0	17.8	12.0	63	52	18 / 288
323512S	3/8	14.0	17.8	12.0	63	60	15 / 240
323514S	7/16	15.8	17.8	15.0	63	68	15 / 240
323516S	1/2	17.8	16.8	15.0	63	68	15 / 240
323518S	9/16	19.7	18.0	16.0	63	72	12 / 192
323520S	5/8	21.8	20.0	18.0	63	88	8 / 128
323522S	11/16	23.8	20.0	18.0	63	112	8 / 128
323524S	3/4	25.8	21.0	20.0	63	126	6 / 96
323526S	13/16	27.8	25.0	20.0	63	126	6 / 96

Star Socket

3375 M

- 3/8" drive star socket
- For torx external screws
- Chrome vanadium steel
- Polished, chrome plated
- DIN 3120

KING TONY	SIZE	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
337504M	E4	6.0	16.8	3.6	28	18	12 / 360
337505M	E5	7.0	16.8	4.0	28	19	12 / 360
337506M	E6	8.0	16.8	5.0	28	20	12 / 360
337507M	E7	8.9	16.8	6.0	28	21	12 / 360
337508M	E8	10.0	16.8	6.5	28	21	12 / 360
337510M	E10	12.0	16.8	7.0	28	22	12 / 360
337511M	E11	12.8	16.8	8.0	28	23	12 / 360
337512M	E12	14.3	16.8	9.0	28	25	12 / 360
337514M	E14	15.9	17.8	9.5	28	29	12 / 360
337516M	E16	18.0	19.8	10.5	28	39	10 / 300
337518M	E18	20.0	21.8	11.0	28	50	10 / 300

3275 M

- 3/8" drive star socket
- Long type
- DIN 3120

KING TONY	SIZE	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
327504M	E4	6.0	16.8	3.6	63	46	20 / 400
327505M	E5	7.0	16.8	4.0	63	48	20 / 400
327506M	E6	8.0	16.8	5.0	63	49	20 / 400
327507M	E7	8.9	16.8	6.0	63	51	20 / 320
327508M	E8	10.0	16.8	6.5	63	53	20 / 320
327510M	E10	12.0	16.8	7.0	63	57	18 / 288
327511M	E11	12.8	16.8	8.0	63	59	18 / 288
327512M	E12	14.3	16.8	9.0	63	62	18 / 288
327514M	E14	15.9	16.8	9.5	63	68	15 / 240
327516M	E16	17.8	17.8	10.5	63	85	15 / 240
327518M	E18	19.8	19.8	11.0	63	90	10 / 160

Thin Wall Deep Socket

- Chrome vanadium alloy steel, polished, chrome plated.
- 4 ball retaining grooves.

3215 M

NEW

- 3/8" drive
- 6 points
- Metric size
- Thin walled design on square driving side
- Specifically heat plug, glow plug

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
321510M	10	13.0	17.8	12.0	65	65	20 / 240
321512M	12	15.0	17.8	15.0	65	57	20 / 240

Thin walled design (D1)

Spark Plug Socket

- Chrome vanadium alloy steel, polished, chrome plated.
- 4 ball retaining grooves.

3630 3635 3660 3665

- 3/8" drive spark plug socket
- 6 / 12 points
- Size combined
  - 16.0mm (5/8")
  - 20.8mm (13/16")
- Inside sleeve
  - rubber
  - magnet
- DIN 3120

Magnet

363516

366516

363521

366521

363016

366016

363021

366021

KING TONY	TYPE	SIZE (mm)	(inch)	D (mm)	L (mm)	g	
363516	6 points Rubber	16.0	(5/8")	21	70	100	10 / 200
366516	6 points Magnet	16.0	(5/8")	21	70	105	10 / 200
363521	6 points Rubber	20.8	(13/16")	27.7	70	145	12 / 120
366521	6 points Magnet	20.8	(13/16")	27.7	70	150	12 / 120
363016	12 points Rubber	16.0	(5/8")	21	70	100	10 / 200
366016	12 points Magnet	16.0	(5/8")	21	70	105	10 / 200
363021	12 points Rubber	20.8	(13/16")	27.7	70	150	12 / 120
366021	12 points Magnet	20.8	(13/16")	27.7	70	155	12 / 120

36A0 36A5

- 3/8" drive spark plug socket
- 6 / 12 points
- Size combined - 14.0mm , 18.0mm ***(for motor use only)***
- Inside sleeve - spring
- DIN 3120

Spring

36A5

36A0

KING TONY	TYPE	SIZE (mm)	D (mm)	L (mm)	g	
36A514	6 points	14.0	18.9	63	69.4	12 / 192
36A518	6 points	18.0	23.8	63	98.2	8 / 128
36A014	12 points	14.0	18.9	63	65.4	12 / 192
36A018	12 points	18.0	23.8	63	98.0	8 / 128

Universal Socket

- Chrome vanadium alloy steel, polished, chrome plated.
- 4 ball retaining grooves.

3750 M

- 3/8" drive
- 12 points
- Metric size
- DIN 3120

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
375010M	10	14.5	18.8	9.0	48.0	59	15 / 240
375011M	11	15.8	18.8	10.0	48.0	57	15 / 240
375012M	12	17.0	18.8	10.0	48.0	56	15 / 240
375013M	13	18.3	18.8	11.0	48.0	56	15 / 240
375014M	14	19.8	18.8	11.0	49.5	58	12 / 192
375015M	15	21.6	18.8	13.0	49.5	64	10 / 160
375016M	16	21.8	18.8	13.0	51.0	63	10 / 160
375017M	17	23.7	18.8	14.0	52.5	67	8 / 128
375018M	18	25.3	18.8	14.0	53.4	64	6 / 96
375019M	19	25.7	18.8	16.0	55.8	73	6 / 96

Bit Socket

- Socket made from chrome vanadium alloy steel
- Bit made from silicon alloy steel (S2)
- Polished, chrome plated.

CAUTION In order to get normal life of bit socket, Always use within limited torque of bits.

3021

- 3/8" drive bit socket
- Phillips head
- DIN ISO 8764-1

KING TONY	No.	Overall Length (mm)	g	
302102	2	50	35	20 / 400
302103	3	50	36	20 / 400
302104	4	50	37	20 / 400

3022

- 3/8" drive bit socket
- Slotted head
- DIN 2380

KING TONY	Tip width (mm)	Tip thickness (mm)	Overall Length (mm)	g	
302205	5	1.0	50	36	20 / 400
302208	8	1.2	50	37	20 / 400
302210	10	1.6	50	38	20 / 400

3023

- 3/8" drive bit socket
- For torx internal screws
- DIN 3120

KING TONY	SIZE	Overall Length (mm)	g	
302308	T8	50	28	20 / 400
302309	T9	50	28	20 / 400
302310	T10	50	28	20 / 400
302315	T15	50	28	20 / 400
302320	T20	50	30	20 / 400
302325	T25	50	34	20 / 400
302327	T27	50	38	20 / 400
302330	T30	50	38	20 / 400
302340	T40	50	40	20 / 400
302345	T45	50	40	20 / 400
302350	T50	50	42	20 / 400

3025

- 3/8" drive bit socket
- Hexagon head
- DIN 7422/3120

KING TONY	mm	Overall Length (mm)	g	
302503	3	50	28	20 / 400
302504	4	50	30	20 / 400
302505	5	50	34	20 / 400
302506	6	50	38	20 / 400
302507	7	50	38	20 / 400
302508	8	50	40	20 / 400
302510	10	50	40	20 / 400
302512	12	50	42	20 / 400

Bit Socket

- Socket made from chrome vanadium alloy steel
- Bit made from silicon alloy steel (S2)
- Polished, chrome plated.

CAUTION In order to get normal life of bit socket, Always use within limited torque of bits.

3039

- 3/8" drive ribe bit socket
- Use for VW, Audi, Fait, cylinder head bolt
- DIN 3120

KING TONY	SIZE	Overall Length (mm)	g	
303904	M4	90	68	8 / 160
303905	M5	90	69	8 / 160
303906	M6	90	71	8 / 160
303907	M7	90	72	8 / 160
303908	M8	90	88	8 / 160
303909	M9	90	89	8 / 160
303910	M10	90	90	8 / 160

3027

- 3/8" drive bit socket
- For tamper resistant torx screws
- DIN 3120

KING TONY	SIZE	Overall Length (mm)	g	
302708	T8	50	28	20 / 400
302709	T9	50	28	20 / 400
302710	T10	50	28	20 / 400
302715	T15	50	28	20 / 400
302720	T20	50	30	20 / 400
302725	T25	50	34	20 / 400
302727	T27	50	38	20 / 400
302730	T30	50	38	20 / 400
302740	T40	50	40	20 / 400
302745	T45	50	40	20 / 400
302750	T50	50	42	20 / 400

302D NEW

- 3/8" drive bit socket
- For torx plus tamper screws
- DIN 3120

KING TONY	SIZE	Overall Length (mm)	g	
302D08	IPR8	50	33.2	20 / 400
302D09	IPR9	50	33.2	20 / 400
302D10	IPR10	50	34.0	20 / 400
302D15	IPR15	50	34.0	20 / 400
302D20	IPR20	50	34.0	20 / 400
302D25	IPR25	50	34.0	20 / 400
302D27	IPR27	50	34.0	20 / 400
302D30	IPR30	50	34.8	20 / 400
302D40	IPR40	50	38.8	20 / 400
302D45	IPR45	50	38.8	20 / 400
302D50	IPR50	50	40.0	20 / 400
302D55	IPR55	50	47.4	15 / 300
302D60	IPR60	50	51.2	12 / 240

Ratchet

- MATERIAL
  - handle of chrome vanadium alloy steel
  - (gear) driver of chrome molybdenum steel
- FINISHING
  - polished, chrome plated
  - black driver by phosphate sunk

3755 DIN 3122

- 3/8" drive reversible ratchet
- 5° gear action degree (72 teeth)

KING TONY	Total Length (inch)	(mm)	g	
3755-08G	8	200	387.0	2 / 40
3755DK	renewal kits		-	-

3755-08G

3755DK

8781012KT

3752 NEW

- 3/8" swivel head reversible quick release ratchet
- 5° gear action degree (72 teeth)
- Multi-angle design for difficult-to-reach fasteners

KING TONY	Overall Length (inch)	(mm)	g	
3752-09P	9	235	409	2 / 32
3752-09G	9	235	378	2 / 32
3752DK	renewal kits		-	-

3752-09P

3752-09G

3752DK

8781012KT

3760 DIN 3122

- 3/8" drive mini reversible ratchet
- 6° gear action degree (64 teeth)
- Five teeth pawl action

KING TONY	Total Length (inch)	(mm)	g	
3760-45	4 - 3/8	110	120.2	6 / 108
3760DK	renewal kits		-	-

3760-45

3760DK

8781012KT

3761 DIN 3122

- 3/8" drive reversible ratchet quick-release
- 11° gear action degree (32 teeth)
- Two teeth pawl action

KING TONY	Total Length (inch)	(mm)	g	
3761-08F	8	200	358.0	2 / 40
3761-08P	8	200	333.0	2 / 40
3761DK	renewal kits		-	-

3761-08F

3761-08P

3761DK

8781012KT

Ratchet

3769 DIN 3122

- 3/8" drive reversible ratchet
- 11° gear action degree (32 teeth)
- Two teeth pawl action

KING TONY	Total Length (inch)	(mm)	g	
3769-08F	8	200	358.0	2 / 40
3769-08P	8	200	358.0	2 / 40
3769DK	renewal kits		-	-

3769-08F

3769-08P

3769DK

8781012KT

3771 DIN 3122

- 3/8" drive reversible ratchet quick-release
- 11° gear action degree (32 teeth)
- Two teeth pawl action

KING TONY	Total Length (inch)	(mm)	g	
3771-08F	8	200	370	2 / 40
3771-08G	8	200	309	2 / 40
3771DK	renewal kits		-	-

3771-08F

3771-08G

3771DK

8781012KT

3779 DIN 3122

- 3/8" drive reversible ratchet
- 11° gear action degree (32 teeth)
- Two teeth pawl action

KING TONY	Total Length (inch)	(mm)	g	
3779-08F	8	200	355	2 / 40
3779-08G	8	200	295	2 / 40
3779DK	renewal kits		-	-

3779-08F

3779-08G

3779DK

8781012KT

3781 DIN 3122

- 3/8" drive flexible ratchet quick-release
- 11° gear action degree (32 teeth)
- Two teeth pawl action

KING TONY	Total Length (inch)	(mm)	g	
3781-11F	11	280	467	2 / 40
3781-11P	11	280	432	2 / 40
3781DK	renewal kits		-	-

3781-11F

3781-11P

3781DK

8781012KT

3789 DIN 3122

- 3/8" drive flexible ratchet
- 11° gear action degree (32 teeth)
- Two teeth pawl action

KING TONY	Total Length (inch)	(mm)	g	
3789-11F	11	280	480	2 / 40
3789-11P	11	280	490	2 / 40
3789DK	renewal kits		-	-

3789-11F

3789-11P

3789DK

8781012KT

Accessory

- MATERIAL - chrome vanadium alloy steel
- FINISHING - polished, chrome plated & black phosphate sunk

3221

DIN 3123

- 3/8" drive extension bar

KING TONY	Total Length (inch)	(mm)	g	
3221-16	1-3/4	44	39	14 / 224
3221-03	3	75	75	12 / 240
3221-06	6	150	146	6 / 120
3221-10	10	250	240	9 / 144
3221-18	18	450	428	1 / 50
3221-24	24	600	570	1 / 50

3221

8773KT

3223

DIN 3120

- 3/8" drive offset extension bar
- Max. torque 150 Nm

KING TONY	Total Length (inch)	(mm)	g	
3223-03	3	75	75	12 / 240
3223-06	6	150	146	6 / 120
3223-10	10	250	240	9 / 144

3223

Warning

The offset extension bar has less strength than normal extension bar. Do not use as a normal extension bar.

8773KT

3293

- 3/8" drive multi-function of extention bar and offset extension bar
- Hex key is applicable to the hex shank
- DIN 3120

KING TONY	Total Length (inch)	(mm)	g	
3293-03	3	75	80	12 / 240
3293-06	6	150	140	6 / 120
3293-10	10	250	240	9 / 144

8773KT

3311

- 3/8" drive flexible extension bar

KING TONY	Total Length (inch)	(mm)	g	
3311-06	6	150	148	5 / 100
3311-12	12	300	172	12 / 108

3311

8773KT

Accessory

- MATERIAL - chrome vanadium alloy steel
- FINISHING - polished, chrome plated & black phosphate sunk

3452 DIN 3122

- 3/8" drive flexible handle
- Action degree -180°

KING TONY	Total Length (inch)	Total Length (mm)	g	
3452-08F	8-1/2	215	259	4 / 80
3452-08G	8-1/2	215	278	2 / 40
3452-10F	10	250	319	4 / 80
3452-10G	10	250	325	3 / 60

3452-08F
3452-10F

3452-08G
3452-10G

3452DK

8781012KT

3571 DIN 3122

- 3/8" drive sliding T-handle

KING TONY	Total Length (inch)	Total Length (mm)	g	
3571-08	8	200	182	4 / 80

3571-08

8781012KT

3792 DIN 3123

- 3/8" drive universal joint

KING TONY	Total Length (inch)	Total Length (mm)	g	
3792	2	50	67	15 / 300

3792

8773KT

3812 3814 DIN 3123 ,ISO3316

- 3/8" drive adapter
- Convert to 1/4" drive or 1/2" drive
- 3812 → Max. torque 80.6 Nm

KING TONY	SPEC.	g	
3812	3/8"Fx1/4"M	31.5	12 / 192
3814	3/8"Fx1/2"M	47	12 / 360

1/4" drive (M)
1/2" drive (M)

3/8" drive (F)

3812 / 3814

8773KT

Bit Holder

3148

- 3/8" drive bit holder
- DIN 3120 / 3126

KING TONY	SIZE	Total Length (mm)	g	
314808S	1/4"	30	33	12 / 360
314810S	5/16"	30	35	12 / 360
314810M	10mm	30	35	12 / 360

Socket Set

3007 MR 01

- 5 PC. 3/8" drive socket wrench set

	Contents			
3007MR01	○ 366021	3789-11F	○ 366516	3221-06 3221-16

kg	
0.98	20

Extension Bar Set

3103 PR

- 3 PC. 3/8" drive offset extension bar set

	Contents
3103PR	3223 3" 6" 10"

kg	
0.4	35

3113 PR

- 3 PC. 3/8" drive extension bar set

	Contents
3113PR	3221 3" 6" 10"

kg	
0.5	35

Socket Rail Set

3013 MR SR
3513 MR

- 13 PC. 3/8" drive socket set
  - Socket rail 290 mm L
  - Rail with 13 PC. 3/8" drive clip

	Contents	
3013MR	○ 3330M 7 8 9 10 11 12 13 14 15 16 17 18 19	
3013SR	○ 3330S 1/4 5/16 11/32 3/8 7/16 15/32 1/2 9/16 19/32 5/8 11/16 3/4 13/16	8731213
3513MR	○ 3335M 7 8 9 10 11 12 13 14 15 16 17 18 19	

3013MR / 3513MR

kg	
0.60	35

Socket Rail Set

3106 PR
3116 PR

- 6 PC. 3/8" drive socket set
  - Socket rail 150 mm L
  - Rail with 6 PC. 3/8" drive clip

3106PR

3116PR

	Contents		
3106PR	3375M	E8 E10 E12 E14 E16 E18	8730606
3116PR	3275M	E4 E5 E8 E10 E12 E14	

	kg		Metal case size (mm)
3106PR	0.28	40	223 x 65 x 32 (0.016 cuft)
3116PR	0.39	50	

3105 PR

- 5 PC. 3/8" + 1/2" drive ribe bit socket set
  - Socket rail 150 mm L
  - Rail with 2 PC. 3/8" & 3 PC. 1/2" drive clip

	Contents		
3105PR	3039	M7 M8	8730605
	4049	M10 M12 M13	

kg	
0.75	1 / 30

Socket Rail

873

- 3/8" drive socket rail
- Rail length from 160 mm to 560 mm

KING TONY		CLIP	L (mm)	g	
870406		-	160	-	-
870311		-	280	-	-
870322		-	560	-	-
8730		-	-	-	-

Customer Selected

Socket Set

3508 MR SR

- 8 PC. 3/8" drive deep socket set

	Contents
3508MR	○ 3235M 10 11 12 13 14 16 17 19
3508SR	○ 3235S 3/8 7/16 1/2 9/16 5/8 11/16 3/4 13/16

3508MR

3508SR

kg		Metal case size (mm)
1.0	20	203 x 79 x 41 (0.023 cuft)

3020 MR SR 02
3520 MR 02

- 20 PC. 3/8" drive socket wrench set

	Contents			
3020MR02	○ 3330M	6 7 8 9 10 11 12 13 14 17 19 21	22 ○ 363021	3779-08F, 3221-03, 3221-06
3520MR02	○ 3335M		23 ○ 363521	3452-08G, 3792
3020SR02	○ 3330S	1/4 5/16 11/32 3/8 7/16 15/32 1/2 9/16 19/32 11/16 3/4 13/16 7/8	○ 363021	3571-08

3020MR02
3520MR02

3020SR02

kg		Metal case size (mm)
1.0	6	372 x 153 x 40 (0.08 cuft)

3023 MR
3523 MR

- 22 PC. 3/8" drive socket wrench set

	Contents		
3023MR	○ 3330M	6 7 8 9 10 11 12 13 14 15 16 17 19 20 21 22	3769-08F, 3571-08, 3452-08F, 3221-03, 3221-06, 3792
3523MR	○ 3335M		

3023MR/3523MR

kg		Metal case size (mm)
2.8	6	372 x 153 x 40 (0.08 cuft)

3023 MR 04
3523 MR 04

- 22 PC. 3/8" drive socket wrench set

	Contents		
3023MR04	○ 3330M	6 7 8 9 10 11 12 13 14 15 16 17 19 20 21 22	3755-08G, 3571-08, 3452-08F, 3221-03, 3221-06, 3792
3523MR04	○ 3335M		

3023MR04 / 3523MR04

kg		Metal case size (mm)
3.0	6	372 x 153 x 40 (0.08 cuft)

Socket Set

3024 MR SR
3524 MR

- 24 PC. 3/8" drive socket wrench set

Contents				
3024MR	○ 3330M	6 7 8 9 10 11 13 14 17 19	3779-08G	⊕ 3021 2 3
3524MR	○ 3335M		3221-06	⊖ 3022 5 8
3024SR	○ 3330S	1/4 5/16 11/32 3/8 7/16 1/2 9/16 5/8 11/16 3/4	3792	● 3025 3 4 5 6 7 8 10

3024MR/3524MR

3024SR

kg		Metal case size (mm)
2.2	10	318 x 147 x 46 (0.076 cuft)

3027 MR SR
3527 MR

- 26 PC. 3/8" drive socket wrench set

Contents				
3027MR	○ 3330M	7 8 9 10 11 12 13 14 15 16 17 18 19	○ 3235M 8 10 11 12 13 14 16 17 19	3779-08G
3527MR	○ 3335M			3221-03
3027SR	○ 3330S	1/4 5/16 11/32 3/8 7/16 15/32 1/2 9/16 19/32 5/8 11/16 3/4 13/16		3792
	○ 3235S	5/16 3/8 7/16 1/2 9/16 5/8 11/16 3/4 13/16		3812

3027MR / 3527MR

3027SR

kg		Metal case size (mm)
2.6	10	318 x 147 x 46 (0.076 cuft)

Socket & Wrench Set

3034 MR
3534 MR

- 36 PC. 3/8" drive socket wrench set

	Contents		
3034MR	3330M: 6 7 8 9 10 11 13 14 17 19	3375: E4 E5 E6 E7 E8 E10 E12 E14 E16 E18	3452-10F, 3779-08G, 3571-08, 3221-03, 3221-06, 3792
3534MR	3335M: 6 7 8 9 10 11 13 14 17 19	3023: T8 T9 T10 T15 T20 T25 T27 T30 T40 T45	

3034MR / 3534MR

kg		Metal case size (mm)
3.1	6	372 x 153 x 40 (0.08 cuft)

3036 CR

- 36 PC. 3/8" drive socket wrench set

	Contents	
3036CR	3330M: 6 7 8 9 10 11 12 13 14 15 16 17 19 20 21 22	3769-08F, 3571-08, 3221-03, 3221-06, 3792
	3330S: 1/4 5/16 11/32 3/8 7/16 15/32 1/2 9/16 19/32 5/8 11/16 3/4 13/16 7/8	3452-08F

kg		Metal case size (mm)
3.27	6	372 x 153 x 40 (0.08 cuft)

3050 MR

- 50 PC. 3/8" drive combination socket set

	Contents	
3050MR	3235M: 8 10 12 13	363516, 363021
	3330M: 6 7 8 9 10 11 12 13 14 15 17 18 19 22	3792, 314810S
	1060: 8 10 12 13 14 17 19	3571-08, 3221-03, 3221-06
	1120: 3 4 5 6 7 8 10	1421 2x100, 6111-06
	1832T: T15 T20 T25 T30 T40 T45 T50	1422 5.5x100, 3734-10F

kg		Blow case size (mm)
4.65	4	405 x 310 x 80 (0.36 cuft)

Standard Socket

- Chrome vanadium alloy steel, polished, chrome plated.
- 4 ball retaining grooves.

○ 4330 M

- 1/2" drive
- 12 points
- Metric size
- Thin walled design on square driving side
- DIN 3124 ,ISO 2725-1

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
433008M	8	13.2	23.3	7.0	38	57	10 / 200
433009M	9	14.0	23.3	7.0	38	60	10 / 200
433010M	10	15.0	23.3	8.0	38	58	10 / 200
433011M	11	16.4	23.3	8.0	38	58	10 / 200
433012M	12	17.8	23.3	9.0	38	60	10 / 200
433013M	13	19.0	23.3	10.0	38	60	10 / 200
433014M	14	20.4	23.3	11.0	38	61	10 / 200
433015M	15	21.6	23.3	11.0	38	62	10 / 200
433016M	16	22.9	23.8	11.0	38	63	10 / 200
433017M	17	24.0	23.2	12.0	38	66	10 / 200
433018M	18	25.2	23.2	13.0	38	66	10 / 200
433019M	19	26.6	23.2	13.0	38	73	10 / 160
433020M	20	27.9	23.2	13.0	38	86	10 / 160
433021M	21	28.9	23.2	14.0	38	97	10 / 160
433022M	22	30.2	24.0	15.0	40	99	10 / 160
433023M	23	31.2	25.0	15.0	40	99	8 / 160
433024M	24	32.1	26.0	17.0	42	113	8 / 160
433025M	25	33.4	27.0	17.0	42	125	8 / 160
433026M	26	35.0	28.0	17.0	42	130	6 / 120
433027M	27	36.6	28.0	19.0	42	135	6 / 120
433028M	28	37.8	30.0	20.0	42	151	6 / 120
433029M	29	39.0	30.0	21.0	44	169	6 / 120
433030M	30	40.0	29.5	21.0	44	169	6 / 120
433032M	32	42.5	30.0	23.0	44	173	6 / 120
433033M	33	43.0	30.0	24.0	46	217	6 / 96
433036M	36	47.0	33.0	24.0	46	238	6 / 96

○ 4330 S

- 1/2" drive
- 12 points
- Inch size
- Thin walled design on square driving side
- ANSI/ASME B107.1

KING TONY	inch	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
433010S	5/16	13.2	21.8	7.0	38	55	10 / 200
433012S	3/8	15.0	21.8	7.0	38	59	10 / 200
433013S	13/32	15.0	23.3	7.0	38	58	10 / 200
433014S	7/16	16.4	23.3	8.0	38	60	10 / 200
433015S	15/32	18.0	23.3	8.0	38	62	10 / 200
433016S	1/2	19.0	23.3	10.0	38	62	10 / 200
433018S	9/16	20.4	23.3	11.0	38	62	10 / 200
433019S	19/32	21.6	23.3	11.0	38	64	10 / 200
433020S	5/8	22.9	24.0	11.0	38	62	10 / 200
433022S	11/16	24.0	23.2	12.0	38	70	10 / 200
433024S	3/4	26.8	23.2	13.0	38	83	10 / 160
433025S	25/32	28.0	23.2	13.0	38	85	10 / 160
433026S	13/16	28.6	23.2	13.0	38	95	10 / 160
433028S	7/8	30.2	24.0	15.0	40	102	10 / 160
433030S	15/16	32.6	26.0	17.0	42	112	8 / 160
433032S	1	34.8	26.8	17.0	42	130	8 / 160
433034S	1-1/16	36.6	28.0	19.0	42	135	6 / 120
433036S	1-1/8	39.0	30.0	21.0	44	160	6 / 120
433038S	1-3/16	40.0	29.5	21.0	44	169	6 / 120
433040S	1-1/4	42.5	30.0	23.0	44	173	6 / 120

Standard Socket

- Chrome vanadium alloy steel, polished, chrome plated.
- 4 ball retaining grooves.

4335 M

- 1/2" drive
- 6 points
- Metric size
- Thin walled design on square driving side
- DIN 3124 ,ISO 2725-1

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
433506M	6	12.0	23.3	7.0	38	105	10 / 200
433507M	7	12.6	23.3	7.0	38	102	10 / 200
433508M	8	13.2	23.3	7.0	38	61	10 / 200
433509M	9	14.0	23.3	7.0	38	59	10 / 200
433510M	10	15.0	23.3	8.0	38	60	10 / 200
433511M	11	16.4	23.3	8.0	38	60	10 / 200
433512M	12	17.8	23.3	9.0	38	61	10 / 200
433513M	13	19.0	23.3	10.0	38	63	10 / 200
433514M	14	20.4	23.3	11.0	38	63	10 / 200
433515M	15	21.6	23.3	11.0	38	66	10 / 200
433516M	16	22.9	23.8	11.0	38	64	10 / 200
433517M	17	24.0	23.2	12.0	38	68	10 / 200
433518M	18	25.2	23.2	13.0	38	75	10 / 200
433519M	19	26.6	23.2	13.0	38	86	10 / 160
433520M	20	27.9	23.2	13.0	38	95	10 / 160
433521M	21	28.9	23.2	14.0	38	97	10 / 160
433522M	22	30.2	24.0	15.0	40	105	10 / 160
433523M	23	31.2	25.0	15.0	40	118	8 / 160
433524M	24	32.1	26.0	17.0	42	138	8 / 160
433525M	25	33.4	27.0	17.0	42	141	8 / 160
433526M	26	35.0	28.0	17.0	42	158	6 / 120
433527M	27	36.6	28.0	19.0	42	161	6 / 120
433528M	28	37.8	30.0	20.0	42	162	6 / 120
433529M	29	39.0	30.0	21.0	44	199	6 / 120
433530M	30	40.0	29.5	21.0	44	214	6 / 120
433532M	32	42.5	30.0	23.0	44	236	6 / 120
433533M	33	43.0	30.0	24.0	46	227	6 / 96
433534M	34	45.0	30.0	24.0	46	231	6 / 96
433536M	36	47.0	33.0	24.0	46	248	6 / 96
433538M	38	49.0	34.0	25.0	50	241	6 / 60
433539M	39	50.0	34.0	25.0	50	240	6 / 60
433541M	41	53.0	36.0	27.0	53	284	6 / 60
433546M	46	59.0	40.0	30.0	58	500	4 / 32

4335 S

- 1/2" drive
- 6 points
- Inch size
- Thin walled design on square driving side
- ANSI/ASME B107.1

KING TONY	inch	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
433510S	5/16	13.2	21.8	7.0	38	60	10 / 200
433512S	3/8	15.0	21.8	7.0	38	58	10 / 200
433514S	7/16	16.4	23.3	8.0	38	60	10 / 200
433515S	15/32	18.0	23.3	8.0	38	63	10 / 200
433516S	1/2	19.0	23.3	10.0	38	61	10 / 200
433518S	9/16	20.4	23.3	11.0	38	61	10 / 200
433519S	19/32	21.6	23.3	11.0	38	65	10 / 200
433520S	5/8	22.9	24.0	11.0	38	60	10 / 200
433522S	11/16	24.0	23.2	12.0	38	67	10 / 200
433524S	3/4	26.8	23.2	13.0	38	87	10 / 160
433525S	25/32	28.0	23.2	13.0	38	96	10 / 160
433526S	13/16	28.6	23.2	13.0	38	91	10 / 160
433528S	7/8	30.2	24.0	15.0	40	102	10 / 160
433530S	15/16	32.6	26.0	17.0	42	118	8 / 160
433532S	1	34.8	26.8	17.0	42	143	8 / 160
433534S	1-1/16	36.6	28.0	19.0	42	167	6 / 120
433536S	1-1/8	39.0	30.0	21.0	44	163	6 / 120
433538S	1-3/16	40.0	29.5	21.0	44	214	6 / 120
433540S	1-1/4	42.5	30.0	23.0	44	226	6 / 120

Deep Socket

- Chrome vanadium alloy steel, polished, chrome plated.
- 4 ball retaining grooves.

○ 4230 M

- 1/2" drive
- 12 points
- Metric size
- Thin walled design on square driving side
- DIN 3124 ,ISO 2725-1

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
423008M	8	13.2	22.0	16	77	107	6 / 120
423009M	9	14.0	22.0	16	77	112	6 / 120
423010M	10	15.2	23.7	24	77	116	6 / 120
423011M	11	16.3	23.7	24	77	119	6 / 120
423012M	12	17.7	23.7	24	77	123	6 / 120
423013M	13	18.7	23.7	24	77	125	6 / 120
423014M	14	20.2	23.7	35	77	138	6 / 120
423015M	15	21.3	23.7	35	77	138	6 / 120
423016M	16	22.6	23.7	35	77	147	6 / 96
423017M	17	23.7	23.2	35	77	151	6 / 96
423018M	18	25.5	23.2	35	77	182	6 / 96
423019M	19	26.7	23.2	35	77	176	6 / 96
423020M	20	27.7	24.0	35	77	201	6 / 96
423021M	21	28.7	25.0	35	77	220	6 / 96
423022M	22	29.8	26.0	35	77	205	6 / 96
423023M	23	31.2	27.5	35	77	207	5 / 60
423024M	24	31.8	28.5	35	77	195	5 / 60
423025M	25	33.4	29.5	35	77	227	5 / 60
423026M	26	34.8	30.5	35	77	252	5 / 60
423027M	27	36.6	31.5	34	77	304	5 / 60
423028M	28	37.8	32.5	34	77	304	5 / 50
423029M	29	38.8	33.5	34	77	308	5 / 50
423030M	30	39.8	34.5	34	77	319	5 / 50
423032M	32	41.8	36.0	34	77	334	5 / 50
423033M	33	43.8	38.5	35	77	360	4 / 48
423036M	36	46.8	40.5	36	77	443	2 / 40

○ 4230 S

- 1/2" drive
- 12 points
- Inch size
- Thin walled design on square driving side
- ANSI/ASME B107.1

KING TONY	inch	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
423010S	5/16	13.2	22.0	9	77	107	6 / 120
423012S	3/8	14.7	22.0	10	77	116	6 / 120
423014S	7/16	16.3	23.7	12	77	119	6 / 120
423016S	1/2	18.7	23.7	14	77	125	6 / 120
423018S	9/16	20.2	23.7	15	77	138	6 / 120
423020S	5/8	22.6	23.7	17	77	147	6 / 96
423022S	11/16	23.7	23.2	35	77	151	6 / 96
423024S	3/4	26.7	23.2	35	77	176	6 / 96
423026S	13/16	28.6	25.0	37	77	190	6 / 96
423028S	7/8	29.8	26.0	37	77	203	6 / 96
423030S	15/16	31.8	28.5	37	77	205	5 / 60
423032S	1	33.8	29.5	37	77	277	5 / 60
423034S	1-1/16	36.6	31.5	28	77	305	5 / 60
423036S	1-1/8	37.8	32.5	28	77	306	5 / 50
423038S	1-3/16	39.8	34.5	34	77	319	5 / 50
423040S	1-1/4	41.8	36.0	34	77	330	5 / 50

Deep Socket

- Chrome vanadium alloy steel, polished, chrome plated.
- 4 ball retaining grooves.

4235 M

- 1/2" drive
- 6 points
- Thin walled design on square driving side
- Metric size
- DIN 3124 ,ISO 2725-1

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
423508M	8	13.2	22.0	16	77	113	6 / 120
423509M	9	14.0	22.0	16	77	114	6 / 120
423510M	10	15.2	23.7	24	77	116	6 / 120
423511M	11	16.3	23.7	24	77	118	6 / 120
423512M	12	17.7	23.7	24	77	125	6 / 120
423513M	13	18.7	23.7	24	77	124	6 / 120
423514M	14	20.2	23.7	35	77	127	6 / 120
423515M	15	21.3	23.7	35	77	140	6 / 120
423516M	16	22.6	23.7	35	77	139	6 / 96
423517M	17	23.7	23.2	35	77	132	6 / 96
423518M	18	25.5	23.2	35	77	136	6 / 96
423519M	19	26.7	23.2	35	77	151	6 / 96
423520M	20	27.7	24.0	35	77	194	6 / 96
423521M	21	28.7	25.0	35	77	163	6 / 96
423522M	22	29.8	26.0	35	77	166	6 / 96
423523M	23	31.2	27.5	35	77	208	5 / 60
423524M	24	31.8	28.5	35	77	212	5 / 60
423525M	25	33.4	29.5	35	77	224	5 / 60
423526M	26	34.8	30.5	35	77	244	5 / 60
423527M	27	36.6	31.5	34	77	270	5 / 60
423528M	28	37.8	32.5	34	77	312	5 / 50
423529M	29	38.8	33.5	34	77	309	5 / 50
423530M	30	39.8	34.5	34	77	307	5 / 50
423532M	32	41.8	36.0	34	77	334	5 / 50
423533M	33	43.8	38.5	35	77	346	4 / 48
423536M	36	46.8	40.5	36	77	410	2 / 40
423538M	38	49.0	40.5	38	77	620	2 / 40
423541M	41	53.0	40.5	40	77	665	2 / 24

4235 S

- 1/2" drive
- 6 points
- Inch size
- Thin walled design on square driving side
- ANSI/ASME B107.1

KING TONY	inch	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
423510S	5/16	13.2	22.0	16	77	116	6 / 120
423512S	3/8	14.7	22.0	16	77	116	6 / 120
423514S	7/16	16.3	23.7	24	77	118	6 / 120
423516S	1/2	18.7	23.7	24	77	130	6 / 120
423518S	9/16	20.2	23.7	35	77	138	6 / 120
423520S	5/8	22.6	23.7	35	77	139	6 / 96
423522S	11/16	23.7	23.2	35	77	115	6 / 96
423524S	3/4	26.7	23.2	35	77	140	6 / 96
423526S	13/16	28.6	25.0	35	77	163	6 / 96
423528S	7/8	29.8	26.0	35	77	166	6 / 96
423530S	15/16	31.8	28.5	35	77	195	5 / 60
423532S	1	33.8	29.5	35	77	277	5 / 60
423534S	1-1/16	36.6	31.5	34	77	239	5 / 60
423536S	1-1/8	37.8	32.5	34	77	309	5 / 50
423538S	1-3/16	39.8	34.5	34	77	307	5 / 50
423540S	1-1/4	41.8	36.0	34	77	334	5 / 50
423542S	1-5/16	44.0	38.5	35	77	377	4 / 48
423544S	1-3/8	46.0	38.5	35	77	401	2 / 40
423546S	1-7/16	47.5	40.5	36	77	424	2 / 40
423548S	1-1/2	49.0	40.5	38	77	461	2 / 40

Deep Socket

- Chrome vanadium alloy steel, polished, chrome plated.
- 4 ball retaining grooves.

4245 M

- 1/2" drive
- 6 points
- Thin walled design on square driving side
- Metric size
- DIN 3120

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
424508M	8	13.2	22.0	9.0	90	110	6/120
424509M	9	14.0	22.0	10.0	90	113	6/120
424510M	10	15.2	23.7	11.0	90	133	6/120
424512M	12	17.7	23.7	13.0	90	155	6/120
424513M	13	18.7	23.7	14.0	90	157	6/120
424514M	14	20.2	23.7	15.0	90	162	6/120

4255 M

- 1/2" drive
- 6 points
- Thin walled design on square driving side
- Metric size
- DIN 3120

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
425508M	8	13.2	22.0	20.0	120	135	6/96
425509M	9	14.0	22.0	25.0	120	145	6/96
425510M	10	15.2	23.7	32.0	120	162	6/96
425512M	12	17.7	23.7	32.0	120	200	6/96
425513M	13	18.7	23.7	32.0	120	202	6/96
425514M	14	20.2	23.7	32.0	120	217	6/96

Star Socket

- Chrome vanadium alloy steel, polished, chrome plated.
- 4 ball retaining grooves.

4375 M

- 1/2" drive star socket
- For torx external screws
- Chrome vanadium steel
- Polished, chrome plated
- DIN 3120

KING TONY	SIZE	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
437510M	E10	13.2	23.8	7.5	37	60	10 / 200
437512M	E12	15.0	23.8	9.0	37	62	10 / 200
437514M	E14	16.4	23.8	10.0	37	64	10 / 200
437516M	E16	18.8	23.8	11.0	37	68	10 / 200
437518M	E18	20.5	23.8	12.5	39	72	10 / 200
437520M	E20	22.8	23.8	14.0	39	74	10 / 200
437522M	E22	24.6	23.8	16.0	39	75	10 / 200
437524M	E24	26.5	23.8	16.0	39	83	10 / 160

4275 M

- 1/2" drive star socket
- Long type

KING TONY	SIZE	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
427510M	E10	13.2	23.8	7.5	77	109	6 / 120
427512M	E12	15.0	23.8	9.0	77	119	6 / 120
427514M	E14	16.4	23.8	10.0	77	125	6 / 120
427516M	E16	18.8	23.8	11.0	77	138	6 / 120
427518M	E18	20.5	23.8	12.5	77	149	6 / 120
427520M	E20	22.8	23.8	14.0	77	167	6 / 120
427522M	E22	24.6	23.8	16.0	77	172	6 / 96
427524M	E24	26.5	23.8	16.0	77	191	6 / 96

Square Socket

4014 M

- 1/2" drive square sockets
- 4 ball retaining grooves
- Chrome vanadium steel
- Polished,chrome plated
- DIN 3120

KING TONY	SIZE (mm)	D (mm)	ℓ (mm)	L (mm)	g	
401408M	8.0	23.5	13.5	35	60	10 / 200
401409M	9.5	23.5	13.5	35	68	10 / 200
401410M	10.0	23.5	13.5	35	72	10 / 200
401411M	10.5	23.5	13.5	35	78	10 / 200
401412M	12.0	23.5	13.5	35	90	10 / 200
401413M	12.7	23.5	13.5	35	97	10 / 200
401414M	13.5	23.5	13.5	35	106	10 / 200
401419M	19.0	25.0	15.5	40	130	10 / 160

Bit Holder

4148

- 1/2" drive bit holder

KING TONY	SIZE	Overall Length (mm)	g	
414808S	1/4"	38	50	10 / 200
414810S	5/16"	38	60	10 / 200
414810M	10mm	38	65	10 / 200

Spark Plug Socket

- Chrome vanadium alloy steel, polished, chrome plated
- 4 ball retaining grooves

4630 4635
4660 4665
463016 466016

- 1/2" drive spark plug socket
- 6 / 12 points
- Size combined
  - 16.0mm (5/8")
  - 20.8mm (13/16")
- Inside sleeve
  - rubber
  - magnet
- DIN 3120

Magnet

KING TONY	TYPE	SIZE (mm) (inch)	D (mm)	L (mm)	g	
463516	6 points Rubber	16.0 (5/8")	20.75	70	110	10 / 200
466516	6 points Magnet	16.0 (5/8")	20.75	70	115	10 / 200
463016	12 points Rubber	16.0 (5/8")	20.75	70	110	10 / 200
466016	12 points Magnet	16.0 (5/8")	20.75	70	115	10 / 200
463521	6 points Rubber	20.8 (13/16")	27.7	70	155	12 / 120
466521	6 points Magnet	20.8 (13/16")	27.7	70	160	12 / 120
463021	12 points Rubber	20.8 (13/16")	27.7	70	160	12 / 120
466021	12 points Magnet	20.8 (13/16")	27.7	70	165	12 / 120

463516 -Thin walled design

466516 -Thin walled design

463016 -Thin walled design

466016 -Thin walled design

463021

466021

463521

466521

Bit Socket

- Socket made from chrome vanadium alloy steel
- Bit made from silicon alloy steel (S2)
- Polished, chrome plated.

CAUTION In order to get normal life of bit socket, Always use within limited torque to bits.

⊕ 4021

- 1/2" drive bit socket
- Phillips head
- DIN ISO 8764-1

KING TONY	No.	Overall Length (mm)	g	
402102	2	60	77	10 / 180
402103	3	60	77	10 / 180
402104	4	60	77	10 / 180

⊖ 4022

- 1/2" drive bit socket
- Slotted head
- DIN 5264/3120

KING TONY	Tip width (mm)	Tip thickness (mm)	Overall Length (mm)	g	
402208	8	1.2	60	77	10 / 180
402210	10	2.0	60	83	10 / 180
402212	12	2.2	60	110	10 / 180
402214	14	2.5	60	112	10 / 180
402216	16	2.5	60	113	10 / 180

◉ 4025
◉ 4035

- 1/2" drive bit socket
- Hexagon head
- DIN 7422

4025

4035

KING TONY	mm	Overall Length (mm)	g	
402503	3	60	68	10 / 180
402504	4	60	68	10 / 180
403504	4	80	90	6 / 120
402505	5	60	70	10 / 180
403505	5	80	90	6 / 120
402506	6	60	72	10 / 180
403506	6	80	90	6 / 120
402507	7	60	75	10 / 180
403507	7	80	90	6 / 120
402508	8	60	75	10 / 180
403508	8	80	93	6 / 120
402510	10	60	85	10 / 180
403510	10	80	107	6 / 120
402512	12	60	117	10 / 180
403512	12	80	145	6 / 120
402514	14	60	120	10 / 180
403514	14	80	145	6 / 120
402517	17	66	153	12 / 120
403517	17	80	200	6 / 120
402519	19	66	225	10 / 120
403519	19	80	245	6 / 96

◉ 4026
◉ 4036
◉ 4066

- 1/2" drive bit socket
- Spline head
- DIN 3120

4026

4036

4066

KING TONY	SIZE	Overall Length (mm)	g	
402605	M 5	60	70	10 / 180
402606	M 6	60	72	10 / 180
403606	M 6	80	85	6 / 120
402608	M 8	60	73	10 / 180
403608	M 8	80	90	6 / 120
402610	M10	60	85	10 / 180
403610	M10	80	107	6 / 120
402612	M12	60	113	10 / 180
403612	M12	80	142	6 / 120
402614	M14	60	117	10 / 180
406608	M8	140	109	6 / 120
406610	M10	140	138	6 / 120
406612	M12	140	175	6 / 120

Bit Socket

- Socket made from chrome vanadium alloy steel
- Bit made from silicon alloy steel (S2)
- Polished, chrome plated.

CAUTION In order to get normal life of bit socket, Always use within limited torque to bits.

402B

- Spline head
- Tamper resistant type

KING TONY	SIZE	Total Length (mm)	g	
402B16	M 16	66	150	10 / 120
402B18	M 18	66	201	10 / 120

4023
4033

- 1/2" drive bit socket
- For torx internal screws DIN 3120

4023

4033

KING TONY	SIZE	Total Length (mm)	g	
402320	T20	60	72	10 / 180
403320	T20	80	78	6 / 120
402325	T25	60	72	10 / 180
403325	T25	80	79	6 / 120
402327	T27	60	72	10 / 180
403327	T27	80	80	6 / 120
402330	T30	60	75	10 / 180
403330	T30	80	80	6 / 120
402340	T40	60	75	10 / 180
403340	T40	80	81	6 / 120
402345	T45	60	80	10 / 180
403345	T45	80	81	6 / 120
402350	T50	60	82	10 / 180
403350	T50	80	82	6 / 120
402355	T55	60	85	10 / 180
403355	T55	80	99	6 / 120
402360	T60	60	115	10 / 180
403360	T60	80	134	6 / 120
NEW 402365	T65	60	116	10 / 180
NEW 403365	T65	80	138	6 / 120
402370	T70	60	116	10 / 180
403370	T70	80	143	6 / 120

404108

- 1/2" drive bit socket
- Spline head
- DIN 3120

Use for Toyota Tercel cylinder head bolt

KING TONY	SIZE	Total Length (mm)	g	
404108	M8.9	100	129.4	6 / 120

4027
4037

- 1/2" drive bit socket
- For tamper resistant torx screws
- DIN 3120

4027

4037

KING TONY	SIZE	Total Length (mm)	g	
402720	T20	60	72	10 / 180
403720	T20	80	78	6 / 120
402725	T25	60	72	10 / 180
403725	T25	80	79	6 / 120
402727	T27	60	72	10 / 180
403727	T27	80	80	6 / 120
402730	T30	60	75	10 / 180
403730	T30	80	80	6 / 120
402740	T40	60	75	10 / 180
403740	T40	80	81	6 / 120
402745	T45	60	80	10 / 180
403745	T45	80	81	6 / 120
402750	T50	60	82	10 / 180
403750	T50	80	82	6 / 120
402755	T55	60	85	10 / 180
403755	T55	80	99	6 / 120
402760	T60	60	115	10 / 180
403760	T60	80	134	6 / 120

Ribe Bit Socket

4049

- 1/2" drive ribe bit socket
- Use for VW, Audi, Fait, cylinder head bolt

KING TONY	SIZE	Total Length (mm)	g	
404904	M4	100	94	6 / 120
404905	M5	100	95	6 / 120
404906	M6	100	96	6 / 120
404907	M7	100	97	6 / 120
404908	M8	100	98	6 / 120
404909	M9	100	100	6 / 120
404910	M10	100	106	6 / 120
404925	M10.5	100	110	6 / 120
404912	M12	100	132	6 / 120
404913	M13	100	162	6 / 120
404914	M14	100	164	6 / 120
404916	M16	100	166	6 / 120

Ratchet

- MATERIAL
  - handle of chrome vanadium alloy steel
  - (gear) driver of chrome molybdenum steel
- FINISHING
  - polished, chrome plated
  - black driver by phosphate sunk

4725 DIN 3122

- 1/2" drive reversible ratchet
- 8° gear action degree (45 teeth)

KING TONY	Total Length (inch)	(mm)	g	
4725-10F	10	250	573.0	2 / 40
4725-10G	10	250	617.0	1 / 20
4725-12F	12	300	642.0	2 / 40
4725-12G	12	300	762..0	1 / 20
4725-12B	12	300	644.0	2 / 40
4725DK01	renewal kits		-	-

4725-10F
4725-12F

4725-10G
4725-12G

4725-12B

4725DK01

4755 DIN 3122

- 1/2" drive reversible ratchet
- 5° gear action degree (72 teeth)

KING TONY	Total Length (inch)	(mm)	g	
4755-10G	10	250	570.0	1 / 20
4755DK	renewal kits		-	1 / 20

4755-10G

4755DK

4752 NEW

- 1/2" swivel head reversible quick release ratchet
- 5° gear action degree (72 teeth)
- Multi-angle design for difficult-to-reach fasteners

KING TONY	Overall Length (inch)	(mm)	g	
4752-12P	12	300	668	1 / 20
4752-12G	12	300	686	1 / 20
4752DK	renewal kits		-	-

4752-09P

4752-12G

4752DK

4760 DIN 3122

- 1/2" drive mini reversible ratchet
- 6° gear action degree (64 teeth)
- Two teeth pawl action

KING TONY	Total Length (inch)	(mm)	g	
4760-05	4-3/4	120	222.4	5 / 108
4760DK	renewal kits		-	-

4760-05

4760DK

Ratchet

- MATERIAL
  - handle of chrome vanadium alloy steel
  - (gear) driver of chrome molybdenum steel
- FINISHING
  - polished, chrome plated
  - black driver by phosphate sunk

4760-05G

DIN 3122 NEW

- 1/2" drive mini reversible ratchet
- 6° gear action degree (64 teeth)
- Two teeth pawl action

KING TONY	Total Length (inch)	(mm)		
4760-05G	4-3/4	120	221	4 / 72
4760DK	renewal kits		-	-

4760-05G

4760DK

8781013KT

4762

DIN 3122

- 1/2" drive reversible ratchet quick-release
- 11° gear action degree (32 teeth)
- Two teeth pawl action

KING TONY	Total Length (inch)	(mm)		
4762-10G	10	250	565	5 / 30
4762-10F	10	250	590	6 / 36
4762-10P	10	250	563	6 / 36
4762-15G	15	375	711	5 / 20
4762-15F	15	375	750	6 / 24
4762-15P	15	375	728	6 / 24
4762DK	renewal kits		-	-

4762-10G / 4762-15G

4762-10F / 4762-15F

4762-10P / 4762-15P

4762DK

8781013KT

4767

DIN 3122

- 1/2" drive reversible ratchet (19mm socket included)
- 11° gear action degree (32 teeth)
- Two teeth pawl action

KING TONY	Total Length (inch)	(mm)		
4767-10G	10	250	530	5 / 30
4767-10F	10	250	563	6 / 36
4767-15G	15	375	690	5 / 20
4767-15F	15	375	736	6 / 24
4767DK	renewal kits		-	-

4767-10G / 4767-15G

4767-10F / 4767-15F

19mm 12 point

4767DK

8781013KT

4768

DIN 3122

- 1/2" drive reversible ratchet
- 11° gear action degree (32 teeth)
- Two teeth pawl action

KING TONY	Total Length (inch)	(mm)		
4768-10G	10	250	549	1 / 20
4768-10F	10	250	589	6 / 36
4768-10P	10	250	562	2 / 40
4768-15G	15	375	720	5 / 20
4768-15F	15	375	776	6 / 24
4768-15P	15	375	734	6 / 24
4768DK	renewal kits		-	-

4768-10G / 4768-15G

4768-10F / 4768-15F

4768-10P / 4768-15P

4768DK

8781013KT

Ratchet

4771 DIN 3122

- 1/2" drive reversible ratchet quick-release
- 11° gear action degree (32 teeth)
  Two teeth pawl action

KING TONY	Total Length (inch)	(mm)	g	
4771-10B	10	250	624	2 / 40
4771-10F	10	250	659	2 / 40
4771-10G	10	250	623	1 / 20
4771DK01	renewal kits		-	-

4771-10B

4771-10F

4771-10G

4771DK01

8781013KT

4779 DIN 3122

- 1/2" drive reversible ratchet
- 11° gear action degree (32 teeth)
  Two teeth pawl action

KING TONY	Total Length (inch)	(mm)	g	
4779-10B	10	250	590	2 / 40
4779-10F	10	250	615	2 / 40
4779-10G	10	250	580	1 / 20
4779DK01	renewal kits		-	-

4779-10B

4779-10F

4779-10G

4779DK01

8781013KT

4781 DIN 3122

- 1/2" drive flexible ratchet quick-release
- 11° gear action degree (32 teeth)
- Two teeth pawl action

KING TONY	Total Length (inch)	(mm)	g	
4781-12F	12	300	792	1 / 20
4781-12P	12	300	758	1 / 20
4781DK	renewal kits		-	-

4781-12F

4781-12P

4781DK

8781013KT

4789 DIN 3122

- 1/2" drive flexible ratchet
- 11° gear action degree (32 teeth)
- Two teeth pawl action

KING TONY	Total Length (inch)	(mm)	g	
4789-12F	12	300	735	1 / 20
4789-12P	12	300	735	1 / 20
4789DK	renewal kits		-	-

4789-12F

4789-12P

4789DK

8781013KT

Accessory

- MATERIAL - chrome vanadium alloy steel
- FINISHING - polished, chrome plated

4121

- 1/2" drive adjustable handle
- Push-Lock design

KING TONY	Total Length (inch)	(mm)	g	
4121-11GR	11-1/2	295	544	1 / 20

4121-11GR

4221

- 1/2" drive extension bar

KING TONY	Total Length (inch)	(mm)	g	
4221-18	18	450	550	1 / 20
4221-24	24	600	685	1 / 20
4221-30	30	750	860	1 / 20
4221-36	36	900	1030	1 / 20

4221

4223 DIN 3120

- 1/2" drive offset extension bar
- Max. torque 320 Nm

KING TONY	Total Length (inch)	(mm)	g	
4223-02	2	55	94	12 / 216
4223-05	5	125	198	4 / 80
4223-10	10	250	357	4 / 64

Warning
The offset extension bar has less strength than normal extension bar. Do not use as a normal extension bar.

4223

8774KT

4251 DIN 3123

- 1/2" drive extension bar

KING TONY	Total Length (inch)	(mm)	g	
4251-02	2	55	98	12 / 216
4251-03	3	75	138	6 / 120
4251-04	4	100	163	4 / 80
4251-05	5	125	192	4 / 80
4251-06	6	150	230	6 / 96
4251-08	8	200	270	4 / 64
4251-10	10	250	433	4 / 64

4251

8774KT

4293

- 1/2" drive multi-function of extention bar and offset extension bar.

KING TONY	Total Length (inch)	(mm)	g	
4293-02	2	55	55	12 / 216
4293-05	5	125	200	4 / 80
4293-10	10	250	420	4 / 64

4293

8774KT

Accessory

- MATERIAL - chrome vanadium alloy steel
- FINISHING - polished, chrome plated

4311 DIN 3122

- 1/2" drive speed brace

KING TONY	Total Length (inch)	(mm)	g	
4311-16F	16-1/4	412	545	5 / 40
4311-16G	16-1/4	412	545	5 / 40

4452 DIN 3122

- 1/2" drive flexible handle
- Action degree -180°

KING TONY	Total Length (inch)	(mm)	g	
4452-15F	15	375	720	2 / 24
4452-18F	18	450	828	2 / 20
4452-24F	24	600	1165	1 / 20
4452DK	renewal kits	(for 15F/18F)	62	250 / 250
4452DK1	renewal kits	(for 24F)		

4452

4452DK

8781013KT

4462 DIN 3122

- 1/2" drive flexible handle
- Action degree -180°

KING TONY	Total Length (inch)	(mm)	g	
4462-18F	18	463	1046	1 / 20
4462-24F	24	613	1350	1 / 20
4462DK	renewal kits		-	-

4462

4462DK

4572 DIN 3122

- 1/2" drive sliding T-handle

KING TONY	Total Length (inch)	(mm)	g	
4572-10	10	250	370	2 / 40
4572-12	12	300	433	3 / 60
4572DK	renewal kits		-	-

4572-10 / 4572-12

4572DK

8781013KT

4573 DIN 3120

- 1/2" drive sliding T-handle

KING TONY	Total Length (inch)	(mm)	g	
4573-10	10	250	497	2 / 40
4573DK	renewal kits		-	-

4573-10

4573DK

Accessory

- MATERIAL - chrome vanadium alloy steel
- FINISHING - polished, chrome plated & black phosphate sunk

4581 DIN 3122

- 1/2" drive 90° L-handle

KING TONY	Total Length (inch)	(mm)	g	
4581-10	10	250	429	2 / 40

4581-10

4583 DIN 3120

- 1/2" drive 105° L-handle

KING TONY	Total Length (inch)	(mm)	g	
4583-12	12-1/2	315	545	1 / 40

4583-12

4584 DIN 3120

- 1/2" drive 90° L-handle

KING TONY	Total Length (inch)	(mm)	g	
4584-12	12	300	550	1 / 40

4584-12

4791 DIN 3123, ISO 3316

- 1/2" drive universal joint

KING TONY	Total Length (inch)	(mm)	g	
4791	3	77.5	163	5 / 100

4791

8774KT

4813 4816 DIN 3123 ,ISO 3316

- 1/2" drive adapter
- Converting to 3/8" drive or 3/4" drive
- 4813 → Max. torque 280 Nm

KING TONY	SPEC.	g	
4813	1/2"Fx3/8"M	61	10 / 200
4816	1/2"Fx3/4"M	114	10 / 200

4813

3/8" drive(M)

4816

3/4" drive(M)

← 1/2"drive(F)

Socket Shelf Set

■ 4072 MR (172 PC.) SR (136 PC.)

■ 4572 MR (172 PC.) SR (136 PC.)

- 1/2" drive standard socket shelf set

4072MR / 4572MR

		Contents	Each Q'ty
4072MR	4330M	8 9 10 11 12 13 14 15 16 17 18	8
		19 20 21 22 23 24 25	7
4572MR	4335M	26 27 28 29 30	6
		32	5
4072SR	4330S	5/16 3/8 7/16 15/32 1/2 9/16 19/32 5/8 11/16	8
		3/4 25/32 13/16 7/8 15/16	7
4572SR	4335S	1 1-1/16 1-1/8 1-3/16	6
		1-1/4	5

	SPEC	kg	CUFT	Metal shelf size (mm)
4072MR 4572MR -A	87103	10.3	2.3	427 x 282 x 297
4072MR 4572MR -D	172 PC. socket content	26.0	0.6	
4072SR 4572SR -A	87103	10.3	2.3	
4072SR 4572SR -D	136 PC. socket content	24.7	0.6	

■ 4066 MR (165 PC.) SR (114 PC.)

■ 4566 MR (165 PC.)

- 1/2" drive standard socket shelf set

4066MR / 4566MR

		Contents	Each Q'ty
4066MR	4230M	8 9 10 11 12 13 14 15 16 17 18	8
		19 20 21 22 23 24	7
4566MR	4235M	26 27 28 29 30	6
		32	5
4066SR	4230S	5/16 3/8 7/16 1/2 9/16 5/8 11/16	8
		3/4 13/16 7/8 15/16 1	7
		1-1/16 1-1/8 1-3/16	6
		1-1/4	5

	SPEC	kg	CUFT	Metal shelf size (mm)
4066MR 4566MR -A	87103	10.3	2.3	427 x 282 x 297
4066MR 4566MR -D	165 PC socket content	40.5	2.1	
4066SR - A	87103	10.3	2.3	
4066SR - D	114 PC. socket content	30.2	2.1	

Socket Rail

■ 874

- 1/2" drive socket rail
- Rail length from 160 mm to 560 mm

KING TONY		CLIP	L (mm)	g	
870406		-	160	-	-
870410		-	260	-	-
870422		-	560	-	-
8740		-	-	-	-

Customer Selected

Socket Rail Set

4010 MR SR
4510 MR SR

- 8 PC. 1/2" drive socket set
- Socket rail 230mm L
  - Rail with 8 PC. 1/2" drive clips

	Contents		
4010MR	○ 4330M	10 12 13 14 17 19 21 22	8740908
4510MR	○ 4335M		
4010SR	○ 4330S	3/8 7/16 1/2 9/16 1/16 3/4 13/16 7/8	
4510SR	○ 4335S		

kg	
0.64	40

4106 PR

- 6 PC. 1/2" drive socket set
- Socket rail 230mm L
  - Rail with 6 PC. 1/2" drive clips

	Contents		
4106PR	✪ 4375M	E10 E12 E14 E16 E18 E20	8740906

kg	
0.51	40

4118 MR

- 8 PC. 1/2" drive socket set
- Socket rail 230mm L
  - Rail with 8 PC. 1/2" drive clips

	Contents		
4118MR	4014	8 9.5 10 10.5 12 12.7 13.5 19	8740908

kg	
0.57	40

4311 MR

- 11 PC. 1/2" drive socket set
- Socket rail 230mm L
  - Rail with 8 PC. 1/2" drive clips

	Contents		
4311MR	○ 4335M	10 11 13 14 15 17 18 19	4725-10G 4572-10 4251-05 8740908

kg	
1.92	12

Socket Rail Set

4116 PR

- 6 PC. 1/2" drive ribe bit socket set
  Socket rail 180mmL
  - Rail with 6 PC. 1/2" drive clips

	Contents	
4116PR	4049 M9 M10 M12 M13 M14 M16	8740706

kg	
0.38	1 / 20

4126 PR

- 4 PC. 1/2" drive socket set
- Socket rail 127mm L
  - Rail with 4 PC. 1/2" drive clips

	Contents	
4126PR	4026 M6 M8 M10 M12	8740504

kg	
0.38	1 / 50

4105 PR

- 5 PC. 1/2" drive socket set
- Socket rail 150mm L
  - Rail with 5 PC. 1/2" drive clips

	Contents	
4105PR	4026 M8 M10 M12 M14 4028 M16	8740605

kg	
0.57	1 / 50

4136 PR

- 4 PC. 1/2" drive socket set
- Socket rail 127mm L
  - Rail with 4 PC. 1/2" drive clips

	Contents	
4136PR	4036 M6 M8 M10 M12	8740504

kg	
0.46	2 / 40

Extension Bar Set

4104 PR

- 4 PC. 1/2" drive extension bar set

	Contents
4104PR	4251 3" 5" 6" 10"

kg	
0.84	1 / 25

Socket & Bit Socket Set

4208 MR SR
4308 MR

- 8 PC. 1/2" drive deep socket set

	Contents
4208MR	4230M: 12 13 14 17 19 21 22 23
4308MR	4235M: 12 13 14 17 19 21 22 23
4208SR	4230S: 1/2 9/16 5/8 11/16 3/4 13/16 7/8 15/16

4208MR / 4308MR

4208SR

kg		Metal case size (mm)
1.93	12	246 x 103 x 38 (0.034 cuft)

4215 MR

- 15 PC. 1/2" drive deep socket set

	Contents
4215MR	4230M: 10 11 12 13 14 15 16 17 19 21 22 24 27 30 32

kg		Metal case size (mm)
3.80	6	445 x 135 x 50 (0.107 cuft)

4315 MR

- 15 PC. 1/2" drive deep socket set

	Contents
4315MR	4235M: 10 11 12 13 14 15 16 17 19 21 22 24 27 30 32

kg		Metal case size (mm)
3.80	6	445 x 135 x 50 (0.107 cuft)

4109 PR
4119 PR

- 9 PC. 1/2" drive torx head bit socket set

	Contents
4109PR	4023: T20 T25 T27 T30 T40 T45 T50 T55 T60
4119PR	4033: T20 T25 T27 T30 T40 T45 T50 T55 T60

4109PR

4119PR

	kg		Metal case size (mm)
4109PR	1.03	20	198 x 105 x 32 (0.023 cuft)
4119PR	1.38		

4110 PR
4120 PR

- 9 PC. 1/2" drive hexagon head bit socket set

	Contents
4110PR	4025: 3 4 5 6 7 8 10 12 14
4120PR	4035: 4 5 6 7 8 10 12 14 17

4110PR

4120PR

	kg		Metal case size (mm)
4110PR	1.03	20	198 x 105 x 32 (0.023 cuft)
4120PR	1.38		

Socket & Wrench Set

4128 PR

- 8 PC. 1/2" drive spline socket set

	Contents	
4128PR	4026	M5 M6 M8 M10
	4028	M16
	4036	M8 M10 M12

kg		Metal case size (mm)
1.24	18	244 x 118 x 37 (0.038 cuft)

4220 MR
4320 MR

- 20 PC. 1/2" drive socket wrench set

	Contents		
4220MR	4330M	8 9 10 11 12 13 14 15 16 17 18 19 21 22 24 27	4755-10G, 4251-05, 4251-10, 4791
4320MR	4335M		

kg		Metal case size (mm)
3.83	6	445 x 135 x 50 (0.107 cuft)

4322 MR

- 24 PC. 1/2" drive socket wrench set

	Contents		
4322MR	4335M	10 11 12 13 14 15 17 19 22 24 27 30	4755-10G, 4251-05, 4251-10, 4791
	4025	4 5 6 7 8 10 12 14	

kg		Metal case size (mm)
5.30	4	445 x 187 x 50 (0.147 cuft)

4325 MR

- 24 PC. 1/2" drive socket wrench set

	Contents		
4325MR	4335M	10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 27 30 32	4779-10G, 4572-10, 4311-16G, 4251-05, 4251-10, 4791

kg		Metal case size (mm)
5.01	4	445 x 187 x 50 (0.147 cuft)

Socket Set

4501 MR

- 15 PC. 1/2" drive socket wrench set

Contents			
4501MR	○ 4335M	8 10 11 12 13 14 17 19 21 22 24 27	4779-10F, 4452-15F, 4251-05

kg		Metal case size (mm)
3.40	6	392 x 90 x 50 (0.062 cuft)

4012 MR SR
4512 MR SR

- 14 PC. 1/2" drive socket wrench set

Contents				
4012MR	○ 4330M	10 11 12 13 14 17 19 21 22 24	○ 463021	4768-10F
4512MR	○ 4335M		○ 463521	4251-05
4012SR	○ 4330S	3/8 7/16 15/32 1/2 9/16 11/16 3/4 13/16 7/8 15/16	○ 463021	4572-12
4512SR	○ 4335S		○ 463521	

4012MR / 4512MR

4012SR/4512SR

kg		Metal case size (mm)
3.50	6	445 x 135 x 50 (0.107 cuft)

4024 MR SR
4524 MR SR
4033 MR SR
4533 MR SR

- 24 PC. 1/2" drive socket wrench set

Contents				
4024MR	○ 4330M	10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 27 30 32	○ 463021	4725-12B, 4121-11GR, 4779-10B, 4223-02, 4573-10, 4583-12
4524MR	○ 4335M		○ 463521	
4033MR	○ 4330M		○ 463021	
4533MR	○ 4335M		○ 463521	
4024SR	○ 4330S	3/8 7/16 15/32 1/2 9/16 19/32 5/8 11/16 3/4 25/32 13/16 7/8 15/16 1 1-1/16 1-1/8 1-3/16 1-1/4	○ 463021	
4524SR	○ 4335S		○ 463521	
4033SR	○ 4330S	5/16 3/8 7/16 15/32 1/2 9/16 19/32 5/8 11/16 3/4 25/32 13/16 7/8 15/16 1 1-1/16 1-3/16 1-1/4	○ 463021	
4533SR	○ 4335S		○ 463521	

4033MR / 4533MR

4024SR / 4524SR

kg		Metal case size (mm)
5.7	4	445 x 187 x 50 (0.147 cuft)

Socket Set

4044 CR
4544 CR

- 43 PC. 1/2" drive socket wrench set

Contents			
4044CR	4330M	8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 30 32	4779-10B, 4121-11G, 4223-02, 4573-10, 4583-12, 4791
	4330S	3/8 7/16 1/2 9/16 5/8 11/16 3/4 13/16 7/8 15/16 1 1-1/8 1-3/16 1-1/4	
4544CR	4335M	8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 30 32	
	4335S	3/8 7/16 1/2 9/16 5/8 11/16 3/4 13/16 7/8 15/16 1 1-1/8 1-3/16 1-1/4	

4044CR / 4544CR

kg		Metal case size (mm)
8.5	2	476 x 282 x 57 (0.27 cuft)

4026 MR SR
4026 MR 03 SR 03
4026 MR 04
4526 MR SR
4526 MR 03 SR 03
4526 MR 04

- 24 PC. 1/2" drive socket wrench set

Contents				
4026MR	4330M	10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 27 30 32	463021, 463521, 4768-10F	
4526MR	4335M			
4026MR03	4330M		4791, 4779-10G	4572-12
4526MR03	4335M	8 10 11 13 14 15 16 17 18 19 20 21 22 23 24 27 30 32	4791	
4026MR04	4330M		4791, 4755-10G	4452-15F
4526MR04	4335M		4791	
4026SR	4330S	5/16 3/8 7/16 15/32 1/2 9/16 19/32 5/8 11/16 3/4 25/32 13/16 7/8 15/16 1 1-1/16 1-3/16 1-1/4	463021, 463521, 4768-10F	4251-05 4251-10
4526SR	4335S			
4026SR03	4330S		4791, 4779-10G	
4526SR03	4335S		4791	

4026MR / 4526MR

4026SR / 4526SR

4026MR03 / 4526MR03

4026MR04 / 4526MR04

kg		Metal case size (mm)
5.95	4	445 x 187 x 50 (0.147 cuft)

Socket Set

4032 MR SR
4532 MR SR

- 24 PC. 1/2" drive socket wrench set

Contents					
4032MR	○ 4330M	10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 27 30 32	○ 463021	4779-10F	
4532MR	○ 4335M		○ 463521	4452-15F	
4032SR	○ 4330S	5/16 3/8 7/16 15/32 1/2 9/16 19/32 5/8 11/16 3/4 25/32 13/16 7/8 15/16 1 1-1/16 1-3/16 1-1/4	○ 463021	4251-05 4251-10	
4532SR	○ 4335S		○ 463521	4791	

4032MR / 4532MR

4032SR / 4532SR

kg		Metal case size (mm)
5.6	4	445 x 187 x 50 (0.147 cuft)

4028 MR SR
4528 MR SR
4028 MR 02
4528 MR 02

- 24 PC. 1/2" drive socket wrench set

Contents					
4028MR	○ 4330M	10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 27 30 32	○ 463021	4779-10G	4572-10
4528MR	○ 4335M		○ 463521		
4028MR02	○ 4330M		○ 463021	4755-10G	4251-05 4251-10
4528MR02	○ 4335M		○ 463521		
4028SR	○ 4330S	3/8 7/16 15/32 1/2 9/16 19/32 5/8 11/16 3/4 25/32 13/16 7/8 15/16 1 1-1/16 1-1/8 1-3/16 1-1/4	○ 463021	4779-10G	4791
4528SR	○ 4335S		○ 463521		

4028MR / 4528MR

4028SR / 4528SR

kg		Metal case size (mm)
5.3	4	445 x 187 x 50 (0.147 cuft)

Socket Set

4042 CR / CR02
4542 CR / CR02

- 42 PC. 1/2" drive socket wrench set

	Contents		
4042CR	○ 4330M ○ 4330S: 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 27 30 32	○ 463021 ○ 463521	4768-10F 4452-18F 4572-12
4542CR	○ 4335M ○ 4335S		
4042CR02	○ 4330M: 5/16 3/8 7/16 1/2 9/16 19/32 5/8 11/16 3/4 25/32 13/16 7/8 15/16 1 1-1/16 1-1/8 1-3/16 1-1/4 ○ 4330S	4779-10G 4791	4251-05 4251-10
4542CR02	○ 4335M ○ 4335S		

4042CR / 4542CR

4042CR02 / 4542CR02

kg		Metal case size (mm)
8.5	2	476 x 282 x 57 (0.27 cuft)

4034 MR
4534 MR

- 33 PC. 1/2" drive socket wrench set

	Contents		
4034MR	○ 4330M: 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 32	○ 463021 ○ 463521	463516 4791 4251-03 4251-05 4251-10 4779-10F 4452-18F 4572-12
4534MR	○ 4335M		

4034MR / 4534MR

kg		Metal case size (mm)
8.2	2	476 x 282 x 57 (0.27 cuft)

41026 MR (25 PC.) SR (25 PC.) ■ 41526 MR (25 PC.) SR (25 PC.)

- 25 PC. 1/2" drive socket wrench set

	Contents		
41026MR	○ 4330M: 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 27 30 32	○ 463021 ○ 463521	4768-10F 4452-15F 4251-05 4251-10 4572-12 4791
41526MR	○ 4335M		
41026SR	○ 4330S: 5/16 3/8 7/16 15/32 1/2 9/16 19/32 5/8 11/16 3/4 25/32 13/16 7/8 15/16 1 1-1/16 1-3/16 1-1/4	○ 463021 ○ 463521	
41526SR	○ 4335S		

41026MR / 41026SR

41526MR / 41526SR

kg		Plastic case size (mm)
5.7	1	445 x 240 x 206 (0.79 cuft)

Impact Driver Set

4108 FR
4111 FR
4112 FR

- 1/2" drive impact driver set

	PC	Contents	
4108FR	8	⊖ 1836S 9 11 ⊕ 1836P 2 3 ⊕ 1880P 2 3	4112
4111FR	6	⊖ 1880S 8 10 ⊕ 1880P 2 3	414810S
4112FR	6	⊖ 1836S 9 11 ⊕ 1836P 2 3	

4112

414810S

4108FR

4112FR

	kg		Metal case size (mm)
4108FR	1.04	24	190 x 60 x 48 (0.019 cuft)
4111FR	1.00		
4112FR	1.00		

4505 MR
4505 SR

- 10 PC. 1/2" drive impact driver & socket set

	Contents	
4505MR	○ 4335M 8 10 12 14	⊖ 1836S 9 11 4112
4505SR	○ 4335S 5/16 3/8 1/2 9/16	⊕ 1836P 2 3 414810S

4505MR

4505SR

	kg		Metal case size (mm)
4505MR	1.56	12	246 x 103 x 38 (0.034 cuft)
4505SR			

Standard Socket

- Chrome vanadium alloy steel, polished, chrome plated.
- 4 ball retaining grooves.

○ 6330 M

- 3/4" drive
- 12 points
- Metric size
- Thin walled design on square driving side
- DIN 3124, ISO 2725-1

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
633017M	17	26.0	32.7	14	51	187	8 / 96
633019M	19	30.0	32.7	14	51	207	8 / 96
633021M	21	32.0	32.7	16	51	210	8 / 96
633022M	22	33.0	35.7	16	51	209	8 / 96
633023M	23	34.0	35.7	16	51	216	8 / 96
633024M	24	35.0	35.7	17	51	219	8 / 96
633026M	26	35.7	35.0	17	52	243	8 / 96
633027M	27	38.0	36.0	19	52	238	8 / 96
633028M	28	39.0	36.0	19	52	233	8 / 96
633029M	29	40.0	38.0	19	52	261	8 / 96
633030M	30	42.0	38.0	21	54	295	6 / 48
633032M	32	44.0	38.0	23	56	317	6 / 48
633033M	33	46.0	39.0	23	56	351	6 / 48
633034M	34	47.0	42.0	24	57	400	6 / 48
633035M	35	48.0	42.0	25	58	406	6 / 36
633036M	36	50.0	42.0	25	58	434	6 / 36
633038M	38	52.0	45.0	27	60	497	6 / 36
633041M	41	56.0	45.0	29	64	581	4 / 32
633042M	42	57.0	45.0	29	64	591	4 / 32
633046M	46	62.0	48.0	33	68	724	4 / 32
633048M	48	64.0	48.0	34	70	775	2 / 24
633050M	50	68.0	48.0	34	72	889	2 / 24
633054M	54	72.0	50.0	35	75	1070	1 / 20
633055M	55	74.0	50.0	37	76	1115	1 / 20
633058M	58	77.0	50.0	37	78	905	1 / 20
633060M	60	80.0	50.0	40	78	1250	1 / 20
633063M	63	83.0	55.0	40	81	1445	1 / 18
633065M	65	85.0	58.0	43	83	1565	1 / 18
633070M	70	92.0	58.0	46	88	1875	1 / 18

○ 6330 S

- 3/4" drive
- 12 points
- Inch size
- Thin walled design on square driving side
- ANSI/ASME B107.1

KING TONY	inch	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
633022S	11/16	26	35.7	14	50.8	195	8 / 96
633024S	3/4	30	35.7	14	50.8	225	8 / 96
633026S	13/16	32	35.7	16	50.8	228	8 / 96
633028S	7/8	33	35.7	16	51.0	230	8 / 96
633030S	15/16	35	35.7	17	51.0	240	8 / 96
633032S	1	35	35.7	17	52.0	242	8 / 96
633034S	1-1/16	38	36.0	19	52.0	238	8 / 96
633036S	1-1/8	40	38.0	19	52.0	261	8 / 96
633038S	1-3/16	42	38.0	21	54.0	295	6 / 48
633040S	1-1/4	44	38.0	23	56.0	317	6 / 48
633042S	1-5/16	46	39.0	23	56.0	351	6 / 48
633044S	1-3/8	48	42.0	25	58.0	406	6 / 36
633046S	1-7/16	50	42.0	25	58.0	434	6 / 36
633048S	1-1/2	52	45.0	27	60.0	497	6 / 36
633050S	1-9/16	54	45.0	28	62.0	537	4 / 32
633052S	1-5/8	56	45.0	29	64.0	581	4 / 32
633054S	1-11/16	58	45.0	29	65.0	591	4 / 32
633056S	1-3/4	60	48.0	31	66.0	657	4 / 32
633058S	1-13/16	62	48.0	34	68.0	724	4 / 32
633060S	1-7/8	64	48.0	34	70.0	775	2 / 24
633062S	1-15/16	66	48.0	34	70.0	832	2 / 24
633064S	2	68	48.0	34	72.0	889	2 / 24
633066S	2-1/16	70	50.0	35	74.0	950	1 / 20
633068S	2-1/8	72	50.0	35	75.0	1020	1 / 20
633070S	2-3/16	74	50.0	37	76.0	1120	1 / 20
633072S	2-1/4	76	50.0	37	76.0	1120	1 / 20
633074S	2-5/16	78	50.0	37	78.0	1160	1 / 20
633076S	2-3/8	80	50.0	40	78.0	1240	1 / 20
633078S	2-7/16	82	55.0	40	81.0	1366	1 / 12
633080S	2-1/2	84	55.0	40	81.0	1460	1 / 12
633082S	2-9/16	85	58.0	43	83.0	1510	1 / 12
633084S	2-5/8	86	58.0	43	83.0	1510	1 / 12
633086S	2-11/16	90	58.0	43	85.0	1555	1 / 12
633088S	2-3/4	92	58.0	46	88.0	1865	1 / 12

Standard Socket

- Chrome vanadium alloy steel, polished, chrome plated.
- 4 ball retaining grooves.

6335 M

- 3/4" drive
- 6 points
- Metric size
- Thin walled design on square driving side
- DIN 3124, ISO 2725-1

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)		
633517M	17	26.0	32.7	14	51	187	8 / 96
633518M	18	28.0	32.7	14	51	196	8 / 96
633519M	19	30.0	32.7	14	51	207	8 / 96
633520M	20	31.0	32.7	16	51	209	8 / 96
633521M	21	32.0	32.7	16	51	210	8 / 96
633522M	22	33.0	35.7	16	51	209	8 / 96
633523M	23	34.0	35.7	16	51	216	8 / 96
633524M	24	35.0	35.7	17	51	219	8 / 96
633525M	25	35.0	35.7	17	52	240	8 / 96
633526M	26	35.7	35.0	17	52	243	8 / 96
633527M	27	38.0	36.0	19	52	238	8 / 96
633528M	28	39.0	36.0	19	52	233	8 / 96
633529M	29	40.0	38.0	19	52	261	8 / 96
633530M	30	42.0	38.0	21	54	295	6 / 48
633531M	31	43.0	38.0	23	55	305	6 / 48
633532M	32	44.0	38.0	23	56	317	6 / 48
633533M	33	46.0	39.0	23	56	351	6 / 48
633534M	34	47.0	42.0	24	57	400	6 / 48
633535M	35	48.0	42.0	25	58	406	6 / 36
633536M	36	50.0	42.0	25	58	434	6 / 36
633537M	37	51.0	45.0	25	59	485	6 / 36
633538M	38	52.0	45.0	27	60	497	6 / 36
633539M	39	53.0	45.0	28	61	520	4 / 32
633540M	40	54.0	45.0	28	62	540	4 / 32
633541M	41	56.0	45.0	29	64	581	4 / 32
633542M	42	57.0	45.0	29	64	591	4 / 32
633543M	43	58.0	45.0	29	65	620	4 / 32
633544M	44	60.0	48.0	31	66	695	4 / 32
633545M	45	61.0	48.0	33	67	715	4 / 32
633546M	46	62.0	48.0	33	68	724	4 / 32
633547M	47	63.0	48.0	33	69	755	4 / 32
633548M	48	64.0	48.0	34	70	775	2 / 24
633549M	49	66.0	48.0	34	70	810	2 / 24
633550M	50	68.0	48.0	34	72	889	2 / 24
633551M	51	69.0	50.0	35	73	895	1 / 20
633552M	52	69.0	50.0	35	73	905	1 / 20
633553M	53	70.0	50.0	35	74	975	1 / 20
633554M	54	72.0	50.0	35	75	1010	1 / 20
633555M	55	74.0	50.0	37	76	1095	1 / 20
633556M	56	75.0	50.0	37	76	1145	1 / 20
633557M	57	76.0	50.0	37	76	1195	1 / 20
633558M	58	77.0	50.0	37	78	1225	1 / 20
633559M	59	78.0	50.0	37	78	1250	1 / 20
633560M	60	80.0	50.0	40	78	1275	1 / 20
633563M	63	83.0	55.0	40	81	1390	1 / 12
633565M	65	85.0	58.0	43	83	1510	1 / 12
633570M	70	92.0	58.0	46	88	1805	1 / 12

6335M

Deep Socket

- Chrome vanadium alloy steel, polished, chrome plated.
- 4 ball retaining grooves.

6235 M

- 3/4" drive
- 6 points
- Metric size
- Thin walled design on square driving side
- DIN 3124, ISO 2725-1

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
623517M	17	26.0	32.7	20	90	388	2 / 48
623518M	18	28.0	32.7	20	90	411	2 / 48
623519M	19	30.0	32.7	20	90	437	2 / 48
623520M	20	31.0	32.7	22	90	440	2 / 48
623521M	21	32.0	32.7	22	90	444	2 / 48
623522M	22	33.0	35.7	22	90	460	2 / 48
623523M	23	34.0	35.7	24	90	462	2 / 48
623524M	24	35.0	35.7	24	90	477	2 / 48
623525M	25	35.0	35.7	25	90	464	2 / 48
623526M	26	35.7	35.0	25	90	433	1 / 24
623527M	27	38.0	36.0	28	90	431	1 / 24
623528M	28	39.0	36.0	28	90	477	1 / 24
623529M	29	40.0	38.0	28	90	502	1 / 24
623530M	30	42.0	38.0	31	90	584	1 / 24
623531M	31	43.0	38.0	34	90	580	1 / 24
623532M	32	44.0	38.0	34	90	580	1 / 24
623533M	33	46.0	39.0	34	90	646	1 / 24
623534M	34	47.0	42.0	34	90	717	1 / 24
623535M	35	48.0	42.0	37	90	677	1 / 24
623536M	36	50.0	42.0	37	90	724	1 / 24
623537M	37	51.0	45.0	37	90	891	1 / 24
623538M	38	52.0	45.0	41	90	913	1 / 24
623539M	39	53.0	45.0	41	90	935	1 / 24
623540M	40	54.0	45.0	41	90	911	1 / 24
623541M	41	56.0	45.0	41	90	864	1 / 24
623542M	42	57.0	45.0	46	95	913	1 / 24
623543M	43	58.0	45.0	46	95	971	1 / 10
623544M	44	60.0	48.0	46	95	1066	1 / 10
623545M	45	61.0	48.0	46	95	1073	1 / 10
623546M	46	62.0	48.0	46	95	1093	1 / 10
623547M	47	63.0	48.0	46	95	1102	1 / 10
623548M	48	64.0	48.0	50	95	1093	1 / 10
623549M	49	66.0	48.0	50	95	1035	1 / 10
623550M	50	68.0	48.0	50	95	1220	1 / 10
623551M	51	69.0	50.0	50	95	1282	1 / 10
623552M	52	69.0	50.0	50	95	1244	1 / 10
623553M	53	70.0	50.0	50	95	1262	1 / 10
623554M	54	72.0	50.0	50	95	1342	1 / 10
623555M	55	74.0	50.0	50	95	1268	1 / 10
623556M	56	75.0	50.0	50	95	1440	1 / 10
623557M	57	76.0	50.0	52	100	1555	1 / 10
623558M	58	78.0	50.0	52	100	1540	1 / 10
623559M	59	78.0	50.0	52	100	1604	1 / 10
623560M	60	80.0	50.0	53	100	1662	1 / 10

Ratchet & Accessory

- Chrome vanadium alloy steel, polished, chrome plated.
- 4 ball retaining grooves.

6779 DIN 3122

- 3/4" drive reversible ratchet
- 15° gear action degree (24 teeth)

KING TONY	Overall Length (inch)	(mm)	g	
6779-20F	20	500	2349	1 / 6
6779DK	renewal kits		-	-

6779-20F

6779DK

8781032KT

6251 DIN 3123

- 3/4" drive extension bars

KING TONY	Overall Length (inch)	(mm)	g	
6251-04	4	110	400	4 / 40
6251-08	8	200	732	2 / 20
6251-16	16	400	1362	1 / 10

6251

8776KT

6452 DIN 3122

- 3/4" drive flexible handle
- Action degree -180°

KING TONY	Overall Length (inch)	(mm)	g	
6452-18F	18	450	1717	1 / 10
6452-30F	30	750	2813	1 / 8
6452DK	renewal kits		-	-

6452-18F

6452DK

8781032KT

6572 DIN 3122

- 3/4" drive sliding T-handle

KING TONY	Overall Length (inch)	(mm)	g	
6572-20	20	500	1542	1 / 10
6572DK	renewal kits		-	-

6572-20

6572DK

8781032KT

6581 DIN 3122

- 3/4" drive 90° L-handles

KING TONY	Overall Length (inch)	(mm)	g	
6581-12	12	300	1307	10
6581-18	18	450	1850	12

6581

6791 DIN 3123, ISO 3316

- 3/4" drive universal joint

KING TONY	Overall Length (inch)	(mm)	g	
6791	4-1/4	108	590	2 / 20

6791

8776KT

6814 6818 DIN 3123, ISO 3316

- 3/4" drive adapters
- Converting to 1/2" drive or 1" drive
- 6814 → Max. torque 620 Nm

KING TONY	SPEC.	g	
6814	3/4"F x 1/2"M	131	8 / 96
6818	3/4"F x 1"M	304	6 / 60

1/2" drive(M)
1" drive(M)

← 3/4" drive(F)

6814 / 6818

8776KT

Socket Set

6016 MR SR
6316 MR

- 16 PC. 3/4" drive socket wrench set

	Contents		
6016MR	○ 6330M	21 22 23 24 27 30 32 36 38 41 46 50	6779-20F
6316MR	○ 6335M		6251-08 6251-16
6016SR	○ 6330S	7/8 15/16 1 1-1/16 1-1/8 1-1/4 1-3/8 1-1/2 1-5/8 1-3/4 1-7/8 2	6572-20

kg		Metal case size (mm)
14.0	1	537 x 177 x 78 (0.26 cuft)

6023 MR SR
6323 MR

- 23 PC. 3/4" drive socket wrench set

	Contents		
6023MR	○ 6330M	21 22 23 24 26 27 28 29 30 32 34 35 36 38 41 46 50	6779-20F
6323MR	○ 6335M		6251-04 6251-08 6251-16
6023SR	○ 6330S	7/8 15/16 1 1-1/16 1-1/8 1-3/16 1-1/4 1-5/16 1-3/8 1-7/16 1-1/2 1-9/16 1-5/8 1-3/4 1-13/16 1-7/8 2	6572-20 6791

kg		Metal case size (mm)
17.1	1	537 x 177 x 78 (0.26 cuft)

6224 CR

- 24 PC. 3/4" drive socket wrench set

	Contents		
6224CR	○ 6330M	22 24 27 30 32 36 38 41 46 50	6779-20F
	○ 6330S	1 1-1/8 1-1/4 1-5/16 1-3/8 1-7/16 1-1/2 1-5/8 1-3/4 2	6251-08 6251-16 6572-20

kg		Metal case size (mm)
15.5	1	537 x 177 x 78 (0.26 cuft)

6226 CR

- 26 PC. 3/4" drive socket wrench set

	Contents		
6226CR	○ 6330M	22 24 27 30 32 36 38 41 46 50	6452-18F
	○ 6330S	7/8 15/16 1 1-1/8 1-3/16 1-5/16 1-3/8 1-7/16 1-5/8 1-3/4 1-7/8 2	6251-04 6251-08 6572-20

kg		Metal case size (mm)
17.5	1	537 x 177 x 78 (0.26 cuft)

Standard Socket

- Chrome vanadium alloy steel, polished, chrome plated.
- 4 ball retaining grooves.

8330 M

- 1" drive
- 12 points
- Metric size
- Thin walled design on square driving side
- DIN 3124, ISO 2725-1

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
833036M	36	52	48	26	65	449	1 / 24
833038M	38	54	48	26	65	478	1 / 24
833041M	41	58	50	29	70	557	1 / 24
833046M	46	65	54	32	75	849	1 / 10
833050M	50	70	54	34	75	996	1 / 10
833054M	54	74	57	38	80	1145	1 / 10
833055M	55	76	57	42	83	1206	1 / 12
833058M	58	79	57	42	83	1263	1 / 12
833060M	60	82	58	46	87	1470	1 / 12
833063M	63	86	58	46	87	1555	1 / 12
833065M	65	88	65	49	90	1670	1 / 12
833067M	67	91	70	49	91	1670	1 / 12
833070M	70	94	70	50	93	2100	1 / 8
833071M	71	95	70	50	93	2068	1 / 8
833075M	75	100	70	50	95	2310	1 / 8
833077M	77	103	80	52	100	2557	1 / 8
833080M	80	107	80	52	100	2580	1 / 8

8330 S

- 1" drive
- 12 points
- Inch size
- Thin walled design on square driving side
- ANSI/ASME B107.1

KING TONY	inch	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
833046S	1-7/16	52	48	26	65	463	1 / 24
833048S	1-1/2	54	48	26	65	489	1 / 24
833054S	1-11/16	60	54	29	70	680	1 / 24
833060S	1-7/8	67	54	34	75	976	1 / 10
833064S	2	71	54	34	75	988	1 / 10
833072S	2-1/4	78	57	42	83	1212	1 / 12
833076S	2-3/8	82	58	46	87	1437	1 / 12
833084S	2-5/8	90	65	49	90	1693	1 / 12
833094S	2-15/16	100	70	52	95	2242	1 / 8
8330A0S	3-1/8	107	80	52	100	2578	1 / 8

Ratchet

8779

DIN 3122

- 1" drive reversible ratchets
- 15° gear action degree (24 teeth)

KING TONY	Total Length (inch)	(mm)	g	
8779-32F	32	800	4400	5
8779DK	renewal kits		-	-

8779-32F

8779DK

Accessory

- Chrome vanadium handle, chrome molybdenum driver
- Chrome plated handle & black phosphate sunk driver

8251 DIN 3123

- 1" drive extension bar

KING TONY	Total Length (inch)	(mm)	g	
8251-08	8	200	1350	1 / 16
8251-16	16	400	2480	1 / 8

8572 DIN 3122

- 1" drive sliding T-handle

KING TONY	Total Length (inch)	(mm)	g	
8572-25	25	630	4200	1 / 6
8572DK	renewal kits		-	-

8572-25

8572DK

8581 DIN 3122

- 1" drive 90° L-handle

KING TONY	Total Length (inch)	(mm)	g	
8581-26	26	650	5120	1/4

8816 DIN 3123, ISO 3316

- 1" drive adapter
- Converting to 3/4" drive
- Max. torque 1800 Nm

KING TONY	SPEC.	g	
8816	1"F x 3/4"M	330	6 / 48

3/4" drive(M)

1" drive(F)

8816

Socket Set

8015 MR SR

- 14 PC. 1" drive socket wrench set

KING TONY	Contents	
8015MR	○ 8330M: 36 41 46 50 55 60 65 70 75 80	8779-32F; 8251-08; 8251-16
8015SR	○ 8330S: 1-7/16 1-1/2 1-11/16 1-7/8 2 2-1/4 2-3/8 2-5/8 2-15/16 3-1/8	8572-25

kg		Metal case size (mm)
34.1	1	660 x 205 x 108 (0.52 cuft)

Socket Set

5022 MR SR
5522 MR

- 21 PC. 1/4" + 3/8" drive combination socket set

	Contents		
5022MR	3330M: 10 11 12 13 14 17 19	2335M: 4 5 5.5 6 7 8 9	363021, 3769-08F, 3221-03, 3221-06
5522MR	3335M		363521
5022SR	2335S: 5/32 3/16 7/32 1/4 9/32 5/16 11/32		363021, 3812, 363516, 2178AE
	3330S: 3/8 7/16 15/32 1/2 9/16 11/16 3/4		

5022MR / 5522MR

5022SR

kg		Metal case size (mm)
1.60	10	285 x 130 x 45 (0.059 cuft)

5039 CR

- 39 PC. 1/4" + 3/8" drive combination socket set

	Contents	
5039CR	2335M: 4.5 5 6 7 8 9 10 11 12	363021, 3769-08F, 3221-03, 3812, 2178AE
	2335S: 3/16 7/32 1/4 9/32 5/16 11/32 3/8 7/16 1/2	
	3330M: 9 10 11 12 13 14 16 17 19	
	3330S: 3/8 7/16 1/2 9/16 5/8 11/16 3/4	

kg		Metal case size (mm)
2.60	10	318 x 147 x 46 (0.076 cuft)

7120 PR
7120 PR 01

- 20 PC. 3/8" + 1/2" drive special purpose socket set

	Contents		
7120PR	3375: E6 E7 E8 E10	4023: T30 T40 T45 T50 T55	4813
	4375: E12 E14 E16 E18 E20		
7120PR01	3023: T10 T15 T20 T25 T27	4027: T30 T40 T45 T50 T55	

kg		Metal case size (mm)
2.1	10	296 x 130 x 41 (0.056 cuft)

Socket Set

7558 MR

- 58 PC. 1/4" + 1/2" drive combination socket set

	Contents	
7558MR	2335M: 4 4.5 5 5.5 6 7 8 9 10 11 12 13 14	2792, 4791
	4335M: 8 10 11 12 13 14 15 16 17 18 19 21 22 24	2221-02, 2221-04, 4251-05
	1025P: PH1 PH2 PH3	2779-55G, 4779-10G
	1025S: 4 6 8	2141
	1025Z: PZ1 PZ2 PZ3	2178AE
	1025H: H3 H4 H5 H6 H7 H8	
	1025U: T10 T15 T20 T25 T27 T30 T40	

kg		Metal case size (mm)
3.8	1 / 4	445 x 187 x 50 (0.147 cuft)

9033 CR

- 135 PC. 1/4" + 3/8" + 1/2" drive combination socket set

	Contents	
9033CR	2335M: 4 4.5 5 5.5 6 7 8 9 10 11 12 13	463516
	2335S: 5/32 3/16 7/32 1/4 9/32 5/16 11/32 3/8 7/16 1/2	463021
	2235M: 4 4.5 5 5.5 6 7 8 9 10 11 12 13	3769-08F
	2235S: 5/32 3/16 7/32 1/4 9/32 5/16 11/32 3/8 7/16 1/2	4768-10F
	3330M: 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22	2178AE
	4330M: 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 30 32	2221-02, 2221-04
	4330S: 3/8 7/16 1/2 9/16 5/8 11/16 3/4 13/16 7/8 15/16 1 1-1/8 1-3/16 1-1/4	2452-05F
	2015M: 3 4 5 6 8 10	2571-45
	2015S: 1/8 3/16 7/32 1/4 5/16 3/8	3221-03, 3221-06
	2011: No. 1 2 3 4	3792
	1115-03: 1.5 2 2.5	3812
	2561: cross bar. 4-1/2"L.	4251-05, 4251-10
	3840: 3/8" drive spin disc.	4572-10
	4840: 1/2" drive spin disc.	4791

kg		Metal case size (mm)
12.3	2	450 x 370 x 56 (0.329 cuft)

Socket & Wrench Set

9063 MR / MR 01
9563 MR / MR 01

- 62 PC. 1/4" + 3/8" + 1/2" drive socket wrench set

Contents

9063MR	4330M, 3330M	4330M 4335M: 12 13 14 15 16 17 18 19 20 21 22 23 24 27 30 32	363021	4768-10F, 3769-08F	2335M: 4 4.5 5 6 7 8 9 10 11 12	4251-06, 4572-12
9563MR	4335M, 3335M		363521	3235M: 12 14 17 19	3023: T20 T25 T27 T30 T40	4791, 3221-06, 3571-08
9063MR01	4330M, 3330M	3330M 3335M: 8 9 10 11 12 13 14 15 17 19	363021	4755-10G, 3779-08G		3792, 3812
9563MR01	4335M, 3335M		363521	3235M: 10 13 17 19	3025: 4 5 6 8 10	2221-04, 2571-45

9063MR / 9563MR

9063MR01 / 9563MR01

kg		Metal case size (mm)
7.4	2	476 x 282 x 57 (0.27 cuft)

Socket & Wrench Set

7075 MR
7075 MR01

- 75 PC. 1/4" + 1/2" drive combination socket set

	Contents		
7075MR	2235M: 8 10 12 13	463516	
	2335M: 4 4.5 5 5.5 6 7 8 9 10 11 12 13	463521	2571-45
	4330M: 10 12 13 14 15 17 18 19 22 24 27 30	4791, 2792	
	1060: 8 10 12 13 14 15 17 18 19	4223-05, 2141	
7075MR01	1421: No.1 x 80, No.2 x 100	6511-10A, 2221-04	
	1422: 4 x 100, 6.5 x 100	4779-10B, 6111-06A	2779-55G
	1025T: T9 T20 T27 T30 T40		
	1025H: H1.5 H2.5 H7 H8 H10	2178, 4121-11G	
	1145: 1.5 2 2.5 3 4 5 6 7 8	7821-30, 4583-12	

7075MR

7075MR01

	kg		Blow case size (mm)
7075MR	7.9	2	475 x 360 x 90 (0.56 cuft)
7075MR01	7.9		

7572 MR

- 72 PC. 1/4" + 1/2" drive combination socket set

	Contents	
7572MR	2235M: 8 10 12 13	463516
	2335M: 4 4.5 5 5.5 6 7 8 9 10	463521
	4335M: 10 12 13 14 15 17 18 19 22 24	4791, 2178AE
	1060: 8 10 12 13 14 15 17 19	2571-45, 2221-04
	1145: 1.5 2 2.5 3 4 5 6 7 8 10	2141, 4251-05
	1025P: PH0 PH1 PH2 PH3	4581-10
	1025H: 3 4 5 6 7 8	4779-10G
	1025S: 4 5.5 7	
	1025T: T10 T15 T20 T25 T27 T30 T40	6114-05

kg		Blow case size (mm)
4.96	4	410 x 280 x 60 (0.247 cuft)

Socket & Wrench Set

7085 MR

- 85 PC. 1/4" + 1/2" drive combination socket set

	Contents	
7085MR	2235M: 7 8 10 12 13	463516
	2335M: 5 5.5 6 7 8 10 11 12 13	463521
	4330M: 10 12 13 14 15 17 18 19 22 24 27 30	414810M, 2792
	1060: 8 10 12 13 14 15 17 18 19 22	4791, 2211-06
	1130: 3 4 5 6 8 10 2.5	2452-05F, 2779-55G
	1147: T10 T15 T20 T25 T27 T30 T40	4779-10G, 4251-05
	1421: No.1 x 80 No.2 x 100	4452-15F
	1422: 4 x 100 5.5 x 100	6516-10C
	1636H: H5 H6 H7 H8 H10 H12	6231-07A, 6111-06A
	1636M: 6 8 10 12	
	1636T: T30 T40 T45 T50 T55 T60	
	19961721: 17 19 13/16" 1/2" x 300mm	

kg		Blow case size (mm)
9.20	2	475 x 360 x 90 (0.553 cuft)

Socket & Wrench Set

7597 MR

- 97 PC. 1/4" + 1/2" drive combination socket set

	Contents	
7597MR	2235M: 7 8 10 12 13	463516
	2335M: 4 4.5 5 5.5 6 7 8 9 10 11 12 13	463521
	4335M: 10 12 13 14 15 16 17 18 19 21 22 24 27 30 32	2141, 2792
	1060: 6 7 8 10 12 13 14 15 16 17 18 19	2571-45, 2221-02, 2221-04
	1421: No.2 x 38	
	1422: 4 x 100 6.5 x 35	2452-05F, 2779-55G
	1461: No.2 x 100 No.3 x 150	4251-10, 4121-11G
	1462: 6.5 x 150	
	1025P: PH0 PH1 PH2 PH3	4791, 4223-02
	1025H: H1.5 H2 H2.5 H3 H4 H5 H6 H7 H8 H10	4583-12, 4573-10
	1025S: 4 5.5 7 8	4779-10B, 6111-06A
	1025U: T8 T10 T15 T20 T25 T27 T30 T40	
	1025Z: PZ1 PZ2 PZ3	6511-10A

kg		Blow case size (mm)
9.2	2	445 x 440 x 50 (0.147 cuft)

9507 MR

- 107 PC. 1/4" + 3/8" + 1/2" drive combination socket set

	Contents	
9507MR	2335M: 4 4.5 5 5.5 6 7 8 9 10	463516
	3330M: 6 7 8 9 10 12 13 14 15 17	463521
	3375M: E4 E5 E6 E7 E8 E10 E11 E12 E14 E16 E18	2792, 3792
	4335M: 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 27 30 32	414810S, 4791
	1060: 8 10 11 12 13 14 15 16 17 18 19 21 22 24	2221-03, 2221-06, 3221-03, 3221-06
	1930: 8 x10 11 x 13 12 x 14 17 x 19	4223-02, 4251-05, 4251-10
	1422: 5.5 x 100	2755-55G, 3734-10F
	1461: No.1 x 75 No.2 x 100	3611-08R
	1462: 6.5 x 150	4452-15F
	1832H: H3 H4 H5 H6 H7 H8 H10 H12	4779-10G
	1832T: T15 T20 T25 T27 T30 T40 T45 T50	6111-06A

kg		Blow case size (mm)
10.7	2	445 x 440 x 50 (0.147 cuft)

Socket & Wrench Set

7553 MR NEW

- 153 PC. 1/4" + 1/2" drive combination socket set

	Contents	
7573MR	2235M: 4 4.5 5 5.5 6 7 8 9 10 11 12 13	414810S
	4335M: 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 32	2178DF
	2235M: 6 7 8 9 10 11 12 13	4223-02
	4235M: 13 14 17 19 22	2792 4792
	2375M: E4 E5 E6 E7 E8	4251-05 4251-10
	4375M: E10 E12 E14 E16 E18 E20	2452-05 4452-18
	4635: 16 20.8	2771-55G 4771-10G
	1060: 8 10 11 12 13 14 15 16 17 18 19 21 22 24 27	6111-06
	1930: 8x10 11x13 12x14	4214-05
	1421: No.2 x 38	6511-10A
	1422: 6.5 x 38	
	1461: NO.1x 75mm, No.2x100mm	
	1462: 5.5x100, 6.5x150 mm	
	1025H: 3 4 5 6	
	1025P: PH0 PH1 PH2	
	1025Z: PZ1 PZ2 PZ3	
	1025T: T10 T15 T20 T25 T27 T30 T40	
	1025S: 4 5.0 6.5	
	1636M: 6 8 10 12	
	1636H: 5 6 7 8 10 12	
	1636T: T30 T40 T45 T50 T55 T60	
	1680H: 5 6 7 8 10 12	
	1680T: T25 T30 T40 T45 T50 T55	
	1680M: 6 8 10 12	

kg		Blow case size (mm)
13.9	2	520 x 460 x 105 (0.89 cuft)

Socket Rail Set

7112 PR

- 12 PC. 3/8" + 1/2" drive star socket set
- Socket rail 260mmL
  - Rail with 6 PC. 1/2" drive & 5 PC. 3/8" drive clips

	Contents	
7112PR	3375M: E4 E5 E6 E8	3571-08, 3814, 8771011
	4375M: E10 E12 E14 E16 E18 E20	

kg	
0.76	24

7113 PR

- 12 PC. 3/8" + 1/2" drive star socket set
- Socket rail 260mmL
  - Rail with 6 PC. 3/8" drive & 6 PC. 1/2" drive clips

	Contents	
7113PR	3375M: E4 E5 E6 E7 E8 E11	8771012
	4375M: E10 E12 E14 E16 E18 E20	

kg	
0.6	1 / 32

Tool Bag

92543 MR

	Contents	
92543MR	1421: PH0 x 60 PH1 x 100 PH2 x 38 PH2 x 150	
	1422: 3.0 x 75 6.5 x 38 6.5 x 150	
	1025Z: PZ1 PZ2 PZ3	
	1025T: T10 T15 T20 T25 T27 T30 T40	
	2335M: 4 5 6 7 8 9 10 11 12 13 14	
	2792, 20317MR, 2178DF, 3611-08	
	2141, 6111-07, 6511-10A, 7976-65	
	79083-03C, 870208, 8720	

kg		Tool bag size (mm)
0.8	8	250 x 400 x 30 mm

Ratchet Set

9415 GR NEW

- 15 PC. 1/4" + 3/8" + 1/2" drive swivel head reversible quick release ratchet set

	Contents
9415GR	2752-06G 3752-09G 4752-12G

kg		Display case size (mm)
5.9	2	299 x 282 x 148 (0.44 cuft)

Notes

Impact Socket &

- Impact Standard Socket
- Deep Socket
- Star Socket
- Bit Socket
- Accessory
- Bit Socket Set
- Thin Wall Socket
- Extra Thin Wall Socket
- Universal Joint Socket
- Rear Wheel Socket
- #5 Spline Drive
- Socket Shelf Set

Accessory

KT Socket			1/4"		3/8"		1/2"		3/4"		1"		1-1/2"	
			mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch
Short Socket	6PT						4525M							
Standard Socket	6PT		2535M		3535M	3535S	4535M	4335S	6515M		8535M	8535S	9535M	
									6535M	6535S				
	12PT						4530M		6510M					
									6530M					
Deep Socket	6PT	Regular			3435M	3435S	4435M	4435S	6435M	6435S	8435M	8435S		
		Thin Wall					4835M 4935M	4935S	6835M 6935M	6935S	8835M			
		Extra Thin Wall					4415M							
	12PT	Regular												
		Thin Wall					4930M							
Rear Wheel Socket									6514M		8514M 8534M	8514S		
Star Socket					3575M		4575M		6575M					
Universal Joint Socket	6PT						4A55, 4B55							
Bit Socket	Hexagon	55L			3055M	3055S								
		60L					4055M	4055S						
		80L					4015M	4015S						
		90L			3065									
		100L					4065							
		150L					4075							
	12PT (Spline)						4056M							
	Torx	55L			3053									
		60L					4053							
		100L					4063							
	Hex bit socket								6015M, 6085 6095					
	Hex bit & bit holder								1740, 609616M 1954, 609622M					

Impact Standard Socket

- Material - chrome molybdenum alloy steel
- Finished with phosphate sunk

2535 M

- 1/4" drive standard length
- 6 points
- Metric size
- DIN 3129 ,ISO 2725-2

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
253504M	4	7.5	13	4	23	12	20 / 600
253545M	4.5	8.1	13	5	23	12	20 / 600
253505M	5	8.8	13	6	23	12	20 / 600
253555M	5.5	9.4	13	6	23	13	20 / 600
253506M	6	10.0	13	7	23	13	20 / 600
253507M	7	11.3	13	7	23	13	20 / 600
253508M	8	12.5	13	8	23	13	20 / 600
253509M	9	13.8	13	8	23	15	12 / 360
253510M	10	15.0	13	9	23	18	12 / 360
253511M	11	16.3	13	9	23	20	12 / 360
253512M	12	17.5	13	9	23	21	12 / 360
253513M	13	18.8	13	9	23	22	12 / 360
253514M	14	19.8	13	9	23	23	10 / 300

1/4" & 3/8" Impact Socket

3535 M

- 3/8" drive standard length
- 6 points
- Metric size
- Thin walled design on square driving side
- DIN 3129 ,ISO 2725-2

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
353506M	6	10.6	19	5	32	31	12 / 360
353507M	7	11.8	19	5	32	33	12 / 360
353508M	8	13.2	19	6	32	34	12 / 360
353509M	9	14.5	19	6	32	39	12 / 360
353510M	10	15.5	19	7	32	38	12 / 360
353511M	11	17.0	19	7	32	38	12/ 360
353512M	12	18.2	19	8	32	41	12 / 360
353513M	13	19.4	22	9	32	53	10 / 200
353514M	14	20.7	22	9	32	54	10 / 200
353515M	15	22.0	22	10	32	55	10 / 200
353516M	16	23.8	22	10	32	57	10 / 200
353517M	17	24.8	22	11	32	60	10 / 200
353518M	18	25.8	22	11	32	63	10 / 200
353519M	19	27.6	22	13	32	64	10 / 160

3535 S

- 3/8" drive standard length
- 6 points
- Inch size
- Thin walled design on square driving side
- ANSI/ASME B107.2

KING TONY	inch	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
353508S	1/4	10.8	19	5	32	31	12 / 360
353510S	5/16	13.0	19	6	32	34	12 / 360
353512S	3/8	15.3	19	7	32	38	12 / 360
353514S	7/16	17.0	19	7	32	38	12 / 360
353516S	1/2	18.2	19	9	32	53	10 / 200
353518S	9/16	20.7	22	9	32	53	10 / 200
353520S	5/8	23.8	22	10	32	57	10 / 200
353522S	11/16	24.5	22	11	32	60	10 / 200
353524S	3/4	27.0	22	11	32	64	10 / 160

Impact Deep Socket

- Material - chrome molybdenum alloy steel
- Finished with phosphate sunk

3435 M

- 3/8" drive deep version
- 6 points
- Metric size
- Thin walled design on square driving side
- DIN 3121

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
343506M	6	10.6	19	10	65	62	6 / 120
343507M	7	11.8	19	10	65	66	6 / 120
343508M	8	13.2	19	12	65	71	6 / 120
343509M	9	14.5	19	12	65	76	6 / 120
343510M	10	15.5	19	12	65	82	6 / 120
343511M	11	17.0	19	13	65	84	6 / 120
343512M	12	18.2	19	14	65	93	6 / 120
343513M	13	19.4	22	14	65	113	6 / 120
343514M	14	20.7	22	14	65	114	6 / 120
343515M	15	22.0	22	16	65	125	6 / 120
343516M	16	23.8	22	16	65	126	6 / 96
343517M	17	24.8	22	17	65	138	6 / 96
343518M	18	25.8	22	18	65	144	6 / 96
343519M	19	27.6	22	20	65	154	6 / 96
343520M	20	28.3	22	20	65	148	6 / 96
343521M	21	29.5	22	22	65	156	6 / 96
343522M	22	30.8	22	22	65	172	5 / 60
343523M	23	32.0	22	24	65	177	5 / 60
343524M	24	32.5	22	24	65	180	5 / 60

3435 S

- 3/8" drive deep version
- 6 points
- Inch size
- Thin walled design on square driving side
- ANSI/ASME B107.2

KING TONY	inch	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
343508S	1/4	10.8	19	10	63.5	62	6 / 120
343510S	5/16	13.0	19	12	63.5	71	6 / 120
343512S	3/8	15.3	19	12	63.5	82	6 / 120
343514S	7/16	17.0	19	13	63.5	84	6 / 120
343516S	1/2	18.2	19	14	63.5	113	6 / 120
343518S	9/16	20.7	22	14	65	114	6 / 120
343520S	5/8	23.8	22	16	65	126	6 / 96
343522S	11/16	24.5	22	17	65	138	6 / 96
343524S	3/4	27.0	22	20	65	154	6 / 96
343526S	13/16	29.5	22	22	65	156	6 / 96
343528S	7/8	30.8	22	22	65	172	5 / 60

Impact Star Socket

- Material - chrome molybdenum alloy steel
- Finished with phosphate sunk

3575 M

- 3/8" drive impact star socket
- For torx external screws
- DIN 3121

KING TONY	SIZE	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
357505M	E5	9.6	19	4.0	32	31	12 / 360
357506M	E6	10.2	19	5.0	32	31	12 / 360
357507M	E7	10.8	19	6.0	32	33	12 / 360
357508M	E8	11.5	19	6.5	32	33	12 / 360
357510M	E10	12.0	19	7.0	32	34	12 / 360
357512M	E12	14.0	19	9.0	32	34	12 / 360
357514M	E14	17.0	19	9.5	32	40	12 / 360

Impact Bit Socket

- Material - chrome molybdenum alloy steel
- Finished with phosphate sunk

CAUTION

1. Do not over - load.
2. Control the air pressure under 6.3 bar, adjust the suitable torque from 0.

3053

- 3/8" drive impact bit socket
- For torx internal screws
- DIN 3121

KING TONY	SIZE	L (mm)	Max.Torq (Nm)	g	
305310	T10	55	4.52	30	12 / 360
305315	T15	55	7.69	30	12 / 360
305320	T20	55	12.66	32	12 / 360
305325	T25	55	18.99	32	12 / 360
305327	T27	55	26.90	33	12 / 360
305330	T30	55	37.40	34	12 / 360
305340	T40	55	65.08	37	12 / 360
305345	T45	55	103.50	41	12 / 360
305350	T50	55	158.75	44	12 / 360

3055 M

- 3/8" drive impact bit socket
- For hexagon head screws
- DIN 3121

KING TONY	SIZE (mm)	L (mm)	Max.Torq (Nm)	g	
305504M	4	55	20.80	35	12 / 360
305505M	5	55	36.00	38	12 / 360
305506M	6	55	62.40	40	12 / 360
305508M	8	55	144.00	45	12 / 360
305510M	10	55	264.00	50	12 / 360
305512M	12	55	420.00	60	12 / 360

3055 S

- 3/8" drive impact bit socket
- For hexagon head screws
- DIN 3121

KING TONY	SIZE (inch)	L (mm)	Max.Torq (Nm)	g	
305506S	3/16	55	36.0	35	12 / 360
305507S	7/32	55	62.4	38	12 / 360
305508S	1/4	55	93.6	39	12 / 360
305510S	5/16	55	144.0	46	12 / 360
305512S	3/8	55	264.0	53	12 / 360
305516S	1/2	55	518.0	70	12 / 360

3065 M

- 3/8" drive impact bit socket
- Hexagon head
- DIN 3121

KING TONY	SIZE (mm)	L (mm)	Max.Torq (Nm)	g	
306504M	4	90	20.8	42	8 / 160
306505M	5	90	36.0	48	8 / 160
306506M	6	90	62.4	55	8 / 160
306508M	8	90	144.0	73	8 / 160
306510M	10	90	264.0	96	8 / 160

Impact Accessory

- Material - chrome molybdenum alloy steel
- Finished with phosphate sunk

3147

- 3/8"drive bit holder

	SIZE	Total Length (mm)	g	
314708S	1/4"	40	44	12 / 420
314710S	5/16"	40	45	12 / 420
314710M	10mm	40	46	12 / 420

3260

- 3/8"drive extension bar
- DIN 3121

	Total Length (inch)	Total Length (mm)	g	
3260-03	3	75	96	6 / 120
3260-06	6	150	168	5 / 100

3260-03

3260-06

3260P

- 3/8"drive extension bar - with ball
- DIN 3121

	Total Length (inch)	Total Length (mm)	g	
3260-03P	3	75	96	6 / 120
3260-06P	6	150	168	5 / 100

3862

- 3/8"drive adapter
- Converting to 1/4" drive
- DIN 3121

	Spec.	g	
3862	3/8"F x 1/4"M	33	24 / 384

3862P NEW

- 3/8"drive adapter- with ball
- Converting to 1/4" drive
- DIN 3121

	Spec.	g	
3862P	3/8"F x 1/4"M	33	24 / 384

3864

- 3/8"drive adapter
- Converting to 1/2" drive
- DIN 3121

	Spec.	g	
3864	3/8"F x 1/2"M	51	24 / 384

3864P

- 3/8"drive adapter - with ball
- Converting to 1/2" drive
- DIN 3121

	Spec.	g	
3864P	3/8"F x 1/2"M	51	24 / 384

Impact Accessory

- Material - chrome molybdenum alloy steel
- Finished with phosphate sunk

3796

- 3/8" drive universal joint
- DIN 3121

KING TONY	L (inch)	L (mm)	g	
3796	2	50	83.4	10 / 200

3796P

- 3/8" drive universal joint - with ball
- DIN 3121

KING TONY	L (inch)	L (mm)	g	
3796P	2	50	83.4	10 / 200

90408
90409

- 3/8" drive locking rings
- High tensile rubber material

90608
90609

- 3/8" drive locking pins
- Chrome vanadium steel
- DIN 3129

	Desp.	ø	d / ℓ	Applied to socket sizes
90408	ring	3.5	12	3535M (6~12 mm) 3535S (1/4~1/2 inch) 3435M (6~12 mm) 3435S (1/4~1/2 inch) 3055M (4~12 mm) 3055S (3/16~1/2 inch) 3065M (4~10 mm) 3053 (T10~T15) 3575M (E5~E14) 3053.3055.3065.3147.3862.3864
90608	pin	2.5	14	
90409	ring	3.5	15	3535M (13~19mm) 3535S (9/16~3/4 inch) 3435M (13~24mm) 3435S (9/16~7/8 inch) 3260.3796
90609	pin	2.5	16	

90408
90409

90608
90609

Impact Bit Socket Set

3406 MP

- 6 PC. 3/8" drive bit socket set
- For hex head screws
- 55 mm L, 4 ~ 12 mm

	Contents						
3406MP	3055	4	5	6	8	10	12

kg		Metal case size (mm)
0.723	20	203 x 79 x 41 (0.023 cuft)

3419 PP

- 9 PC. 3/8" drive bit socket set
- For torx internal head
- 55 mm L, T10 ~ T50

	Contents								
3419PP	3053	T10	T15	T20	T25	T27	T30	T40	T45	T50

kg		Metal case size (mm)
0.62	20	203 x 79 x 41 (0.023 cuft)

Impact Short Socket

- Material - chrome molybdenum alloy steel
- Finished with phosphate sunk

4525 M NEW

- 1/2" drive short length
- 6 points
- Metric size
- Thin walled design on square driving side
- For impact wrench (No.33451-045) use
- DIN 3129 ,ISO 2725-2

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
452517M	17	26	26	5.5	26.5	66	10 / 160
452519M	19	28	26	10	26.5	64	10 / 160
452521M	21	30	30	10	26.5	82	8 / 160
452522M	22	32	30	10	26.5	88	8 / 160
452524M	24	34	30	12	28.5	97	6 / 120

Impact Standard Socket

- Material - chrome molybdenum alloy steel
- Finished with phosphate sunk

4530 M

- 1/2" drive standard length
- 12 points
- Metric size
- Thin walled design on square driving side
- DIN 3129 ,ISO 2725-2

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
453008M	8	14	25	7	38	67	10 / 200
453009M	9	15	25	7	38	67	10 / 200
453010M	10	17	25	8	38	70	10 / 200
453011M	11	18	25	8	38	71	10 / 200
453012M	12	19	25	9	38	72	10 / 200
453013M	13	20	25	10	38	72	10 / 200
453014M	14	22	25	10	38	77	10 / 200
453015M	15	23	30	11	38	112	10 / 160
453016M	16	24	30	11	38	112	10 / 160
453017M	17	26	30	12	38	115	10 / 160
453018M	18	27	30	13	38	115	10 / 160
453019M	19	28	30	13	38	120	10 / 160
453020M	20	29.2	30	13	38	120	10 / 160
453021M	21	30	30	14	40	125	8 / 160
453022M	22	32	30	14	40	143	8 / 160
453023M	23	33	30	15	40	143	8 / 160
453024M	24	34	30	15	42	152	6 / 120
453025M	25	36	30	15	42	168	6 / 120
453026M	26	37	30	15	42	173	6 / 120
453027M	27	38	30	16	44	176	6 / 120
453028M	28	41	30	16	44	194	6 / 120
453029M	29	41	30	17	44	194	6 / 120
453030M	30	42	30.5	17	44	201	6 / 120
453032M	32	46	30	19	44	205	6 / 120
453033M	33	46	30	19	46	227	6 / 96
453034M	34	46	30	20	46	231	6 / 96
453036M	36	47	30	20	46	248	6 / 96
NEW 453038M	38	50	30	21	50	248	6 / 60
453041M	41	52	30	22	52	248	6 / 60

Impact Standard Socket

- Material - chrome molybdenum alloy steel
- Finished with phosphate sunk

4535 M

- 1/2" drive standard length
- 6 points
- Metric size
- Thin walled design on square driving side
- DIN 3129 ,ISO 2725-2

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
453508M	8	14	25	7	38	67	10 / 200
453509M	9	15	25	7	38	67	10 / 200
453510M	10	17	25	8	38	70	10 / 200
453511M	11	18	25	8	38	71	10 / 200
453512M	12	19	25	9	38	72	10 / 200
453513M	13	20	25	10	38	72	10 / 200
453514M	14	22	25	10	38	77	10 / 200
453515M	15	23	30	11	38	112	10 / 160
453516M	16	24	30	11	38	112	10 / 160
453517M	17	26	30	12	38	115	10 / 160
453518M	18	27	30	13	38	115	10 / 160
453519M	19	28	30	13	38	120	10 / 160
453520M	20	29.2	30	13	38	120	10 / 160
453521M	21	30	30	14	40	125	8 / 160
453522M	22	32	30	14	40	143	8 / 160
453523M	23	33	30	15	40	143	8 / 160
453524M	24	34	30	15	42	152	6 / 120
453525M	25	36	30	15	42	168	6 / 120
453526M	26	37	30	15	42	173	6 / 120
453527M	27	38	30	16	44	176	6 / 120
453528M	28	41	30	16	44	194	6 / 120
453529M	29	41	30	17	44	194	6 / 120
453530M	30	42	30.5	17	44	201	6 / 120
453532M	32	46	30	19	44	205	6 / 120
453533M	33	46	30	19	46	227	6 / 96
453534M	34	46	30	20	46	231	6 / 96
453536M	36	47	30	20	46	248	6 / 96
453538M	38	50	30	21	50	241	6 / 60
453539M	39	51	30	22	50	240	6 / 60
453541M	41	52	30	22	52	283	6 / 60
453546M	46	59	30	23	55	408	4 / 32

Impact Standard Socket

- Material - chrome molybdenum alloy steel
- Finished with phosphate sunk

4535 S

- 1/2" drive standard length
- 6 points
- Inch size
- Thin walled design on square driving side
- ANSI/ASME B107.2

KING TONY	inch	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
453510S	5/16	14	25	7	38	67	10 / 200
453512S	3/8	17	25	7	38	70	10 / 200
453514S	7/16	18	25	8	38	71	10 / 200
453516S	1/2	20	25	10	38	72	10 / 200
453518S	9/16	22	25	10	38	77	10 / 200
453520S	5/8	24	25	11	38	112	10 / 160
453522S	11/16	26	30	12	38	115	10 / 160
453524S	3/4	28	30	13	38	120	10 / 160
453526S	13/16	30	30	14	40	125	8 / 160
453528S	7/8	32	30	14	40	143	8 / 160
453530S	15/16	34	30	15	42	152	6 / 120
453532S	1	36	30	15	42	168	6 / 120
453534S	1-1/16	38	30	16	44	176	6 / 120
453536S	1-1/8	41	30	17	44	194	6 / 120
453538S	1-3/16	42	30.5	17	44	201	6 / 120
453540S	1-1/4	46	30	18	44	205	6 / 120

Impact Deep Socket

- Material - chrome molybdenum alloy steel
- Finished with phosphate sunk

○ 4430 M

- 1/2" drive deep version
- 12 points
- Metric size
- Thin walled design on square driving side
- DIN 3121

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
443008M	8	14	25	12	78	130	6 / 120
443009M	9	15	25	12	78	135	6 / 120
443010M	10	17	25	12	80	150	6 / 120
443011M	11	18	25	13	80	160	6 / 120
443012M	12	19	25	14	80	170	6 / 120
443013M	13	20	25	14	80	165	6 / 120
443014M	14	22	25	14	80	180	6 / 120
443015M	15	23	30	16	80	236	6 / 96
443016M	16	24	30	16	80	243	6 / 96
443017M	17	26	30	16	80	255	6 / 96
443018M	18	27	30	17	80	267	6 / 96
443019M	19	28	30	18	80	260	6 / 96
443020M	20	29.2	30	20	80	252	6 / 96
443021M	21	30	30	20	80	251	6 / 96
443022M	22	32	30	22	80	304	5 / 60
443023M	23	33	30	24	80	310	5 / 60
443024M	24	34	30	24	80	318	5 / 60
443027M	27	38	30	27	80	368	5 / 60
443030M	30	42	30.5	30	80	422	5 / 50
443032M	32	46	30	32	80	460	1 / 24
443036M	36	47	30	36	80	535	1 / 24

○ 4435 M

- 1/2" drive deep version
- 6 points
- Metric size
- Thin walled design on square driving side
- DIN 3121

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
443508M	8	14	25	12	78	116	6 / 120
443509M	9	15	25	12	78	125	6 / 120
443510M	10	17	25	12	80	136	6 / 120
443511M	11	18	25	13	80	144	6 / 120
443512M	12	19	25	14	80	157	6 / 120
443513M	13	20	25	14	80	157	6 / 120
443514M	14	22	25	14	80	172	6 / 120
443515M	15	23	30	16	80	223	6 / 96
443516M	16	24	30	16	80	230	6 / 96
443517M	17	26	30	16	80	240	6 / 96
443518M	18	27	30	17	80	255	6 / 96
443519M	19	28	30	18	80	236	6 / 96
443520M	20	29.2	30	20	80	244	6 / 96
443521M	21	30	30	20	80	240	6 / 96
443522M	22	32	30	22	80	296	5 / 60
443523M	23	33	30	24	80	300	5 / 60
443524M	24	34	30	24	80	308	5 / 60
443525M	25	36	30	24	80	342	5 / 60
443526M	26	37	30	27	80	344	5 / 60
443527M	27	38	30	27	80	356	5 / 60
443528M	28	41	30	27	80	424	5 / 50
443529M	29	41	30	27	80	404	5 / 50
443530M	30	42	30.5	30	80	416	5 / 50
443532M	32	46	30	32	80	510	1 / 24
443533M	33	46	30	32	80	521	1 / 24
443534M	34	46	30	33	80	539	1 / 24
443536M	36	47	30	36	80	556	1 / 24
443538M	38	50	30	38	80	617	1 / 24
443541M	41	52	30	38	80	635	1 / 24
443546M	46	59	30	40	80	825	1 / 24

Impact Deep Socket

- Material - chrome molybdenum alloy steel
- Finished with phosphate sunk

4435 S

- 1/2" drive deep version
- 6 points
- Inch size
- Thin walled design on square driving side
- ANSI/ASME B107.2

KING TONY	inch	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
443510S	5/16	14	25	12	78	123	6 / 120
443512S	3/8	17	25	12	80	148	6 / 120
443514S	7/16	18	25	13	80	148	6 / 120
443516S	1/2	20	25	14	80	159	6 / 120
443518S	9/16	22	25	14	80	170	6 / 120
443520S	5/8	24	25	16	80	232	6 / 96
443522S	11/16	26	30	17	80	235	6 / 96
443524S	3/4	28	30	18	80	251	6 / 96
443526S	13/16	30	30	20	80	243	6 / 96
443528S	7/8	32	30	22	80	292	5 / 60
443530S	15/16	34	30	24	80	308	5 / 60
443532S	1	36	30	24	80	336	5 / 60
443534S	1-1/16	38	30	27	80	356	5 / 60
443536S	1-1/8	41	30	27	80	401	5 / 50
443538S	1-3/16	42	30.5	30	80	409	5 / 50
443540S	1-1/4	46	30	32	80	423	1 / 24

Impact Thin Wall Socket

- Material - chrome molybdenum alloy steel
- Finished with phosphate sunk

4835 M

- 1/2" drive thin wall version
- 6 points
- Metric size
- Thin walled design on square driving side
- DIN 3121

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
483510M	10	16	25	20	52	92	10 / 180
483511M	11	17	25	20	52	92	10 / 180
483512M	12	18	25	20	52	92	10 / 180
483513M	13	19	25	20	52	95	10 / 180
483514M	14	21	25	20	52	101	10 / 180
483516M	16	23	25	20	52	149	8 / 80
483517M	17	25	25	23	52	152	8 / 80
483519M	19	27	30	23	52	148	8 / 80
483521M	21	29	30	25	52	152	8 / 80
483522M	22	31	30	25	52	164	8 / 80
483523M	23	32	30	26	52	172	8 / 80
483524M	24	33	30	26	52	174	8 / 80
483526M	26	36	30	27	65	241	6 / 60
483527M	27	37	30	27	65	248	6 / 60
483530M	30	41	30.5	27	65	296	5 / 50

Impact Thin Wall Socket

- Material - chrome molybdenum alloy steel
- Finished with phosphate sunk

4930 M

- 1/2" drive deep thin wall version
- 12 points
- Metric size
- Thin walled design on square driving side
- DIN 3121

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
493008M	8	13.2	25	20	78	130	6 / 120
493009M	9	14.0	25	20	78	135	6 / 120
493010M	10	15.5	25	20	80	150	6 / 120
493011M	11	16.7	25	20	80	160	6 / 120
493012M	12	18.0	25	20	80	170	6 / 120
493013M	13	19.0	25	20	80	165	6 / 120
493014M	14	20.5	25	20	80	180	6 / 120
493015M	15	21.5	30	20	80	236	6 / 96
493016M	16	23.0	30	20	80	243	6 / 96
493017M	17	24.5	30	23	80	255	6 / 96
493018M	18	25.5	30	23	80	267	6 / 96
493019M	19	27.0	30	23	80	260	6 / 96
493020M	20	28.0	30	23	80	252	6 / 96
493021M	21	29.0	30	25	80	251	6 / 96
493022M	22	30.5	30	25	80	304	5 / 60
493023M	23	32.0	30	26	80	310	5 / 60
493024M	24	33.0	30	26	80	318	5 / 60
493027M	27	37.0	30	27	80	368	5 / 60
493030M	30	40.5	30	27	80	422	5 / 50
493032M	32	42.5	30	27	80	460	5 / 50
493036M	36	45.5	30	32	80	535	1 / 24

4935 M

- 1/2" drive deep thin wall version
- 6 points
- Metric size
- Thin walled design on square driving side
- DIN 3121

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
493510M	10	15.5	25	20	80	132	6 / 120
493511M	11	16.7	25	20	80	151	6 / 120
493512M	12	18.0	25	20	80	148	6 / 120
493513M	13	19.0	25	20	80	148	6 / 120
493514M	14	20.5	25	20	80	156	6 / 120
493516M	16	23.0	30	20	80	213	6 / 96
493517M	17	24.5	30	23	80	230	6 / 96
493519M	19	27.0	30	23	80	238	6 / 96
493521M	21	29.0	30	25	80	234	6 / 96
493522M	22	30.5	30	25	80	294	5 / 60
493523M	23	32.0	30	26	80	300	5 / 60
493524M	24	33.0	30	26	80	285	5 / 60
493526M	26	35.5	30	27	80	341	5 / 60
493527M	27	37.0	30	27	80	358	5 / 60
493530M	30	40.5	30	27	80	413	5 / 60

4935 S

- 1/2" drive deep thin wall version
- 6 points
- Inch size
- Thin walled design on square driving side
- ANSI/ASME B107.2

KING TONY	inch	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
493510S	5/16	13.0	25	20	80	129	6 / 120
493512S	3/8	16.0	25	20	80	145	6 / 120
493514S	7/16	16.7	25	20	80	148	6 / 120
493516S	1/2	19.0	25	20	80	159	6 / 120
493518S	9/16	20.5	25	20	80	165	6 / 120
493520S	5/8	23.0	25	20	80	170	6 / 120
493522S	11/16	24.5	30	23	80	235	6 / 96
493524S	3/4	27.0	30	23	80	255	6 / 96
493526S	13/16	29.0	30	25	80	292	5 / 60
493528S	7/8	30.5	30	25	80	308	5 / 60
493530S	15/16	33.0	30	26	80	336	5 / 60
493532S	1	34.0	30	26	80	356	5 / 60
493534S	1-1/16	37.0	30	27	80	405	5 / 60
493536S	1-1/8	39.0	30	27	80	414	5 / 50
493538S	1-3/16	40.5	30	27	80	417	5 / 50
493540S	1-1/4	42.5	30	27	80	422	5 / 50

Impact Extra Thin Wall Socket

- Material - Cr-Mo
- For aluminum alloy wheel
- Finished with phosphate sunk
- Super thin wall version has less strength than standard deep version

Thin walled design (D1)

4415 M

- 1/2" drive super thin wall version
- 6 points
- Metric size
- DIN 3121

NEW

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
441517M	17	23.8	25	17	80	236	6 / 96
441519M	19	25.8	30	20	80	249	6 / 96
441521M	21	27.8	30	22	80	241	6 / 96
441522M	22	29.5	30	24	80	215	6 / 96

Impact Star Socket

- Material - chrome molybdenum alloy steel
- Finished with phosphate sunk

4575 M

- 1/2" drive impact star socket
- For torx external screws
- DIN 3121

KING TONY	SIZE	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
457510M	E10	14.0	25.0	7.5	38	67	10 / 200
457512M	E12	15.9	25.0	9.0	38	69	10 / 200
457514M	E14	17.7	25.0	10.0	38	71	10 / 200
457516M	E16	20.0	25.0	11.0	38	76	10/ 200
457518M	E18	22.0	25.0	12.5	38	79	10 / 200
457520M	E20	24.5	30.0	14.0	38	118	10 / 160

Impact Universal Joint Socket

4A55 M

- 1/2" drive deep version
- 6 points
- metric size
- special design for confined spaces
- DIN 3121

Deep Version

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
4A5510M	10	17.0	27.5	19	91	195	10 / 80
4A5511M	11	19.0	27.5	19	91	207	10 / 80
4A5512M	12	19.0	27.5	19	91	202	10 / 80
4A5513M	13	21.8	27.5	19	91	207	10 / 80
4A5514M	14	22.0	27.5	19	91	217	10 / 80
4A5515M	15	22.0	27.5	19	91	228	10 / 80
4A5516M	16	23.9	27.5	19	91	234	10 / 80
4A5517M	17	26.0	27.5	19	91	256	6 / 60
4A5518M	18	26.0	27.5	19	91	248	6 / 60
4A5519M	19	27.9	27.5	19	91	259	6 / 60
4A5521M	21	30.0	27.5	19	91	272	6 / 60
4A5522M	22	31.7	27.5	23.5	91	278	6 / 60
4A5524M	24	35.8	27.5	24	91	309	6 / 60

4A55 S

- 1/2" drive deep version
- 6 points
- Inch size
- special design for confined spaces
- DIN 3121

NEW

Deep Version

KING TONY	inch	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
4A5512S	3/8	17.0	27.5	19	91	195	10 / 80
4A5514S	7/16	19.0	27.5	19	91	207	10 / 80
4A5516S	1/2	21.8	27.5	19	91	207	10 / 80
4A5518S	9/16	22.0	27.5	19	91	217	10 / 80
4A5520S	5/8	23.9	27.5	19	91	234	10 / 80
4A5522S	11/16	26.0	27.5	19	91	256	6 / 60
4A5524S	3/4	27.9	27.5	19	91	259	6 / 60
4A5526S	13/16	30.0	27.5	19	91	273	6 / 60
4A5528S	7/8	31.7	27.5	23.5	91	278	6 / 60
4A5530S	15/16	35.8	27.5	24	91	309	6 / 60

Impact Universal Joint Socket

4B55 M

- 1/2" drive standard length
- 6 points
- metric size
- special design for confined spaces
- DIN 3121

Standard Length

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
4B5510M	10	17.0	27.5	12	64	161	10 / 120
4B5511M	11	19.0	27.5	12	64	166	10 / 120
4B5512M	12	19.0	27.5	12	64	162	10 / 120
4B5513M	13	21.8	27.5	12	64	176	10 / 120
4B5514M	14	22.0	27.5	12	64	174	10 / 120
4B5515M	15	22.0	27.5	12	64	172	10 / 120
4B5516M	16	23.9	27.5	12	64	180	10 / 120
4B5517M	17	25.0	27.5	12	64	173	10 / 120
4B5518M	18	25.8	27.5	12	64	173	10 / 120
4B5519M	19	27.9	27.5	12	64	187	10 / 120
4B5521M	21	30.0	27.5	12	64	190	10 / 120
4B5522M	22	31.7	27.5	12	64	196	10 / 120
4B5524M	24	35.8	27.5	12	64	217	6 / 96

4B55 S

- 1/2" drive standard length
- 6 points
- Inch size NEW
- special design for confined spaces
- DIN 3121

Standard Length

KING TONY	inch	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
4B5512S	3/8	17.0	27.5	12	64	161	10 / 120
4B5514S	7/16	19.0	27.5	12	64	166	10 / 120
4B5516S	1/2	21.8	27.5	12	64	176	10 / 120
4B5518S	9/16	22.0	27.5	12	64	174	10 / 120
4B5520S	5/8	23.9	27.5	12	64	180	10 / 120
4B5522S	11/16	25.0	27.5	12	64	173	10 / 120
4B5524S	3/4	27.9	27.5	12	64	187	10 / 120
4B5526S	13/16	30.0	27.5	12	64	190	10 / 120
4B5528S	7/8	31.7	27.5	12	64	196	10 / 120
4B5530S	15/16	35.8	27.5	12	64	217	6 / 96

Impact Universal Joint Socket Set

4440 SP NEW

- 10 PC. 1/2" drive deep impact universal socket set

	Contents
4440SP	3/8 7/16 1/2 9/16 5/8 1/16 3/4 3/16 7/8 5/16 4A55S

kg		Metal case size (mm)
3.3	5	318 x 147 x 46 (0.076cuft)

4450 SP NEW

- 10 PC. 1/2" drive impact universal socket set

	Contents
4450SP	3/8 7/16 1/2 9/16 5/8 1/16 3/4 3/16 7/8 5/16 4B55S

kg		Metal case size (mm)
2.8	5	318 x 147 x 46 (0.076cuft)

Impact Bit Socket

- Material - chrome molybdenum alloy steel
- Finishing - with phosphate sunk

CAUTION
1. Do not over - load.
2. Control the air pressure under 6.3 bar, adjust the suitable torque from 0.

4053
4063

- 1/2" drive impact bit socket
- For torx internal screws
- DIN 3121

KING TONY	SIZE	L (mm)	Max.Torq (Nm)	g	
405325	T25	60	20.0	73.0	10 / 180
406325	T25	100	20.0	97.0	6 / 120
405327	T27	60	30.0	73.5	10 / 180
406327	T27	100	30.0	97.5	6 / 120
405330	T30	60	40.0	74.0	10 / 180
406330	T30	100	40.0	98.0	6 / 120
405340	T40	60	70.0	85.0	10 / 180
406340	T40	100	70.0	110.0	6 / 120
405345	T45	60	110.0	90.0	10 / 180
406345	T45	100	110.0	130.0	6 / 120
405350	T50	60	165.5	95.0	10 / 180
406350	T50	100	165.5	150.0	6 / 120
405355	T55	60	260.0	100.0	10 / 180
406355	T55	100	260.0	160.0	6 / 120
405360	T60	60	450.0	105.0	10 / 180
406360	T60	100	450.0	170.0	6 / 120

4053

4063

4055 M

- 1/2" drive impact bit socket
- Hexagon head
- DIN 3121

KING TONY	SIZE (mm)	L (mm)	Max.Torq (Nm)	g	
405504M	4	60	20.8	72	10 / 180
405505M	5	60	36.0	73	10 / 180
405506M	6	60	62.4	74	10 / 180
405507M	7	60	93.6	76	10 / 180
405508M	8	60	144.0	78	10 / 180
405510M	10	60	264.0	86	10 / 180
405512M	12	60	420.0	99	10 / 180
405513M	13	60	518.0	105	10 / 180
405514M	14	60	650.0	110	10 / 180

4055 S

- 1/2" drive impact bit socket
- Hexagon head
- ANSI/ASME B107.2

KING TONY	SIZE (inch)	L (mm)	Max.Torq (Nm)	g	
405506S	3/16	60	36.0	66	10 / 180
405508S	1/4	60	93.6	74	10 / 180
405510S	5/16	60	144.0	77	10 / 180
405512S	3/8	60	264.0	80	10 / 180
405514S	7/16	60	420.0	84	10 / 180
405516S	1/2	60	518.0	88	10 / 180

4056 M

- 1/2" drive impact bit socket
- Spline head
- DIN 3121

KING TONY	SIZE	L (mm)	Max.Torq (Nm)	g	
405608M	M 8	60	144.0	73	10 / 180
405610M	M10	60	264.0	81	10 / 180
405612M	M12	60	420.0	88	10 / 180

Impact Bit Socket

- Material - chrome molybdenum alloy steel
- Finished with phosphate sunk

CAUTION
1. Do not over - load.
2. Control the air pressure under 6.3 bar, adjust the suitable torque from 0.

4015 M

- 1/2" drive impact bit socket
- Hexagon head
- DIN 3121

KING TONY	SIZE (mm)	L (mm)	Max.Torq (Nm)	g	
401505M	5	80	36.0	84	6 / 120
401506M	6	80	62.4	86	6 / 120
401507M	7	80	93.6	89	6 / 120
401508M	8	80	144.0	96	6 / 120
401509M	9	80	229.0	114	6 / 120
401510M	10	80	264.0	136	6 / 120
401512M	12	80	420.0	145	6 / 120
401513M	13	80	518.0	155	6 / 120
401514M	14	80	650.0	164	6 / 120
401517M	17	80	715.0	248	6 / 96
401519M	19	80	786.0	246	6 / 96

4015 S

- 1/2" drive impact bit socket
- Hexagon head
- DIN 3121

KING TONY	SIZE (inch)	L (mm)	Max.Torq (Nm)	g	
401508S	1/4	80	144	87	6 / 120
401512S	3/8	80	420	125	6 / 120
401516S	1/2	80	518	150	6 / 120

4065 M

- 1/2" drive impact bit socket
- Hexagon head
- DIN 3121

KING TONY	SIZE (mm)	L (mm)	Max.Torq (Nm)	g	
406504M	4	100	20.8	96	6 / 120
406505M	5	100	36.0	97	6 / 120
406506M	6	100	62.4	98	6 / 120
406508M	8	100	144.0	110	6 / 120
406510M	10	100	264.0	150	6 / 120
406512M	12	100	420.0	170	6 / 120
406514M	14	100	650.0	190	6 / 120

4075 M

- 1/2" drive impact bit socket
- Hexagon head
- DIN 3121

KING TONY	SIZE (mm)	L (mm)	Max.Torq (Nm)	g	
407505M	5	150	36.0	115	6 / 120
407506M	6	150	62.4	125	6 / 120
407508M	8	150	144.0	145	6 / 120
407510M	10	150	264.0	185	6 / 120
407512M	12	150	420.0	225	6 / 120
407514M	14	150	650.0	250	6 / 120

Impact Accessory

- Material - chrome molybdenum alloy steel
- Finished with phosphate sunk

4147

- 1/2" drive bit holder
- DIN 3121

KING TONY	SIZE	Overall Length (mm)	g	
414708S	1/4"	48	69	12 / 216
414710S	5/16"	48	70	12 / 216
414710M	10 mm	48	72	12 / 216

414A08S

- 1/2" drive bit holder
- Quick-release
- DIN 3121

KING TONY	SIZE	Overall Length (mm)	g	
414A08S	1/4"	51.2	93.6	10 / 180

Impact Accessory

- Material - chrome molybdenum alloy steel
- Finished with phosphate sunk

4260

- 1/2" drive extension bar
- DIN 3121

KING TONY	Total Length (inch)	(mm)	g	
4260-03	3	75	197	4 / 80
4260-04	4	100	255	4 / 80
4260-05	5	125	277	2 / 40
4260-06	6	150	340	4 / 80
4260-10	10	250	452	4 / 48
4260-12	12	300	595	2 / 40

4260P

- 1/2" drive extension bar - with ball
- DIN 3121

KING TONY	Total Length (inch)	(mm)	g	
4260-03P	3	75	197	4 / 80
4260-04P	4	100	255	4 / 80
4260-05P	5	125	277	2 / 40
4260-06P	6	150	340	4 / 80
4260-10P	10	250	452	4 / 48
4260-12P	12	300	595	2 / 40

4796

- 1/2" drive universal joint
- DIN 3121

KING TONY	L (inch)	(mm)	g	
4796	2-3/8	59	121	6 / 96

4796P

- 1/2" drive universal joint - with ball
- DIN 3121

KING TONY	L (inch)	(mm)	g	
4796P	2-3/8	59	121	6 / 96

4797 4798

- 1/2" drive universal joint
- DIN 3121

KING TONY	Total Length (inch)	(mm)	g	
4797	2-1/2	67	172	6 / 96
4798	3	75	222	6 / 96

4797

4798

4797P 4798P
479AP

- 1/2" drive universal joint - with ball
- DIN 3121

KING TONY	Total Length (inch)	(mm)	g	
479AP	2-3/8	61	161	6 / 96
4797P	2-1/2	65	172	6 / 96
4798P	3	74	222	6 / 96

4797P

4798P

479AP

Impact Accessory

- Material - chrome molybdenum alloy steel
- Finished with phosphate sunk

4863 4866

- 1/2" drive adapter
- Converting to 3/8", 3/4" drive
- 4863→ Max. torque 380 Nm
- DIN 3121

KING TONY	Spec.	g	
4863	1/2"F x 3/8"M	95	10 / 160
4866	1/2"F x 3/4"M	174	8 / 160

4863P 4866P

- 1/2" drive adapter - with ball
- Converting to 3/8", 3/4" drive
- 4863→ Max. torque 320 Nm
- DIN 3121

KING TONY	Spec.	g	
4863P	1/2"F x 3/8"M	95	10 / 160
4866P	1/2"F x 3/4"M	174	8 / 160

4873

- 1/2" drive adapter
- Converting to 3/8"
- 4873→ Max. torque 320 Nm
- DIN 3121

KING TONY	Spec.	d (mm)	g	
4873	1/2"F x 3/8"M	25	80	10 / 160

4863 4873

4873P

- 1/2" drive adapter - with ball
- Converting to 3/8"
- 4873→ Max. torque 320 Nm
- DIN 3121

KING TONY	Spec.	d (mm)	g	
4873P	1/2"F x 3/8"M	25	80	10 / 160

4863P 4873P

90401
90402

- 1/2" drive locking ring
- High tensile rubber material

90601
90602

- 1/2" drive locking pins
- Chrome vanadium steel
- DIN 3129

	Desp.	ø	d / ℓ	Applied to socket sizes
90401	ring	3.5	19	4535M (8~14mm) 4535S (15/16"~9/16") 4435M (8~14mm) 4435S (15/16"~9/16") 4015M (5~14mm) 4015S (1/4"~1/2") 4055M (4~14mm) 4055S (3/16"~1/2") 4935M (10~14mm) 4935S (7/16"~9/16")
90601	pin	3.0	20	4415M (17mm) 4575 (E10~E18) 4835M (10~17mm) 414A085,4053.4063 4530M (8~14mm) 4065.4075.4873.4015 4147.4055.4056
90402	ring	3.5	23	4535M (15~46mm) 4535S (11/16"~1-1/4") 4435M (15~46mm) 4435S (5/8"~1-1/4") 4935M (16~30mm) 4935S (11/16"~1-1/4") 4015M (17 19mm) 4260.4796.4797.4863 4415M (19 21mm) 4873.4866
90602	pin	3.0	25	4530M (15~36mm) 4575M (E20) 4835M (19~30mm)

90401
90402

90601
90602

Impact Socket Set

○ 4408 MP
○ 4408 SP

- 8 PC. 1/2" drive impact socket set
- 6 points, standard length
- 10~24 mm (3/8"~15/16")

		Contents
4408MP	4535M	10 12 13 14 17 19 21 24
4408SP	4535S	3/8 7/16 1/2 9/16 11/16 3/4 13/16 15/16

4408MP

4408SP

	kg		Metal case size (mm)
4408MP	1.3	20	270 x 73 x 46 (0.032 cuft)
4408SP	1.3		

○ 4412 MP

- 11 PC. 1/2" drive impact socket set
- 6 points, standard length
- 10~21 mm

		Contents
4412MP	4535M	10 11 12 13 14 15 16 17 18 19 21

kg		Metal case size (mm)
1.5	8	224 x 94 x 40 (0.03 cuft)

○ 4414 SP

- 14 PC. 1/2" drive impact socket set
- 6 points, standard length
- 3/8"~1-1/4"

		Contents
4414SP	4535S	3/8 7/16 1/2 9/16 5/8 11/16 3/4 13/16 7/8 15/16 1 1-1/16 1-1/8 1-1/4

kg		Metal case size (mm)
2.4	8	270 x 100 x 49 (0.048 cuft)

○ 4410 MP
○ 4410 SP

- 8 PC. 1/2" drive impact socket set
- 6 points, deep version
- 12~23 mm (1/2"~15/16")

		Contents
4410MP	4435M	12 13 14 17 19 21 22 23
4410SP	4435S	1/2 9/16 5/8 11/16 3/4 13/16 7/8 15/16

4410MP

4410SP

	kg		Metal case size (mm)
4410MP 4410SP	2.3	12	246 x 103 x 38 (0.034 cuft)

Impact Socket Set

4415 MP

- 15 PC. 1/2" drive impact socket set
- 6 points, deep version
- 10~32 mm

	Contents
4415MP	4435M: 10 11 12 13 14 15 16 17 18 19 21 24 26 29 32

4415MP

kg		Metal case size (mm)
4.9	6	445 x 135 x 50 (0.106 cuft)

4415 MP 03

- 15 PC. 1/2" drive impact socket set
- 6 points, deep version
- 10~32 mm

	Contents
4415MP03	4435M: 10 11 12 13 14 15 16 17 19 21 22 24 27 30 32

4415MP03

kg		Metal case size (mm)
4.9	6	445 x 135 x 50 (0.106 cuft)

4416 SP

- 14 PC. 1/2" drive impact socket set
- 6 points, deep version
- 3/8"~1-1/4"

	Contents
4416SP	4435S: 3/8 7/16 1/2 9/16 5/8 11/16 3/4 13/16 7/8 15/16 1 1-1/16 1-1/8 1-1/4

4416SP

kg		Metal case size (mm)
4.8	6	445 x 135 x 50 (0.106 cuft)

4413 MP

- 8 PC. 1/2" drive impact socket set
- 6 points, thin wall version
- 10~24 mm

	Contents
4413MP	4835M: 10 12 13 14 17 19 21 24

4413MP

kg		Metal case size (mm)
1.5	20	270 x 73 x 46 (0.032 cuft)

Impact Bit Socket Set

- Material - chrome molybdenum alloy steel
- Finishing with phosphate sunk

4417 PP

- 7 PC. 1/2" drive impact bit socket set
- For torx internal screws
- 60mm L, T25 ~ T60

		Contents
4417PP	4053	T25 T30 T40 T45 T50 T55 T60

4417PP

kg		Metal case size (mm)
0.94	20	198 x 105 x 32 (0.023 cuft)

4407 MP

- 7 PC. 1/2" drive impact bit socket
- For hex head screws
- 60mm L, 4 ~ 14 mm

		Contents
4407MP	4055	4 5 6 8 10 12 14

4407MP

kg		Metal case size (mm)
0.94	20	198 x 105 x 32 (0.023 cuft)

4467 PP

- 7 PC. 1/2" drive impact bit socket set
- For torx internal screws
- 100mm L, T25 ~T60

		Contents
4467PP	4063	T25 T30 T40 T45 T50 T55 T60

4467PP

kg		Metal case size (mm)
1.31	18	244 x 118 x 37 (0.038 cuft)

4457 MP

- 7 PC. 1/2" drive impact bit socket
- For hex head screws
- 100mm L, 4 ~ 14 mm

		Contents
4457MP	4065	4 5 6 8 10 12 14

4457MP

kg		Metal case size (mm)
1.44	18	244 x 118 x 37 (0.038 cuft)

4476 MP

- 6 PC. 1/2" drive impact bit socket set
- For hex head screws
- 150mm L, 5 ~ 14 mm

		Contents
4476MP	4075	5 6 8 10 12 14

4476MP

kg		Metal case size (mm)
1.47	18	244 x 118 x 37 (0.038 cuft)

Impact Socket Shelf Set

- Material from chrome molybdenum alloy steel
- Finished with phosphate sunk

○ 4472 MP 4472MP : 158 PC.
○ 4472 SP 4472SP : 106 PC.

▪ Standard impact socket

		Contents	Each Q'ty
4472MP	4535M	8 9 10 11 12 13 14	8
		15 16 17 18 19 20 21	6
		22 23 24	7
		25 26 27 28	6
		29 30 32	5
4472SP	4535S	5/16 3/8 7/16 1/2 9/16	8
		5/8 11/16 3/4 13/16	6
		7/8 15/16	7
		1 1-1/16 1-1/8	6
		1-3/16 1-1/4	5

4472MP / 4472SP

	SPEC.	kg	CUFT	Metal case size (mm)
4472MP-A	87103	10.3	2.3	427 x 282 x 297 (1.866 cuft)
4472MP-D	158 pcs socket content	19.2	0.6	
4472SP-A	87103	10.3	2.3	
4472SP-D	106 pcs socket content	13	0.6	

○ 4466 MP 4466MP : 166 PC.
○ 4466 SP 4466SP : 102 PC.

▪ Deep impact socket

		Contents	Each Q'ty
4466MP	4435M	8 9 10 11 12 13 14	8
		15 16 17 18 19 20 21 22 23 24	7
		25 26 27 28 29	6
		30 32	5
4466SP	4435S	5/16 3/8 7/16 1/2 9/16	8
		5/8 11/16 3/4 13/16 7/8 15/16	7
		1 1-1/16 1-1/8	6
		1-3/16 1-1/4	5

4466MP / 4466SP

	SPEC.	kg	CUFT	Metal case size (mm)
4466MP-A	87103	10.3	2.3	427 x 282 x 297 (1.866 cuft)
4466MP-D	166 pcs socket content	42.3	2.0	
4466SP-A	87103	10.3	2.3	
4466SP-D	102 pcs socket content	27.6	2.0	

Impact Standard Socket

- Material - chrome molybdenum alloy steel
- Finished with phosphate sunk

6510 M

- 3/4" drive standard length
- Lightweight type
- 12 points
- Metric size
- Thin walled design on square driving side
- DIN 3121

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
651017M	17	29.0	38	10	50	227	8 / 96
651018M	18	30.0	38	10	50	225	8 / 96
651019M	19	32.0	38	10	50	238	8 / 96
651021M	21	35.0	38	13	50	254	8 / 96
651022M	22	36.0	38	13	50	260	8 / 96
651023M	23	37.0	38	15	50	263	8 / 96
651024M	24	38.0	38	15	50	249	8 / 96
651026M	26	38.0	38	15	53	260	6 / 48
651027M	27	42.0	38	18	53	332	6 / 48
651028M	28	44.0	38	18	53	353	6 / 48
651029M	29	45.0	38	18	53	362	6 / 48
651030M	30	46.0	38	20	53	342	6 / 48

3/4" Impact Socket

6515 M

- 3/4" drive standard length
- Lightweight type
- 6 points
- Metric size
- Thin walled design on square driving side
- DIN 3121

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
651514M	14	25.0	38	10	50	215	8 / 96
651515M	15	26.0	38	10	50	217	8 / 96
651516M	16	27.5	38	10	50	220	8 / 96
651517M	17	29.0	38	10	50	225	8 / 96
651518M	18	30.0	38	10	50	230	8 / 96
651519M	19	32.0	38	10	50	238	8 / 96
651521M	21	35.0	38	13	50	252	8 / 96
651522M	22	36.0	38	13	50	257	8 / 96
651523M	23	37.0	38	15	50	283	8 / 96
651524M	24	38.0	38	15	50	288	8 / 96
651525M	25	38.0	38	15	53	321	8 / 96
651526M	26	38.0	38	15	53	321	6 / 48
651527M	27	42.0	38	18	53	320	6 / 48
651528M	28	44.0	38	18	53	345	6 / 48
651529M	29	45.0	38	18	53	350	6 / 48
651530M	30	46.0	38	20	53	360	6 / 48

6530 M

- 3/4" drive standard length
- 12 points
- Metric size
- Thin walled design on square driving side
- DIN 3129 ,ISO 2725-2

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
653017M	17	29.0	44	10	50	316	6 / 48
653019M	19	32.0	44	10	50	329	6 / 48
653021M	21	35.0	44	13	50	341	6 / 48
653022M	22	36.0	44	13	50	346	6 / 48
653023M	23	37.0	44	15	50	350	6 / 48
653024M	24	38.0	44	15	50	352	6 / 48
653026M	26	40.0	44	15	53	358	6 / 48
653027M	27	42.0	44	18	53	380	6 / 48
653028M	28	44.0	44	18	53	394	6 / 48
653029M	29	45.0	44	18	53	404	6 / 48
653030M	30	46.0	44	20	53	412	6 / 48
653032M	32	48.0	44	20	57	460	6 / 36
653033M	33	50.0	44	20	57	479	6 / 36
653034M	34	51.0	44	22	57	491	6 / 36
653035M	35	52.0	44	22	57	497	6 / 36
653036M	36	53.0	44	22	57	519	6 / 36
653038M	38	56.0	44	22	57	540	4 / 32
653040M	40	58.0	44	22	58	567	4 / 32
653041M	41	59.0	44	24	58	580	4 / 32
653042M	42	61.0	44	24	58	600	2 / 24
653046M	46	66.0	44	24	62	950	2 / 24
653063M	63	84.5	54	40	80	1343	1 / 12
653065M	65	86.5	54	43	80	1373	1 / 12
653070M	70	92.0	54	45	83	1451	1 / 12

Impact Standard Socket

- Material - chrome molybdenum alloy steel
- Finished with phosphate sunk

6535 M

- 3/4" drive standard length
- Standard type
- 6 points
- Metric size
- Thin walled design on square driving side
- DIN 3129 ,ISO 2725-2

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
653517M	17	29.0	44	10	50	316	6 / 48
653518M	18	30.0	44	10	50	324	6 / 48
653519M	19	32.0	44	10	50	329	6 / 48
653521M	21	35.0	44	13	50	341	6 / 48
653522M	22	36.0	44	13	50	346	6 / 48
653523M	23	37.0	44	15	50	350	6 / 48
653524M	24	38.0	44	15	50	352	6 / 48
653526M	26	40.0	44	15	53	358	6 / 48
653527M	27	42.0	44	18	53	380	6 / 48
653528M	28	44.0	44	18	53	394	6 / 48
653529M	29	45.0	44	18	53	404	6 / 48
653530M	30	46.0	44	20	53	412	6 / 48
653532M	32	48.0	44	20	57	460	6 / 36
653533M	33	50.0	44	20	57	479	6 / 36
653534M	34	51.0	44	22	57	491	6 / 36
653535M	35	52.0	44	22	57	497	6 / 36
653536M	36	53.0	44	22	57	519	6 / 36
653538M	38	56.0	44	22	57	540	4 / 32
653540M	40	58.0	44	22	58	567	4 / 32
653541M	41	59.0	44	24	58	580	4 / 32
653542M	42	61.0	44	24	58	616	2 / 24
653543M	43	62.0	44	24	58	636	2 / 24
653544M	44	64.0	44	24	62	676	2 / 24
653546M	46	66.0	44	24	62	717	2 / 24
653548M	48	68.0	44	26	65	925	2 / 24
653550M	50	71.0	44	26	65	955	1 / 20
653552M	52	74.0	54	30	68	1085	1 / 20
653554M	54	76.0	54	30	68	1125	1 / 20
653555M	55	77.0	54	30	70	1160	1 / 20
653557M	57	79.0	54	32	70	1198	1 / 20
653558M	58	81.0	54	32	70	1226	1 / 20
653560M	60	84.0	54	32	70	1313	1 / 20
653563M	63	84.5	54	40	80	1341	1 / 12
653565M	65	86.5	54	43	80	1358	1 / 12

6535 S

- 3/4" drive standard length
- Standard type
- 6 points
- Inch size
- Thin walled design on square driving side
- ANSI/ASME B107.2

KING TONY	inch	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
653522S	11/16	29	38	10	50	225	8 / 96
653524S	3/4	32	38	10	50	238	8 / 96
653526S	13/16	35	38	13	50	252	8 / 96
653528S	7/8	36	38	13	50	257	8 / 96
653530S	15/16	37	38	15	50	288	8 / 96
653532S	1	38	38	15	53	320	8 / 96
653534S	1-1/16	42	40	18	53	325	6 / 48
653536S	1-1/8	45	44.7	18	53	355	6 / 48
653538S	1-3/16	46	40	20	53	365	6 / 48
653540S	1-1/4	48	44	20	57	460	6 / 36
653542S	1-5/16	50	44	20	57	479	6 / 36
653544S	1-3/8	52	44	22	57	497	6 / 36
653546S	1-7/16	54	44	22	57	529	6 / 36
653548S	1-1/2	56	44	22	57	540	4 / 32
653550S	1-9/16	58	44	22	58	567	4 / 32
653552S	1-5/8	59	44	24	58	580	4 / 32
653554S	1-11/16	63.5	44	25	58	636	2 / 24
653556S	1-3/4	64	44	25	62	676	2 / 24
653558S	1-13/16	66	44	25.5	62	717	2 / 24
653560S	1-7/8	68	54	27	65	925	2 / 24
653562S	1-15/16	70	54	27	65	955	1 / 20
653564S	2	72	54	28	68	1035	1 / 20
653566S	2-1/16	74	54	30	68	1078	1 / 20
653568S	2-1/8	76	54	30	68	1122	1 / 20
653570S	2-3/16	77	54	30.5	70	1151	1 / 20
653572S	2-1/4	79	54	32.5	70	1208	1 / 20
653574S	2-5/16	81	54	32.5	70	1245	1 / 20
653576S	2-3/8	84	54	33.5	70	1349	1 / 20

Impact Deep Socket

- Material - chrome molybdenum alloy steel
- Finished with phosphate sunk

6435 M

- 3/4" drive deep version
- 6 points
- Metric size
- Thin walled design on square driving side
- DIN 3121

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
643519M	19	32	44	16	90	558	1 / 24
643521M	21	35	44	18	90	592	1 / 24
643522M	22	36	44	18	90	607	1 / 24
643523M	23	37	44	23	90	607	1 / 24
643524M	24	38	44	23	90	626	1 / 24
643525M	25	40	44	25	90	661	1 / 24
643526M	26	40	44	25	90	623	1 / 24
643527M	27	42	44	27	90	623	1 / 24
643528M	28	44	44	27	90	670	1 / 24
643529M	29	45	44	27	90	670	1 / 24
643530M	30	46	44	27	90	691	1 / 24
643532M	32	48	44	30	90	728	1 / 24
643533M	33	50	44	30	90	790	1 / 24
643534M	34	51	44	32	90	794	1 / 24
643535M	35	52	44	32	90	803	1 / 24
643536M	36	53	44	32	90	809	1 / 24
643538M	38	56	44	34	90	882	1 / 24
643540M	40	58	44	34	90	928	1 / 24
643541M	41	59	44	34	90	938	1 / 24
643542M	42	61	44	36	95	1074	1 / 24
643543M	43	62	44	38	95	1103	1 / 10
643544M	44	64	44	38	95	1180	1 / 10
643546M	46	66	44	38	95	1210	1 / 10
643548M	48	68	44	40	95	1391	1 / 10
643550M	50	71	44	40	95	1479	1 / 10
643555M	55	77	54	45	100	1810	1 / 10
643560M	60	84.5	54	50	100	2010	1 / 6
643565M	65	86.5	54	54	100	1990	1 / 6

6435 S

- 3/4" drive deep version
- 6 points
- Inch size
- Thin walled design on square driving side
- ANSI/ASME B107.2

KING TONY	inch	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
643524S	3/4	32	38	16	90	455	1 / 24
643526S	13/16	35	38	18	90	490	1 / 24
643528S	7/8	36	38	18	90	495	1 / 24
643530S	15/16	37	38	23	90	495	1 / 24
643532S	1	38	38	25	90	500	1 / 24
643534S	1-1/16	42	44	27	90	624	1 / 24
643536S	1-1/8	44.7	44	27	90	680	1 / 24
643538S	1-3/16	46	44	27	90	684	1 / 24
643540S	1-1/4	48	44	30	90	733	1 / 24
643542S	1-5/16	50	44	30	90	789	1 / 24
643544S	1-3/8	52	44	32	90	804	1 / 24
643546S	1-7/16	54	44	32	90	844	1 / 24
643548S	1-1/2	56	44	34	90	871	1 / 24
643550S	1-9/16	58	44	34	90	928	1 / 24
643552S	1-5/8	59	44	34	90	941	1 / 24
643554S	1-11/16	63.5	44	38	95	1111	1 / 10
643556S	1-3/4	64	44	38	95	1168	1 / 10
643558S	1-13/16	66	44	38	95	1241	1 / 10
643560S	1-7/8	68	54	40	95	1397	1 / 10
643562S	1-15/16	70	54	40	95	1448	1 / 10
643564S	2	72	54	40	95	1521	1 / 10

Impact Thin Wall Socket

- Material - chrome molybdenum alloy steel
- Finished with phosphate sunk

6835 M

- 3/4" drive thin wall version
- 6 points
- Metric size
- Thin walled design on square driving side
- DIN 3121

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
683517M	17	28.0	44	16	60	320	6 / 48
683519M	19	30.0	44	16	60	348	6 / 48
683521M	21	33.0	44	18	60	355	6 / 48
683522M	22	34.0	44	18	60	362	6 / 48
683523M	23	35.0	44	23	60	370	6 / 48
683524M	24	36.5	44	23	60	378	6 / 48
683526M	26	39.0	44	25	80	400	1 / 24
683527M	27	40.0	44	26	80	424	1 / 24
683529M	29	43.0	44	26	80	460	1 / 24
683530M	30	44.0	44	26	80	478	1 / 24
683532M	32	46.5	44	26	80	512	1 / 24

6935 M

- 3/4" drive deep thin wall version
- 6 points
- Metric size
- Thin walled design on square driving side
- DIN 3121

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
693519M	19	30.0	44	16	90	562	1 / 24
693521M	21	33.0	44	18	90	597	1 / 24
693522M	22	34.0	44	18	90	612	1 / 24
693523M	23	35.0	44	23	90	614	1 / 24
693524M	24	36.5	44	23	90	619	1 / 24
693526M	26	39.0	44	25	90	629	1 / 24
693527M	27	40.0	44	27	90	631	1 / 24
693529M	29	43.0	44	27	90	672	1 / 24
693530M	30	44.0	44	27	90	693	1 / 24
693532M	32	46.5	44	30	90	733	1 / 24

6935 S

- 3/4" drive deep thin wall version
- 6 points
- Inch size
- Thin walled design on square driving side
- ANSI/ASME B107.2

KING TONY	inch	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
693524S	3/4	30.0	38	16	90	370	1 / 24
693526S	13/16	33.0	38	18	90	380	1 / 24
693528S	7/8	34.0	38	18	90	385	1 / 24
693530S	15/16	36.5	38	23	90	415	1 / 24
693532S	1	38.0	38	23	90	500	1 / 24
693534S	1-1/16	40.0	44	25	90	654	1 / 24
693536S	1-1/8	43.0	44	25	90	680	1 / 24
693538S	1-3/16	44.0	44	27	90	684	1 / 24
693540S	1-1/4	46.5	44	30	90	733	1 / 24

Impact Star Socket

- Material - chrome molybdenum alloy steel
- Finished with phosphate sunk

6575 M

- 3/4" drive impact star socket
- For torx external screws
- DIN 3121

NEW

KING TONY	SIZE	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
657524M	E24	32.5	44.0	17.0	56	382	6 / 48
657526M	E26	35.0	44.0	19.0	56	403	6 / 48
657528M	E28	36.5	44.0	25.5	56	414	6 / 48
657530M	E30	37.5	44.0	27.0	65	460	1 / 24
657532M	E32	39.5	44.0	29.0	65	470	1 / 24

Rear Wheel Socket

- Chrome molybdenum steel, phosphate sunk.

6514 M

- 3/4" drive
- 4 points
- Metric size
- DIN 3121

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
651417M	17	39.8	34	28	53	350	1 / 24
651419M	19	39.8	34	28	53	332	1 / 24
651420M	20	41.8	36	28	53	377	1 / 24
651421M	21	41.8	36	28	53	370	1 / 24

Impact Bit Socket

- Material - chrome molybdenum alloy steel
- Finished with phosphate sunk

6015 M

- 3/4" impact hex bit socket
- DIN 3121

KING TONY	SIZE	L (mm)	g	
601514M	14	87	325	2/48
601517M	17	87	343	2/48
601519M	19	87	365	2/48
601521M	21	87	490	1/24
601522M	22	87	522	1/24
601524M	24	87	555	1/24
601527M	27	87	604	1/24

1740
609616 M

- Hex bit & bit holder
- DIN 3121

KING TONY	S (mm)	L (mm)	g	
174010H	10	40	46	20 / 400
174012H	12	40	52	20 / 400
174014H	14	40	60	20 / 200
174017H	17	40	73	20 / 200
174019H	19	40	80	20 / 200
174022H	22	40	97	12 / 120
609616M	16	52	370	6 / 48

1740

609616M

6085

- 3/4" impact hex bit socket
- DIN 3121

KING TONY	S (mm)	L (mm)	g	
608510	10	77	416	4 / 40
608512	12	77	422	4 / 40
608514	14	77	430	4 / 40
608517	17	77	443	4 / 40
608519	19	77	450	4 / 40
608522	22	77	473	4 / 40

Impact Bit Socket

- Material - chrome molybdenum alloy steel
- Finished with phosphate sunk

1954
609622 M

- Hex bit & bit holder
- DIN 3121

KING TONY	S (mm)	L (mm)	g	
195419H	19	54.5	140	12 / 120
195422H	22	54.5	162	12 / 120
195424H	24	54.5	176	10 / 100
195427H	27	54.5	200	10 / 100
195432H	32	54.5	243	6 / 60
609622M	22	60.0	530	6 / 48

1954

609622M

6095

- 3/4" impact hex bit socket
- DIN 3121

KING TONY	S (mm)	L (mm)	g	
609519	19	93	670	1 / 24
609522	22	93	692	1 / 24
609524	24	93	706	1 / 24
609527	27	93	730	1 / 24
609532	32	93	783	1 / 24

Impact Accessory

- Chrome molybdenum alloy steel, phosphate sunk.

6260

- 3/4" drive extension bar
- DIN 3121

KING TONY	Overall Length (inch)	(mm)	g	
6260-04	4	100	577	2 / 20
6260-07	7	175	867	2 / 20
6260-10	10	250	1155	1 / 16
6260-13	13	330	1423	1 / 10

6260P

- 3/4" drive extension bars - with ball
- DIN 3121

KING TONY	Overall Length (inch)	(mm)	g	
6260-04P	4	100	577	2 / 20
6260-07P	7	175	867	2 / 20
6260-10P	10	250	1155	1 / 16
6260-13P	13	330	1423	1 / 10

6797 6798

- 3/4" drive universal joint
- DIN 3121

KING TONY	Overall Length (inch)	(mm)	g	
6797	4-1/2	114	742	2 / 20
6798	4-1/4	108	736	2 / 20

6797

6798

6797P 6798P

- 3/4" drive universal joint - with ball
- DIN 3121

KING TONY	Overall Length (inch)	(mm)	g	
6797P	4-1/2	114	742	2 / 20
6798P	4-1/4	108	736	2 / 20

6797P

6798P

Impact Accessory

6864 6868

- 3/4" drive adapter
- Converting to 1/2" drive
- 6864 → Max. torque 660 Nm
- DIN 3121

KING TONY	Spec.	g	
6864	3/4"F x 1/2"M	313	6 / 48
6868	3/4"F x 1"M	413	6 / 48

6864
6868

6864P 6868P

- 3/4" drive adapter - with ball
- Converting to1/2" drive
- 6864 → Max. torque 660 Nm
- DIN 3121

KING TONY	Spec.	g	
6864P	3/4"F x 1/2"M	313	6 / 48
6868P	3/4"F x 1"M	413	6 / 48

6864P
6868P

6874

- 3/4" drive adapter
- Converting to 1/2" drive
- 6874 → Max. torque 660 Nm
- DIN 3121

KING TONY	Spec.	d (mm)	g	
6874	3/4"F x 1/2"M	38	255	6 / 48

6874

6864 6874

6874P

- 3/4" drive adapter - with ball
- Converting to 1/2" drive
- 6874 → Max. torque 660 Nm
- DIN 3121

KING TONY	Spec.	d (mm)	g	
6874P	3/4"F x 1/2"M	38	255	6 / 48

6874P

6864P 6874P

90403
90404
90405

- 3/4" drive locking ring
- High tensile rubber material

90603
90604
90607

- 3/4" drive locking pins
- Chrome vanadium steel
- DIN 3129

	Desp.	ø	d / ℓ	Applied to socket sizes
90403	ring	3.5	33	6015M (14~19mm) 6435S (3/4"~1") 6510M (17~30mm) 6535S (11/16"~1-3/16") 6515M (17~30mm) 6935S (3/4"~1") 6874
90607	pin	3.0	30	
90404	ring	5.5	37	6535M (17~46mm) 6535S (1-1/4" ~ 1-13/16") 6435M (19~46mm) 6435S (1-1/16"~1-13/16") 6935M (19~32mm) 6935S (1-1/16"~1-1/4") 6015M (21~27mm) 6260.6797.6798.6864 6530M (17~46mm) 6868 6835M (17~32mm) 609616M.609622M
90603	pin	4.0	35	
90405	ring	5.5	44	6535M (48~65mm) 6535S (1-7/8" ~ 2-3/8") 6435M (48~50mm) 6435S (1-7/8" ~ 2")
90604	pin	4.0	45	

90403
90404
90405

90603
90604
90607

Impact Socket Set

○ 6408 MP
○ 6408 MP 10
○ 6408 SP 10

- 8 PC. 3/4" drive impact socket set
- 6 points, standard / lightweight type
- 19~38 mm (3/4"~1-1/2")

	Contents
6408MP	6535M: 19 22 24 27 30 32 36 38
6408MP10	6515M: 19 22 24 27 30; 6535M: 32 36 38
6408SP10	6535S: 3/4 7/8 15/16 1-1/16 1-3/16 1-1/4 1-7/16 1-1/2

6408MP / 6408MP10

6408SP10

	kg		Metal case size (mm)
6408MP	3.9	6	241 x 124 x 68 (0.07 cuft)
6408MP10	3.5		
6408SP10	3.5		

○ 6409 MP
○ 6409 MP 10
○ 6409 SP 10

- 8 PC. 3/4" drive impact socket set
- 6 points, standard / lightweight type
- 26~38 mm (1"~1-1/2")

	Contents
6409MP	6535M: 26 29 30 32 34 35 36 38
6409MP10	6515M: 26 29 30; 6535M: 32 34 35 36 38
6409SP10	6535S: 1 1-1/16 1-1/8 1-1/4 1-5/16 1-3/8 1-7/16 1-1/2

6409MP / 6409MP10

6409SP10

	kg		Metal case size (mm)
6409MP	4.7	2	445 x 100 x 65 (0.10 cuft)
6409MP10	4.6		
6409SP10	4.6		

○ 6410 MP
○ 6410 SP

- 8 PC. 3/4" drive impact socket set
- 6 points, deep version
- 26~38 mm (1"~1-1/2")

	Contents
6410MP	6435M: 26 29 30 32 34 35 36 38
6410SP	6435S: 1 1-1/16 1-1/8 1-1/4 1-5/16 1-3/8 1-7/16 1-1/2

6410MP

6410SP

	kg		Metal case size (mm)
6410MP	7.1	2	445 x 100 x 65 (0.10 cuft)
6410SP			

Impact Bit Socket Set

6411 MP

- 11 PC. 3/4" drive impact bit socket set

	Contents	
6411MP	6096M 16 22	1740 10 12 14 17 1954 19 22 24 27 32

kg		Metal case size (mm)
1.5	8	270 x 100 x 49 (0.048 cuft)

Impact Standard Socket

- Material - chrome molybdenum alloy steel
- Finished with phosphate sunk

○ 8535 M

- 1" drive standard length
- 6 points
- Metric size
- Thin walled design on square driving side
- DIN 3129 ,ISO2725-2

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
853519M	19	35	54	15	58	508	1 / 24
853521M	21	37	54	15	58	529	1 / 24
853522M	22	38	54	15	58	520	1 / 24
853523M	23	39	54	17	58	542	1 / 24
853524M	24	41	54	17	58	529	1 / 24
853525M	25	42	54	17	58	567	1 / 24
853526M	26	43	54	19	58	558	1 / 24
853527M	27	44	54	19	58	538	1 / 24
853528M	28	45	54	19	58	538	1 / 24
853529M	29	47	54	19	58	600	1 / 24
853530M	30	48	54	20	60	592	1 / 24
853532M	32	51	54	20	62	679	1 / 24
853533M	33	52	54	20	62	700	1 / 24
853534M	34	53	54	20	62	766	1 / 24
853535M	35	54	54	20	62	779	1 / 24
853536M	36	56	54	20	65	729	1 / 24
853538M	38	58	54	22	65	742	1 / 24
853540M	40	60	54	22	65	800	1 / 24
853541M	41	61	54	22	70	846	1 / 24
853542M	42	64	54	22	70	890	1 / 20
853544M	44	67	54	26	70	1000	1 / 20
853546M	46	68	54	26	75	1075	1 / 20
853548M	48	70	54	26	75	1085	1 / 20
853550M	50	73	54	26	75	1170	1 / 20
853552M	52	75	54	30	80	1300	1 / 12
853553M	53	76	54	30	80	1300	1 / 12
853554M	54	78	54	30	80	1400	1 / 12
853555M	55	79	54	32	83	1433	1 / 12
853558M	58	83	54	32	83	1542	1 / 12
853560M	60	86	54	32	87	1758	1 / 12
853563M	63	90	54	34	87	1750	1 / 12
853565M	65	92	54	34	90	1758	1 / 12
853566M	66	94	54	34	90	1966	1 / 12
853568M	68	95	54	34	90	1966	1 / 12
853570M	70	97	54	34	93	2112	1 / 8
853571M	71	99	86	36	93	2925	1 / 8
853575M	75	104	86	36	95	3188	1 / 8
853580M	80	110	86	43	95	3350	1 / 4
853585M	85	115	86	43	95	3250	1 / 4
853590M	90	122	86	43	100	3950	1 / 4
853595M	95	130	95	52	105	4290	1 / 2
8535A0M	100	136	95	51	105	4600	1 / 2

Impact Standard Socket

- Material - chrome molybdenum alloy steel
- Finished with phosphate sunk

8535 S

- 1" drive standard length
- 6 points
- Inch size
- Thin walled design on square driving side
- ANSI/ASME B107.2

KING TONY	inch	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
853524S	3/4	35	54	15	58	508	1 / 24
853526S	13/16	37	54	15	58	529	1 / 24
853528S	7/8	38	54	15	58	520	1 / 24
853530S	15/16	41	54	17	58	529	1 / 24
853532S	1	42	54	17	58	567	1 / 24
853534S	1-1/16	44	54	19	58	538	1 / 24
853536S	1-1/8	47	54	19	58	600	1 / 24
853538S	1-3/16	48	54	20	60	592	1 / 24
853540S	1-1/4	51	54	20	62	679	1 / 24
853542S	1-5/16	52	54	20	62	700	1 / 24
853544S	1-3/8	54	54	20	62	779	1 / 24
853546S	1-7/16	56	54	20	65	729	1 / 24
853548S	1-1/2	58	54	22	65	742	1 / 24
853550S	1-9/16	60	54	22	65	800	1 / 24
853552S	1-5/8	61	54	22	70	846	1 / 24
853554S	1-11/16	64	54	22	70	890	1 / 20
853556S	1-3/4	67	54	26	70	1000	1 / 20
853558S	1-13/16	68	54	26	75	1075	1 / 20
853560S	1-7/8	70	54	26	75	1085	1 / 20
853562S	1-15/16	72	54	26	75	1140	1 / 20
853564S	2	74	54	30	75	1235	1 / 20
853566S	2-1/16	75	54	30	80	1300	1 / 12
853568S	2-1/8	78	54	30	80	1400	1 / 12
853570S	2-3/16	79	54	32	83	1433	1 / 12
853572S	2-1/4	82	54	32	83	1500	1 / 12
853574S	2-5/16	83	54	32	83	1542	1 / 12
853576S	2-3/8	86	54	32	87	1758	1 / 12
853578S	2-7/16	88	54	34	87	1760	1 / 12
853580S	2-1/2	90	54	34	87	1750	1 / 12
853582S	2-9/16	92	54	34	90	1758	1 / 12
853584S	2-5/8	94	54	34	90	1966	1 / 12
853586S	2-11/16	95	54	34	90	1966	1 / 12
853588S	2-3/4	97	54	34	93	2112	1 / 8
853590S	2-13/16	99	86	36	93	2925	1 / 8
853592S	2-7/8	102	86	36	93	3050	1 / 8
853594S	2-15/16	104	86	36	95	3188	1 / 8
853596S	3	106	86	36	95	3205	1 / 8
8535A0S	3-1/8	110	86	43	95	3350	1 / 4
8535A4S	3-1/4	112	86	43	95	3300	1 / 4
8535A8S	3-3/8	117	86	43	100	3550	1 / 4
8535B2S	3-1/2	122	86	43	100	3950	1 / 4

Impact Deep Socket

- Chrome molybdenum alloy steel, phosphate sunk.

8435 M

- 1" drive deep version
- 6 points
- Metric size
- Thin walled design on square driving side
- DIN 3121

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
843524M	24	41	54	25	90	850	1 / 24
843527M	27	44	54	25	90	879	1 / 24
843528M	28	45	54	25	90	892	1 / 24
843530M	30	48	54	28	90	916	1 / 24
843532M	32	51	54	28	90	979	1 / 24
843533M	33	52	54	28	92	1016	1 / 24
843534M	34	53	54	28	92	1029	1 / 24
843535M	35	54	54	28	92	1016	1 / 24
843536M	36	56	54	32	92	1033	1 / 24
843538M	38	58	54	32	92	1025	1 / 24
843540M	40	60	54	32	92	1075	1 / 24
843541M	41	61	54	32	92	1083	1 / 24
843542M	42	64	54	32	92	1100	1 / 24
843546M	46	68	54	35	95	1137	1 / 12
843548M	48	70	54	35	95	1400	1 / 12
843550M	50	73	54	35	95	1518	1 / 6
843552M	52	75	54	40	100	1637	1 / 6
843554M	54	78	54	40	100	1750	1 / 6
843555M	55	79	54	40	100	1862	1 / 6
843558M	58	83	54	42	100	1925	1 / 6
843560M	60	86	54	42	100	2050	1 / 6
843565M	65	92	54	50	110	2663	1 / 6
843570M	70	97	54	59	110	2921	1 / 4

8435 S

- 1" drive deep version
- 6 points
- Inch size
- Thin walled design on square driving side
- ANSI/ASME B107.1

KING TONY	inch	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
843530S	15/16	40.8	54	25	90	850	1 / 24
843532S	1	42	54	25	90	860	1 / 24
843534S	1-1/16	44	54	25	90	879	1 / 24
843536S	1-1/8	46.3	54	25	90	900	1 / 24
843538S	1-3/16	48	54	28	90	916	1 / 24
843540S	1-1/4	51	54	28	90	979	1 / 24
843542S	1-5/16	52	54	28	92	1016	1 / 24
843544S	1-3/8	54	54	28	92	1016	1 / 24
843546S	1-7/16	56	54	32	92	1033	1 / 24
843548S	1-1/2	58	54	32	92	1025	1 / 24
843550S	1-9/16	60	54	32	92	1075	1 / 24
843552S	1-5/8	61	54	32	92	1083	1 / 24
843554S	1-11/16	64	54	32	92	1100	1 / 24
843556S	1-3/4	67	54	32	92	1120	1 / 12
843558S	1-13/16	68	54	35	95	1137	1 / 12
843560S	1-7/8	70	54	35	95	1400	1 / 6
843562S	1-15/16	72	54	35	95	1480	1 / 6
843564S	2	74	54	35	95	1577	1 / 6
843566S	2-1/16	75	54	40	100	1637	1 / 6
843568S	2-1/8	78	54	40	100	1750	1 / 6
843570S	2-3/16	79	54	40	100	1862	1 / 6
843572S	2-1/4	82	54	42	100	1900	1 / 6

Impact Thin Wall Socket

- Chrome molybdenum steel, phosphate sunk.

8835 M

- 1" drive deep version
- Thin wall version
- 6 points
- Metric size
- Thin walled design on square driving side
- DIN 3121

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
883524M	24	38.0	54	26	80	626	1 / 24
883527M	27	42.0	54	26	80	643	1 / 24
883529M	29	44.0	54	26	80	700	1 / 24
883530M	30	46.0	54	30	80	696	1 / 24
883532M	32	48.0	54	30	80	714	1 / 24
883533M	33	49.0	54	30	80	748	1 / 24
883534M	34	50.0	54	30	80	764	1 / 24
883535M	35	52.0	54	32	80	776	1 / 24
883536M	36	53.0	54	32	80	779	1 / 24
883538M	38	56.0	54	32	80	810	1 / 24
883541M	41	59.5	54	32	80	866	1 / 24

Rear Wheel Socket

- Chrome molybdenum steel, phosphate sunk.

8514 M
8514 S
8524 M

- 1" drive
- 4 points
- Metric size
- DIN 3121

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
851417M	17	40.0	54	30.0	60	618	1 / 24
851419M	19	42.0	54	30.0	60	618	1 / 24
851420M	20	43.0	54	30.0	60	621	1 / 24
851421M	21	44.0	54	30.0	60	621	1 / 24
851422M	22	45.5	54	30.0	60	621	1 / 24
NEW 852421M	21	44.0	48	30.0	60	621	1 / 24
851426S	13/16	44	54	30.0	60	625	1 / 24

8514M
deep version

8524M

8534 M

- 1" drive
- 4 points
- Metric size
- DIN 3121

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
853417M	17	38.0	54	23.5	76	628	1 / 24
853419M	19	43.0	54	23.5	76	682	1 / 24
853421M	21	47.0	54	23.5	76	733	1 / 24

8534M

Impact Accessory

- Chrome molybdenum alloy steel, phosphate sunk.

8260

- 1" drive extension bars
- DIN 3121

KING TONY	Overall Length (inch)	(mm)	g	
8260-07	7	175	1393	1 / 16
8260-10	10	250	1891	1 / 12
8260-13	13	330	2455	1 / 9

8260P

- 1" drive extension bars - with ball
- DIN 3121

KING TONY	Overall Length (inch)	(mm)	g	
8260-07P	7	175	1393	1 / 16
8260-10P	10	250	1891	1 / 12
8260-13P	13	330	2455	1 / 9

8797

- 1" drive universal joint
- DIN 3121

KING TONY	Overall Length (inch)	(mm)	g	
8797	5	128	1530	1 /18

8797P

- 1" drive universal joint - with ball
- DIN 3121

KING TONY	Overall Length (inch)	(mm)	g	
8797P	5	128	1530	1 /18

Impact Accessory

- Chrome molybdenum alloy steel, phosphate sunk.

8866

- 1" drive adapters
- Converting to 3/4" drive
- Max. → torque 1412 Nm
- DIN 3121

	Spec.		
8866	1"F x 3/4"M	562	4 / 32

8866P

- 1" drive adapters - with ball
- Converting to 3/4" drive
- Max. → torque 2400 Nm
- DIN 3121

	Spec.		
8866P	1"F x 3/4"M	562	4 / 32

8869

- 1" drive adapter
- Converting to 1-1/2" drive
- DIN 3121

	Spec.		
8869	1" F x 1-1/2"M	963	1 / 24

8869P

- 1" drive adapter - with ball
- Converting to 1-1/2" drive
- DIN 3121

	Spec.		
8869P	1" F x 1-1/2"M	963	1 / 24

90405 90406

- 1" drive locking ring
- High tensile rubber material

90605 90606

- 1" drive locking pin
- Chrome vanadium steel
- DIN 3129

	Desp.	ø	d / ℓ	Applied to socket sizes
90405	ring	5.5	44	8535M (19~70mm) 8535S (3/4"~2-3/4") 8435M (24~60mm) 8435S (15/16"~2-1/4") 8835M (24~60mm) 8514M.8514S.8534M.806519M 8260.8797.8866.8869
90605	pin	5.0	45	
90406	ring	10	75	8535M (71~90mm) 8535S (2-13/16"~3-1/2")
90606	pin	5.0	75	

90405
90406

90605
90606

Impact Socket Set

○ 8408 MP

- 8 PC. 1" drive impact socket set
- 6 PC. thin wall version, 24 ~ 41 mm
- 2 pcs budd wheel,17 & 21 mm

	Contents	
8408MP	8835M	24 27 32 36 38 41
	8534M	17 21

8408MP

kg		Metal case size (mm)
6.9	2	445 x 120 x 68 (0.128 cuft)

○ 8409 MP

- 8 PC. 1" drive impact socket set
- 6 points, deep version
- 24 ~ 41mm

	Contents	
8409MP	8435M	24 27 30 32 33 36 38 41

8409MP

kg		Metal case size (mm)
7.82	2	445 x 100 x 65 (0.104 cuft)

○ 8410 MP
○ 8410 SP

- 8 PC. 1" drive impact socket set
- 6 points, standard length
- 24 ~ 41 mm (15/16" ~ 1-5/8")

	Contents	
8410MP	8535M	24 27 30 32 33 36 38 41
8410SP	8535S	15/16 1-1/16 1-3/16 1-1/4 1-5/16 1-7/16 1-1/2 1-5/8

8410MP

8410SP

	kg		Metal case size (mm)
8410MP 8410SP	6.4	4	280 x 130 x 74 (0.095 cuft)

Impact Standard Socket

- Material - chrome molybdenum alloy steel
- Finished with phosphate sunk

9535 M

- 1-1/2" drive standard length
- 6 points
- Metric size
- Thin walled design on square driving side
- DIN 3129

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
953532M	32	56	86	23	80	1945	1/6
953533M	33	57	86	23	80	1935	1/6
953534M	34	58	86	24	80	1947	1/6
953536M	36	62	86	26	80	1905	1/6
953538M	38	64	86	26	80	2002	1/6
953541M	41	68	86	28	80	2125	1/6
953542M	42	70	86	28	80	2295	1/6
953546M	46	73	86	30	85	2233	1/6
953550M	50	78	86	32	85	2300	1/6
953555M	55	85	86	36	93	2660	1/6
953560M	60	90	86	40	95	2840	1/6
953565M	65	96	86	42	100	3150	1/6
953570M	70	103	86	46	103	3460	1/6
953575M	75	108	86	48	105	3700	1/4
953580M	80	115	86	52	105	3900	1/4
953585M	85	121	86	55	110	4175	1/4
953590M	90	127	86	58	110	4600	1/4
953595M	95	134	127	50	110	7570	1/1
9535A0M	100	140	127	53	115	8104	1/1
9535A5M	105	146	127	53	115	8340	1/1
9535B0M	110	152	127	56	125	9400	1/1
9535B5M	115	160	127	60	125	9766	1/1
9535C0M	120	166	127	62	130	10460	1/1
9535C5M	125	172	127	65	135	11148	1/1
9535D0M	130	180	127	68	140	12423	1/1
9535D5M	135	185	127	70	145	13090	1/1
9535E0M	140	190	127	75	150	13570	1/1
9535F0M	150	200	127	80	155	14270	1/1

1-1/2"

Impact Socket & Accessory

Impact Accessory

- Chrome molybdenum alloy steel, phosphate sunk.

9868

- 1-1/2" drive adapter
- Converting to 1" drive
- Max. → torque 2515Nm
- DIN 3121

KING TONY	Spec.	g	
9868	1-1/2" F x 1"M	2360	1 / 6

9868P

- 1-1/2" drive adapter - with ball
- Converting to 1" drive
- Max. → torque 2515Nm
- DIN 3121

KING TONY	Spec.	g	
9868P	1-1/2" F x 1"M	2360	1 / 6

#5 Spline Drive Impact Socket

- Chrome molybdenum alloy steel, phosphate sunk

5535 M

14-teeth spline drive
- 6 points
- Metric size
- Thin walled design on spline drive side

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)		
553533M	33	52	60	20	100	-	-
553535M	35	54	60	20	100	-	-
553538M	38	58	60	22	100	-	-
553541M	41	61	60	22	100	-	-

5535 S

14-teeth spline drive
- 6 points
- Inch size
- Thin walled design on spline drive side

KING TONY	inch	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)		
553534S	1-1/16	44	60	19	80	-	-
553536S	1-1/8	47	60	19	80	-	-
553540S	1-1/4	51	60	20	80	-	-
553542S	1-5/16	52	60	20	100	-	-
553546S	1-7/16	56	60	20	100	-	-

5534 M

14-teeth spline drive
- 4 points
- Metric size
- Thin walled design on spline drive side

KING TONY	mm	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)		
553417M	17	37	60	25	75	-	-
553421M	21	44	60	25	75	-	-

5534 S

14-teeth spline drive
- 4 points
- Inch size
- Thin walled design on spline drive side

KING TONY	inch	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)		
553426S	13/16	44	60	25	75	-	-
553430S	15/16	48	60	25	75	-	-

Pneumatic Tools

- Impact Wrench
- Composite Impact Wrench
- Impact Socket & Wrench Set
- Impact Screwdriver
- Cordless Impact Wrench Set

Motorcycle | Auto | Truck | Agriculture | Construction | Factory

KING TONY

Impact Wrench Series Instruction List

KING TONY	Drive	Maximum Torque ft.lb	Maximum Torque Nm	Motorcycle	Auto	Truck	Agriculture	Construction	Factory	Page
33311-020	3/8"	200	271	●	●				●	159
33351-030	3/8" (Composite)	300	407	●	●				●	168
33451-030	1/2" (Composite)	300	407	●	●				●	168
33421-040	1/2"	500	678	●	●	●			●	160
33411-020	1/2"	200	271	●	●	●			●	161
33411-040	1/2"	500	678	●	●	●			●	161
33411-050	1/2"	650	881	●	●	●			●	161
33412-040	1/2"	500	678	●	●	●			●	161
33412-050	1/2"	650	881	●	●	●			●	161
NEW 33451-045	1/2"	450	610	●	●	●			●	159
33461-060	1/2" (Composite)	600	813	●	●	●			●	168
33462-060	1/2" (Composite)	600	813	●	●	●			●	168
33611-055	3/4"	700	949			●	●		●	162
33612-055	3/4"	700	949			●	●		●	162
33621-075	3/4"	800	1085			●	●		●	162
33622-075	3/4"	800	1085			●	●		●	162
33631-110	3/4"	1100	1491			●	●		●	162
33632-110	3/4"	1100	1491			●	●		●	162
33841-180	1"	1800	2440			●	●	●		163
33842-180	1"	1800	2440			●	●	●		163
33851-120	1"	1200	1626			●	●	●		163
33852-120	1"	1200	1626			●	●	●		163
33811-150	1"	1500	2033			●	●	●		164
33812-150	1"	1500	2033			●	●	●		164
33831-180	1"	1800	2440			●	●	●		164
33832-180	1"	1800	2440			●	●	●		164
33851-250	1"	2500	3388			●	●	●		165
33852-250	1"	2500	3388			●	●	●		165
33861-200	1"	2000	2712			●	●	●		165
33862-200	1"	2000	2712			●	●	●		165
33911-250	1-1/2"	2500	3388			●		●		166
33912-250	1-1/2"	2500	3388			●		●		166
33921-300	1-1/2"	3000	4065			●		●		166
33922-300	1-1/2"	3000	4065			●		●		166

Impact Wrench

33311

20% More Power Less Vibration

- 3/8" drive super duty impact wrench
- Aluminum alloy housing
- Nickel chrome molybdenum square driver
- Variable speed trigger
- Muffled on handle exhaust
- Standard anvil is available
- General specification
  - Rotary speed : 10000RPM
  - Air pressure : 90PSI recommended
  - Air inlet thread size : 1/4"
  - Air hose size : 3/8" ID
  - For an assembly line use

Mechanism-Jumbo Hammer

KING TONY	Type	Maximum Torque ft.lb	Nm	Average Air Consumption (CFM)	Std. Bolt Size inch	mm	Overall Length inch	Sound DBA Pressure (Power) DB (Power)	kg	
33311-020	Standard anvil	200	271	2.5	7/16"	M11	5-1/2"	95.35	1.35	1 / 8

33451-045 NEW

- 1/2" Drive Air Impact Wrench-Super Mini Design
- Twin Hammer type. Overall Length 125mm, Only 1.6kg
- Aluminum alloy housing
- Nickel chrome molybdenum square driver
- Unique design two step trigger whrn tightening or loosening fasteners
  - Free speed : 9000 RPM
  - Air pressure : 90 PSI recommended
  - Air inlet : 1/4"
  - Air hose size : 3/8" ID

Mini Design Wrench

Twin Hammer

KING TONY	Type	Maximum Torque ft.lb	Nm	Average Air Consumption (CFM)	Std. Bolt Size inch	mm	Overall Length inch	Sound DBA Pressure (Power) DB (Power)	Vib M/S2	kg	
33451-045	Standard anvil	450	610	5.8	5/8"	16	4-4/5"	91	3.6	1.6	1 / 10

Impact Wrench

33421

- 1/2" drive super duty impact wrench
- Aluminum alloy housing
- Nickel chrome molybdenum square driver
- Variable speed trigger
- Muffled on front exhaust
- Standard anvil is available
- General specification
  - Rotary speed : 8000RPM
  - Air Pressure : 90PSI recommended
  - Air inlet thread size : 1/4"
  - Air hose size : 3/8" ID

20% *More Power Less Vibration*

Twin Hammer

KING TONY	Type	Maximum Torque ft.lb	Maximum Torque Nm	Average Air Consumption (CFM)	Std. Bolt Size inch	Std. Bolt Size mm	Overall Length inch	Sound DBA Pressure (Power) DB (Power)	kg	
33421-040	Standard anvil	500	678	4.0	5/8"	M16	6-3/4"	101.02	2.56	1 / 8

Impact Wrench

33411 & 33412

- 1/2" drive impact wrench
- Aluminum alloy housing
- Nickel chrome molybdenum square driver
- Variable speed trigger
- Muffled on handle exhaust
- Standard & 2" extension anvil is available
- General specification
  - Free speed : 8000 RPM (33411&33412)
  - Rotary speed : 10000RPM (33411-020)
  - Air pressure : 90 PSI recommended
  - Air inlet : 1/4"
  - Air hose size : 3/8" ID
  - For an assembly line use (33411-020)

20% More Power Less Vibration

33411-020

Mechanism - Jumbo Hammer

14103GP

Twin Hammer

33411-040

33412-040

New Twin Hammer

33411-050

33412-050

KING TONY	Type	Maximum Torque ft.lb	Nm	Average Air Consumption (CFM)	Std. Bolt Size inch	mm	Overall Length inch	Sound DBA Pressure (Power) DB (Power)	Vib M/S2	kg	
33411-020	Standard anvil	200	271	2.5	7/16"	M11	5-1/2"	95.48	-	1.35	1 / 10
33411-040	Standard anvil	500	678	4.0	5/8"	M16	7-23/64"	95.22	4.85	2.6	1 / 8
33411-050	Standard anvil	650	881	4.4	3/4"	M19	7-41/64"	96.50	8.13	2.8	1 / 8
33412-040	Long anvil	500	678	4.0	5/8"	M16	9-23/64"	91.00	4.80	2.8	1 / 8
33412-050	Long anvil	650	881	4.4	3/4"	M19	9-23/64"	96.19	6.84	3.2	1 / 8
14103GP		3 pcs repair tools									

Impact Wrench

20% More Power Less Vibration

33611 & 33612
33621 & 33622

- 3/4" drive impact wrench
- Aluminum alloy housing
- Nickel chrome molybdenum square driver
- Variable speed trigger
- Muffled on handle exhaust
- Standard & 6" extension anvil is available
- General specification
  - Free speed : 6500 RPM
  - Air pressure : 90 PSI recommended
  - Air inlet : 1/4"
  - Air hose size : 3/8" ID

33611-055

33612-055

33621-075

33622-075

33012 33011 33013

14103GP

KING TONY	Type	Maximum Torque ft.lb	Maximum Torque Nm	Average Air Consumption (CFM)	Std. Bolt Size inch	Std. Bolt Size mm	Overall Length inch	Sound DBA Pressure (Power) DB (Power)	Vib M/S2	kg	
33611-055	Standard anvil	700	949	4.4	7/8"	M20	7-13/32"	96.56	8.64	3.00	1 / 8
33612-055	Long anvil	700	949	4.4	7/8"	M20	11-13/32"	96.86	-	3.00	1 / 8
33621-075	Standard anvil	800	1085	7.0	1"	M24	8-63/64"	97.28	6.89	4.50	1 / 4
33622-075	Long anvil	800	1085	7.0	1"	M24	12-63/64"	86.00	6.46	4.50	1 / 4
14103GP		3 pcs repair tools								0.58	1 / 20

33631 & 33632

- 3/4" drive impact wrench
- Nickel chrome molybdenum square driver
- Variable speed trigger
- Muffled on handle exhaust
- Standard & 6" extension anvil is available
- General specification
  - Free speed : 5500 RPM
  - Air pressure : 90 PSI recommended
  - Air inlet : 3/8"
  - Air hose size : 1/2" ID

33631-110

33632-110

KING TONY	Type	Maximum Torque ft.lb	Maximum Torque Nm	Average Air Consumption (CFM)	Std. Bolt Size inch	Std. Bolt Size mm	Overall Length inch	Sound DBA Pressure (Power) DB (Power)	Vib M/S2	kg	
33631-110	Standard anvil	1100	1491	9.5	1-3/16"	M30	8-43/64"	98.35	5.31	5.60	1/4
33632-110	long anvil	1100	1491	9.5	1-3/16"	M30	14-55/64"	97.20	-	6.04	1/4

Impact Wrench

33841 & 33842

- 1" drive impact wrench
- Nickel chrome molybdenum square driver
- Variable speed trigger
- Muffled on handle exhaust
- Standard & 6" extension anvil are available
- General specification
  - Free speed : 4000 RPM
  - Air pressure : 90 PSI recommended
  - Air inlet : 1/2"
  - Air hose size : 3/4" ID

New Twin Hammer !!

33841-180

33842-180

	Type	Maximum Torque ft.lb	Maximum Torque Nm	Average Air Consumption (CFM)	Std. Bolt Size inch	Std. Bolt Size mm	Overall Length inch	Sound DBA Pressure (Power) DB (Power)	Vib M/S2	kg	
33841-180	Standard anvil	1800	2440	9.0	1-27/64"	M36	12-3/32"	101.56	4.37	10.62	1 / 2
33842-180	Long anvil	1800	2440	9.0	1-27/64"	M36	20-5/64"	99.85	-	12.52	1 / 2

33851 & 33852

- 1" drive impact wrench
- Nickel chrome molybdenum square driver
- Variable speed trigger
- Muffled on handle exhaust
- Standard & 6" extension anvil are available
- General specification
  - Free speed : 5500 RPM
  - Air pressure : 90 PSI recommended
  - Air inlet : 3/8"
  - Air hose size : 1/2" ID

New Twin Hammer !!

33851-120

33852-120

	Type	Maximum Torque ft.lb	Maximum Torque Nm	Average Air Consumption (CFM)	Std. Bolt Size inch	Std. Bolt Size mm	Overall Length inch	Sound DBA Pressure (Power) DB (Power)	kg	
33851-120	Standard anvil	1200	1626	9.5	1-17/64"	M32	8-53/64"	99.75	5.64	1 / 4
33852-120	Long anvil	1200	1626	9.5	1-17/64"	M32	14-1/64"	86.00	6.04	1 / 4

Impact Wrench

20% More Power Less Vibration

33811 & 33812
33831 & 33832

- 1" drive impact wrench
- Aluminum alloy housing
- Nickel chrome molybdenum square driver
- Variable speed trigger
- Side exhaust
- 6" extension & short anvil are available
- General specification
  - Free speed : 4000 RPM
  - Air pressure : 90 PSI recommended
  - Air inlet : 1/2"
  - Air hose size : 3/4" ID

33811-150

33812-150

33831-180

33832-180

KING TONY	Type	Maximum Torque ft.lb	Maximum Torque Nm	Average Air Consumption (CFM)	Std. Bolt Size inch	Std. Bolt Size mm	Overall Length inch	Sound DBA Pressure (Power) DB (Power)	Vib M/S2	kg	
33811-150	Standard anvil	1500	2033	9.0	1-1/4"	M36	14-19/32"	101.17	10.77	10.3	1 / 1
33812-150	Long anvil	1500	2033	9.0	1-1/4"	M36	20-19/32"	100.40	6.13	11.3	1 / 1
33831-180	Standard anvil	1800	2440	9.0	1-1/2"	M38	14-19/32"	102.11	8.84	11.5	1 / 1
33832-180	Long anvil	1800	2440	9.0	1-1/2"	M38	20-19/32"	103.99	6.6	12.5	1 / 1

Impact Wrench

33851-250 & 33852-250

- 1" drive impact wrench
- Nickel chrome molybdenum square driver
- Variable speed trigger
- Standard & 8" extension anvil are available
- General specification
  - Free speed : 3000 RPM
  - Air pressure : 90 PSI recommended
  - Air inlet : 1/2"
  - Air hose size : 3/4" ID

33851-250

33852-250

KING TONY	Type	Maximum Torque ft.lb	Maximum Torque Nm	Average Air Consumption (CFM)	Std. Bolt Size inch	Std. Bolt Size mm	Overall Length inch	Sound DBA Pressure (Power) DB (Power)	Vib M/S2	kg	
33851-250	Standard anvil	2500	3388	14.5	1-25/32"	M45	17-11/64"	89	6.30	15.8	1 / 1
33852-250	Long anvil	2500	3388	14.5	1-25/32"	M45	24-7/8"	87	-	18.7	1 / 1

33861 & 33862

Maximum Torque 2000ft.lb !

- 1" drive impact wrench
- Light weight
- Nickel chrome molybdenum square driver
- Comfortable rubber handle

General specification:
- Free speed : 5000 RPM
- Air pressure : 90 PSI recommended
- Air inlet : 1/2"
- Air hose size : 1/2" ID

33861-200

33862-200

KING TONY	Type	Maximum Torque ft.lb	Maximum Torque Nm	Average Air Consumption (CFM)	Std. Bolt Size inch	Std. Bolt Size mm	Overall Length inch	kg	
33861-200	Standard anvil	2000	2712	9	1-27/64	M36	8-53/64	7.1	1 / 1
33862-200	Long anvil	2000	2712	9	1-27/64	M36	14-55/64	8.1	1 / 1

Impact Wrench

33911 & 33912
33921 & 33922

- 1-1/2" drive impact wrench
- Nickel chrome molybdenum square driver
- Variable speed trigger
- Standard & 8" extension anvil are available
- General specification

  - Free speed : 3000 RPM
  - Air pressure : 90 PSI recommended
  - Air inlet : 1/2"
  - Air hose size : 3/4" ID

33911-250
33921-300

33912-250
33922-300

KING TONY	Type	Maximum Torque ftlb	Maximum Torque Nm	Average Air Consumption (CFM)	Std. Bolt Size inch	Std. Bolt Size mm	Overall Length inch	Sound DBA Pressure (Power) DB (Power)	Vib M/S2	kg	
33911-250	Standard anvil	2500	3388	14.5	1-25/32"	M45	17-53/64"	85	6.32	15.8	1 / 1
33912-250	long anvil	2500	3388	14.5	1-25/32"	M45	23-53/64"	85	6.53	18.7	1 / 1
33921-300	Standard anvil	3000	4065	16.0	2"	M50	17-3/4"	90	8.86	19.7	1 / 1
33922-300	long anvil	3000	4065	16.0	2"	M50	25-15/32"	90	7.12	22.8	1 / 1

Composite Impact Wrench

Patented Three-way Air inlet Function
Increases 10% and more at horsepower delivery than same level tools.

End Cap Slider-Guide Trigger
Easy operation design.

Improved Throttle Valve Seat
Easier maintenance allowed.

Composite Grip
Super lightweight & Ergonomic design, isolating from the coldness.

Air Regulator
Forward and reverse directions offers 4 section of speed selection.

Improved Air Inlet
Effectively reduces the damage of thread.

33351-030
33451-030

33461-060

33462-060

Composite Impact Wrench

33351 & 33451

- 3/8" & 1/2" drive impact wrench
  (3/8" drive 33351)
  (1/2" drive 33451)
- Light weight durable composite housing.
- Nickel chrome molybdenum square driver
- Variable speed trigger
- Muffler on handle exhaust
- General specification
  - Free speed : 10000 RPM
  - Air pressure : 90 PSI recommended
  - Air inlet : 1/4"
  - Air hose size : 3/8" ID

Twin Hammer

KING TONY	Type	Maximum Torque ft.lb	Maximum Torque Nm	Average Air Consumption (CFM)	Std. Bolt Size inch	Std. Bolt Size mm	Overall Length inch	Sound DBA Pressure (Power) DB (Power)	Vib M/S2	kg	
33351-030	Standard anvil	300	407	4.2	3/8"	M10	5-1/2"	92.00	2.07	1.3	1 / 12
33451-030	Standard anvil	300	407	4.2	3/8"	M10	5-1/2"	92.88	2.66	1.3	1 / 12

33461 & 33462

- 1/2" drive impact wrench
- Light weight durable composite housing.
- Nickel chrome molybdenum square driver
- Variable speed trigger
- Muffler on handle exhaust
- Standard & 6" extension anvil is available
- General specification
  - Free speed : 8000 RPM
  - Air pressure :
    90 PSI recommended
  - Air inlet : 1/4"
  - Air hose size : 3/8" ID

Twin Hammer

33461-060

33462-060

KING TONY	Type	Maximum Torque ft.lb	Maximum Torque Nm	Average Air Consumption (CFM)	Std. Bolt Size inch	Std. Bolt Size mm	Overall Length inch	Sound DBA Pressure (Power) DB (Power)	Vib M/S2	kg	
33461-060	Standard anvil	600	813	4.9	3/4"	M19	7-1/32"	94.61	4.23	2.1	1 / 8
33462-060	Long anvil	600	813	4.9	3/4"	M19	9-5/8"	93.87	-	2.5	1 / 8

Air Ratchet Wrench

360° exhaust rotation direct air away from working area.

The ergonomically enhanced composite handle grip with professional and super touch.

Regular

KING TONY

1.Dust-free design

2.Prevents deformation and triples the life of the parts.

Air Ratchet Wrench

37221 & 37321

- 1/4" & 3/8" drive air ratchet wrench
  (1/4" drive 37221)
  (3/8" drive 37321)
- 360° exhaust rotation direct air away from working area.
- Dust-free design of ratchet housing keeps away the dirt and other objects.
- General specification
  - Free speed :
    250 RPM (37221)
    270 RPM (37321)
  - Air pressure : 90 PSI recommended
  - Air inlet : 1/4"
  - Air hose size : 3/8" ID

KING TONY	Type	Maximum Torque ft.lb	Maximum Torque Nm	Average Air Consumption (CFM)	Std. Bolt Size inch	Std. Bolt Size mm	Overall Length inch	Sound DBA Pressure (Power) DB (Power)	Vib M/S2	kg	
37221-030	Standard anvil	20	27	2.8	1/4"	M6	8-1/16"	98	2.32	0.67	1 / 30
37321-050	Standard anvil	40	54	2.8	5/16"	M8	8-1/16"	98	2.26	0.67	1 / 30

37323

- 3/8" drive air ratchet wrench
- 360° exhaust rotation direct air away from working area.
- Dust-free design of ratchet housing keeps away the dirt and other objects.
- General specification
  - Free speed : 280 RPM
  - Air pressure : 90 PSI recommended
  - Air inlet : 1/4"
  - Air hose size : 3/8" ID

KING TONY	Type	Maximum Torque ft.lb	Maximum Torque Nm	Average Air Consumption (CFM)	Std. Bolt Size inch	Std. Bolt Size mm	Overall Length inch	Sound DBA Pressure (Power) DB (Power)	Vib M/S2	kg	
37323-080	Standard anvil	80	108	4.0	3/8"	M10	11"	107	2.52	1.25	1 / 12

37423

- 1/2" drive air ratchet wrench
- 360° exhaust rotation direct air away from working area.
- Dust-free design of ratchet housing keeps away the dirt and other objects.
- General specification
  - Free speed : 280 RPM
  - Air pressure : 90 PSI recommended
  - Air inlet : 1/4"
  - Air hose size : 3/8" ID

KING TONY	Type	Maximum Torque ft.lb	Maximum Torque Nm	Average Air Consumption (CFM)	Std. Bolt Size inch	Std. Bolt Size mm	Overall Length inch	Sound DBA Pressure (Power) DB (Power)	Vib M/S2	kg	
37423-080	Standard anvil	80	108	4.0	3/8"	M10	11"	107	2.07	1.25	1 / 12

Impact Screwdriver

■ 33111

- 1/4" drive impact screwdriver
- General specification
  - Free speed : 10000RPM
  - Air pressure : 90 PSI recommended
  - Air inlet thread size : 1/4"
  - Air hose size : 3/8" ID

Mechanism-Hex.Twin Dog

KING TONY	Free Speed RPM	Air Inlet NPT	Average Air Consumption (CFM)	Capacity Screw Size inch	Capacity Screw Size mm	Overall Length inch	Max Torque	Sound DBA Pressure (power)	kg	
33111	10000	1/4	7.5	3/16	M5	7-1/2	26ft-lb	90	0.73	20

Cordless Impact Wrench Set

○ 44504MP

- Voltage : DC 19.2V
- Chuck : 1/2" (13mm) Square Drive
- Dimension : 261×78×270 mm (10.3"×3.1"×10.6")
- Charger : 2.0Ah Ni-Cd

- Body cotain TPR+GF, double injection housing
- Interchangeable motor caron-brush to extend motor's life
- LED light indicator, side handle & ergonomic grip to help you in work
- Impact function - shorten working time
- Safe device - Thermostat controller to make the motor stop automatically when temperature reach 70℃
- Easy realease slide battery pack - quick and safe

Contents:

■ Cordless Impact Wrench

■ 2.0AH Ni-Cd Battery Pack x 2

■ 1HR Charger

■ Auxiliary Handle

■ Safety Instructions & Operation Manual

KING TONY	Unload Speed (rpm)	Max Torque (N-m / in-lb)	Charger Suitable	g	
44504MP	0 ~ 2500	310 / 2742	CE (European) UL (American & Asia)	6833	1 / 3
44504MPB	0 ~ 2500	310 / 2742		6833	1 / 3

Impact Socket & Wrench Set

○ 44116 MP

21 PC. 1/2" drive impact socket wrench set

- **Sockets**
  - -10 PC. 6 points, standard length, 9 ~ 27mm
  - -3 PC. 6 points thin wall version, 17 ~ 21mm
- **Impact wrench**
  - -1 PC impact wrench
- **Accessories**
  - -1 PC extension bar
  - -1 PC universal joint
  - -2 PC. ring Ø 3.5 x 19mm & Ø 3.5 x 23mm
  - -2 PC. pin Ø 3 x 20 & Ø 3 x 25 (6150)

44116MP

Contents		
44116MP	4535M: 9 10 11 13 14 17 19 22 24 27 4415M: 17 19 21	33411-040; 4260-05; 4797; 90401; 90402; 90601; 90602; SY-221M (Japanesque type)

kg		Blow case size (mm)
6.1	4	315 x 250 x 120 (0.339 cuft)

○ 44118 MP

23 PC. 1/2" drive impact socket wrench set

- **Sockets**
  - -14 PC. 6 points, deep version, 10 ~ 27mm
- **Impact wrench**
  - -1 PC impact wrench
- **Accessories**
  - -2 PC. extension bar, 3" & 5" L
  - -1 PC universal joint
  - -2 PC. ring Ø 3.5 x 19mm & Ø 3.5 x 23mm
  - -2 PC. pin Ø 3 x 20mm & Ø 3 x 25mm (6150)

44118MP

Contents		
44118MP	4435M: 10 11 12 13 14 16 17 19 21 22 23 24 26 27	33411-040; 4260-03; 4260-05; 4797; 90401; 90402; 90601; 90602; SY-221M (Japanesque type)

kg		Blow case size (mm)
8.4	2	420 x 315 x 100 (0.475 cuft)

Impact Socket & Wrench Set

○ 64111 MP

14 PC. 3/4" drive impact socket wrench set

- **Sockets**
  - -8 PC. 6 points, standard length, 26 ~ 38mm
- **Impact wrench**
  - -1 PC impact wrench
- **Accessories**
  - -1 PC extension bar, 7" L
  - -1 PC universal joint
  - -1 PC ring Ø 5.5 x 37mm
  - -1 PC pin Ø 4 x 35
  - -1 PC air adaptor

	Contents	
64111MP	6535M: 26 27 28 30 32 35 36 38	33621-075, 6260-07, 6797, 90404, 90603, SY-221M (Japanesque type)

kg		Blow case size (mm)
10.8	2	420 x 315 x 100 (0.475 cuft)

○ 64115 MP

18 PC. 3/4" drive impact socket wrench set

- **Sockets**
  - -12 PC. 6 points, standard length
- **Impact wrench**
  - -1 PC impact wrench
- **Accessories**
  - -1 PC extension bar, 7" L
  - -1 PC universal joint
  - -1 PC ring Ø 5.5 x 37mm
  - -1 PC pin Ø 4.0 x 35mm
  - -1 PC air adaptor

	Contents	
64115MP	6535M: 24 26 27 29 30 32 33 34 35 36 38 41	33621-075, 6260-07, 6797, 90404, 90603, SY-221M (Japanesque type)

kg		Blow case size (mm)
13.3	2	510 x 390 x 115 (0.822 cuft)

Notes

Torque Tools

Difference of torque wrench

Square driver	Model	Tolerance of torque-KT	Tolerence of torque - international standard	KING TONY	Nm	in-lb	ft-lb	Torque value display type	Torque lock design	Quality application	Page
Industry Quality Adjustable Torque Wrench											
1/4"		±3%	±4%	34262 series	4~20	30~200		laser scale	easy lock / auto lock	Industry level	155
3/8"				34362 series	4~100	30~200	10~80				
1/2"				34462 series	40~340		20~250				
3/4"				34662 series	100~1000		50~750				
1"				34862 series	200~1500		150~1000				
Mini-Type Industry Quality Torque Wrench											
1/4"		±3%	±4%	3426C series	3~25			laser scale	easy lock / auto lock	Industry level	156
3/8"				3436C series	3~25						
72 PT Industry Quality Adjustable Torque Wrench											
1/4"		±3%	±4%	3426A series	2~20	20~200		laser scale	easy lock / auto lock	Industry level	157
3/8"				3436A series	20~100		10~80				
1/2"				3446A series	40~400		20~250				
3/4"				3466A series	80~400						
Industry Quality Interchangeable Torque Wrench											
9 x 12 mm		±3%	±4%	34512 series	2~100	20~200	10~80	laser scale	easy lock / auto lock	Industry level	158
14 x 18 mm				34522 series	20~340		10~250				
Professional Quality Adjustable Torque Wrench											
1/4"		±4%	±4%	34223 series	5~25	10~250		caved scale	regular lock / screw lock	Professional level	162
3/8"				34323 series	5~110		5~80				
1/2"				34423 series	42~350		30~250				
Electronic Torque Wrench											
3/8"		±2%	±4%	34367 & 34387	Nm 27~135 kg.cm 275~1376	in.lb 239~1195 kg.m 2.75~13.76	ft.lb 19.9~99.6	Operation Mode	LCD display	Professional level	163
1/2"				34467 & 34487	Nm 40~200 kg.cm 408~2038	in.lb 354~1170 kg.m 4.08~20.38	ft.lb 29.5~147.5				

■ Torque Wrench ■ Interchangeable Torque Wrench Set ■ Insert Tool
■ Electronic Torque Wrench ■ Electronic Torque Adapter ■ Torque Screwdriver

KING TONY

Torque Wrench

Industry Quality Adjustable Torque Wrench

Design for easy torque-adjusting
Quality accords to DIN ISO 6789 & ASME B107.14M-2004
Tolerance of torque ±3%
CW/CCW Direction

Dual Scale - English & Newton Meter (in. lb. / ft. lb. & Nm)

	Square drive	Torque Range in. lb. / ft. lb.	Incr.	Torque Range Nm	Incr.	Overall Length mm		
34262-1CG	1/4"	30~200 in. lb.	1 in. lb.	4.0~22.0 Nm	0.12 Nm	324	640	1/12
34362-1CG	3/8"	30~200 in. lb.	1 in. lb.	4.0~22.0 Nm	0.12 Nm	324	640	1/12
34362-2CG	3/8"	10~80 ft. lb.	0.5 ft. lb.	16.9~105.1 Nm	0.7 Nm	435	1300	1/12
34462-1CG	1/2"	20~150 ft. lb.	1 ft. lb.	34~197 Nm	1.4 Nm	521	1590	1/12
34462-2CG	1/2"	30~250 ft. lb.	1 ft. lb.	47~332 Nm	1.4 Nm	613	1810	1/12
34662-1CG	3/4"	50~450 ft. lb.	5 ft. lb.	102~576 Nm	6.8 Nm	1048	5500	1/2
34662-2CG	3/4"	100~600 ft. lb.	5 ft. lb.	169~779 Nm	6.8 Nm	1234	5600	1/2
34662-3CG	3/4"	150~750 ft. lb.	5 ft. lb.	237~983 Nm	6.8 Nm	1238	6150	1/2
34862-1CG	1"	150~750 ft. lb.	5 ft. lb.	237~983 Nm	6.8 Nm	1238	6150	1/2

Single scale - Newton Meter (Nm)

	Square drive	Torque Range Nm	Incr.	Overall Length mm		
34262-1DG	1/4"	4~20 Nm	0.1 Nm	324	640	1/12
34262-2DG	1/4"	2~10 Nm	0.1 Nm	281	560	1/12
34262-3DG	1/4"	5~30 Nm	0.5 Nm	325	640	1/12
34362-1DG	3/8"	4~20 Nm	0.1 Nm	324	640	1/12
34362-2DG	3/8"	20~100 Nm	0.5 Nm	435	1300	1/12
34362-3DG	3/8"	10~60 Nm	0.5 Nm	325	1300	1/12
34462-1DG	1/2"	40~200 Nm	1 Nm	521	1590	1/12
34462-2DG	1/2"	60~340 Nm	2 Nm	613	1810	1/12
34662-1DG	3/4"	100~600 Nm	5 Nm	1048	5500	1/2
34662-2DG	3/4"	150~800 Nm	5 Nm	1234	5600	1/2
34662-3DG	3/4"	200~1000 Nm	5 Nm	1238	6150	1/2
34862-1DG	1"	200~1000 Nm	5 Nm	1238	6150	1/2

Single scale - English (in.lb./ft.lb.)

	Square drive	Torque Range in. lb. / ft. lb.	Incr.	Overall Length mm		
34262-1EG	1/4"	30~200 in. lb.	1 in. lb.	324	640	1/12
34362-1EG	3/8"	30~200 in. lb.	1 in. lb.	324	640	1/12
34362-2EG	3/8"	10~80 ft. lb.	0.5 ft. lb.	435	1300	1/12
34462-1EG	1/2"	20~150 ft. lb.	1 ft. lb.	521	1590	1/12
34462-2EG	1/2"	30~250 ft. lb.	1 ft. lb.	613	1810	1/12
34662-1EG	3/4"	50~450 ft. lb.	5 ft. lb.	1048	5500	1/2
34662-2EG	3/4"	100~600 ft. lb.	5 ft. lb.	1234	5600	1/2
34662-3EG	3/4"	150~750 ft. lb.	5 ft. lb.	1238	6150	1/2
34862-1EG	1"	150~750 ft. lb.	5 ft. lb.	1238	6150	1/2

Dual Scale - Newton Meter & English (Nm & ft. lb.)

	Square drive	Torque Range Nm	Incr.	Torque Range ft. lb.	Incr.	Overall Length mm		
34462-1FG	1/2"	40~200 Nm	1 Nm	33.2~143.8 ft. lb.	0.8 ft. lb.	521	1590	1/12
34462-2FG	1/2"	60~340 Nm	2 Nm	51.6~243.4 ft. lb.	1.5 ft. lb.	613	1720	1/12

Dual Scale - Kilogram-force Centimeter & Newton Meter (kgf.cm & Nm)

	Square drive	Torque Range kgf.cm	Incr.	Torque Range Nm	Incr.	Overall Length mm		
34422-3GG	1/2"	200~1000 Kgf.cm	5 Kgf.cm	22.1~95.6 Nm	0.5 Nm	435	1300	1/12
34422-1GG	1/2"	400~2000 Kgf.cm	10 Kgf.cm	44.1~191.2 Nm	1 Nm	521	1590	1/12

Certificate of calibration

Testing is in compliance with International standards with test equipment and reference standards calibrated by a laboratory traceable to International standards.

1 N.M. = 0.738 ft.lb. = 0.102 kgf.m
1 ft.lb. = 1.356 N.M. = 0.138 kgf.m
1 in.lb. = 0.113 N.M. = 1.152 kgf.cm

	RENEWAL KITS
34262-1DK	
34362-1DK 34362-2DK	
34462-1DK	
34662-1DK 34662-3DK	
34862-1DK	

CAUTION
1. Do not use this torque wrench over its scale range.
2. Do not use this torque wrench as a normal hand tool.
3. Torque wrench need to be calibrated periodically for accuracy.

Mini-type Industry Quality Torque Wrench

Industrial application
Quality accords to DIN ISO 6789 & ASME B107.14M-2004
Tolerance of torque ±3%
CW/CCW Direction

Single scale - Newton Meter (Nm)

	Square drive	Torque Range Nm	Incr.	Overall Length mm		
3426C-1DF	1/4"	3~15 Nm	0.1 Nm	211	330	24
3426C-2DF	1/4"	5~25 Nm	0.2 Nm	249	430	24
3436C-1DF	3/8"	3~15 Nm	0.1 Nm	211	450	24
3436C-2DF	3/8"	5~25 Nm	0.2 Nm	249	550	24

	RENEWAL KITS
3426C-1DK 3426C-2DK	
3436C-1DK 3436C-2DK	

Industry Quality Adjustable Torque Wrench

Design for easy torque-adjusting
Quality accords to DIN ISO 6789 & ASME B107.14M-2004
Tolerance of torque ±3%
CW/CCW Direction

34862-2CG, 34862-2DF
34862-2EG, 34862-2FF

34862-2CF, 34862-2DG
34862-2EF, 34862-2FG

Dual Scale - English & Newton Meter (in. lb. / ft. lb. & Nm)

	Square drive	Torque Range ft. lb.	Incr.	Torque Range Nm	Incr.	Overall Length mm		
34862-2CG	1"	200~1000 ft. lb.	5 ft. lb.	305~1322 Nm	6.8 Nm	1850	12200	1/2
34862-2CF	1"	200~1000 ft. lb.	5 ft. lb.	305~1322 Nm	6.8 Nm	1850	12200	1/2

Single scale - Newton Meter (Nm)

	Square drive	Torque Range Nm	Incr.	Overall Length mm		
34862-2DF	1"	300~1500 Nm	10 Nm	1850	12200	1/2
34862-2DG	1"	300~1500 Nm	10 Nm	1850	12200	1/2

Single scale - English (in.lb./ft.lb.)

	Square drive	Torque Range ft. lb.	Incr.	Overall Length mm		
34862-2EG	1"	200~1000 ft. lb.	5 ft. lb.	1850	12200	1/2
34862-2EF	1"	200~1000 ft. lb.	5 ft. lb.	1850	12200	1/2

Dual Scale - Newton Meter & English (Nm & ft. lb.)

	Square drive	Torque Range Nm	Incr.	Torque Range ft. lb.	Incr.	Overall Length mm		
34862-2FF	1"	300~1500 Nm	10 Nm	258~1070 ft. lb.	7.4 ft. lb.	1850	12200	1/2
34862-2FG	1"	300~1500 Nm	10 Nm	258~1070 ft. lb.	7.4 ft. lb.	1850	12200	1/2

	RENEWAL KITS
34862-2DK	

CAUTION
1. Do not use this torque wrench over its scale range.
2. Do not use this torque wrench as a normal hand tool.
3. Torque wrench need to be calibrated periodically for accuracy.

Torque Wrench

72 Teeth Industry Quality Adjustable Torque Wrench

Colorful quick release button design
Fixed head version allows using in narrow spaces
Quality accords to DIN ISO 6789 & ASME B107.14M-2004
Tolerance of torque ±3%
CW/CCW Direction

Single scale - Newton Meter (Nm)

	Square drive	Torque Range Nm	Incr.	Total Length mm		
3426A-1DG	1/4"	2~10 Nm	0.1 Nm	285	560	1/24
3426A-2DG	1/4"	4~20 Nm	0.1 Nm	325	640	1/24
3436A-2DG	3/8"	20~100 Nm	0.5 Nm	430	1300	1/24
3446A-1DG	1/2"	40~200 Nm	1 Nm	490	1460	1/12
3446A-2DG	1/2"	60~340 Nm	2 Nm	590	1750	1/12

Single scale - English (in.lb./ft.lb.)

	Square drive	Torque Range in. lb. / ft. lb.	Incr.	Total Length mm		
3426A-1EG	1/4"	20~100 in. lb.	1 in. lb.	285	560	560
3426A-2EG	1/4"	30~200 in. lb.	1 in. lb.	325	640	640
3436A-2EG	3/8"	10~80 ft. lb.	0.5 ft. lb.	430	1300	1300
3446A-1EG	1/2"	20~150 ft. lb.	1 ft. lb.	490	1460	1460
3446A-2EG	1/2"	30~250 ft. lb.	1 ft. lb.	590	1750	1750

	RENEWAL KITS
3426A-1DK	
3436A-2DK	
3446A-1DK	

CAUTION
1. Do not use this torque wrench over its scale range.
2. Do not use this torque wrench as a normal hand tool.
3. Torque wrench need to be calibrated periodically for accuracy.

Industry Quality Interchangeable Torque Wrench

Using standard insert head
Quality accords to DIN ISO 6789 & ASME B107.14M-2004
Positive button design which removes the insert head easily
Tolerance of torque ±3%
CW/CCW Direction

Dual Scale - English & Newton Meter (in. lb. / ft. lb. & Nm)

KING TONY	Size mm	Torque Range in.lb. / ft.lb.	Incr.	Torque Range Nm	Incr.	Total Length (mm)	g		
34512-1CG	9x12	20~100 in.lb.	1 in.lb	2.8~10.7 Nm	0.12 Nm	261	510	1 / 12
34512-2CG	9x12	30~200 in.lb.	1 in.lb	4.0~22.0 Nm	0.12 Nm	306	590	1 / 12
34512-3CG	9x12	10~80 ft.lb.	0.5 ft.lb	16.9~105.1 Nm	0.7 Nm	430	1270	1 / 12
34522-1CG	14x18	10~80 ft.lb.	0.5 ft.lb	16.9~105.1 Nm	0.7 Nm	430	1270	1 / 12
34522-2CG	14x18	20~150 ft.lb.	1 ft.lb	34~197 Nm	1.4 Nm	485	1410	1 / 12
34522-3CG	14x18	30~250 ft.lb.	1 ft.lb	47~332 Nm	1.4 Nm	580	1590	1 / 12

Single scale - English (in.lb./ft.lb.)

KING TONY	Size mm	Torque Range in.lb. / ft.lb.	Incr.	Total Length (mm)	g	
34512-1EG	9x12	20~100 in.lb.	1 in.lb	261	510	1 / 12
34512-2EG	9x12	30~200 in.lb.	1 in.lb	306	590	1 / 12
34512-3EG	9x12	10~80 ft.lb.	0.5 ft.lb	430	1270	1 / 12
34522-1EG	14x18	10~80 ft.lb.	0.5 ft.lb	430	1270	1 / 12
34522-2EG	14x18	20~150 ft.lb.	1 ft.lb	485	1410	1 / 12
34522-3EG	14x18	30~250 ft.lb.	1 ft.lb	580	1590	1 / 12

Single scale - Newton Meter (Nm)

KING TONY	Size mm	Torque Range Nm	Incr.	Total Length (mm)	g	
34512-1DG	9x12	2~10 Nm	0.1Nm	261	510	1 / 12
34512-2DG	9x12	4~20 Nm	0.1Nm	306	590	1 / 12
34512-4DG	9x12	10~60 Nm	0.5Nm	306	590	1 / 12
34512-3DG	9x12	20~100 Nm	0.5Nm	430	1270	1 / 12
34522-1DG	14x18	20~100 Nm	0.5Nm	430	1270	1 / 12
34522-2DG	14x18	40~200 Nm	1Nm	485	1410	1 / 12
34522-3DG	14x18	60~340 Nm	2Nm	580	1590	1 / 12

Dual Scale - Newton Meter & English (Nm & ft. lb.)

KING TONY	Size mm	Torque Range Nm	Incr.	Torque Range in.lb. / ft.lb.	Incr.	Total Length (mm)	g	
34512-1FG	9x12	2~10 Nm	0.1 Nm	22.1~84.1 in.lb	0.9 in.lb	261	510	1 / 12
34512-2FG	9x12	4~20 Nm	0.1 Nm	39.8~172.6 in.lb.	0.9 in.lb	306	590	1 / 12
34512-3FG	9x12	20~100 Nm	0.5 Nm	16.6~71.9 ft.lb.	0.4 ft.lb	430	1270	1 / 12
34522-1FG	14x18	20~100 Nm	0.5 Nm	16.6~71.9 ft.lb.	0.4 ft.lb	430	1270	1 / 12
34522-2FG	14x18	40~200 Nm	1 Nm	33.2~143.8 ft.lb.	0.8 ft.lb	485	1410	1 / 12
34522-3FG	14x18	60~340 Nm	2 Nm	51.6~243.4 ft.lb.	1.5 ft.lb	580	1590	1 / 12

CAUTION
1. Do not use this torque wrench over its scale range.
2. Do not use this torque wrench as a normal hand tool.
3. Torque wrench need to be calibrated periodically for accuracy.

Insert Tool

- Chrome-plated.

345031 & 345032

- Ratchet Insert tool

KING TONY	Size	▭ mm	Lw* (mm)	L (mm)		
34503102R	1/4"DR	9x12	17	46	71	12 / 192
34503103R	3/8"DR	9x12	26	58	106	10 / 160
34503203R	3/8"DR	14x18	27	70	218	6 / 96
34503204R	1/2"DR	14x18	27	70	256	6 / 96
NEW 34503206R	3/4"DR	14x18	27	71.5	348	4 / 64

345031

345032

345011 & 345012

- Open end Insert Tool

345011

345012

KING TONY	Size mm / inch	▭ mm	Lw* (mm)	L (mm)		
34501107M	7	9x12	17	37	36	12 / 192
34501108M	8	9x12	17	37	37	12 / 192
34501109M	9	9x12	17	37	37	12 / 192
34501110M	10	9x12	17	38	41	12 / 192
34501111M	11	9x12	17	39	39	12 / 192
34501112M	12	9x12	17	39	40	12 / 192
34501113M	13	9x12	17	39	45	12 / 192
34501114M	14	9x12	20	43	54	12 / 192
34501115M	15	9x12	20	43	55	12 / 192
34501116M	16	9x12	20	43	57	12 / 192
34501117M	17	9x12	20	44	58	12 / 192
34501118M	18	9x12	20	45	59	12 / 192
34501119M	19	9x12	20	45	64	12 / 192
34501108S	1/4	9x12	17	37	36	12 / 192
34501110S	5/16	9x12	17	37	38	12 / 192
34501112S	3/8	9x12	17	38	39	12 / 192
34501114S	7/16	9x12	17	39	41	12 / 192
34501116S	1/2	9x12	17	39	43	12 / 192
34501118S	9/16	9x12	20	43	53	12 / 192
34501120S	5/8	9x12	20	43	57	12 / 192
34501122S	11/16	9x12	20	44	62	12 / 192
34501124S	3/4	9x12	20	45	65	12 / 192

KING TONY	Size	▭ mm	Lw* (mm)	L (mm)		
34501213M	13	14x18	25	58	117	12 / 192
34501214M	14	14x18	25	58	120	12 / 192
34501215M	15	14x18	25	58	116	12 / 192
34501216M	16	14x18	25	59	127	10 / 160
34501217M	17	14x18	25	60	138	10 / 160
34501218M	18	14x18	25	60	136	10 / 160
34501219M	19	14x18	25	61	140	10 / 160
34501221M	21	14x18	25	61	160	6 / 96
34501222M	22	14x18	25	62	162	6 / 96
34501224M	24	14x18	25	63	168	6 / 96
34501227M	27	14x18	32	69	239	6 / 96
34501230M	30	14x18	32	70	249	6 / 96
34501232M	32	14x18	32	73	248	6 / 72
34501234M	34	14x18	32	74	252	6 / 72
34501236M	36	14x18	32	75	244	6 / 72
34501238M	38	14x18	32	74	229	6 / 72
34501241M	41	14x18	40	79	315	6 / 72

Insert Tool

- Chrome-plated.

345021 & 345022

- Ring Insert tool

345021

345022

KING TONY	Size mm /inch	▭ mm	Lw* (mm)	L (mm)		
34502107M	7	9x12	17	39	37	12 / 288
34502108M	8	9x12	17	40	36	12 / 288
34502110M	10	9x12	17	41	39	12 / 288
34502111M	11	9x12	17	43	42	12 / 288
34502112M	12	9x12	17	43	51	12 / 288
34502113M	13	9x12	17	44	51	12 / 288
34502114M	14	9x12	17	45	52	12 / 288
34502115M	15	9x12	17	45	53	12 / 288
34502116M	16	9x12	17	46	56	12 / 288
34502117M	17	9x12	17	47	55	12 / 192
34502118M	18	9x12	17	47	60	12 / 192
34502119M	19	9x12	17	49	63	12 / 192
34502121M	21	9x12	17	50	68	12 / 192
34502122M	22	9x12	17	51	70	12 / 192
34502108S	1/4	9x12	17	39	38	12 / 288
34502110S	5/16	9x12	17	40	37	12 / 288
34502112S	3/8	9x12	17	41	42	12 / 288
34502114S	7/16	9x12	17	43	41	12 / 288
34502116S	1/2	9x12	17	43	52	12 / 288
34502118S	9/16	9x12	17	45	53	12 / 288
34502120S	5/8	9x12	17	46	58	12 / 288
34502122S	11/16	9x12	17	47	62	12 / 192
34502124S	3/4	9x12	17	49	62	12 / 192
34502126S	13/16	9x12	17	50	72	12 / 192
34502128S	7/8	9x12	17	51	69	12 / 192

KING TONY	Size	▭ mm	Lw* (mm)	L (mm)		
34502213M	13	14x18	25	62	129	12 / 192
34502214M	14	14x18	25	63	132	12 / 192
34502215M	15	14x18	25	63	132	12 / 192
34502216M	16	14x18	25	63	137	12 / 192
34502217M	17	14x18	25	65	141	12 / 192
34502218M	18	14x18	25	65	138	10 / 160
34502219M	19	14x18	25	66	144	10 / 160
34502221M	21	14x18	25	67	151	10 / 160
34502222M	22	14x18	25	68	156	6 / 96
34502224M	24	14x18	25	69	161	6 / 96
34502227M	27	14x18	32	78	204	6 / 96
34502230M	30	14x18	32	79	204	6 / 96
34502232M	32	14x18	32	81	213	6 / 96
34502234M	34	14x18	32	82	225	6 / 90
34502236M	36	14x18	32	83	230	6 / 90
34502241M	41	14x18	40	86	235	6 / 90

Interchangeable Torque Wrench Set

34520
34510

KING TONY	□ mm	Contents							kg	
345201D11MR	14x18		34522-1DG		34503203R	345012	13 14 15 17 19 22 24 27 30		3.7	1 / 6
345202D11MR			34522-2DG		34503204R				3.8	1 / 6
345203D11MR			34522-3DG		34503204R				4	1 / 6
345201E11MR			34522-1EG		34503203R				3.7	1 / 6
345202E11MR			34522-2EG		34503204R				3.8	1 / 6
345203E11MR			34522-3EG		34503204R				4	1 / 6

KING TONY	□ mm	Contents							kg	
345102D08MR	9X12		34512-2DG		34503102R	345011	10 13 17	345021	10 13 17	1.3	1 / 18
NEW 345104D08MR			34512-4DG		34503103R					1.3	1 / 18
345101E08MR			34512-1EG		34503102R					1.2	1 / 18
345102E08MR			34512-2EG		34503102R					1.3	1 / 18

Torque Wrench

Professional Quality Adjustable Torque Wrench

Quality accords to DIN ISO 6789 & ASME B107.14M-2004

Tolerance of torque ±4%

Recyclable cylindrical package

Dual Scale - Newton Meter & Kilogram-force Centimeter / Kilogram-force meter (Nm & kgf.cm / kgf.m)

	Square drive	Torque Range Nm	Incr.	Torque Range kgf.cm / kgf.m	Incr.	Total Length mm		
34223-1A	1/4"	5~25 Nm	0.1 Nm	51~255 kgf.cm	1 kgf.cm	280	595	1/12
34323-1A	3/8"	5~25 Nm	0.1 Nm	51~255 kgf.cm	1 kgf.cm	280	595	1/12
34323-2A	3/8"	20~110 Nm	1 Nm	2.04~11.22 kgf.m	0.1 kgf.m	370	820	1/12
34423-1A	1/2"	42~210 Nm	1 Nm	4.3~21.4 kgf.m	0.41 kgf.m	450	1340	1/12
34423-2A	1/2"	50~350 Nm	1 Nm	5.1~35.7 kgf.m	0.1kgf.m	570	2400	1/12

Dual Scale - English & Kilogram-force Centimeter / Kilogram-force meter (in. lb. / ft. lb. & kgf.cm / kgf.m)

	Square drive	Torque Range in. lb. / ft. lb	Incr.	Torque Range kgf.cm / kgf.m	Incr.	Total Length mm		
34223-1B	1/4"	25~250 in. lb.	1.5 in. lb.	29~288 kgf.cm	1.13 kgf.cm	280	595	1/12
34323-1B	3/8"	25~250 in. lb.	1.5 in. lb.	29~288 kgf.cm	1.13 kgf.cm	280	595	1/12
34323-2B	3/8"	5~80 ft. lb.	0.5 ft. lb.	0.7~11.10 kgf.m	0.07 kgf.m	370	820	1/12
34423-1B	1/2"	10~150 ft. lb.	1 ft. lb.	1.4~20.7 kgf.m	0.14 kgf.m	450	1340	1/12
34423-2B	1/2"	30~250 ft. lb.	2 ft. lb.	4.2~34.6 kgf.m	0.27 kgf.m	570	2400	1/12

Dual Scale - English & Newton Meter (in. lb. / ft. lb. & Nm)

	Square drive	Torque Range in. lb. / ft. lb.	Incr.	Torque Range Nm	Incr.	Total Length mm		
34223-1C	1/4"	25~250 in. lb.	1.5 in. lb.	2.8~28.2 Nm	0.17 Nm	280	595	1/12
NEW 34323-1C	3/8"	25~250 in. lb.	1.5 in. lb.	2.8~28.2 Nm	0.17 Nm	280	595	1/12
NEW 34323-2C	3/8"	5~80 ft. lb.	0.5 in. lb.	6.8~108.5Nm	0.68 Nm	370	820	1/12
34423-1C	1/2"	10~150 ft. lb.	1 ft. lb.	13.6~203.4 Nm	1.35 Nm	450	1658	1/12
NEW 34423-2C	1/2"	30~250 ft. lb.	2 ft. lb.	40.7~339 Nm	2.71 Nm	570	2400	1/12

Certificate of calibration

Testing is in compliance with International standards with test equipment and reference standards calibrated by a laboratory traceable to International standards.

1 N.M = 0.738 ft.lb = 0.102 kgf.m
1 ft.lb = 1.356 N.M = 0.138 kgf.m
1 in.lb = 0.113 N.M = 1.152 kgf.cm

	RENEWAL KITS
34223-1DK	
34323-1DK 34323-2DK	
34423-1DK1	

CAUTION

1. Do not use this torque wrench over its scale range.
2. Do not use this torque wrench as a normal hand tool.
3. Torque wrench need to be calibrated periodically for accuracy.

Electronic Torque Wrench

Electronic Torque Wrench

Electronic torque value readout
CW +/- 2% and CCW +/- 3% operation
DIN ISO 6789-2003 & ASME B107.28-2005
Peak hold and track mode selectable
Buzzer and LED indicator for presettable target torque
Engineering units (Nm, ft.lb, in.lb, kgf.cm,kgf.m) adjustable
Auto shut off after about 80 seconds
Angle accuracy (34387/34487)

CE

Electronic Torque Wrench (34367-2AG, 34467-1AG)

Electronic Torque Angle-controlled Wrench (34387-2AG, 34487-1AG)

Torque Accuracy	CW ± 2% CCW ± 3%
Memory	50
Display resolution	0.1 Nm/ft.lb. ,0.01 kgf.m, 1.0 lb.in/ kg.cm
Operation Mode	Peak/Track
Unit Selection	kg.cm, kg.m, lb.in, lb.ft, Nm
Gear Teeth	36
Buttons	6
Battery	AAA x 3
Battery Life	110 hrs (continuous operation)
Operating Ambient Temperature	-10°C- 60°C (13.9°F-139.9°F)
Storage Temperature	-20°C-70°C (-4°F-157.9°F)
Operating relative humidity	15 to 90% noncondensing
Auto shut off	80 seconds (if do not use ratchet.)
Angle Accuracy	(±1% of reading)+(±1%@angular velocity >10°/sec < 180°/sec)+ (±1% of Text Texture)
Angle	0°~360° (34387-2AG,34487-1AG)

	Square drive	Torque Range Nm	ft. lb.	in. lb	kg.cm	kg.m	Total Length mm		
34367-2AG	3/8"	27-135 Nm	19.9-99.6 ft. lb.	239~1195 in. lb.	275~1376 kgf.cm	2.75~13.76 kgf.m	460	1400	1/6
34467-1AG	1/2"	40-200 Nm	29.5-147.5 ft. lb.	354~1770in. lb.	408~2038 kgf.cm	4.08~20.38 kgf.m	530	1500	1/6
34387-2AG	3/8"	27-135 Nm	19.9-99.6 ft. lb.	239~1195 in. lb.	275~1376 kgf.cm	2.75~13.76 kgf.m	460	1400	1/6
34487-1AG	1/2"	40-200 Nm	29.5-147.5 ft. lb.	354~1770in. lb.	408~2038 kgf.cm	4.08~20.38 kgf.m	530	1500	1/6

CAUTION

Important Safeguards

1. Do not press "M" and " ⏻ " button together please.
2. The system will enter into Calibration Mode.
3. Tun off power please.

Electronic Torque Adapter

34207-1A &34307-1A & 34407-1A

CE

Product Specifications:

Accuracy	±2%
Memory	50
Display resolution	0.1 Nm /ft.lb. ,0.01 kgf.m
Operation Mode	Peak/Track
Unit Selection	kgf.m , ft.lb. , Nm
Battery	CR2032 x 1 pcs
Battery Life	110hrs (continuous operation)
Operating Ambient Temperature	-10°C - 60°C (13.9°F - 139.9°F)
Storage Temperature	-20°C - 70°C (-4°F - 157.9°F)
Operating relative humidity	15 to 90% noncondensing
Auto shut off	80 seconds (if do not use electronic torque adapter.)
LED indicator	Green. Yellow. Red
Overload Alarm	34207-1A: 37.5 Nm (27.6 ft.lb.) 34307-1A: 168.8 Nm(124.5 ft.lb.) 34407-1A: 250 Nm (184.4 ft.lb.)

	Square drive	Torque Range Nm	Torque Range ft. lb.	Torque Range kgf.m	Size		
34207-1A	1/4"	6~30 Nm	4.4~22.1ft.lb.	0.61~3.06 kgf.m	L75 x W45mm	124	12/48
34307-1A	3/8"	27~135 Nm	19.9~99.6 ft.lb.	2.75~13.76 kgf.m	L75 x W45mm	198	12/48
34407-1A	1/2"	40~200 Nm	29.5~147.5 ft.lb.	4.08~20.38 kgf.m	L75 x W45mm	198.5	12/48

CAUTION
1. Do not use this torque wrench over its scale range.
2. Do not use this torque wrench as a normal hand tool.
3. Torque wrench need to be calibrated periodically for accuracy.

CE

34607-1A

Product Specifications:

Accuracy	±2%
Memory	50
Display resolution	0.1 Nm /ft.lb. ,0.01 kgf.m
Operation Mode	Peak/Track
Unit Selection	kgf.m , ft.lb. , Nm
Battery	AA x 2 pcs
Battery Life	110hrs (continuous operation)
Operating Ambient Temperature	-10°C - 60°C (13.9°F - 139.9°F)
Storage Temperature	-20°C - 70°C (-4°F - 157.9°F)
Operating relative humidity	15 to 90% noncondensing
Auto shut off	80 seconds (if do not use electronic torque adapter.)
LED indicator	Green. Yellow. Red
Overload Alarm	625 Nm (461 ft.lb.)

	Square drive	Torque Range Nm	Torque Range ft. lb.	Torque Range kgf.m	Size		
34607-1A	3/4"	100 ~500 Nm	73.8~368.8 .ft.lb.	10.19~50.95 kgf.m	L110 x W56 mm	585	6/24

CAUTION
1. Do not use this torque wrench over its scale range.
2. Do not use this torque wrench as a normal hand tool.
3. Torque wrench need to be calibrated periodically for accuracy.

A/C & REFRIGERATION SERVICE TOOLS

3411

NEW

- CRV-open end series
- Unique design of head to prevents slipping of the nut while use
- Tolerance of torque ±4%
- The customization for the torque setting

KING TONY	Size	Nm	L (mm)			
341118-17M	17	18	260	1/4"	480	1/40
341142-22M	22	42	260	3/8"	480	1/40
341155-26M	26	55	260	1/2"	480	1/40
3411B5-29M	29	65	310	5/8"	570	1/20

A/C & REFRIGERATION SERVICE TOOLS SET

3411003MR

NEW

	Contents		
3411003MR	3411 17 22 26 29	3.29	1/5

Torque Screwdriver

34111

- Tolerance of torque ±5% quality meets DIN ISO 6789 & ASME B107.14M-2004
- 6.3mm (1/4") Hex driver for bit
- Automatic adjustment knob design
- Easy-to-read laser scale
- Ergonomic comfort rubber grip

KING TONY	SIZE	Torque Range cNm / Nm / in-lb	Incr.	Total Length mm		
34111-1DG	1/4"	10~120 cNm	1 cNm	180	207	1/24
34111-1EG	1/4"	3~15 in-lb	0.1 in-lb	180	207	1/24
34111-2DG	1/4"	1~6 Nm	0.1 Nm	248	475	1/24
34111-2EG	1/4"	10~50 in-lb	0.5 in-lb	248	475	1/24

Torque Angle Gauge

34440 34660

- Square Drive :
  34440 (1/2" x 1/2")
  34660 (3/4" x 3/4")
- 360° angle scale- clearly marked in 2° increments, and in intervals of 10° and 30°.
- Indicator etched on clear plastic plate-protects angle scale from dirt and grease.
- Adjustable arm keeps angle scale stationary.
- Arm has two lengths for additional flexibility in placement against components.
- Tough composite dial and rotating index allow operator to accurately tighten fixing to manufacturers exact standard.

34440 34660

KING TONY	spec.	g	
34440	1/2"Fx1/2"M	190	1 / 20
34660	3/4"Fx3/4"M	623	1 / 12

Torque Multiplier

34688

- Torque multiplication with 1:5, accuracy guaranteed better than ±5%.
- Reaction bar supplied in two styles for maximum versatility.
- Ideal construction offers minimal maintenance and extended life.
- Portable package brings convenience for use in different working places.

Set contents:

Multiplier head 1 pc		34688-05A
Reaction bar 2 pc		34688-P01 34688-P02

KING TONY	Ratio	Input Square	Output Square	Max Input Torque Nm / lbf.ft	Max Output Torque Nm / lbf.ft	A mm	B mm	kg	
34688	1:5	3/4"	1"	540/400	2700 / 2000	108	128.1	7.4	1 / 2

Professional Torque Tester

ZV001

- Features:

Calibration range	40~400 Nm
Display	5 effective digits max.
Accuracy	±1%
Units of measurement	Lb-in, Lb-ft, Kg-cm, Nm
Operating temperature Range	+5°C~+40°C
Storage temperature range	0°C~+50°C
Max. operating humidity	25~85 % RH
Power Supply	90~260 Volts a.c. at 50-60 Hz input.
Power consumption	Less than 1.5 W
Power cable	1800 mm
Base materials/ Finish	Aluminum Alloy/ Anodization
Dimensions	820(L)x435(W)x320(H) mm
PC conection	RS 232

ZV001	57	1 / 1

Notes

Wrench

- Wrench & Special Purpose Wrench
- T-shaped Driver & T-type Plug Socket
- T-type Universal Joint & Socket Wrench

KING TONY

Combination Wrench

1060
5060

- European slimline type
- 15° open end angle
- 15° ring end offset from shaft
- Chrome vanadium steel
- Chrome plated
- Metric size - DIN3113 ,ISO 7738
- Inch size -ANSI/ASME B107.6

KING TONY	Size mm / inch	L (mm)	g	
1060-55	5.5	105	16	12 / 504
1060-06	6.0	105	18	12 / 504
1060-07	7.0	115	20	12 / 504
1060-08	8.0	125	25	12 / 504
1060-09	9.0	135	34	12 / 504
1060-10	10.0	145	39	12 / 504
1060-11	11.0	155	46	12 / 504
1060-12	12.0	165	56	12 / 216
1060-13	13.0	175	69	12 / 216
1060-14	14.0	185	80	12 / 216
1060-15	15.0	195	93	12 / 192
1060-16	16.0	205	111	12 / 192
1060-17	17.0	215	119	12 / 192
1060-18	18.0	225	138	12 / 144
1060-19	19.0	235	158	12 / 144
1060-20	20.0	245	182	12 / 144
1060-21	21.0	255	203	12 / 96
1060-22	22.0	265	225	12 / 96
1060-23	23.0	275	251	12 / 96
1060-24	24.0	285	287	6 / 54
1060-25	25.0	295	326	6 / 54
1060-26	26.0	305	344	6 / 54
1060-27	27.0	315	371	6 / 54
1060-28	28.0	325	387	6 / 48
1060-29	29.0	335	456	6 / 48
1060-30	30.0	345	514	6 / 48
1060-32	32.0	365	557	6 / 48
5060-08	1/4	105	18	12 / 504
5060-10	5/16	125	25	12 / 504
5060-12	3/8	145	39	12 / 504
5060-14	7/16	155	46	12 / 504
5060-16	1/2	175	69	12 / 216
5060-18	9/16	185	80	12 / 216
5060-20	5/8	205	111	12 / 192
5060-22	11/16	215	119	12 / 192
5060-24	3/4	235	158	12 / 144
5060-26	13/16	255	203	12 / 96
5060-28	7/8	265	220	12 / 96
5060-30	15/16	285	287	6 / 54
5060-32	1	295	326	6 / 54
5060-34	1-1/16	315	371	6 / 54
5060-36	1-1/8	335	456	6 / 48
5060-40	1-1/4	365	557	6 / 48

1071
5071

- Jumbo type
- 15° open end angle
- 15° ring end offset from shaft
- Medium carbon steel
- Polished, chrome plated
- Metric size-DIN 3113 ,ISO 7738
- Inch size-ANSI/ASME B107.6

KING TONY	Size mm / inch	L (mm)	g	
1071-33	33	420	765	5 / 20
1071-34	34	420	745	5 / 20
1071-35	35	430	960	5 / 20
1071-36	36	430	960	5 / 20
1071-38	38	455	1155	5 / 20
1071-41	41	495	1402	5 / 15
1071-42	42	495	1394	5 / 15
1071-44	44	500	1479	5 / 15
1071-46	46	500	1515	5 / 15
1071-48	48	565	2550	5 / 10
1071-50	50	565	2550	5 / 10
5071-42	1-5/16	420	760	5 / 20
5071-44	1-3/8	430	970	5 / 20
5071-46	1-7/16	430	950	5 / 20
5071-48	1-1/2	455	1150	5 / 20
5071-50	1-9/16	500	1546	5 / 15
5071-52	1-5/8	500	1402	5 / 15
5071-54	1-11/16	500	1432	5 / 15
5071-56	1-3/4	500	1419	5 / 15
5071-58	1-13/16	500	1478	5 / 15
5071-60	1-7/8	565	2540	5 / 10
5071-62	1-15/16	565	2550	5 / 10
5071-64	2	565	2540	5 / 10

8781007KT applied to 1060-06 – 1060-12 , 5060-08 – 5060-16
8781013KT applied to 1060-13 – 1060-22 , 5060-18 – 5060-28
8781032KT applied to 1060-24 – 1060-32 , 5060-30 – 5060-40

Combination Wrench Set

1207	MR SR	1212	MR	1218	MR 01
1208	MR	1214	MR SR	1226	MR
1210	MR	1214	MR 01	1214	SR01
1211	MR SR	1215	MR	1216	SR
1211	SR 01	1215	MR 01		

Wallet sets:

KING TONY	PC/SET	Contents	kg	
1207MR	7	10 11 12 13 14 17 19	0.60	1/30
1207SR	7	3/8 7/16 1/2 9/16 5/8 11/16 3/4		
1208MR	8	10 11 12 13 14 17 19 22	0.65	1/24
1210MR	10	8 10 12 13 14 17 19 21 22 24	1.38	1/16
1211MR	11	8 9 10 11 12 13 14 17 19 22 24	1.4	1/16
1211SR	11	1/4 5/16 3/8 7/16 1/2 9/16 11/16 3/4 13/16 7/8 15/16		
1211SR01	11	1/4 5/16 3/8 7/16 1/2 9/16 5/8 11/16 3/4 7/8 1		
1212MR	12	8 9 10 11 12 13 14 15 16 17 19 22	1.03	1/16
1214MR	14	10 11 12 13 14 16 17 19 21 22 24 27 30 32	2.70	1/8
1214SR	14	5/16 3/8 7/16 1/2 9/16 5/8 11/16 3/4 13/16 7/8 15/16 1 1-1/8 1-1/4		
1214MR01	14	10 11 13 14 16 17 18 19 21 22 24 27 30 32		
1215MR	14	8 9 10 11 12 13 14 15 16 17 19 21 22 24	1.63	1/12
1215MR01	14	8 10 11 12 13 14 15 16 17 18 19 21 22 24		
1214SR01	14	3/8 7/16 1/2 9/16 5/8 11/16 3/4 13/16 7/8 15/16 1 1-1/16 1-1/8 1-1/4	3.23	1/8
1216SR	16	1/4 5/16 3/8 7/16 1/2 9/16 5/8 11/16 3/4 13/16 7/8 15/16 1 1-1/16 1-1/8 1-1/4	3.44	1/8
1218MR01	18	6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 24	2.50	1/9
1226MR	26	6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 32	5.30	1/4

Nylon Pouch:

1207MR / SR

1208MR

1210MR

1211MR / SR / SR01

1212MR

1214MR / MR01 / SR
1215MR / MR01

1214SR 01

1216SR

1226MR

Combination Wrench Set NEW

1211	MRN	1218	MRN
1214	MRN 01	1226	MRN
1215	MRN	1296	MRN

Wallet sets:

KING TONY	PC./SET	Contents	kg	
1211MRN	11	8 9 10 11 12 13 14 17 19 22 24	1.4	1/16
1214MRN01	14	10 11 12 13 14 16 17 19 21 22 24 27 30 32	2.70	1/8
1215MRN	14	8 9 10 11 12 13 14 15 16 17 19 21 22 24	1.63	1/12
1218MRN	18	6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 24	2.50	1/9
1226MRN	26	6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 32	5.30	1/4
1296MRN	6	34 36 38 41 46 50	8.87	1/2

Tetoron pouch:

1211MRN

1214MRN01

1215MRN

1218MRN

1226MRN

Jumbo type: (1071)

1296MRN

Stubby Combination Wrench

10D0

short pattern

- Chrome vanadium alloy steel.
- Short pattern design enables greater access in
- confined spaces.

Metric size - DIN3113

KING TONY	Size mm	D1	D2	H1	H2	L (mm)	g	
10D0-08	8	18.1	13.8	4.6	6.0	85	20	20 / 360
10D0-09	9	19.3	14.5	4.8	6.4	90	25	20 / 360
10D0-10	10	20.5	15.1	4.8	6.4	95	27	20 / 360
10D0-11	11	22.7	16.7	5.9	7.9	100	45	20 / 360
10D0-12	12	24.7	18.0	6.2	8.3	105	49	20 / 360
10D0-13	13	27.2	19.1	6.5	8.7	110	59	20 / 360
10D0-14	14	28.8	21.4	7.0	9.2	115	65	15 / 270
10D0-15	15	31.0	22.4	7.4	9.7	120	73	15 / 270
10D0-16	16	33.0	23.8	7.8	10.3	125	85	15 / 270
10D0-17	17	35.0	26.2	8.1	10.7	130	116	15 / 180
10D0-18	18	37.0	27.3	8.6	11.3	135	123	15 / 180
10D0-19	19	39.0	28.6	9.0	11.8	140	135	12 / 144

Stubby Combination Wrench Set

1282MR

NEW

KING TONY	PC/SET	Contents	kg	
1282MR	12	8 9 10 11 12 13 14 15 16 17 18 19	1.03	1/24

45° Ring End Offset Combination Wrench

1063

NEW

- Chrome vanadium steel
- Chrome plated
- Metric size DIN3113, ISO 7738, ISO 3318

KING TONY	Size mm/ inch	L (mm)	g	
1063-06	6	110	19	20 / 360
1063-07	7	120	26	20 / 360
1063-08	8	130	32	20 / 320
1063-09	9	140	39	20 / 320
1063-10	10	150	46	20 / 320
1063-11	11	160	59	20 / 320
1063-12	12	170	73	20 / 240
1063-13	13	180	78	20 / 240
1063-14	14	190	103	15 / 240
1063-15	15	200	118	15 / 180
1063-16	16	210	135	15 / 180
1063-17	17	220	153	15 / 120
1063-18	18	230	179	12 / 96
1063-19	19	240	198	12 / 96
1063-21	21	260	224	10 / 80
1063-22	22	270	258	10 / 80
1063-24	24	290	317	10 / 80
1063-27	27	320	448	6 / 48
1063-30	30	350	552	6 / 48
1063-32	32	370	683	6 / 48
5063-14	7/16	160	59	20 / 320
5063-16	1/2	180	78	20 / 240
5063-18	9/16	190	103	15 / 240

45° Ring End Offset Combination Wrench Set

1272MR

NEW

KING TONY	PC/SET	Contents	kg	
1272MR	12	6 7 8 9 10 11 12 13 14 17 19 22	1.21	1/18

Open End Wrench & Set

1900
5900

- European slimline type
- 15° open end angle
- Chrome vanadium steel
- Chrome plated
- Metric size - DIN3110
- Inch size -ANSI/ASME B107.6

KING TONY	Size mm / inch	L (mm)	g	
19005507	5.5 x 7	123	28	12 / 576
19000607	6 x 7	123	28	12 / 576
19000708	7 x 8	140	36	12 / 576
19000809	8 x 9	140	39	12 / 576
19000810	8 x 10	140	38	12 / 576
19000911	9 x 11	156	55	12 / 288
19001011	10 x 11	156	65	12 / 288
19001012	10 x 12	156	65	12 / 288
19001113	11 x 13	172	78	12 / 288
19001213	12 x 13	172	86	12 / 288
19001214	12 x 14	172	78	12 / 288
19001314	13 x 14	172	78	12 / 288
19001317	13 x 17	195	124	12 / 192
19001415	14 x 15	188.5	114	12 / 192
19001417	14 x 17	204	146	12 / 192
19001617	16 x 17	204	146	12 / 192
19001618	16 x 18	221	165	12 / 144
19001719	17 x 19	221	177	12 / 144
19001819	18 x 19	221	178	12 / 144
19001921	19 x 21	237	210	12 / 144
19001922	19 x 22	237	210	12 / 144
19002022	20 x 22	237	210	12 / 144
19002123	21 x 23	247	258	6 / 72
19002224	22 x 24	247	258	6 / 72
19002326	23 x 26	263	281	6 / 72
19002426	24 x 26	263	281	6 / 72
19002427	24 x 27	263	326	6 / 72
19002528	25 x 28	279	373	6 / 48
19002632	26 x 32	298	481	6 / 48
19002730	27 x 30	298	481	6 / 48
19002732	27 x 32	298	481	6 / 48
19003032	30 x 32	298	481	6 / 48
59000810	1/4 x 5/16	123	28	12 / 576
59001012	5/16 x 3/8	140	39	12 / 576
59001214	3/8 x 7/16	156	65	12 / 288
59001416	7/16 x 1/2	172	78	12 / 288
59001618	1/2 x 9/16	172	78	12 / 288
59001820	9/16 x 5/8	188.5	114	12 / 192
59002022	5/8 x 11/16	204	146	12 / 192
59002224	11/16 x 3/4	221	177	12 / 144
59002628	13/16 x 7/8	237	210	12 / 144
59003032	15/16 x 1	247	258	6 / 72
59003034	15/16 x 1-1/16	263	281	6 / 72
59003236	1 x 1-1/8	279	373	6 / 48
59003640	1-1/8 x 1-1/4	298	481	6 / 48

Nylon pouch:

1108MR / SR

1110MR / SR

1112MR / SR

Tetoron pouch:

1112MRN

KING TONY	PC/SET	Contents	kg	
1108MR	8	6 x 7 8 x 9 10 x 11 12 x 13 14 x 15 16 x 17 18 x 19 20 x 22	0.91	1/24
1108SR	8	1/4 x 5/16 5/16 x 3/8 3/8 x 7/16 7/16 x 1/2 9/16 x 5/8 5/8 x 11/16 11/16 x 3/4 13/16 x 7/8		
1110MR	10	6 x 7 8 x 9 10 x 11 12 x 13 14 x 15 16 x 17 18 x 19 20 x 22 24 x 27 25 x 28	1.67	1/16
1110SR	10	1/4 x 5/16 5/16 x 3/8 3/8 x 7/16 7/16 x 1/2 9/16 x 5/8 5/8 x 11/16 11/16 x 3/4 13/16 x 7/8 15/16 x 1-1/16 1 x 1-1/8		
1112MR	12	6 x 7 8 x 9 10 x 11 12 x 13 14 x 15 16 x 17 18 x 19 20 x 22 21 x 23 24 x 27 25 x 28 30 x 32	2.35	1/10
1112SR	12	1/4 x 5/16 5/16 x 3/8 3/8 x 7/16 7/16 x 1/2 9/16 x 5/8 5/8 x 11/16 11/16 x 3/4 13/16 x 7/8 15/16 x 1 15/16 x 1-1/16 1 x 1-1/8 1-1/8 x 1-1/4		
1112MRN		6 x 7 8 x 9 10 x 11 12 x 13 14 x 15 16 x 17 18 x 19 20 x 22 21 x 23 24 x 27 25 x 28 30 x 32		

8781007KT applied to 1900-0507 ~1900-1213 , 5900-0810 ~ 5900-1416

8781013KT applied to 1900-1214 ~1900-2224 , 5900-1820 ~ 5900-2628

8781032KT applied to 1900-2326 ~1900-3032 , 5900-3032 ~ 5900-3640

45° Offset Ring Wrench

1960
5960

- 45° deep ring offset
- Thin wall rings
- Chrome vanadium steel
- Chrome plated
- Metric size - DIN 838
- INCH size - ANSI/ASME B107.6

KING TONY	Size mm / inch	L (mm)	g	
19600607	6 x 7	165	45	12 / 360
19600809	8 x 9	175	53	12 / 360
19600810	8 x 10	185	53	12 / 360
NEW 19601011	10 x 11	195	60	12 / 360
19601012	10 x 12	185	60	12 / 360
19601113	11 x 13	205	62	12 / 240
NEW 19601213	12 x 13	205	62	12 / 240
19601214	12 x 14	220	100	12 / 240
NEW 19601415	14 x 15	235	151	12 / 144
19601417	14 x 17	235	151	12 / 144
NEW 19601617	16 x 17	240	151	12 / 144
19601719	17 x 19	250	221	6 / 72
NEW 19601819	18 x 19	250	222	6 / 72
19601921	19 x 21	270	340	6 / 72
NEW 19602022	20 x 22	270	340	6 / 72
19602224	22 x 24	320	479	6 / 48
19602326	23 x 26	360	465	6 / 48
19602427	24 x 27	360	479	6 / 48
19602732	27 x 32	380	580	6 / 36
19603032	30 x 32	380	650	6 / 36
59601214	3/8 x 7/16	185	53	12 / 360
59601618	1/2 x 9/16	220	100	12 / 240
59602022	5/8 x 11/16	240	151	12 / 144
59602428	3/4 x 7/8	270	340	6 / 72
59603032	15/16 x 1	360	465	6 / 48

45° Offset Ring Wrench Set

1606 MR
1609 MR

KING TONY	PC./SET	Contents	kg	
1606MR	6	10 x 12, 12 x 14, 14 x 17, 17 x 19, 19 x 21, 23 x 26	1.6	1/16
1609MR	9	8 x 9, 10 x 12, 11 x 13, 12 x 14, 14 x 17, 17 x 19, 19 x 21, 22 x 24, 23 x 26	1.93	1/8

1606MR

1609MR

45° Offset Ring Wrench NEW

1961

- Mini type
- 45° deep ring offset
- Thin wall rings
- Chrome vanadium steel
- Chrome plated
  Metric size - DIN 838

KING TONY	Size mm / inch	L (mm)	g	
19610809	8 x 9	112	27.6	12 / 336
19611011	10 x 11	115	42.2	12 / 336
19611213	12 x 13	130	57.6	12 / 240
19611415	14 x 15	140	84.0	12 / 240
19611617	16 x 17	150	96.8	10 / 200
19611819	18 x 19	157	113.6	6 / 120

75° Offset Ring Wrench & Set

1970
5970

- European slimline type
- 75° deep ring offset
- Thin wall rings
- Chrome vanadium steel
- Chrome plated
- Metric size - DIN 838
- INCH size - ANSI/ASME B107.6

KING TONY	Size mm / inch	L (mm)	g	
19700607	6 x 7	168	43	12 / 360
19700809	8 x 9	183	62	12 / 360
19700810	8 x 10	183	62	12 / 360
19701011	10 x 11	198	88	12 / 240
19701012	10 x 12	198	88	12 / 240
19701113	11 x 13	217	131	12 / 144
19701213	12 x 13	217	131	12 / 144
19701214	12 x 14	217	131	12 / 144
19701314	13 x 14	217	131	12 / 144
19701415	14 x 15	239	152	12 / 144
19701417	14 x 17	260	189	6 / 96
19701617	16 x 17	260	189	6 / 96
19701719	17 x 19	292	240	6 / 96
19701819	18 x 19	292	240	6 / 96
19701921	19 x 21	318	330	6 / 60
19702022	20 x 22	318	330	6 / 60
19702123	21 x 23	326.5	362	6 / 60
19702224	22 x 24	326	362	6 / 60
19702326	23 x 26	344	436	6 / 48
19702426	24 x 26	329	436	6 / 48
19702427	24 x 27	329	436	6 / 48
19702528	25 x 28	347	488	6 / 48
19703032	30 x 32	362	600	6 / 36

KING TONY	Size mm / inch	L (mm)	g	
59700810	1/4 x 5/16	168	43	12 / 360
59701012	5/16 x 3/8	183	62	12 / 360
59701214	3/8 x 7/16	198	88	12 / 240
59701416	7/16 x 1/2	217	131	12 / 144
59701618	1/2 x 9/16	217	134	12 / 144
59701820	9/16 x 5/8	260	152	12 / 96
59702022	5/8 x 11/16	260	189	6 / 96
59702224	11/16 x 3/4	292	240	6 / 96
59702428	3/4 x 7/8	318	330	6 / 60
59702628	13/16 x 7/8	326.5	330	6 / 60
59703032	15/16 x 1	329	436	6 / 48
59703436	1-1/16 x 1-1/8	347	488	6 / 48
59703640	1-1/8 x 1-1/4	365	679	6 / 48

KING TONY	PC./SET	Contents	kg	
1706MR	6	6 x 7, 8 x 9, 10 x 11, 12 x 13, 14 x 15, 16 x 17	0.80	1/24
1707SR	7	1/4 x 5/16, 3/8 x 7/16, 1/2 x 9/16, 5/8 x 11/16, 3/4 x 7/8, 15/16 x 1, 1-1/16 x 1-1/8	2.00	1/12
1708MR	8	6 x 7, 8 x 9, 10 x 11, 12 x 13, 14 x 15, 16 x 17, 18 x 19, 21 x 23	1.43	1/12
1710MR	10	6 x 7, 8 x 9, 10 x 11, 12 x 13, 14 x 15, 16 x 17, 18 x 19, 21 x 23, 24 x 27, 30 x 32	2.60	1/8
1712MR	12	6 x 7, 8 x 9, 10 x 11, 12 x 13, 14 x 15, 16 x 17, 18 x 19, 20 x 22, 21 x 23, 24 x 26, 25 x 28, 30 x 32	3.32	1/6
NEW 1712MRN	12	6 x 7, 8 x 9, 10 x 11, 12 x 13, 14 x 15, 16 x 17, 18 x 19, 20 x 22, 21 x 23, 24 x 26, 25 x 28, 30 x 32	3.32	1/6

Nylon pouch:

1706MR

1707SR

1708MR

1710MR

1712MR

Tetoron pouch:

1712MRN

Straight Ring Wrench

19C0

- Thin wall rings
- Chrome vanadium steel
- Chrome plated
- Metric size - DIN 837

KING TONY	Size mm / inch	L (mm)	g	
19C00607	6 x 7	121	17	20 / 480
19C00809	8 x 9	137	27	20 / 480
19C01011	10 x 11	154	51	20 / 320
19C01213	12 x 13	164	70	20 / 240
19C01415	14 x 15	182	92	20 / 240
19C01617	16 x 17	211	118	12 / 144
19C01819	18 x 19	226	151	12 / 144
19C02022	20 x 22	240	187	10 / 120
19C02123	21 x 23	255	242	10 / 120
19C02426	24 x 26	270	290	6 / 72
19C02528	25 x 28	285	339	6 / 72
19C03032	30 x 32	335	520	5 / 40

Suitable for narrow space

Straight Ring Wrench Set

1C08MR & 1C12MR

KING TONY	PC/SET	Contents	kg	
1C08MR	8	6 x 7, 8 x 9, 10 x 11, 12 x 13, 14 x 15, 16 x 17, 18 x 19, 20 x 22	0.79	1 / 24
1C12MR	12	6 x 7, 8 x 9, 10 x 11, 12 x 13, 14 x 15, 16 x 17, 18 x 19, 20 x 22, 21 x 23, 24 x 26, 25 x 28, 30 x 32	2.23	1 / 12

1C08MR

1C12MR

Half Moon Ring Wrench

1950

- Chrome vanadium steel
- Chrome plated
- Metric sizes
- Specially designed for starter bolts
- Used mainly in automotive applications for starter motors, inlet and exhaust manifolds

KING TONY	S1 (mm)	S2 (mm)	D1 (mm)	D2 (mm)	L (mm)	H1 (mm)	H2 (mm)	H (mm)	g	
19500810	8	10	15.6	14.3	137	6.5	6.2	42	40	12 / 288
19501012	10	12	15.6	18.2	141	6.6	6.5	50	55	12 / 288
19501113	11	13	18.2	21.0	166	8.2	8.0	63	93	8 / 128
19501214	12	14	18.2	21.0	166	8.2	8.0	63	94	8 / 128
19501315	13	15	22.0	25.0	190	9.2	8.2	75	126	6 / 72
19501417	14	17	22.0	25.0	190	9.2	8.2	75	126	6 / 72
19501618	16	18	25.5	28.0	220	9.6	8.8	79	156	5 / 60
19501719	17	19	25.5	28.0	220	9.6	8.8	79	174	5 / 60
19501922	19	22	28.6	32.5	256	11.1	10.1	91	255	5 / 40

Half Moon Ring Wrench

1951 NEW

- American type
- Chrome vanadium steel
- Chrome plated
- Metric sizes
- Specially designed for starter bolts
- Used mainly in automotive applications for starter motors, inlet and exhaust manifolds

KING TONY	S1 (mm)	S2 (mm)	D1 (mm)	D2 (mm)	L (mm)	H1 (mm)	H2 (mm)	H (mm)	g	
19510810	08	10	12.5	16.5	125	7.0	7.4	36	48.0	12 / 240
19511012	10	12	17.5	19.0	149	8.0	8.5	46	67.8	12 / 240
19511113	11	13	17.5	19.0	149	8.0	8.5	46	76.0	12 / 240
19511214	12	14	21.4	23.4	169	8.2	8.4	50	95.4	10 / 120
19511517	15	17	23.5	27.0	194	9.5	10.0	56	151.2	8 / 96
19511719	17	19	26.5	27.7	194	9.2	9.6	56	141.4	8 / 96
19511922	19	22	29.0	32.3	225	11.0	12.0	66	235.0	5 / 60

Star Box End Wrench

1920

- Chrome vanadium steel
- Chrome plated
- Metric size
- Inch size -ANSI/ASME B107.6

KING TONY	Size	L (mm)	g	
19200608	E6 x E8	114.0	18.8	12 / 504
19200711	E7 x E11	126.5	27.4	12 / 504
19201012	E10 x E12	142.5	32.6	12 / 384
19201418	E14 x E18	183.0	86.2	12 / 240
19201622	E16 x E22	205.0	119.0	12 / 192
19202024	E20 x E24	225.0	172.2	12 / 144

Star Box End Wrench Set

1406 PR

KING TONY	PC./SET	Contents	kg	
1406PR	6	E6 x E8 E7 x E11 E10 x E12 E14 x E18 E16 x E22 E20 x E24	0.46	1/15

Flare Nut Wrench

1930
5930

6 points
12° ring offset
Chrome vanadium steel
Chrome plated
DIN 3118

KING TONY	Size mm / inch	L (mm)	g	
19300810	8 x 10	130	53	12 / 216
19300911	9 x 11	130	55	12 / 216
19301011	10 x 11	150	78	12 / 192
19301012	10 x 12	150	74	12 / 192
19301113	11 x 13	170	106	12 / 144
19301213	12 x 13	170	104	12 / 144
19301214	12 x 14	170	102	12 / 144
19301417	14 x 17	190	132	12 / 144
19301719	17 x 19	210	170	8 / 128
19301922	19 x 22	230	218	9 / 108
59301012	5/16 x 3/8	130	53	12 / 216
59301214	3/8 x 7/16	150	78	12 / 192
59301618	1/2 x 9/16	170	102	12 / 144
59301820	9/16 x 5/8	190	132	12 / 144
59302224	11/16 x 3/4	210	170	6 / 96
59302428	3/4 x 7/8	230	218	6 / 72

1931

- **12** points
- 12° ring offset
- Chrome vanadium steel
- Chrome plated
  DIN 3118

KING TONY	Size mm	L (mm)	g	
19312224	22 x 24	250	310	6 / 72
19312427	24 x 27	270	359	6 / 48
19313032	30 x 32	290	471	5 / 40

Flare Nut Wrench Set

1306 MR SR

	PC./SET	Contents	kg	
1306MR	6	8 x 10 10 x 12 11 x 13 12 x 14 17 x 19 19 x 22	0.90	1/30
1306SR	6	5/16 x 3/8 3/8 x 7/16 1/2 x 9/16 9/16 x 5/8 11/16 x 3/4 3/4 x 7/8	0.86	1/30
NEW 1306MRN	6	8 x 10 10 x 12 11 x 13 12 x 14 17 x 19 19 x 22	0.90	1/30

Nylon pouch:

Tetoron pouch:

Flexible Ring Socket Wrench

- Chrome vanadium alloy steel, polished, chrome plated.
- 4 ball retaining grooves.

○ 3350 M

NEW

- 3/8" drive
- 12 points
- Metric size
- Flexible head folds up to 200°
- Combine use with F-handle,handle,T-handle speed-handle
- Suitable for all hydraulic, fuel, oil brake, A/C, auto
- tool and air line work DIN 3120

KING TONY	mm	D1 (mm)	D2 (mm)	L (mm)	g	
335008M	8	15.0	18.8	45.0	44	12 / 360
335009M	9	18.0	18.8	49.0	49	12 / 360
375010M	10	18.0	18.8	49.0	48	12 / 360
375011M	11	22.0	18.8	53.0	58	12 / 360
375012M	12	22.0	18.8	53.0	58	12 / 360
375013M	13	26.0	18.8	60.0	83	12 / 240
375014M	14	26.0	18.8	60.0	80	12 / 240
375015M	15	27.0	18.8	60.0	77	12 / 240
375016M	16	32.0	24.7	73.5	160	6 / 96
375017M	17	33.0	24.7	73.5	159	6 / 96
375018M	18	33.0	24.7	73.5	155	6 / 96
375019M	19	32.0	24.7	73.5	154	6 / 96

Flexible Crow Foot Socket Wrench

◉ 3351 M

NEW

- 3/8" drive
- 6 points
- Metric size
- Flexible head folds up to 200°
- Combine use with F-handle,handle,T-handle speed-handle
- Suitable for all hydraulic, fuel, oil brake, A/C, auto tool and air line work
- DIN 3120

KING TONY	mm	D1 (mm)	D2 (mm)	L (mm)	g	
335108M	8	15.0	18.8	45.0	44	12 / 360
335109M	9	18.0	18.8	49.0	47	12 / 360
375110M	10	18.0	18.8	49.0	47	12 / 360
375111M	11	22.0	18.8	53.0	56	12 / 360
375112M	12	22.0	18.8	530	55	12 / 360
375113M	13	26.0	18.8	60.0	77	12 / 240
375114M	14	26.0	18.8	60.0	75	12 / 240
375115M	15	27.0	18.8	60.0	75	12 / 240
375116M	16	32.0	24.7	73.5	152	6 / 96
375117M	17	33.0	24.7	73.5	149	6 / 96
375118M	18	33.0	24.7	73.5	155	6 / 96
375119M	19	33.3	24.7	73.5	152	6 / 96

Combination Swivel Head Socket Wrench

1020

- Slim pattern, with free moving socket wrench
- Sockets can rotate up to 180°
- Metric sizes
- Chrome vanadium steel
- Chrome plated

KING TONY	Size mm	L (mm)	g	
1020-08	8	170	65	10 / 180
1020-09	9	170	65	10 / 180
1020-10	10	180	75	10 / 160
1020-11	11	188	105	10 / 160
1020-12	12	190	114	10 / 120
1020-13	13	206	140	10 / 120
1020-14	14	225	186	10 / 120
1020-15	15	225	195	6 / 72
1020-16	16	234	234	6 / 72
1020-17	17	234	234	4 / 48
1020-18	18	252	307	4 / 48
1020-19	19	250	307	4 / 48

Combination Swivel Head Socket Wrench Set

1B06 MR

	PC./SET	Contents	kg	
1B06MR	6	1020 10 12 13 14 17 19	1.056	1 / 24

Double Swivel End Socket Wrench

1910

- Thin walled heads
- Swivel through a wide radius
- Sockets can rotate up to 180°
- Metric sizes
- Chrome Vanadium Steel
- Chrome plated

KING TONY	Size mm	L (mm)	g	
19100607	6 x 7	182	72	12 / 216
19100809	8 x 9	182	78	12 / 216
19100810	8 x 10	185	85	10 / 160
19101011	10 x 11	200	115	10 / 160
19101012	10 x 12	205	119	10 / 120
19101213	12 x 13	220	155	10 / 120
19101214	12 x 14	225	175	10 / 80
19101415	14 x 15	240	235	10 / 120
19101617	16 x 17	259	330	10 / 80
19101819	18 x 19	275	410	6 / 54
19102022	20 x 22	305	595	4 / 36
19102123	21 x 23	305	640	4 / 32
19102427	24 x 27	335	775	4 / 32

Double Swivel End Socket Wrench Set

1A06 MR

	Contents	kg	
1A06MR	1910 8 x 9 10 x 11 12 x 13 14 x 15 16 x 17 18 x 19	1.32	1 / 16

Slugging Wrench

10A0

- Open end slugging
- Finished with phosphate sunk

KING TONY	Size mm	L (mm)	g	
10A0-24	24	178	302	6 / 72
10A0-27	27	180	320	6 / 72
10A0-30	30	190	400	6 / 60
10A0-32	32	190	418	6 / 60
10A0-36	36	215	600	6 / 24
10A0-41	41	233	902	5 / 20
10A0-46	46	255	1122	4 / 16
10A0-50	50	275	1555	2 / 16
10A0-55	55	298	2015	2 / 12
10A0-60	60	320	2515	1 / 10
10A0-65	65	340	3260	1 / 8
10A0-70	70	370	4390	1 / 5
10A0-75	75	372	4140	1 / 5
10A0-80	80	395	6820	1 / 4
10A0-85	85	395	6300	1 / 4
10A0-90	90	440	9270	1 / 2
10A0-95	95	440	8700	1 / 2
10A0-A0	100	480	10500	1 / 2
10A0-A5	105	480	10300	1 / 2
10A0-B0	110	505	14420	1 / 1
10A0-B5	115	505	14420	1 / 1
10A0-C0	120	510	15450	1 / 1

10B0

- Ring slugging
- Finished with phosphate sunk

KING TONY	Size mm	L (mm)	g	
10B0-24	24	162	239	6 / 72
10B0-27	27	180	247	6 / 72
10B0-30	30	190	354	6 / 72
10B0-32	32	190	404	6 / 60
10B0-36	36	205	499	6 / 36
10B0-41	41	230	658	6 / 24
10B0-46	46	240	886	4 / 16
10B0-50	50	253	1096	4 / 16
10B0-55	55	265	1357	2 / 16
10B0-60	60	280	1654	2 / 12
10B0-65	65	298	1865	2 / 12
10B0-70	70	330	2868	1 / 8
10B0-75	75	330	2984	1 / 8
10B0-80	80	345	3674	1 / 6
10B0-85	85	345	3710	1 / 6
10B0-90	90	380	5850	1 / 4
10B0-95	95	380	5350	1 / 4
10B0-A0	100	410	6445	1 / 4
10B0-A5	105	415	6500	1 / 3
10B0-B0	110	440	6442	1 / 3
10B0-B5	115	440	6500	1 / 3
10B0-C0	120	480	11124	1 / 2

Heavy Duty Offset Ring Wrench

10C0

- Chrome-plated
- To be used with extension tubes item "11"
- Chrome Vanadium Steel

KING TONY	Size mm	L (mm)	g	
10C0-24	24	179.2	450	6 / 48
10C0-27	27	186.4	500	6 / 48
10C0-30	30	194.9	580	4 / 36
10C0-32	32	229.7	810	4 / 24
10C0-36	36	240.6	870	4 / 24
10C0-41	41	259.4	1100	2 / 16
10C0-46	46	275.3	1400	2 / 16
10C0-50	50	285.1	1600	2 / 16
10C0-55	55	296.4	1800	1 / 12
10C0-60	60	341.4	2800	1 / 9
10C0-65	65	351.2	3200	1 / 4

11

- Tubes for item 10C0
- Chrome plated

KING TONY	Size ø mm	L (mm)	Applied to socket sizes	g	
111946	26 x 19	460	10C0-24 (24mm), 10C0-27 (27mm), 10C0-30 (30mm)	1050	20
112261	28 x 22	610	10C0-32 (32mm), 10C0-36 (36mm), 10C0-41 (41mm)	1450	16
112576	32 x 25	760	10C0-46 (46mm), 10C0-50 (50mm), 10C0-55 (55mm)	2400	6
113086	36 x 30	860	10C0-60 (60mm), 10C0-65 (65mm)	2610	4

Double End Socket Wrench

19A0

- Chrome vanadium steel
- Chrome plated

KING TONY	mm	D1 (mm)	D2 (mm)	P1 (mm)	P2 (mm)	L (mm)	g	
19A00607	6x7	10	11	7	7	105	44	30 / 180
19A00809	8x9	13	14	8	8	110	60	30 / 180
19A01011	10x11	15	16	9	9	120	79	24 / 144
19A01213	12x13	18	19	11	11	140	142	18 / 144
19A01415	14x15	20	22	13	13	145	138	12 / 96
19A01617	16x17	23	24	14	14	155	190	10 / 90
19A01819	18x19	25	26	17	17	165	243	8 / 72
19A02022	20x22	28	30	18	18	170	288	8 / 72
19A02123	21x23	29	31	18	18	185	318	6 / 54
19A02426	24x26	33	35	20	20	190	396	4 / 36
19A02528	25x28	34	37	22	22	205	511	4 / 24
19A02729	27x29	37	39	23	23	210	595	2 / 12
19A03032	30x32	40	42	27	27	210	671	2 / 12

Doubleend socket wrench forthe hollow tube design, a long-type screw may be used.

Bar For Double end Socket Wrench

- Chrome vanadium alloy steel
- Chrome plated

KING TONY	L (mm)	ø (mm)	ø1 (mm)	ø2 (mm)	ø3 (mm)	ø4 (mm)	Applied to socket wrench sizes
19A0-09	220	7.8	6.75	4.75	5.75	2.8	19A00607~19A02022
19A0-15	300	12.7	11.75	9.75			19A02123~19A03032

Speed Wrench

Speed Wrench

Metric size from 8 ~ 24 mm

3731

3732

Flexible Speed Wrench

Metric size from 8 ~ 19 mm

3730

Open-Side Speed Wrench

Metric size from 8 ~ 19 mm

3721

Double End Speed Wrench

Metric size from 8 ~ 19 mm

3737

Metric size from 6 to 24 mm

3736

KING TONY		Apply to speed wrench	Function
373202H		10 mm	1/4" Bit
373202R		10 mm	1/4" drive
373203R		13 mm	3/8" drive
373225H		13 mm	5/16" Bit
373204R		19 mm	1/2" drive

Flexible Speed Wrench

3730

- Flexible head, open end and ratchet ring - wrench
- Metric sizes from 8 to 19 mm
- Polished with chrome finish
- 5° gear action (72 teeth)

KING TONY	Size mm	D1	D2	H1	H2	L (mm)	g	
373008M	8	16.2	16.7	4.3	6.5	127.0	40	12 / 384
373009M	9	18.2	18.6	4.6	6.9	131.5	40	12 / 384
373010M	10	20.3	20.0	5.0	7.3	136.0	60	12 / 384
373011M	11	22.5	21.8	5.4	7.7	141.0	60	10 / 320
373012M	12	24.3	23.0	5.8	8.2	147.5	80	10 / 320
373013M	13	26.8	25.2	6.1	8.6	154.0	100	6 / 192
373014M	14	28.7	26.8	6.4	9.0	160.0	100	10 / 200
373015M	15	30.5	28.3	6.9	9.4	169.0	120	10 / 160
373016M	16	32.9	29.8	7.2	9.9	179.0	160	10 / 160
373017M	17	34.5	31.8	7.6	10.3	190.0	180	10 / 160
373018M	18	37.0	32.8	8.0	10.7	203.0	200	10 / 160
373019M	19	39.2	33.9	8.6	11.2	215.0	220	12 / 144

Speed Wrench

3731

- Open end and ratchet ring -wrench
- Metric sizes from 8 to 24 mm
- Polished with chrome finish
- 5° gear action (72 teeth)

KING TONY	Size mm	D1	D2	H1	H2	L (mm)	g	
373108M	8	16.7	17.0	4.0	6.5	140.0	25	12 / 384
373109M	9	18.7	18.6	4.4	6.9	149.0	35	12 / 384
373110M	10	20.8	20.2	4.8	7.3	158.0	40	12 / 240
373111M	11	23.0	22.0	5.2	7.7	165.0	60	12 / 240
373112M	12	24.6	23.4	5.5	8.2	171.0	75	12 / 240
373113M	13	26.8	25.5	5.8	8.6	178.0	80	10 / 160
373114M	14	29.0	26.9	6.2	9.0	190.0	100	10 / 160
373115M	15	31.0	28.3	6.5	9.4	199.0	115	10 / 160
373116M	16	33.0	29.8	6.8	9.9	208.0	135	10 / 160
373117M	17	35.5	31.8	7.2	10.3	225.0	165	6 / 60
373118M	18	37.5	32.7	7.7	10.7	236.0	195	6 / 60
373119M	19	39.4	34.0	8.2	11.2	247.0	225	6 / 60
373121M	21	45.8	40.1	9.0	13.0	287.8	320	6 / 54
373122M	22	45.8	40.1	9.0	13.0	287.8	340	6 / 54
373124M	24	51.8	46.5	10.0	14.5	321.0	475	6 / 54

Speed Wrench

3732

- Combined with 5° open end and ratchet ring - wrench
- Metric sizes from 8 to 24 mm
- Polished with chrome finish
- 5° gear action (72 teeth)
- 2 ways locking design
- Take - up: 13°

KING TONY	Size mm	D1	D2	H1	H2	L (mm)	g	
373208M	8	16.7	16.6	4.6	6.5	140	20	12 / 384
373209M	9	18.8	18.4	4.9	6.9	150	25	12 / 384
373210M	10	20.8	20.0	5.3	7.3	159	40	12 / 240
373211M	11	23.0	21.8	5.6	7.7	165	60	12 / 240
373212M	12	25.0	22.7	6.0	8.2	172	75	12 / 240
373213M	13	27.1	24.7	6.4	8.6	178	95	10 / 160
373214M	14	29.2	27.0	6.8	9.0	191	110	10 / 160
373215M	15	31.3	28.3	7.0	9.4	200	120	10 / 160
373216M	16	33.4	30.0	7.2	9.9	208	160	10 / 60
373217M	17	35.5	31.8	7.7	10.3	226	175	6 / 60
373218M	18	37.6	32.6	8.2	10.7	237	205	6 / 60
373219M	19	39.7	33.8	8.8	11.2	248	220	6 / 60
373221M	21	46.0	40.0	9.0	13.0	290	320	6 / 54
373222M	22	46.0	40.0	9.0	13.0	290	320	6 / 54
373224M	24	52.2	46.0	10.0	14.5	323	465	6 / 54

3736

- Double end wrench
- Metric sizes from 8 to 19 mm
- Polished with chrome finish
- 5° gear action (72 teeth)

KING TONY	Size mm	D1	D2	H1	H2	L (mm)	g	
37360809M	8x9	16.8	20.2	6.5	6.9	128	45	10 / 320
37361011M	10x11	20.2	21.8	7.3	7.7	150	65	10 / 200
37361213M	12x13	23.0	24.8	8.2	8.6	170	100	10 / 200
37361415M	14x15	26.5	29.5	9.0	9.4	190	120	10 / 160
37361618M	16x18	29.5	33.5	9.9	10.7	210	190	10 / 120
37361719M	17x19	31.5	33.5	10.3	11.2	230	210	10 / 120

3737

- Double end speed wrench
- Metric sizes from 6 to 24 mm
- Polished with chrome finish
- 5° gear action (72 teeth)
- 2 ways locking design
- Take - up: 13°

KING TONY	Size mm	D1	D2	H1	H2	L (mm)	g	
37370607M	6x7	14.2	17.2	6.3	6.5	115	36	10 / 320
37370809M	8x9	16.8	20.2	6.5	6.9	128	45	10 / 320
37371011M	10x11	20.2	21.8	7.3	7.7	150	61	10 / 200
37371213M	12x13	23.0	24.8	8.2	8.6	170	90	10 / 200
37371415M	14x15	26.5	29.5	9.0	9.4	190	130	10 / 160
37371618M	16x18	29.5	33.5	9.9	10.7	210	183	10 / 120
37371719M	17x19	31.5	33.5	10.3	11.2	230	209	10 / 120
37372123M	21x23	40.0	46.0	13	14.5	260	408	8 / 64
37372224M	22x24	40.0	46.0	13	14.5	260	397	8 / 64

Open-side Speed Wrench

3721

- Open-side speed wrench
- Torque rating exceeds ANSI specifications by 30% plus
- Made of the highest quality Chrome Vanadium Steel
- The special ratcheting open end design will not slip off the screw when torque is applied.

KING TONY	Size mm / inch	D1	D2	H1	H2	L (mm)	g	
372108M	8	17.8	13.3	5.0	6.0	136.0	38	12 / 384
372110M	10	22.2	16.6	6.0	7.2	161.0	60	12 / 240
372111M	11	25.4	17.5	6.6	7.4	168.0	68	12 / 288
372112M	12	26.3	19.2	7.5	7.9	174.0	83	12 / 288
372113M	13	28.2	20.3	7.9	8.6	180.0	100	10 / 240
372114M	14	31.5	21.3	8.5	9.2	193.0	123	10 / 120
372115M	15	32.8	23.6	8.5	9.7	200.0	143	10 / 120
372116M	16	34.9	23.6	9.0	10.8	207.0	171	10 / 120
372117M	17	37.4	28.1	9.5	10.9	227.0	191	10 / 100
372118M	18	39.0	28.0	9.8	11.2	239.0	220	10 / 100
372119M	19	41.2	29.3	9.8	12.2	250.0	250	10 / 100
372110S	5/16	17.8	13.3	5.0	6.0	136.0	38	12 / 384
372112S	3/8	22.2	16.6	6.0	7.2	161.0	59	12 / 288
372114S	7/16	25.4	17.5	6.6	7.4	168.0	68	12 / 288
372116S	1/2	28.2	20.3	7.9	8.6	180.0	97	10 / 240
372118S	9/16	31.5	21.3	8.5	9.2	193.0	120	10 / 120
372120S	5/8	34.9	25.6	9.0	10.8	207.0	163	10 / 120
372122S	11/16	37.4	28.1	9.5	10.9	227.0	184	10 / 100
372124S	3/4	41.2	29.3	9.8	12.2	250.0	246	6 / 60

Open-side speed wrench

Combination wrench 17mm

Speed Wrench Set

12107 MR
12207 MR

- 7 PC. speed wrench set

	Contents
12107MR	3731
12207MR	3732
	10 11 12 14 15 17 19

12107MR

12207MR

	kg	
12107MR 12207MR	0.91	1/24

12112 MR
12212 MR

- 12 PC. speed wrench set

	Contents
12112MR	3731
12212MR	3732
	8 9 10 11 12 13 14 15 17 19 22 24

12112MR

12212MR

	kg	
12112MR 12212MR	1.95	1/8

Speed Wrench Set

12114 MR
12214 MR

- 14 PC. speed wrench set

		Contents
12114MR	3731	8 9 10 11 12 13 14 15 16 17 18 19 22 24
12214MR	3732	

12114MR

12214MR

	kg	
12114MR 12214MR	2.50	1/12

14111 MR
14108 SR

- Open-side speed wrench set

		PC/SET	Contents
14111MR	3721	11	8 10 11 12 13 14 15 16 17 18 19
14108SR		8	5/16 3/8 7/16 1/2 9/16 5/8 11/16 3/4

14111MR

14108SR

	kg	
14111MR	1.590	1 / 12
14108SR	1.108	1 / 16

12709 MR

- 9 PC. speed wrench set

		Contents
12709MR	3737	6x7 8x9 10x11 12x13 14x15 16x18 17x19 21x23 22x24

12709MR

	kg	
12709MR	1.50	1 / 16

12706 MR

- 6 PC. speed wrench set

		Contents
12706MR	3737	8x9 10x11 12x13 14x15 16x18 17x19

12706MR

	kg	
12706MR	0.72	1 / 16

13012 MR

- 12 PC. flexible speed wrench set

		Contents	kg	
13012MR	3730	8 9 10 11 12 13 14 15 16 17 18 19	2.167	1/6

Speed Wrench Set

13013 MR

- 13 PC. flexible speed wrench set

	Contents	kg	
13013MR	3730: 8 10 12 13 14 16 17 18 19 373202H 373202R 373203R 373204R	1.66	1/8

13113 MR
13213 MR

- 13 PC. speed wrench set

	Contents	
13113MR	3731	8 10 12 13 14 16 17 18 19
13213MR	3732	
	373202H 373202R 373203R 373204R	

13113MR

13213MR

	kg	
13113MR 13213MR	1.64	1/8

91162 MR
91262 MR

- 62 PC. speed wrench set

	Contents				
91162MR	3731: 8 10 12 13 14 16 17 18 19	2375M: E4 E5 E6 E7 E8	1636H: H4 H5 H6 H7 H8 H10 H12	314810M: 373202R	
		3375M: E10 E11 E12	1636M: 5 6 8 10 12		373203R
91262MR	3732: 8 10 12 13 14 16 17 18 19	4375M: E10 E12 E14 E16 E18 E20	1636T 1636U: T10 T15 T20 T25 T27 T30 T40 T45 T50 T55 T60	414810M:	373204R

91162MR

91262MR

	kg	
91162MR 91262MR	12.3	1/4

91168 MR
91268 MR

- 68 PC. speed wrench set

	Contents				
91168MR	3731: 8 9 10 11 12 13 14 15 16 17 18 19 21 22 24	2375M: E4 E5 E6 E7 E8	1636H: H4 H5 H6 H7 H8 H10 H12	314810M: 373202R	
		3375M: E10 E11 E12	1636M: 5 6 8 10 12		373203R
91268MR	3732: 8 9 10 11 12 13 14 15 16 17 18 19 21 22 24	4375M: E10 E12 E14 E16 E18 E20	1636T 1636U: T10 T15 T20 T25 T27 T30 T40 T45 T50 T55 T60	414810M:	373204R

91168MR

91268MR

	kg	
91168MR 91268MR	12.3	1/4

Angled Socket Wrench

1080

- Angle and through-hole design
- High quality steel, chrome plated
- Deep recess at one side and open end socket at the other, easily fit over protruding studs
- ISO 2236

KING TONY	mm	B (mm)	P (mm)	H (mm)	C (mm)	L (mm)	g	
1080-06	6	10.0	7.0	15	29	105	55	12 / 240
1080-07	7	11.5	8.0	15	30	110	60	12 / 240
1080-08	8	12.5	10.0	20	32	120	62	12 / 216
1080-09	9	14.0	10.0	20	33	125	65	12 / 216
1080-10	10	15.0	11.0	20	35	130	100	6 / 60
1080-11	11	16.5	12.0	20	37	135	115	6 / 60
1080-12	12	17.5	12.0	25	40	140	155	6 / 60
1080-13	13	19.0	14.0	25	47	150	180	6 / 60
1080-14	14	20.0	14.0	30	48	160	185	6 / 60
1080-15	15	21.5	15.0	35	50	170	210	6 / 60
1080-16	16	22.5	17.0	35	54	185	285	6 / 60
1080-17	17	24.0	18.0	35	56	195	315	6 / 60
1080-18	18	25.0	19.5	40	58	210	370	4 / 40
1080-19	19	26.5	20.5	40	62	215	425	4 / 40
1080-20	20	27.5	21.5	45	63	220	445	2 / 20
1080-21	21	29.0	23.5	45	65	230	495	2 / 20
1080-22	22	30.0	23.5	45	67	245	530	2 / 16
1080-23	23	31.5	24.5	45	74	255	610	2 / 16
1080-24	24	32.5	24.5	45	77	265	670	2 / 16
1080-25	25	34.0	24.5	50	79	275	780	2 / 16
1080-26	26	35.0	25.5	50	80	285	805	2 / 16
1080-27	27	36.5	27.5	55	84	295	975	2 / 16
1080-28	28	37.5	27.5	55	86	315	1005	2 / 16
1080-29	29	39.0	28.5	65	90	320	1060	2 / 16
1080-30	30	40.0	28.5	65	93	330	1290	2 / 12
1080-32	32	42.5	28.5	65	95	355	1410	2 / 12

6 points

12 points

Angled Socket Wrench Set

1805 MR 1808 MR 1812 MR 1826 MR

	Contents	Pack	PC/SET	kg	
1805MR	10 11 13 14 17	Color box	5	1.12	1/22
1808MR	8 10 11 12 13 14 17 19	Pouch	8	1.73	1/18
1812MR	8 10 11 12 13 14 16 17 18 19 22 24	Pouch	12	4.75	1/4
1826MR	6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 32	Color box	26	15.00	1/2

NEW

1805MR

1826MR

1808MR

1812MR

Angled Socket Wrench

1081

- Angle and through-hole design
- High quality steel, chrome plated
- Deep recess at one side and open end socket at the other, easily fit over protruding studs
- ISO 2236

KING TONY	mm	B (mm)	P (mm)	H (mm)	C (mm)	L (mm)	g	
1081-06	6	10.0	7.0	15	29	105	55	12 / 240
1081-07	7	11.5	8.0	15	30	110	60	12 / 240
1081-08	8	12.5	10.0	20	32	120	62	12 / 216
1081-09	9	14.0	10.0	20	33	125	65	12 / 216
1081-10	10	15.0	11.0	20	35	130	100	6 / 60
1081-11	11	16.5	12.0	20	37	135	115	6 / 60
1081-12	12	17.5	12.0	25	40	140	155	6 / 60
1081-13	13	19.0	14.0	25	47	150	180	6 / 60
1081-14	14	20.0	14.0	30	48	160	185	6 / 60
1081-15	15	21.5	15.0	35	50	170	210	6 / 60
1081-16	16	22.5	17.0	35	54	185	285	6 / 60
1081-17	17	24.0	18.0	35	56	195	315	6 / 60
1081-18	18	25.0	19.5	40	58	210	370	4 / 40
1081-19	19	26.5	20.5	40	62	215	425	4 / 40
1081-20	20	27.5	21.5	45	63	220	445	2 / 20
1081-21	21	29.0	23.5	45	65	230	495	2 / 20
1081-22	22	30.0	23.5	45	67	245	530	2 / 16
1081-23	23	31.5	24.5	45	74	255	610	2 / 16
1081-24	24	32.5	24.5	45	77	265	670	2 / 16
1081-25	25	34.0	24.5	50	79	275	780	2 / 16
1081-26	26	35.0	25.5	50	80	285	805	2 / 16
1081-27	27	36.5	27.5	55	84	295	975	2 / 16
1081-28	28	37.5	27.5	55	86	315	1005	2 / 16
1081-29	29	39.0	28.5	65	90	320	1060	2 / 16
1081-30	30	40.0	28.5	65	93	330	1290	2 / 12
1081-32	32	42.5	28.5	65	95	355	1410	2 / 12

Angled Socket Wrench Set

1912 MR 1926 MR

	Contents	Pack	PC/SET	kg	
1912MR	8 10 11 12 13 14 16 17 18 19 22 24	Nylon Pouch	12	4.75	1/4
1926MR	6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 32	Color box	26	15.00	1/2
1912MRN	8 10 11 12 13 14 16 17 18 19 22 24	Teloron Pouch	12	4.75	1/4

1912MR

1926MR

1912MRN

Angled Socket Wrench

1084
5084

- High quality steel, chrome plated
- Conic profile and thin walled
- Convenient to facilitate the force-depth objects

KING TONY	mm / inch	D1 (mm)	D2 (mm)	H1 (mm)	L1 (mm)	L (mm)	g	
1084-08	8	12.5	14.0	10	88	230	191	12 / 48
1084-09	9	14.0	15.5	10	88	230	191	12 / 48
1084-10	10	15.0	16.5	10	88	230	191	10 / 40
1084-11	11	16.0	17.5	11	88	230	294	10 / 40
1084-12	12	17.4	19.5	12	98	245	311	6 / 30
1084-13	13	18.9	21.0	12	98	245	395	6 / 30
1084-14	14	19.8	22.0	12	98	260	350	6 / 24
1084-15	15	21.7	24.0	13	98	260	391	6 / 24
1084-16	16	22.2	24.5	13	98	260	388	6 / 24
1084-17	17	24.5	27.0	14	98	260	488	6 / 24
1084-18	18	25.5	28.0	15	98	260	567	6 / 24
1084-19	19	27.1	30.0	15	98	260	595	6 / 24
5084-16	1/2	18.9	21.0	23	12	245	320	6 / 30
5084-18	9/16	19.8	22.0	23	12	260	336	6 / 24

Adjustable Wrench

3611

- Chrome vanadium steel
- Polish, phosphate & chrome plated
- Japanesque type
- Metric size-DIN 3117
- Inch size-ANSI / ASME B107.8

KING TONY	mm	H1 (mm)	Overall Length (mm)	g	
3611-06R	20	7	150	125	12 / 108
3611-06P	20	7	150	125	12 / 108
3611-08R	25	8	200	226	12 / 48
3611-08P	25	8	200	226	12 / 48
3611-10R	30	11	250	430	10 / 60
3611-10P	30	11	250	430	10 / 60
3611-12R	35	13	300	680	5 / 40
3611-12P	35	13	300	680	5 / 40
3611-15HR	43	13	356	1485	1 / 20
3611-15HP	43	13	356	1485	1 / 20
3611-18HR	52	18	450	1750	1 / 6
3611-18HP	52	18	450	1750	1 / 6
3611-24HR	62	23	600	3343	1 / 6
3611-24HP	62	23	600	3343	1 / 6

3611P

3611R

3611HP

3611HR

3631-10R

- Chrome vanadium steel Chrome plated
- Magic button to switch ratchet
- function on/off
- Metric size-DIN 3117

KING TONY	mm	Overall Length (mm)	g	
3631-10R	32	250	597	6 / 36

- Ratchet function
- Can be used in limited space
- Comfortable handle
- Easy to operate and save time

3631-10R (TPR + PP)

Adjustable hook spanner wrench

3641 NEW

- Material - CR-V alloy steel
- Capacity:13~180mm
- The joint is equipped with a spring washer to ensure smooth and reliable operation

KING TONY	Size mm	g	
3641-35	13-35	96	12/144
3641-50	35-50	166	12/108
3641-80	50-80	352	10/60
3641-C0	80-120	652	5/30
3641-I0	120-180	1260	4/16

Pipe Wrench

6531

- High quality steel

KING TONY	Size (inch)	A (mm)	L (mm)	g	
6531-10	10	32	229	0.60	1/24
6531-12	12	40	272	0.78	1/24
6531-14	14	55	316	1.05	1/12
6531-18	18	60	405	1.72	1/12
6531-24	24	75	541	3.15	1/6
6531-36	36	90	825	6.28	1/2
6531-48	48	130	1034	9.75	1/2

Special Purpose Wrench

3203

- Strap wrench for oil filter

KING TONY	Capacity (mm)	Total Length (mm)	(inch)	g	
3203	Ø 60~140	223	8-3/4	242	50
3203A0	Ø 60~260	223	8-3/4	300	50

320300

- Strap for 3203

KING TONY	L (mm)	W (mm)	t (mm)	g	
320300	530	16	3.5	43	80

3204

- Chain wrench for oil filter

KING TONY	Capacity (mm)	Total Length (mm)	(inch)	g	
3204	Ø 60~140	225	8-3/4	359	50

Assembling Wheel Nut Wrench

1996

PAT. 192461

- Chrome vanadium alloy steel
- For most car wheel nuts in metric
- Polished, chrome plated

KING TONY	(mm)	(inch)	(inch)	L (mm)	g	
19961721	17 19	13/16"	1/2"	300	1.1	20

Wheel Nut Wrench

1991

- Chrome vanadium alloy steel
- For most car wheel nuts in metric
- Polished, chrome plated
- DIN 3119 ISO 6788

KING TONY	(mm)	(inch)	L (mm)	g	
19911722	17 19 21 22	1/2"	400	1700	6
199104R	19	1/2"	34	84	-

1993

- Chrome vanadium alloy steel
- For most car wheel nuts in metric
- Polished, chrome plated

KING TONY	(mm)	(inch)	L (mm)	g	
19932427	24 27 32	3/4"	700	4333	4

Socket Wrench

1185 M

- Chrome vanadium alloy steel
- T-shaped long arm type
- Standard socket driver
- DIN 475

KING TONY	Size (mm)	ℓ (mm)	L (mm)	g	
118508M	8	200	250	186	10 / 100
118509M	9	200	250	231	10 / 100
118510M	10	200	250	228	10 / 100
118511M	11	200	250	234	10 / 100
118512M	12	250	250	386	10 / 60
118513M	13	250	300	421	10 / 60
118514M	14	250	300	429	10 / 60
118517M	17	300	360	710	6 / 36
118519M	19	300	360	725	6 / 36

Socket Wrench

○ 1184 M

- Chrome vanadium alloy steel
- T-shaped long arm type
- Deep socket driver
- DIN 475

KING TONY	Size (mm)	ℓ (mm)	L (mm)	g	
118406M	6	120	190	53	10 / 40
118407M	7	120	190	73	10 / 40
118408M	8	200	300	212	10 / 40
118409M	9	200	300	307	10 / 40
118410M	10	200	300	317	10 / 40
118411M	11	200	300	327	10 / 40
118412M	12	200	300	328	10 / 40
118413M	13	200	300	333	10 / 40
118414M	14	200	300	345	10 / 40
118417M	17	250	300	602	6 / 24

T-shaped Driver

■ 3511

- Chrome vanadium alloy steel
- 3/8" square drive

KING TONY	ℓ (mm)	L (mm)	g	
3511-06	170	268	325	5 / 30
3511-10	250	268	386	6 / 30

■ 4511

- Chrome vanadium alloy steel
- 1/2" square drive

KING TONY	ℓ (mm)	L (mm)	g	
4511-06	170	268	400	5 / 30
4511-10	250	268	468	6 / 30

T-type Spark Plug Socket

○ 1563

- Chrome vanadium alloy steel
- T-type spark plug socket

KING TONY	Size (mm)	ℓ (mm)	L (mm)	g	
15631612	16	200	300	363	10/40
15631615	16	200	385	400	10/40
15631618	16	200	460	450	10/40
15632112	21	200	300	388	10/40
15632115	21	200	385	438	10/40
15632118	21	200	460	488	10/40

T-type Spark Plug Socket

○ 1566

- Chrome vanadium alloy steel
- T-type universal spark plug socket with magnet

KING TONY	Size (mm)	ℓ (mm)	L (mm)	g	
15661612	16	200	300	400	10/40
15661615	16	200	385	420	10/40
15661618	16	200	460	460	10/40
15662112	21	200	300	420	10/40
15662115	21	200	385	460	10/40
15662118	21	200	460	510	10/40

T-type Universal Joint

■ 3795

- Chrome vanadium alloy steel
- 3/8" drive T-type universal joint

KING TONY	ℓ (mm)	L (mm)	g	
3795-15	200	375	375	10 / 40
3795-18	200	455	425	10 / 40
3795-24	200	600	500	10 / 40
3795-30	200	750	600	10 / 30

■ 4795

- Chrome vanadium alloy steel
- 1/2" drive T-type universal joint

KING TONY	ℓ (mm)	L (mm)	g	
4795-18	200	460	567	10 / 30
4795-24	200	600	700	10 / 30
4795-30	200	750	850	10 / 20
4795-36	200	900	1000	10 / 20

T-type Universal Socket

○ 5722

NEW

- T-type universal socket

KING TONY	SIZE (mm)	ℓ (mm)	L (mm)	g	
572210M	10	150	170	400	10/60
572212M	12	150	170	400	10/60

T-type Universal Socket

5742

- Chrome vanadium alloy steel
- T-type universal socket

KING TONY	SIZE (mm)	ℓ (mm)	L (mm)	g	
574208M	8	200	320	328	10/40
574210M	10	200	320	330	10/40
574212M	12	200	320	332	10/40
574213M	13	200	320	333	10/40
574214M	14	200	320	335	10/40
574217M	17	200	320	340	10/40

5752

- Chrome vanadium alloy steel
- T-type universal socket

KING TONY	SIZE (mm)	ℓ (mm)	L (mm)	g	
575208M	8	200	450	427	10/40
575210M	10	200	450	430	10/40
575212M	12	200	450	432	10/40
575213M	13	200	450	433	10/40
575214M	14	200	450	435	10/40
575217M	17	200	450	440	10/40

5762

- Chrome vanadium alloy steel
- T-type universal socket

KING TONY	SIZE (mm)	ℓ (mm)	L (mm)	g	
576208M	8	200	600	519	10/40
576210M	10	200	600	520	10/40
576212M	12	200	600	522	10/40
576213M	13	200	600	523	10/40
576214M	14	200	600	525	10/40
576217M	17	200	600	540	10/40

5755

- Chrome vanadium alloy steel
- T-type universal socket

KING TONY	SIZE (mm)	ℓ (mm)	L (mm)	g	
575510M	10	200	396	400	10/40
575512M	12	200	400	400	10/40

T-type Universal Socket

5772

- Chrome vanadium alloy steel
- T-type universal socket

KING TONY	SIZE (mm)	ℓ (mm)	L (mm)	g	
577208M	8	200	400	425	10 / 40
577210M	10	200	400	425	10 / 40
577212M	12	200	400	425	10 / 40
577213M	13	200	450	425	10 / 40
577214M	14	200	450	425	10 / 40
577217M	17	200	450	425	10 / 40

5774 NEW

- Chrome vanadium alloy steel
- T-type universal socket

KING TONY	SIZE (mm)	ℓ (mm)	L (mm)	g	
577406M	6	200	390	420	10 / 30
577407M	7	200	390	420	10 / 30
577408M	8	200	390	420	10 / 30
577409M	9	200	390	420	10 / 30
577410M	10	200	500	480	10 / 30
577411M	11	200	500	480	10 / 30
577412M	12	200	500	480	10 / 30
577413M	13	200	500	480	10 / 30
577414M	14	200	500	500	10 / 30
577415M	15	200	500	500	10 / 30
577416M	16	200	500	500	10 / 30
577417M	17	200	500	500	10 / 30
577418M	18	200	500	500	10 / 30
577419M	19	200	500	500	10 / 30

T-type Bit Holder

21A107 NEW

- Applied with power bit

KING TONY	SIZE (inch)	ℓ (mm)	L (mm)	g	
21A107	1/4"	150	175	194	10/60

Pliers

- Combination Pliers
- Long Nose Pliers
- Diagonal Cutting Pliers
- Bent Nose Pliers
- End Cutting Pliers
- Groove Joint Pliers
- Circlip Pliers
- Slip Joint Pliers
- Plastic Pliers
- Cable Cutting Pliers
- Wire Stripping Pliers
- Water Pump Pliers
- Lock-Grip Pliers
- Miniature Long Nose Pliers
- Lock Sheet Metal Grip Pliers
- Lock Chain Grip Pliers
- C-clamp Grip Pliers
- Crimping Tools

KING TONY
KING TONY
KING TONY
KING TONY
KING TONY

KING TONY

Combination Pliers

6111

- European type
- Polished head
- Grip material - PP + TPR
- DIN ISO 5746

KING TONY	L (mm)	L (inch)	Cutting Capacties(mm) Soft wire	Medium hard wire	Hard wire	Piano wire	g	
6111-06	163	6-1/2	4.0	2.8	1.8	1.6	200	8 / 96
6111-07	188	7-1/2	4.0	3.0	2.0	1.6	260	8 / 80
6111-08	213	8-1/4	4.0	3.0	2.0	1.6	340	8 / 72

6112

- Hi-leverage type
- Polished heads

KING TONY	L (mm)	L (inch)	Material	Cutting Capacties(mm) Soft wire	Medium hard wire	Hard wire	Piano wire	g	
6112-09A	225	9	PP+TPR	4.0	3.0	2.2	2.0	359	6 / 60
6112-09C	225	9	PVC	4.0	3.0	2.2	2.0	359	6 / 60

6114

- Mini type
- Grip material - PP + TPR
- DIN ISO 5746

KING TONY	L (mm)	L (inch)	Cutting Capacties(mm) Soft wire	Medium hard wire	Hard wire	g	
6114-05	140	5-1/2	3.0	2.0	1.6	100	8 / 160

Long Nose Pliers

- Grip material - PP +TPR

6311

- European type
- DIN ISO 5745

KING TONY	L (mm)	L (inch)	Cutting Capacties(mm) Soft wire	Medium hard wire	Hard wire	Piano wire	g	
6311-06	163	6-1/2	4.0	2.8	1.8	1.6	150	10 / 120
6311-08	200	8	4.0	3.0	2.0	1.6	220	8 / 80

6313

- Japanese type
- DIN ISO 5745

KING TONY	L (mm)	L (inch)	Cutting Capacties(mm) Soft wire	Medium hard wire	Hard wire	Piano wire	g	
6313-06	163	6-1/2	4.0	2.8	1.8	1.6	140	10 / 100

6314

- Mini type
- DIN ISO 5745

KING TONY	L (mm)	L (inch)	Cutting Capacties(mm) Soft wire	Medium hard wire	Hard wire	g	
6314-05	134	5-1/4	3.0	2.0	1.6	105	8 / 160

Diagonal Cutting Nippers

- Grip material - PP + TPR
- Polished heads

6211

- European type
- DIN 5749

KING TONY	L (mm)	L (inch)	Cutting Capacties(mm) Soft wire	Medium hard wire	Hard wire	Piano wire	g	
6211-06	163	6-1/2	4.0	2.8	2.0	1.6	180	8 / 96

6213

- Japanese type

KING TONY	L (mm)	L (inch)	Cutting Soft wire	g	
6213-06	163	6-1/2	1.25	140	8 / 96

6214

- Mini type

KING TONY	L (mm)	L (inch)	Ø Max.mm Soft wire	g	
6214-45	115	4-1/2	0.6	97	8 / 160
6214-05	127	5	1.25	105	8 / 160

6231

- Heavy duty type
- DIN ISO 5749

KING TONY	L (mm)	L (inch)	Cutting Capacties(mm) Soft wire	Medium hard wire	Hard wire	Piano wire	g	
6231-07	188	7-1/2	5.0	3.5	2.2	2.0	220	8 / 80
6231-08	200	8	4.0	3.0	2.2	2.0	280	8 / 80

Bent Nose Pliers

- Grip material - PP + TPR

6331

- European type
- DIN ISO 5745

KING TONY	L (mm)	L (inch)	Cutting Capacties(mm) Soft wire	Medium hard wire	Hard wire	Piano wire	g	
6331-06	163	6-1/2	4.0	2.8	1.8	1.6	160	10 / 100
6331-08	200	8	4.0	3.0	2.0	1.6	200	8 / 80

6334

- Mini type
- DIN ISO 5745

KING TONY	L (mm)	L (inch)	Cutting Capacties(mm) Soft wire	Medium hard wire	Hard wire	g	
6334-05	127	5	3.0	2.0	1.6	105	8 / 160

End Cutting Pliers

6411

- European type
- Grip material - PP + TPR
- DIN ISO 5748

KING TONY	L (mm)	L (inch)	Cutting Capacties(mm) Soft wire	Medium hard wire	Hard wire	Piano wire	g	
6411-06	163	6-1/2	4.0	3.0	1.6	1.6	240	8 / 80

6431

- European type
- Grip material - PVC
- DIN ISO 9242

KING TONY	L (mm)	L (inch)	Cutting Capacties(mm) Soft wire	Medium hard wire	Hard wire	g	
6431-10	254	10	3.0	2.0	1.6	445	6 / 48
6431-11	278	11	3.0	2.2	1.8	510	6 / 48

Groove Joint Pliers

6511

- 7 positions opening
- DIN ISO 8976

6511-10A

6511C

KING TONY	A (mm)	B (mm)	L (mm)	L (inch)	(mm)	g	
6511-10A	33	50	253	10	50	400	6 / 48
6511-10C	33	50	253	10	50	400	6 / 48
6511-13C	43	50	325	13	65	808	2 / 16
6511-17C	58	55	425	17	100	1150	2 / 12

6516

- German type
- 7 positions opening
- Grip material - PVC
- DIN ISO 8976

KING TONY	L (mm)	L (inch)	(mm)	g	
6516-10	253	10	36	300	8 / 64

Stripping Pliers

6711

- With spring and adjusting screw

KING TONY	L (mm)	L (inch)	Ø mm	g	
6711-06	155	6	5	160	8 / 80

Circlip Pliers

67HS & 67HB
68HS & 68HB

- For internal retaining rings
- Straight and angled pattern
- DIN 5254 & DIN 5256

KING TONY	Overall Length (mm)	(inch)	Ø- tips	Capacity Ø mm	g	
67HS-07	180	7	1.8	20~62	130	12 / 144
67HB-07	180	7	1.8	20~62	130	12 / 144
68HS-05	125	5	1.3	12~28	126	10 / 80
68HS-07	180	7	1.8	20~62	130	12 / 144
68HS-10	250	10	2.3	40~100	291	8 / 64
68HB-05	125	5	1.3	12~28	119	10 / 80
68HB-07	170	6-3/4	1.8	20~62	130	12 / 144
68HB-10	241	9-1/2	2.3	40~100	291	6 / 48

67HS 67HB 68HS 68HB

Japanese type European type

67SS & 67SB
68SS & 68SB

- For external retaining rings
- Straight and angled pattern
- DIN 5254 & DIN 5256

KING TONY	Overall Length (mm)	(inch)	Ø- tips	Capacity Ø mm	g	
67SS-07	180	7	1.8	20~62	130	12 / 144
67SB-07	180	7	1.8	20~62	130	12 / 144
68SS-05	125	5	1.3	12~28	126	10 / 80
68SS-07	180	7	1.8	20~62	130	12 / 144
68SS-10	250	10	2.3	40~100	291	8 / 64
68SB-05	125	5	1.3	12~28	119	10 / 80
68SB-07	170	6-3/4	1.8	20~62	130	12/ 144
68SB-10	241	9-1/2	2.3	40~100	291	6 / 48

67SS 67SB 68SS 68SB

Japanese type European type

Slip Joint Pliers

6463

- 2 position adjustment
- Serrated jaws

KING TONY	L (mm)	(inch)	g	
6463-08C	210	8	290	8 / 80

6463-08C

Plastic Pliers

6921

- European type
- Polished heads
- CAUTION : In order to get normal life of plier, do not cut steel wire.

KING TONY	L (mm)	(inch)	Grip Material	g	
6921-05A	132	5	PP + TPR	89	6 / 120
6921-06A	155	6	PP + TPR	132	8 / 96
6921-07A	178	7	PP + TPR	170	6 / 60
6921-05C	132	5	PVC	89	6 / 120
6921-06C	155	6	PVC	132	6 / 60
6921-07C	178	7	PVC	170	6 / 60

6921A

6921C

Circlip Pliers Set

42114GP

KING TONY	PC./SET	Contents	kg	
42114GP	4	68HS-07, 68HB-07, 68SS-07, 68SB-07	0.62	1/32

42116GP

KING TONY	PC./SET	Contents	kg	
42116GP	6	68HS-07, 68HB-07, 68HS-10, 68SS-07, 68SB-07, 68SS-10	1.33	1/18

European Type Pliers Set

42104GP

KING TONY	PC./SET	Contents	kg	
42104GP	4	6111-06, 6211-06, 6311-08, 6511-10A	1.17	1/18

42104GP01

KING TONY	PC./SET	Contents	kg	
42104GP01	4	6111-06, 6211-06, 6311-08, 6516-10	1.17	1/18

Insulated Pliers

1000V

Combination Pliers(European type)

- Grip material-TPR.
- Polished heads.

6116-07A / 6116-08A

- Chrome vanadium steel
- IEC DIN EN 60900

KING TONY	L (mm)	L (inch)	Cutting Capacties(mm) Soft wire	Medium hard wire	Hard wire	Piano wire	g	
6116-07A	185	7-1/2	4.0	3.0	2.0	1.6	290	10 / 60
6116-08A	200	8	4.0	3.0	2.0	1.6	386	10 / 60

Long Nose Pliers

- Grip material-TPR.
- Polished heads.

6318-08A

- Chrome vanadium steel
- IEC DIN EN 60900

KING TONY	L (mm)	L (inch)	Cutting Capacties(mm) Soft wire	Medium hard wire	Hard wire	Piano wire	g	
6318-08A	210	8-1/4	4.0	3.0	2.0	1.6	250	10 / 60

Diagonal Cutting Pliers

- Grip material-TPR.
- Polished heads.

6216-06A

- Chrome vanadium steel
- IEC DIN EN 60900

KING TONY	L (mm)	L (inch)	Cutting Capacties(mm) Soft wire	Medium hard wire	Hard wire	Piano wire	g	
6216-06A	167	6-1/2	4.0	2.8	2.0	1.6	230	10 / 60

Diagonal Cutting Pliers(Heavy Duty)

- Grip material-TPR.
- Polished heads.

6236-07A

- Chrome vanadium steel
- IEC DIN EN 60900

KING TONY	L (mm)	L (inch)	Cutting Capacties(mm) Soft wire	Medium hard wire	Hard wire	Piano wire	g	
6236-07A	190	7-1/2	5.0	3.5	2.2	2.0	280	10 / 60

Bent Nose Pliers

1000V

- Grip material-TPR.
- Polished heads.

6336-08A

- Chrome vanadium steel
- IEC DIN EN 60900

KING TONY	L (mm)	L (inch)	Cutting Capacties(mm) Soft wire	Medium hard wire	Hard wire	Piano wire	g	
6336-08A	200	8	4.0	3.0	2.0	1.6	250	10 / 60

Cable Cutting Pliers

- Grip material-TPR.
- Polished heads.

6146-08A

- Chrome vanadium steel
- IEC DIN EN 60900

KING TONY	L (mm)	L (inch)	(mm) Ø mm	g	
6146-08A	214	8-1/4	14	360	10 / 60

Wire Stripping Pliers(With Spring)

- Grip material-TPR.
- Polished heads.

6716-06A

- Chrome vanadium steel
- IEC DIN EN 60900

KING TONY	L (mm)	L (inch)	Ø mm	g	
6716-06A	160	6-1/4	5	205	10 / 60

Water Pump Pliers(Box Joint)

- Grip material-TPR.
- Polished heads.

6516-10A

- Chrome vanadium steel
- IEC DIN EN 60900

KING TONY	L (mm)	L (inch)	(mm)	g	
6516-10A	250	10	36	420	10 / 50

Lock - Grip Pliers

- MATERIAL - chrome molybdenum alloy steel
- FINISHING - option 1 : chrome plated (R)
  option 2 : nickel plated (N)

6011

- Curved jaw with wire cutter
- With adjusting screw and release lever
- Jaw width 10mm, length 30mm
- ASME B107.24

KING TONY	Overall Length (mm)	(inch)	Jaw Capacity (mm)	g	
6011-05R	140	5-1/2	29	166	6 / 48
6011-07R	185	7	38	367	8 / 32
6011-07N	185	7	38	367	8 / 32
6011-10R	225	9	48	542	8 / 32
6011-10N	225	9	48	542	8 / 32

6011R

6011N

6031

- Straight jaw
- With adjusting screw and release lever
- Jaw width 10mm, length 30mm
- ASME B107.24

KING TONY	Overall Length (mm)	(inch)	Jaw Capacity (mm)	g	
6031-07R	185	7	33	392	8 / 32
6031-07N	185	7	33	392	8 / 32
6031-10R	225	9	45	573	8 / 32
6031-10N	225	9	45	573	8 / 32

6031R

6031N

Miniature Long Nose Pliers

6315

- ASME B107.24

KING TONY	Overall Length (mm)	(inch)	Jaw Capacity (mm)	g	
6315-06	165	6	51	205	8 / 64
6315-09	221	9	70	393	36

6315

Lock Sheet Metal Grip Pliers

6605

- Material-chrome molybdenum alloy steel.
- Finishing-nickel plated.
- With adjusting screw and release lever
- Makes bending, forming, and crimping sheet metal easier.

KING TONY	Overall Length (mm)	(inch)	Jaw Capacity (mm)	g	
6605-08	206	8	13	455	1/18

6605

Lock Chain Grip Pliers

6655-09

- Chain can hold around any shape or size.
- Convenient for awkwardly shaped pieces.
- With adjusting screw and release lever.

KING TONY	Total Length (mm)	(inch)	Capacity (mm)	g	
6655-09	225	9	Ø 60~140	733	1/18

6665-09

- U-shaped jaws allow enhanced visibility and more working space
- Holds work in proper alignment
- For use in welding or holding awkward shapes in place

KING TONY	Total Length (mm)	(inch)	Jaw Capacity (mm)	g	
6665-09	230	9	43	625	1/18

C-clamp Grip Pliers

6615

6615-06

6615-11

KING TONY	Total Length (mm)	(inch)	Jaw Capacity (mm)	g	
6615-06	170	6-3/4	50	230	6 / 72
6615-11	280	11	100	790	1/20
6615-18	456	18	200	1136	1/10

6615-18

6625

- C-clamp grip pliers with moving jaw

6625-06

6625-11

KING TONY	Total Length (mm)	(inch)	Jaw Capacity (mm)	g	
6625-06	175	7	54	250	6 / 72
6625-11	280	11	96	840	1/20
6625-18	467	18-1/2	200	1220	1/10

6625-18

Crimping Tools

6721-10

- Wire cutter.
- Crimps insulated terminals.
- Bolt cutter.
- Crimps non-insulated terminals.(Open barrel)
- Wire stripper.

FUNCTION:

Wire cutter

Open barrel terminal crimping

Non-Insulated terminal Crimping

Bolt-cutter

Insulated terminal Crimping

Wire stripper

KING TONY	Wire cutter Ø mm²	Insulated terminal Crimping	Bolt-cutter	Non insulated terminal crimp	Open barrel terminal crimping	Wire stripper mm²		
6721-10	6	0.5~6	M2.6~5	0.5~6	1.5~6	0.75~6.0	248	5 / 50

6731-09

- Wire cutter.
- Crimps insulated terminals.
- Bolt cutter.
- Crimps non-insulated terminals.
- Wire stripper.

FUNCTION:

Wire cutter

Insulated terminal Crimping

Bolt-cutter

Wire stripper

Open barrel terminal crimping

KING TONY	Wire cutter Ø mm²	Insulated terminal Crimping	Bolt-cutter	Open barrel terminal crimping	Wire stripper mm²		
6731-09	6	1.5~6	M2.6~5	1.5~6	0.75~6.0	230	5 / 50

6741-06

- Wire cutter.
- Wire stripper.

FUNCTION:

Wire cutter

Wire stripper

Peel the electric wire's shell

KING TONY	Wire cutter Ø mm²	Wire stripper mm²		
6741-06	6	0.5~5.5	103	10 / 100

Snips & Cutter

- Aviation Tin Snips
- Offset Tin Snips
- Figure Tin Snips
- Offset Tin Snips
- Straight Pattern Snips
- Duckbill Circular Pattern Snips
- Steel Strap Cutter
- Electrician Scissors
- Bolt Cutter
- Automatically Reloading Utility Cutter
- Ratchet Tubing Cutter

KING TONY

Aviation Tin Snips

74010~74060

- Drop forged chorme molybdenum alloy steel.
- Blades with serrated edges.
- Perfect for professional user.
- Cuts up to 1.2mm rolled steel or 0.7mm stainless steel.
- Induction hardened cutting edges 59-62 HRC.
  - Special laborsaving design
  - High tensile strength provided for longer life
  - High torsional strength spring designed for longer life
  - Solid and comfortable handle with non-slip design
  - Hang-up hole provided for convenient storage
  - Safety auto latch (D.PAT.)

74010

74020

74030

74040

74060

KING TONY	Overall Length (mm)	Cutting Length (mm)	Color of Handle	Cutting Capacities (mm) Copper (soft)	Cold-rolled Steel (soft)	Hard Steel HRC 30 (Hard)	Stainless Steel304		
74010	248	35	Red	1.50	1.20	0.80	0.70	375	6 / 48
74020	248	35	Green	1.50	1.20	0.80	0.70	375	6 / 48
74030	250	38	Yellow	1.50	1.20	0.80	0.70	380	6 / 48
74040	230	25	Yellow	2.00	1.60	1.20	1.20	370	6 / 36
74060	290	75	Orange	1.10	0.94	0.70	0.53	450	6 / 36

Offset Tin Snips

74150~74160

- Offset blades keep hands away from metal.
- Unique design for professional users.
- Drop forged chrome molybdenum alloy steel blades with serrated edges.
- Induction hardened cutting edges 59-62 HRC.
- Cuts up to 1.2mm cold rolled steel or 0.7mm stainless steel.

74150

74160

KING TONY	Overall Length (mm)	Cutting Length (mm)	Color of Handle	Cutting Capacities (mm) Copper (soft)	Cold-rolled Steel (soft)	Hard Steel HRC 30 (Hard)	Stainless Steel304		
74150	235	35	Red	1.50	1.20	1.00	0.70	4	6 / 48
74160	235	35	Blue	1.50	1.20	1.00	0.70	4	6 / 48

Figure Tin Snips

74250~74270

- Superior cutting performance.
- Popular in Europe.
- Features high - impact handle with fixed handle open width.
- Drop froged chrome molybdenum alloy steel blades with serrated edges.
- Induction hardened cutting edges 59-62 HRC.
- Cuts up to 1.5mm cold rolled steel or 0.9mm stainless steel.
  - Special laborsaving design
  - High tensile strength provided for longer life
  - High torsional strength spring designed for longer life
  - Solid and comfortable handle with non-slip design
  - Hang-up hole provided for convenient storage
  - Safety auto latch (D.PAT.)

74250

74260

74270

KING TONY	Overall Length (mm)	Cutting Length (mm)	Color of Handle	Cutting Capacities (mm)					
				Copper (soft)	Cold-rolled Steel (soft)	Hard Steel HRC 30 (Hard)	Stainless Steel304		
74250	260	35	Red	1.80	1.50	1.00	0.90	480	6 / 36
74260	260	35	Blue	1.80	1.50	1.00	0.90	480	6 / 36
74270	260	35	Yellow	1.80	1.50	1.00	0.90	480	6 / 36

Offset Tin Snips

74350~74360

- Offset blades keep hands away from metal.
- Superior cutting performance.
- Popular in Europe.
- Features high - impact handle with fixed handle open width.
- Drop froged chrome molybdenum alloy steel blades with serrated edges.
- Induction hardened cutting edges 59-62 HRC.
- Cuts up to 1.5mm cold rolled steel or 0.9mm stainless steel.
  - Special laborsaving design
  - High tensile strength provided for longer life
  - High torsional strength spring designed for longer life
  - Solid and comfortable handle with non-slip design
  - Hang-up hole provided for convenient storage
  - Safety auto latch (D.PAT.)

74350

74360

KING TONY	Overall Length (mm)	Cutting Length (mm)	Color of Handle	Cutting Capacities (mm)					
				Copper (soft)	Cold-rolled Steel (soft)	Hard Steel HRC 30 (Hard)	Stainless Steel304		
74350	260	32	Red	1.80	1.50	1.00	1.00	520	6 / 36
74360	260	32	Blue	1.80	1.50	1.00	1.00	520	6 / 36

Straight Pattern Snips

74407~74416

- American type.
- Popular for American & Asian users.
- One - piece forged construction.
- Cushion handle with smooth, comfortable bows for ease in use and safety.
- Designed for cutting straight and wide curves to the left or right.
- Drop forged of high carbon steel.
- Indction hardened cutting edges 58 - 61 HRC.

74407 ~ 74416

	Overall Length (mm)	Cutting Length (mm)	Color of Handle	Cutting Capacities (mm)					
				Copper (soft)	Cold-rolled Steel (soft)	Hard Steel HRC 30 (Hard)	Stainless Steel304		
74407	178	40	Black	0.60	0.56	0.40	0.38	270	10 / 60
74408	203	40	Black	0.70	0.61	0.50	0.41	340	6 / 48
74410	254	51	Black	0.94	0.78	0.60	0.45	480	6 / 36
74412	305	70	Black	1.15	0.91	0.70	0.63	650	6 / 24
74414	356	76	Black	1.41	1.20	1.00	0.70	780	6 / 24
74416	415	63	Black	2.00	1.60	1.20	1.00	1700	3 / 12

Offset Tin Snips

74508~74514

- British type.
- Popular in British Confederation countries & Asia.
- One - piece forged construction.
- Comfortable vinyl coated handles.
- Drop forged of high carbon steel.
- Induction hardened cutting edges 58 - 61 HRC.

74508 ~ 74514

	Overall Length (mm)	Cutting Length (mm)	Color of Handle	Cutting Capacities (mm)					
				Copper (soft)	Cold-rolled Steel (soft)	Hard Steel HRC 30 (Hard)	Stainless Steel304		
74508	203	42	Blue	0.70	0.61	0.50	0.41	330	6 / 48
74510	245	52	Blue	0.94	0.78	0.60	0.45	440	6 / 36
74512	305	60	Blue	1.15	0.91	0.70	0.63	670	6 / 24
74514	356	65	Blue	1.40	1.20	100	0.70	920	6 / 24

Duckbill Circular Pattern Snips

74607~74613

- American type.
- Popular for American & Asian users.
- One - piece forged construction.
- Cushion handle with smooth, comfortable bows for ease in use and safety.
- Designed for cutting straight and wide curves to the left or right.
- Drop forged of high carbon steel.
- Indction hardened cutting edges 58 - 61 HRC.

74607 ~ 74613

KING TONY	Overall Length (mm)	Cutting Length (mm)	Color of Handle	Cutting Capacities (mm)					
				Copper (soft)	Cold-rolled Steel (soft)	Hard Steel HRC 30 (Hard)	Stainless Steel304	g	
74607	178	40	Blue	0.60	0.54	0.38	0.38	250	10 / 60
74610	254	51	Blue	0.94	0.61	0.45	0.45	460	6 / 36
74613	330	72	Blue	1.20	0.84	0.61	0.61	720	6 / 24

Steel Strap Cutter

74900

- One - piece forged construction.
- Durable vinyl coated handles.
- Drop forged of high carbon steel.
- Induction hardened cutting edges 58-61 HRC.
- Cuts up to 28mm in width, 0.8mm in thickness.

74900

KING TONY	Overall Length (mm)	Cutting Length (mm)	Color of Handle	Cutting Capacities (mm)					
				Copper (soft)	Cold-rolled Steel (soft)	Hard Steel HRC 30 (Hard)	Stainless Steel304	g	
74900	305	32	Red	-	1.00	0.80	0.60	750	6 / 24

Electrician Scissors

- Grip material - PP + TPR

6AB12-55

- Electronic scissors

KING TONY	Overall Length (mm)	(mm)	Cutting Capacities (mm)							g	
			Electric Cable	Cardboard	Rubber	Leather	Rolled Steel	Copper (soft)	Aluminum		
6AB12-55	145	55	10	10	10	10	0.5	0.5	0.5	94	12 / 72

Utility Cutter

7971-07

KING TONY	L (mm)	g	
7971-07	165	180	12 / 72

- Automatically reloading snap-off blades.
- Ergonomic soft ABS TPR handle.
- Stainless steel blade guide.
- Blade lock knob.
- 4-blade cartridge(18mm).

7971-07P02
(18mm, 10 PC.)

• Blade reloading automatically

• Knob-lock mechanism

• Blade snapped

Utility Cutter

7976-65 NEW

KING TONY	L (mm)	g	
7976-65	165	82	8 / 64

• Operation:

• Knob-lock mechanism

• Blade snapped

Bolt Cutter

6131

● GS / TUV

- Chrome vanadium alloy steel
- Center cut

KING TONY	Total Length (mm)	(inch)	Capacity materials (mm)	kg	
6131-12	300	12	5	0.76	1/20
6131-14	350	14	7	1.00	1/20
6131-18	450	18	8	1.51	1/12
6131-24	600	24	10	2.35	1/10
6131-30	750	30	13	3.75	1/6
6131-36	900	36	16	5.50	1/5
6131-42	1050	42	18	8.56	1/3

6131P01

- Spare blade for 6131
- Center cut

KING TONY	Total Length (mm)	(inch)	Capacity materials (mm)	kg	
6131-12P01	95 x 57	12	4~5	0.26	40
6131-14P01	110 x 65	14	5~7	0.40	40
6131-18P01	125 x 72	18	6~8	0.85	20
6131-24P01	150 x 86	24	8~10	0.87	20
6131-30P01	170 x 97	30	9~13	1.25	10
6131-36P01	190 x 112	36	11~16	1.85	10
6131-42P01	205 x 122	42	13~18	3.10	5

Ratchet Tubing Cutter

7912-21&7912-22

EASY OPERATION

● Use standard hex key to remove back-up blade located in the handle base.

● Deploy foldable reamer provided to smoothen sharp edges.

1. Place tube securely between cutter jaws.

2. Rotate clock-wise to tighten jaw grip.

3. Pull knob out, down & release in a single action to start cutting procedure.

4. Repeat "Up & Down" action until open face up.

5. Tighten tool around the tube when needed. Repeat each actions until tube is cut.

7912-21 / 7912-22

ADDED VALUE:

- Comes with spare blade.
- Provided with foldable reamer.

INNOVATIVE FEATURES:

- Cuts without having to rotate tool completely around tubing.
- Ratchet mechanism allows for tight area operation.
- Cuts through some of the toughest surfaces: stainless steel, wall conduit, copper and aluminum.
- Exclusive one hand operation. Limited risks of hand-fatigue and injuries.

KING TONY	CAPACITY O (mm)	Max. Cutting Thickness(mm) Stainless	Other	DESCRIPTION	g		Remark: w / blades
7912-21	8-28.5	2	3.0	w/o reamer, w / blades	389	1 / 40	with spare blades
7912-22	12-35	2	3.0	w / blades	452	1 / 40	

Ratchet Tubing Cutter

7912-23

EASY OPERATION

1. Place tube securely between cutter jaws.

2. Rotate clock-wise to tighten jaw grip.

3. Pull knob out, down & release in a single action to start cutting procedure.

4. Repeat "Up & Down" action until open face up.

5. Tighten tool around the tube when needed. Repeat each actions until tube is cut.

- **INNOVATIVE FEATURES:**
  Cuts without having to rotate tool completely around tubing.
- Ratchet mechanism allows for tight area operation.
  Cuts through some of the toughest surfaces:
- stainless steel, wall conduit, copper and aluminum.
- Exclusive one hand operation.
- Limited risks of hand-fatigue and injuries.
  Apply to cut car's exhaust pipe.

7912-23

KING TONY	CAPACITY O (mm)	Max. Cutting Thickness(mm)			
		Stainless	Other		
7912-23	32-67	2	3.0	1122.6	1 / 10

Notes

Screwdriver & Key

- Screwdriver & Set
- Heavy Duty Screwdriver
- Nutspinner
- Power Bits
- Screwdriver Handle
- Insulated Screwdriver & Set
- Precision Screwdriver & Set
- Bit & Set
- Bit Accessory
- Bicycle Tool Set
- Hex Key Wrench & Set
- Ball Hex Key Wrench & Set
- Star L-wrench & Set
- L-type Wrench & Set
- T-type Wrench

& Bit

Standard Screwdriver

- SHANK MATERIAL - CR - V alloy steel
- GRIP MATERIAL - PVC
- FINISHING - chrome plated
  It is used in the working environment less than 60° C

⊕ 1411

- PHILLIPS head, round shank.
- Metric size-DIN ISO 8764

KING TONY	⊕No.	Ø x L (mm)	Ø x L (inch)	g	
14110003	0	3 x 75	1/8 x 3	40	12 / 240
14110104	1	5 x 100	3/16 x 4	52	12 / 240
14110214	2	6 x 38	1/4 x 1-1/2	38	12 / 144
14110204	2	6 x 100	1/4 x 4	74	12 / 96
14110204-E*	2	6 x 100	1/4 x 4	109	12 / 96
14110205-E*	2	6 x 125	1/4 x 5	113	12 / 144
14110206	2	6 x 150	1/4 x 6	95	12 / 144
14110206-E*	2	6 x 150	1/4 x 6	119	12 / 144
14110208-E*	2	6 x 200	1/4 x 8	137	12 / 144
14110306	3	8 x 150	5/16 x 6	132	12 / 144
14110308	3	8 x 200	5/16 x 8	151	12 / 144

* Enlarged handle

1411

8781013KT applied to 14110003, 14110104, 14110214, 14110204, 14110206

8781032KT applied to 14110204-E*, 14110206-E*, 14110208-E*, 14110306, 14110308

⊖ 1412

- SLOTTED head, round shank.
- Metric size-DIN ISO 2380

KING TONY	W x L (mm)	T x Ø (mm)	W x L (inch)	g	
14120303	3.0 x 75	0.5 x 3	1/8 x 3	36	12 / 240
14120404	4.0 x 100	0.8 x 4	5/32 x 4	42	12 / 240
14125504	5.5 x 100	0.8 x 5	7/32 x 4	60	12 / 240
14126514	6.5 x 38	1.2 x 6	1/4 x 1-1/2	39	12 / 144
14126504	6.5 x 100	1.2 x 6	1/4 x 4	60	12 / 96
14126504-E*	6.5 x 100	1.2 x 6	1/4 x 4	108	12 / 96
14126506	6.5 x 150	1.2 x 6	1/4 x 6	85	12 / 144
14126506-E*	6.5 x 150	1.2 x 6	1/4 x 6	117	12 / 144
14120806	8.0 x 150	1.2 x 8	5/16 x 6	130	12 / 144
14120808	8.0 x 200	1.2 x 8	5/16 x 8	152	12 / 144

* Enlarged handle

1412

8781013KT applied to 14120303, 14120404, 14125504, 14126514, 14126504, 14126506

8781032KT applied to 14126504-E*, 14126506-E*, 14120806, 14120808

⊕⊖ 2411

- Two-way screwdriver hex shank

KING TONY	⊕ No.	W (mm)	T (mm)	L (mm)	L (inch)	g	
24110204	2	7.0	1.2	100	4	74	20 / 160
24110214	2	7.0	1.2	38	1-1/2	42	20 / 240

24110204

24110214

8781032KT applied to 24110204

Standard Screwdriver

- SHANK MATERIAL- SNCM + V alloy steel
- GRIP MATERIAL - PP +TPR
- FINISHING - chrome plated with black tip

⊕ 1421

- PHILLIPS head, round shank.
- Metric size-DIN ISO 8764

KING TONY	⊕ No.	ØxL (mm)	ØxL (inch)	g	
14210023	0	3.2 x 60	1/8 x 2-3/8	35	12 / 144
14210132	1	4.5 x 80	3/16 x 3-1/8	43	12 / 96
14210104	1	4.5 x 100	3/16 x 4	52	12 / 96
14210214	2	6.0 x 38	1/4 x 1-1/2	38	12 / 144
14210204	2	6.0 x 100	1/4 x 4	74	12 / 96
14210206	2	6.0 x 150	1/4 x 6	95	12 / 144
14210306	3	8.0 x 150	5/16 x 6	132	12 / 144

1421

8781013KT applied to 14210023, 14210132, 14210104, 14210204, 14210206
8781032KT applied to 14210306

⊖ 1422

- SLOTTED head, round shank.
- Metric size-DIN ISO 2380

KING TONY	WxL (mm)	TxØ (mm)	WxL (inch)	g	
14220303	3.0 x 75	0.5 x 3	1/8 x 3	36	12 / 144
14220404	4.0 x 100	0.8 x 4	5/32 x 4	42	12 / 96
14220503	5.0 x 75	0.8 x 5	3/16 x 3	40	12 / 96
14220504	5.0 x 100	0.8 x 5	3/16 x 4	45	12 / 96
14225503	5.5 x 75	1.0 x 5	7/32 x 3	50	12 / 96
14225504	5.5 x 100	1.0 x 5	7/32 x 4	60	12 / 96
14225505	5.5 x 125	1.0 x 5	7/32 x 5	70	12 / 144
14225506	5.5 x 150	1.0 x 5	7/32 x 6	80	12 / 144
14226514	6.5 x 38	1.2 x 6	1/4 x 1-1/2	39	12 / 144
14226504	6.5 x 100	1.2 x 6	1/4 x 4	60	12 / 96
14226506	6.5 x 150	1.2 x 6	1/4 x 6	85	12 / 144
14220806	8.0 x 150	1.2 x 8	5/16 x 6	130	12 / 144
14220807	8.0 x 175	1.2 x 8	5/16 x 7	141	12 / 144
14220808	8.0 x 200	1.2 x 8	5/16 x 8	152	12 / 144

1422

8781013KT applied to 14220303, 14220404, 14225503, 14220504, 14225503, 14225504, 14225505, 14225506, 14225504, 14226506, 14220806, 14220807, 14220808
8781032KT applied to 14220806, 14220807, 14220808

Extra long shank screwdriver

⊕ PHILLIPS head

KING TONY	⊕ No.	ØxL (mm)	ØxL (inch)	g	
14210112	1	4.5 x 300	3/16 x 12	80	12 / 96
14210212	2	6.0 x 300	1/4 x 12	127	12 / 96
14210116	1	4.5 x 400	3/16 x 16	93	12 / 96
14210216	2	6.0 x 400	1/4 x 16	150	12 / 96

1421xx12
1421xx16

⊖ SLOTTED head

KING TONY	WxL (mm)		TxØ (mm)	WxL (inch)	g	
14220512	5.0	300	0.8 x 5	3/16 x 12	105	12 / 96
14226512	6.5	300	1.2 x 6	1/4 x 12	127	12 / 96
14220516	5.0	400	0.8 x 5	3/16 x 16	121	12 / 96
14226516	6.5	400	1.2 x 6	1/4 x 16	150	12 / 96

1422xx12
1422xx16

Standard Screwdriver

- SHANK MATERIAL - SNCM + V alloy steel
- GRIP MATERIAL - PP + TPR
- FINISHING - chrome plated with black tip

1423

- For TORX head screws, round shank.

KING TONY	Size	Ø x L (mm)	Ø x L (inch)	g	
14230803	T8	3.2 x 75	5/32 x 3	49	12 / 144
14230903	T9	3.2 x 75	5/32 x 3	49	12 / 144
14231003	T10	3.2 x 75	5/32 x 3	49	12 / 144
14231503	T15	4.0 x 75	3/16 x 3	55	12 / 144
14232004	T20	5.0 x 100	3/16 x 4	53	12 / 144
14232504	T25	6.0 x 100	1/4 x 4	83	12 / 144
14232704	T27	6.0 x 100	1/4 x 4	83	12 / 144
14233005	T30	6.0 x 125	1/4 x 5	89	12 / 144
14234006	T40	8.0 x 150	5/16 x 6	142	12 / 144

1423

8781013KT applied to 14230803, 14230903, 14231003, 14231503, 14232004, 14232504, 14232704, 14233005
8781032KT applied to 14234006

1424

- SQUARE head
- Metric size

KING TONY	No.	Ø x L (mm)	g	
14240105	1	5.0 x 125	64	20 / 240
14240204	2	6.0 x 100	87	12 / 144
14240206	2	6.0 x 150	102	12 / 144

1424

1427

- For TORX head screws, round shank.
- Tamper resistant type

KING TONY	Size	Ø x L (mm)	Ø x L (inch)	g	
14270803	T8	3.2 x 75	1/8 x 3	49	12 / 144
14270903	T9	3.2 x 75	1/8 x 3	49	12 / 144
14271003	T10	3.2 x 75	1/8 x 3	49	12 / 144
14271503	T15	4.0 x 75	5/32 x 3	55	12 / 144
14272004	T20	5.0 x 100	3/16 x 4	53	12 / 144
14272504	T25	5.0 x 100	3/16 x 4	83	12 / 144
14272704	T27	6.0 x 100	1/4 x 4	83	12 / 144
14273005	T30	6.0 x 125	1/4 x 5	89	12 / 144
14274006	T40	8.0 x 150	5/16 x 6	142	12 / 144

1427

8781013KT applied to14270803, 14270903, 14271003, 14271503, 14272004, 14272504, 14272704, 14273005
8781032KT applied to 14274006

1428

- POZIDRIV head, round shank.
  Metric size-DIN ISO 8764

KING TONY	No.	Ø x L (mm)	Ø x L (inch)	g	
14280023	0	3.2 x 60	1/8 x 2-3/8	35	12 / 96
14280132	1	4.5 x 80	3/16 x 3-1/8	43	12 / 96
14280104	1	4.5 x 100	3/16 x 4	52	12 / 96
14280204	2	6.0 x 100	1/4 x 4	74	12 / 96
14280306	3	8.0 x 150	5/16 x 6	132	12 / 144

1428

8781032KT applied to 14280023, 14280132, 14280104, 14280204
8781032KT applied to 14280306

Standard Screwdriver Set

- SHANK MATERIAL - SNCM + V alloy steel
- GRIP MATERIAL - PP + TPR
- FINISHING - chrome plated with black tip

Screwdriver sets:

KING TONY	PC./SET	Contents			kg	
30115MR	5	1421 ⊕	No.1 x 80	No.2 x 100	0.54	1/20
		1422 ⊖	4 x 100 6.5 x 150	5.5 x 125		
30117MR	7	1421 ⊕	No.1 x 80	No.2 x 100	0.72	1/20
		1422 ⊖	3 x 75 5.5 x 125 8 x 175	4 x 100 6.5 x 150		
30118MR	8	1422 ⊖	3 x 75 5 x 100 8 x 200 6.5 x 150	5 x 75 8 x 150 6.5 x 100 6.5 x 38	0.87	1/20
31116MR	6	1421 ⊕	No.0 x 60 No.2 x 100	No.1 x 80	0.56	1/20
		1422 ⊖	3 x 75 6.5 x 150	5.5 x 100		
31216MR	6	1421 ⊕	No.1 x 80	No.2 x 100	0.56	1/20
		1422 ⊖	5 x 75 6.5 x 100	5 x 100 6.5 x 150		
30127MR	7	1428 ⊕	No.1 x 80 No.3 x 150	No.2 x 100	0.82	1/20
		1422 ⊖	4 x 100 6.5 x 150	5.5 x 125 8 x 175		
30307PR	7	1427 ✡	T10 T15 T20 T25 T27 T30 T40		0.78	1/20
30309PR	9	1427 ✡	T8 T9 T10 T15 T20 T25 T27 T30 T40		0.88	1/20
30317PR	7	1423 ✡	T10 T15 T20 T25 T27 T30 T40		0.78	1/20
30319PR	9	1423 ✡	T8 T9 T10 T15 T20 T25 T27 T30 T40		0.88	1/20

30115MR

30117MR

30118MR

31116MR

31216MR

30127MR

30307PR

30309PR

30317PR

30319PR

Heavy Duty Screwdriver

- SHANK MATERIAL - CR - V alloy steel
- GRIP MATERIAL - PVC
- FINISHING - chrome plated
  It is used in the working environment less than 60° C

⊕ 1481

- PHILLIPS head, hex-shank
  Metric size-DIN ISO 8764

KING TONY	⊕ No.	W x L (mm)	W x L (inch)	g	
14810103	1	5.0 x 75	7/32 x 3	70	12 / 240
14810204	2	6.0 x 100	1/4 x 4	90	12 / 144
14810204-E*	2	6.0 x 100	1/4 x 4	130	12 / 96
14810205	2	6.0 x 125	1/4 x 5	115	12 / 144
14810205-E*	2	6.0 x 125	1/4 x 5	170	12 / 144
14810306	3	8.0 x 150	5/16 x 6	206	12 / 144
14810412	4	10.0 x 300	12/32 x 12	362	10 / 40

* : Enlarged handle

1481

8781013KT applied to 14810103, 14810204, 14810205

8781032KT applied to 14810204-E*, 14810306, 14810412, 14810205-E*

⊖ 1482

- SLOTTED head, hex-shank
- Metric size-DIN ISO 2380

KING TONY	W x L (mm)	T x Ø (mm)	W x L (inch)	g	
14825503	5.5 x 75	0.8 x 5.0	7/32 x 3	70	12 / 240
14826504	6.5 x 100	1.2 x 6.0	1/4 x 4	90	12 / 144
14826504-E*	6.5 x 100	1.2 x 6.0	1/4 x 4	130	12 / 96
14826505-E*	6.5 x 125	1.2 x 6.0	1/4 x 5	170	12 / 144
14826506	6.5 x 150	1.2 x 6.0	1/4 x 6	120	12 / 144
14820806	8.0 x 150	1.2 x 8.0	5/16 x 6	185	12 / 144
14821012	10.0 x 300	1.6 x 10.0	12/32 x 12	337	10 / 40

* : Enlarged handle

1482

8781013KT applied to 14825503, 14826504

8781032KT applied to 114826504-E*, 14826506, 14826505-E*, 14820806, 14821012

Heavy Duty Screwdriver Set

⊖ ⊕ 35114 MR

- 14 PC. standard & insulated screwdriver set

KING TONY	Contents	kg	
35114MR	1411 ⊕ No.0 x 75 No.1 x 100 No.2 x 100 No.2 x 150 No.2 x 38 No.3 x 150	2.2	1/4
	1412 ⊖ 3 x 75 4 x 100 5.5 x 100 6.5 x 150 6.5 x 38 8 x 200		
	1472 ⊖ 6.5 x 150		
	1482 ⊖ 10 x 300		

Heavy Duty Screwdriver

- SHANK MATERIAL - SNCM + V alloy steel
- GRIP MATERIAL - PP + TPR
- FINISHING - chrome plated with black tips

⊕ 1461

- PHILLIPS head, hex-shank
  Metric size-DIN ISO 8764

KING TONY	No.	ØxL (mm)	ØxL (inch)	g	
14610103	1	5.0 x 75	7/32 x 3	110	12 / 96
14610204	2	6.0 x 100	1/4 x 4	125	12 / 96
14610306	3	8.0 x 150	5/16 x 6	206	12 / 144

⊖ 1462

- SLOTTED head, hex-shank
- Metric size-DIN ISO 2380

KING TONY	WxL (mm)	TxØ (mm)	WxL (inch)	g	
14625504	5.5 x 100	1.0 x 5.0	7/32 x 4	113	12 / 96
14626504	6.5 x 100	1.2 x 6.0	1/4 x 4	132	12 / 96
14626506	6.5 x 150	1.2 x 6.0	1/4 x 6	155	12 / 144
14620806	8.0 x 150	1.2 x 8.0	5/16 x 6	219	12 / 144
14620807	8.0 x 175	1.2 x 8.0	5/16 x 7	216	12 / 144

Heavy Duty Screwdriver Set

⊖ ⊕ 30206 MR

- 6 PC. screwdriver sets:

KING TONY	PC./SET	Pack	Contents	kg	
30206MR	6	Color Box	⊕ No.1 x 75 No.2 x 100 No.3 x 150 ⊖ 5.5 x 100 6.5 x 150 8.0 x 175	1.2	1 / 20

30206MR

Nutspinner

- SHANK MATERIAL - chrome vanadium alloy steel
- GRIP MATERIAL - PP + TPR
- Shank finishing - chrome plated
  Shank length - 125mm

○ 1450

KING TONY	SIZE (mm)	L1	L2	L	g	
1450 - 04	4.0	4.5	125	223	70	12 / 144
1450 - 45	4.5	4.5	125	223	65	12 / 144
1450 - 05	5.0	5.0	125	223	75	12 / 144
1450 - 55	5.5	5.0	125	223	75	12 / 144
1450 - 06	6.0	6.0	125	223	75	12 / 144
1450 - 07	7.0	6.0	125	223	75	12 / 144
1450 - 08	8.0	7.0	125	235	100	12 / 144
1450 - 09	9.0	7.0	125	235	105	12 / 144
1450 - 10	10.0	8.0	125	235	105	12 / 144
1450 - 11	11.0	9.0	125	245	160	12 / 144
1450 - 12	12.0	10.0	125	245	160	12 / 144
1450 - 13	13.0	10.0	125	245	160	10 / 120

Nutspinner NEW

- SHANK MATERIAL - chrome vanadium alloy steel
- GRIP MATERIAL - PP + TPR
- Shank finishing - chrome plated
  Shank length - 125mm

5450

5450

KING TONY	SIZE (inch)	L1	L2	L	g	
5450 - 08	1/4	6	125	223	100	12 / 144
5450 - 10	5/16	7	125	225	105	12 / 144

Nutspinner Set NEW

9-30110 CR

KING TONY	Contents		kg	
9-30110CR	1450	6 7 8 9 10 11 12 13	1.4	6
	5450	1/4 5/16		

Power Bit

- Bits for screwdriver handle 91232
- Material - SNCM + V alloy steel

1317

KING TONY	No.		L (mm)	L (inch)	g	
1317012PN	⊕ PH1	⊕ PH2	175	7	45	40 / 400
1317012ZN	⊕ PZ2	⊕ PZ1	175	7	45	40 / 400
1317046SN	⊖ 4.0	⊖ 6.0	175	7	45	40 / 400
1317057SN	⊖ 5.0	⊖ 7.0	175	7	45	40 / 400
1317115TN	✱ T10	✱ T15	175	7	45	40 / 400
1317225TN	✱ T20	✱ T25	175	7	45	40 / 400
1317340TN	✱ T30	✱ T40	175	7	45	40 / 400
1317401PN	⊖ 4.0	⊕ PH1	175	7	45	40 / 400
131744BHN	◉ 4.0	◉ 4.0	175	7	45	40 / 400
1317501ZN	⊖ 5.0	⊕ PZ1	175	7	45	40 / 400
131755BHN	◉ 5.0	◉ 5.0	175	7	45	40 / 400
1317602PN	⊖ 6.0	⊕ PH2	175	7	45	40 / 400
131766BHN	◉ 6.0	◉ 6.0	175	7	45	40 / 400
1317702ZN	⊖ 7.0	⊕ PZ2	175	7	45	40 / 400

Screwdriver Handle

91232

KING TONY	Total Length (mm)	(inch)	g	
91232	135	5-1/4	84	-

91232

Standard Screwdriver Set

31416MR

- 96 PC. standard screwdriver shelf set

	Contents					Each Q'ty
31416MR	1421 ⊕	No.0 x 60	No.1 x 80	No.1 x 100	No.2 x 38	6
		No.2 x 100	No.2 x 150	No.3 x 150		
	1422 ⊖	3.0 x 75	4.0 x 100	5.5 x 75		
		5.5 x 100	5.5 x 125	6.5 x 38		
		6.5 x 100	6.5 x 150	8.0 x 150		

	kg	CUFT	Screwdriver shelf size (mm)
31416MR-A	3.3	1.97	600 x 240 x 210
31416MR-D	6.2	0.71	

31516MR

- 96 PC. standard & heavy duty screwdriver shelf set

	Contents					Each Q'ty
31516MR	1427	T8 x 75	T9 x 75	T10 x 75		6
		T15 x 75	T20 x 100	T25 x 100		
		T27 x 100	T30 x 125	T40 x 150		
	1461 ⊕	No.1 x 75	No.2 x 100	No.3 x 150		
	1462 ⊖	5.5 x 100	6.5 x 100	6.5 x 150	8.0 x 175	

	kg	CUFT	Screwdriver shelf size (mm)
31516MR-A	3.3	1.97	600 x 240 x 210
31516MR-D	10.1	0.71	

31519MR

- 114 PC. standard screwdriver shelf set

	Contents					Each Q'ty
31519MR	1411 ⊕	No.0 x 75	No.1 x 100	No.2 x 100	No.2 x 100E*	6
		No.2 x 150	No.2 x 150E*	No.2 x 38	No.3 x 150	
		No.3 x 200				
	1412 ⊖	3.0 x 75	4.0 x 100	5.5 x 100		
		6.5 x 100	6.5 x 150	6.5 x 100E*		
		6.5 x 38	8 x 150	8 x 200	6.5 x 150E*	

* Enlarged handle

	kg	CUFT	Screwdriver shelf size (mm)
31519MR-A	3.5	1.21	650 x 250 x 210
31519MR-D	10.34	0.714	

31512MR

- 72 PC. standard screwdriver shelf set

	Contents					Each Q'ty
31512MR	24110204 ⊕ ⊖	No.2 x 100		1481 ⊕	No.2 x 125	6
	24110214 ⊕ ⊖	No.2 x 38		1482 ⊖	6.5 x 150	
31512MR01	1481 ⊕	No.2 x 100	No.1 x 75	1481 ⊕	No.2 x 125E*	
		No.2 x 100E*	No.3 x 150			
	1482 ⊖	5.5 x 75	6.5 x 100	1482 ⊖	6.5 x 125E*	
		6.5 x 100E*	8 x 150			

* Enlarged handle

	kg	CUFT	Screwdriver shelf size (mm)
31512MR-A	2.47	0.78	420 x 250 x 210
31512MR-D	8.23	0.714	

Screwdriver Set

32518 MR

- 11 PC. two-way screwdriver set

	Contents		
32518MR	1317012PN	⊕ PH1	⊕ PH2
	1317012ZN	⊕ PZ2	⊕ PZ1
	1317046SN	⊖ 4.0	⊖ 6.0
	1317057SN	⊖ 5.0	⊖ 7.0
	1317115TN	T10	T15
	1317225TN	T20	T25
	1317340TN	T30	T40
	131744BHN	4.0	4.0
	131755BHN	5.0	5.0
	131766BHN	6.0	6.0
	91232		

32518MR

kg		Blow case size (mm)
0.7	20	233 x 120 x 43 (0.07 cuft)

32518 MR01

- 11PC. two-way screwdriver set

	Contents		
32518MR01	1317115TN	T10	T15
	1317225TN	T20	T25
	1317340TN	T30	T40
	1317401PN	⊖ 4.0	⊕ PH1
	131744BHN	4.0	4.0
	1317501ZN	⊖ 5.0	⊕ PZ1
	131755BHN	5.0	5.0
	1317602PN	⊖ 6.0	⊕ PH2
	131766BHN	6.0	6.0
	1317702ZN	⊖ 7.0	⊕ PZ2
	91232		

32518MR01

kg		Blow case size (mm)
0.7	20	233 x 120 x 43 (0.07 cuft)

32518 MR02

- 11 PC. two-way screwdriver set

	Contents		
32518MR02	1317115TN	T10	T15
	1317225TN	T20	T25
	1317340TN	T30	T40
	1317401PN	⊖ 4.0	⊕ PH1
	131744BHN	4.0	4.0
	1317012PN	⊕ PH1	⊕ PH2
	131755BHN	5.0	5.0
	1317602PN	⊖ 6.0	⊕ PH2
	131766BHN	6.0	6.0
	1317057SN	⊖ 5.0	⊖ 7.0
	91232		

32518MR02

kg		Blow case size (mm)
0.7	20	233 x 120 x 43 (0.07 cuft)

Insulated Screwdriver

- SHANK MATERIAL - SNCM + V alloy steel
- GRIP MATERIAL - PP + TPR
- FINISHING - chrome plated with black tip

⊕ 1471

- PHILLIPS head, round shank.
- Metric size-IEC 60900:2004

KING TONY	No.	Ø x L (mm)	Ø x L (inch)	g	
14710003	0	3.0 x 75	1/8 x 3	37	12 / 144
14710104	1	4.5 x 100	3/16 x 4	54	12 / 216
14710204	2	6.0 x 100	1/4 x 4	77	12 / 144
14710306	3	8.0 x 150	5/16 x 6	135	12 / 144

1471

⊖ 1472

- SLOTTED head, round shank.
- Metric size-IEC 60900:2004

KING TONY	W x L (mm)	T x Ø (mm)	W x L (inch)	g	
14720303	3.0 x 75	0.5 x 3.0	1/8 x 3	38	12 / 144
14720404	4.0 x 100	0.8 x 4.0	3/16 x 4	44	12 / 96
14725505	5.5 x 125	1.0 x 5.5	7/32 x 5	72	12 / 144
14726506	6.5 x 150	1.2 x 6.5	1/4 x 6	87	12 / 144
14720807	8.0 x 175	1.2 x 8.0	5/16 x 8	143	12 / 144

1472

⊛ 1478

- POZIDRIV head, round shank.
- Metric size-IEC 60900:2004

KING TONY	No.	Ø x L (mm)	Ø x L (inch)	g	
14780003	0	3.0 x 75	1/8 x 3	37	12 / 144
14780104	1	4.5 x 100	3/16 x 4	54	12 / 96
14780204	2	6.0 x 100	1/4 x 4	77	12 / 144
14780306	3	8.0 x 150	5/16 x 6	135	12 / 144

1478

Insulated Screwdriver Set

⊛⊖30607 MR ⊕⊖30617 MR

packing:

KING TONY	PC. / SET	Contents	kg	
30607MR	7	⊛ No.1 x 100 No.2 x 100 No.3 x 150 ⊖ 4 x 100 5.5 x 125 6.5 x 150 8.0 x 175	0.86	1/20
30617MR	7	⊕ No.1 x 100 No.2 x 100 No.3 x 150 ⊖ 4 x 100 5.5 x 125 6.5 x 150 8.0 x 175	0.86	1/20

30607MR

30617MR

Precision Screwdriver

- SHANK MATERIAL - SNCM + V alloy steel
- GRIP MATERIAL - PP + TPR
- FINISHING - chrome plated with black tip

⊕ 1431

- PHILLIPS head, round shank.
- Metric size-DIN 5261

KING TONY	No.	Ø x L (mm)	g	
14313015	No.000	2.0 x 40	7	10 / 320
14312015	No.00	2.5 x 40	7	10 / 320
14311015	No.0	3.0 x 40	13	10 / 100
14311115	No.1	4.0 x 40	16	10 / 100
14313003	No.000	2.0 x 75	8	10 / 320
14312003	No.00	2.5 x 75	8	10 / 320
14311003	No.0	3.0 x 75	14	10 / 100
14311103	No.1	4.0 x 75	18	10 / 100

1431

⊖ 1432

- SLOTTED head, round shank.
- Metric size-DIN 5263

KING TONY	W x L (mm)	T x Ø (mm)	g	
14320615	0.6 x 40	0.15 x 0.6	9	10 / 320
14320815	0.8 x 40	0.20 x 0.8	9	10 / 320
14321015	1.0 x 40	0.20 x 1.0	9	10 / 320
14321515	1.5 x 40	0.25 x 1.5	10	10 / 320
14321815	1.8 x 40	0.27 x 1.8	10	10 / 320
14322015	2.0 x 40	0.30 x 2.0	11	10 / 100
14322515	2.5 x 40	0.40 x 2.5	12	10 / 100
14323015	3.0 x 40	0.50 x 3.0	13	10 / 100
14323515	3.5 x 40	0.55 x 3.5	14	10 / 100
14324015	4.0 x 40	0.60 x 4.0	16	10 / 100
14321003	1.0 x 75	0.20 x 1.0	11	10 / 320
14321503	1.5 x 75	0.25 x 1.5	11	10 / 320
14321803	1.8 x 75	0.27 x 1.8	11	10 / 320
14322003	2.0 x 75	0.30 x 2.0	11	10 / 100
14322503	2.5 x 75	0.40 x 2.5	13	10 / 100
14323003	3.0 x 75	0.50 x 3.0	15	10 / 100
14323503	3.5 x 75	0.55 x 3.5	16	10 / 100
14324003	4.0 x 75	0.60 x 4.0	18	10 / 100

1432

✱ 1433

- For TORX head, round shank.

KING TONY	No.	Ø x L (mm)	g	
14330415	T4	3 X 40	10	10 / 320
14330515	T5	3 X 40	10	10 / 320
14330615	T6	3 X 40	10	10 / 320
14330715	T7	3 X 40	10	10 / 320
14330815	T8	3 X 40	10	10 / 320
14330902	T9	4 X 50	16	10 / 100
14331002	T10	4 X 50	16	10 / 100
14331502	T15	4 X 50	16	10 / 100
14332002	T20	4 X 50	16	10 / 100
14330403	T4	3 X 75	11	10 / 320
14330503	T5	3 X 75	11	10 / 320
14330603	T6	3 X 75	11	10 / 320
14330703	T7	3 X 75	11	10 / 320
14330803	T8	3 X 75	11	10 / 320
14330903	T9	4 X 75	18	10 / 100
14331003	T10	4 X 75	18	10 / 100
14331503	T15	4 X 75	18	10 / 100
14332003	T20	4 X 75	18	10 / 100

1433

Precision Screwdriver

○ 91230

Screwdriver handle for interchangeable blades 2431, 2433
Handle material - polypropylene (PP)

KING TONY	L (mm)	L (inch)	g	
91230	100	4-1/2	12	10 / 100

⊕⊖ 2431

Screwdriver blade for combination type
Phillips / Slotted head, hexagonal shank
Blade material - SNCM + V alloy steel
Finishing - chrome plated with black tip

KING TONY	No.	W (mm)	T (mm)	Ø (mm)	L (mm)	g	
24312020	PH00	2.0	0.30	4	120	11	20 / 200
24311030	PH0	3.0	0.50	4	120	11	20 / 200
24311140	PH1	4.0	0.60	4	120	11	20 / 200

✱✱ 2433

Screwdriver blade for combination type
Phillips / Slotted head, hexagonal shank
Blade material - SNCM + V alloy steel
Finishing - chrome plated with black tip

KING TONY	SIZE	Ø (mm)	L (mm)	g	
24330610	T6 x T10	4	120	11	20 / 200
24330715	T7 x T15	4	120	11	20 / 200
24330820	T8 x T20	4	120	11	20 / 200
24330915	T9 x T15	4	120	11	20 / 200

Precision Screwdriver Set

⊕⊖32108 MR ⊕⊖32118 MR
⊖32209 MR ⊖ 32218 MR
✱ 32309 PR ⊕⊖✱ 32607 MR

KING TONY	PC. / SET	Contents	kg	
32108MR	8	⊕ No.000 x 40 No.00 x 40 No.0 x 40 No.1 x 40 ⊖ 1.5 x 40 2.0 x 40 2.5 x 40 3.0 x 40	0.24	1/30
32118MR	8	⊕ No.000 x 75 No.00 x 75 No.0 x 75 No.1 x 75 ⊖ 1.5 x 75 2.0 x 75 2.5 x 75 3.0 x 75	0.32	
32209MR	9	⊖ 0.8 x 40 1.0 x 40 1.5 x 40 1.8 x 40 2.0 x 40 2.5 x 40 3.0 x 40 3.5 x 40 4.0 x 40	0.26	
32218MR	8	⊖ 1.0 x 75 1.5 x 75 1.8 x 75 2.0 x 75 2.5 x 75 3.0 x 75 3.5 x 75 4.0 x 75	0.32	
32309PR	9	✱ T4 x 40 T5 x 40 T6 x 40 T7 x 40 T8 x 40 T9 x 50 T10 x 50 T15 x 50 T20 x 50	0.26	
32607MR	8	91230 ⊕ ⊖ PH00 x 2.0 PH0 x 3.0 PH1 x 4.0 ✱ ✱ T6 x T10 T7 x T15 T8 x T20 T9 x T15	0.22	

32108MR

32209MR

32118MR

32309PR

32218MR

32607MR

⊕⊖✱ 31419 MR

- 114 PC. precision screwdriver shelf set (40L)

KING TONY			Contents	Each Q' ty
31419MR	1431	⊕	No.000 x 40 No.00 x 40 No.0 x 40	6
			No.1 x 40	6
	1432	⊖	0.6 x 40 0.8 x 40 1.0 x 40 1.5 x 40	6
			1.8 x 40 2.0 x 40 2.5 x 40 3.0 x 40	6
			3.5 x 40 4.0 x 40	6
	1433	✱	T4 x 40 T5 x 40 T6 x 40 T7 x 40	6
			T8 x 40	6

31419MR

kg		Metal case size (mm)
1.1	0.63	383x136x130

Bit

- Silicon chrome vanadium alloy steel (S2)
- Anti-rust oiled, sand-blasted.
- Total length : 25 mm

1/4" *Hex size shank driver*

order unit one box

Item No.xxxxxxx.B

⊕ 1025P

- PHILLIPS head
- DIN 2351-2

KING TONY	⊕ No.	g	
102500P (102500P.B)	0	4.5	20 / 200 (50 / 1000)
102501P (102501P.B)	1	5.0	20 / 200 (50 / 1000)
102502P (102502P.B)	2	5.5	20 / 200 (50 / 1000)
102503P (102503P.B)	3	6.0	20 / 200 (50 / 1000)

⊕ 102512P

- PHILLIPS head
- Reduced for dry-wall
- DIN 2351-2

KING TONY	⊕ No.	g	
102512P (102512P.B)	2	5.5	20 / 200 (50 / 1000)

Bit

- Silicon chrome vanadium alloy steel (S2)
- Anti-rust oiled, sand-blasted.
- Total length : 25 mm

1/4" Hex size shank driver

1025S

- SLOTTED head
- DIN 2351-1

KING TONY	Tip width (mm)	Tip thickness (mm)			
102503S1 (102503S1.B)	3.0	0.5	4.5	20 / 200	(50 / 1000)
102535S1 (102535S1.B)	3.5	0.6	4.5	20 / 200	(50 / 1000)
102504S1 (102504S1.B)	4.0	0.5	4.5	20 / 200	(50 / 1000)
102504S2 (102504S2.B)	4.0	0.8	5.0	20 / 200	(50 / 1000)
102545S1 (102545S1.B)	4.5	0.6	5.0	20 / 200	(50 / 1000)
102505S1 (102505S1.B)	5.0	0.8	5.0	20 / 200	(50 / 1000)
102555S1 (102555S1.B)	5.5	0.8	5.0	20 / 200	(50 / 1000)
102555S2 (102555S2.B)	5.5	1.0	5.0	20 / 200	(50 / 1000)
102506S1 (102506S1.B)	6.0	1.0	5.0	20 / 200	(50 / 1000)
102565S1 (102565S1.B)	6.5	1.2	5.5	20 / 200	(50 / 1000)
102507S1 (102507S1.B)	7.0	1.2	5.5	20 / 200	(50 / 1000)
102508S1 (102508S1.B)	8.0	1.2	6.0	20 / 200	(50 / 1000)
102508S2 (102508S2.B)	8.0	1.6	6.0	20 / 200	(50 / 1000)

1025T

- For TORX INTERNAL screws

KING TONY	SIZE			
102506T (102506T.B)	T6	4.5	20 / 200	(50 / 1000)
102507T (102507T.B)	T7	4.5	20 / 200	(50 / 1000)
102508T (102508T.B)	T8	4.5	20 / 200	(50 / 1000)
102509T (102509T.B)	T9	4.5	20 / 200	(50 / 1000)
102510T (102510T.B)	T10	4.5	20 / 200	(50 / 1000)
102515T (102515T.B)	T15	5.0	20 / 200	(50 / 1000)
102520T (102520T.B)	T20	5.0	20 / 200	(50 / 1000)
102525T (102525T.B)	T25	5.0	20 / 200	(50 / 1000)
102527T (102527T.B)	T27	5.0	20 / 200	(50 / 1000)
102530T (102530T.B)	T30	5.0	20 / 200	(50 / 1000)
102540T (102540T.B)	T40	6.0	20 / 200	(50 / 1000)

1025Z

- POZIDRIV type
- DIN 3128

KING TONY	No.			
102501Z (102501Z.B)	1	5.0	20 / 200	(50 / 1000)
102502Z (102502Z.B)	2	5.5	20 / 200	(50 / 1000)
102503Z (102503Z.B)	3	5.5	20 / 200	(50 / 1000)

1025R

- SQUARE head

KING TONY	SIZE No.			
102500R (102500R.B)	0	4.5	20 / 200	(50 / 1000)
102501R (102501R.B)	1	5.0	20 / 200	(50 / 1000)
102502R (102502R.B)	2	5.0	20 / 200	(50 / 1000)
102503R (102503R.B)	3	5.5	20 / 200	(50 / 1000)

1025H
5025H

- HEXAGON head
- DIN 2351-3

KING TONY	mm / inch			
102515H (102515H.B)	1.5	4.0	20 / 200	(50 / 1000)
102502H (102502H.B)	2.0	4.5	20 / 200	(50 / 1000)
102525H (102525H.B)	2.5	4.5	20 / 200	(50 / 1000)
102503H (102503H.B)	3.0	5.0	20 / 200	(50 / 1000)
102504H (102504H.B)	4.0	5.5	20 / 200	(50 / 1000)
102505H (102505H.B)	5.0	6.0	20 / 200	(50 / 1000)
102506H (102506H.B)	6.0	6.0	20 / 200	(50 / 1000)
102507H (102507H.B)	7.0	7.5	20 / 200	(50 / 1000)
102508H (102508H.B)	8.0	9.0	20 / 200	(50 / 1000)
102510H (102510H.B)	10.0	11.5	20 / 200	(50 / 1000)
502503H (502503H.B)	3/64	4.0	20 / 200	(50 / 1000)
502504H (502504H.B)	1/16	4.0	20 / 200	(50 / 1000)
502505H (502505H.B)	5/64	4.5	20 / 200	(50 / 1000)
502506H (502506H.B)	3/32	5.0	20 / 200	(50 / 1000)
502507H (502507H.B)	7/64	5.0	20 / 200	(50 / 1000)
502508H (502508H.B)	1/8	5.0	20 / 200	(50 / 1000)
502509H (502509H.B)	9/64	5.0	20 / 200	(50 / 1000)
502510H (502510H.B)	5/32	5.5	20 / 200	(50 / 1000)

1025U

- For TORX head screws
- **Tamper resistant type**

KING TONY	SIZE			
102507U (102507U.B)	T7	4.0	20 / 200	(50 / 1000)
102508U (102508U.B)	T8	4.5	20 / 200	(50 / 1000)
102509U (102509U.B)	T9	4.5	20 / 200	(50 / 1000)
102510U (102510U.B)	T10	4.5	20 / 200	(50 / 1000)
102515U (102515U.B)	T15	4.5	20 / 200	(50 / 1000)
102520U (102520U.B)	T20	5.0	20 / 200	(50 / 1000)
102525U (102525U.B)	T25	5.0	20 / 200	(50 / 1000)
102527U (102527U.B)	T27	5.0	20 / 200	(50 / 1000)
102530U (102530U.B)	T30	5.5	20 / 200	(50 / 1000)
102540U (102540U.B)	T40	5.5	20 / 200	(50 / 1000)

1025V

NEW

- For inside 5-star screws
- **Tamper resistant type**

KING TONY	SIZE		
102508V	IPR 8	5.0	20 / 200
102509V	IPR 9	5.0	20 / 200
102510V	IPR 10	5.0	20 / 200
102515V	IPR 15	5.0	20 / 200
102520V	IPR 20	5.0	20 / 200
102525V	IPR 25	5.0	20 / 200
102527V	IPR 27	5.0	20 / 200
102530V	IPR 30	5.0	20 / 200
102540V	IPR 40	6.4	20 / 200

Bit

- Silicon chrome vanadium alloy steel (S2)
- Anti-rust oiled, sand-blasted.

order unit: one blister card

1/4" *Hex size shank driver*

⊛⊛ 1360ZZ

- Double POZIDRIV head

No.		Total Length (mm)		
1360012Z	1 / 2	60	13.0	10 / 100
1360022Z	2 / 2	60	13.5	10 / 100
1360023Z	2 / 3	60	13.5	10 / 100

⊕⊕ 1360PP

- Double PHILLIPS head

No.		Total Length (mm)		
1360012P	1 / 2	60	13.0	10 / 100
1360022P	2 / 2	60	13.5	10 / 100
1360023P	2 / 3	60	13.5	10 / 100

⊛⊖ 1360ZS

- POZIDRIV / SLOTTED head

No.		Tip width (mm)	Tip thickness (mm)	Total Length (mm)		
1360451Z	1	4.5	0.6	60	13.0	10 / 100
1360552Z	2	5.5	1.0	60	13.5	10 / 100
1360703Z	3	7.0	1.2	60	13.5	10 / 100

⊕⊖ 1360PS

- PHILLIPS / SLOTTED head

No.		Tip width (mm)	Tip thickness (mm)	Total Length (mm)		
1360451P	1	4.5	0.6	60	13.0	10 / 100
1360552P	2	5.5	1.0	60	13.5	10 / 100
1360703P	3	7.0	1.2	60	13.5	10 / 100

order unit: one box

5/16" *Hex size shank driver*

⊕ 1800P

- PHILLIPS head. 36 / 80mm L
- DIN ISO 2251-2

No.		Total Length (mm)		
183602P	2	36	12	20 / 200
188002P	2	80	31	10 / 100
181202P	2	125	50	10 / 100
183603P	3	36	12	20 / 200
188003P	3	80	31	10 / 100
181203P	3	125	50	10 / 100
183604P	4	36	12	20 / 200
188004P	4	80	31	10 / 100

⊖ 1800S

- SLOTTED head. 36 / 80mm L
- DIN ISO 2351-1

Tip width (mm)	Tip thickness (mm)	Total Length (mm)		
183608S	8	1.2	36	11.5	20 / 200
188008S	8	1.2	80	32.0	10 / 100
183609S	9	1.6	36	13.0	20 / 200
183610S	10	1.6	36	14.5	20 / 200
188010S	10	1.6	80	33.0	10 / 100
183611S	11	2.0	36	16.0	20 / 200
183612S	12	2.0	36	17.5	12 / 120
188012S	12	2.0	80	34.0	6 / 60

⊛ 1800T

- For TORX INTERNAL screws. 32 / 70 mm L

SIZE	Total Length (mm)		
183215T	T15	32	10.0	20 / 200
187015T	T15	70	22.0	10 / 100
183220T	T20	32	10.0	20 / 200
187020T	T20	70	22.0	10 / 100
183225T	T25	32	10.0	20 / 200
187025T	T25	70	22.0	10 / 100
183227T	T27	32	10.5	20 / 200
187027T	T27	70	22.0	10 / 100
183230T	T30	32	10.5	20 / 200
187030T	T30	70	22.0	10 / 100
183240T	T40	32	10.0	20 / 200
187040T	T40	70	22.5	10 / 100
183245T	T45	32	10.5	20 / 200
187045T	T45	70	22.0	10 / 100
183250T	T50	32	10.5	20 / 200
187050T	T50	70	22.0	10 / 100

Bit

- Silicon chrome vanadium alloy steel (S2)
- Anti-rust oiled, sand-blasted

10mm *Hex size shank driver*

order unit :one blister card

1600T

- For TORX head, 36/80mmL

KING TONY	(mm)	Overall Length (mm)	g	
163610T	T10	36	16.9	12 / 120
168010T	T10	80	46.3	6 / 60
163615T	T15	36	17.3	12 / 120
168015T	T15	80	46.5	6 / 60
163620T	T20	36	17.6	12 / 120
168020T	T20	80	46.8	6 / 60
163625T	T25	36	17.8	12 / 120
168025T	T25	80	47.1	6 / 60
163627T	T27	36	18.2	12 / 120
168027T	T27	80	47.2	6 / 60
163630T	T30	36	18.3	12 / 120
168030T	T30	80	47.2	6 / 60
163640T	T40	36	19.9	12 / 120
168040T	T40	80	48.0	6 / 60
163645T	T45	36	20.9	12 / 120
168045T	T45	80	49.1	6 / 60
163650T	T50	36	22.9	12 / 120
168050T	T50	80	50.0	6 / 60
163655T	T55	36	28.0	12 / 120
168055T	T55	80	52.3	6 / 60
163660T	T60	36	32.6	12 / 120
168060T	T60	80	70.4	6 / 60

1600H

- HEXAGON head, 36/80mmL

KING TONY	(mm)	Overall Length (mm)	g	
163604H	4	36	17.3	12 / 120
168004H	4	80	47.2	6 / 60
163605H	5	36	18.6	12 / 120
168005H	5	80	48.0	6 / 60
163606H	6	36	19.2	12 / 120
168006H	6	80	49.4	6 / 60
163607H	7	36	20.1	12 / 120
168007H	7	80	50.3	6 / 60
163608H	8	36	21.3	12 / 120
168008H	8	80	50.8	6 / 60
163610H	10	36	24.1	12 / 120
168010H	10	80	53.8	6 / 60
163612H	12	36	30.5	12 / 120
168012H	12	80	72.9	6 / 60

1600M

- SPLINE head, 36/80mmL

KING TONY	(mm)	Overall Length (mm)	g	
163605M	5	36	18.3	12 / 120
168005M	5	80	47.2	6 / 60
163606M	6	36	18.7	12 / 120
168006M	6	80	47.9	6 / 60
163608M	8	36	19.8	12 / 120
168008M	8	80	49.0	6 / 60
163610M	10	36	22.4	12 / 120
168010M	10	80	51.6	6 / 60
163612M	12	36	27.7	12 / 120
168012M	12	80	70.1	6 / 60

1600U

- For TORX head, 36/80mmL
- Tamper resistant type

KING TONY	(mm)	Overall Length (mm)	g	
163610U	T10	36	16.9	12 / 120
168010U	T10	80	46.3	6 / 60
163615U	T15	36	17.3	12 / 120
168015U	T15	80	46.5	6 / 60
163620U	T20	36	17.6	12 / 120
168020U	T20	80	46.8	6 / 60
163625U	T25	36	17.8	12 / 120
168025U	T25	80	47.1	6 / 60
163627U	T27	36	18.2	12 / 120
168027U	T27	80	47.2	6 / 60
163630U	T30	36	18.3	12 / 120
168030U	T30	80	47.2	6 / 60
163640U	T40	36	19.9	12 / 120
168040U	T40	80	48.0	6 / 60
163645U	T45	36	20.9	12 / 120
168045U	T45	80	49.1	6 / 60
163650U	T50	36	22.9	12 / 120
168050U	T50	80	50.0	6 / 60
163655U	T55	36	28.0	12 / 120
168055U	T55	80	52.3	6 / 60
163660U	T60	36	32.6	12 / 120
168060U	T60	80	70.4	6 / 60

Power Bit Set

1003MQ NEW

- 1/4"Hexagon head bits 25mm length

	Contents	kg	
1003MQ	4 5 6	0.02	24/576

1003LQ NEW

1/4"Slotted head bits 25mmlength

	Contents	kg	
1003LQ	4.5x0.6 6.5x1.2 8.0x1.2	0.02	24/576

1003PQ NEW

1/4"Philips head bits 25mm length

	Contents	kg	
1003PQ	#1 #2 #3	0.02	24/576

1003ZQ NEW

- 1/4"Pozidriv head bits 25 mm length

	Contents	kg	
1003ZQ	#1 #2 #3	0.02	24/576

1003TQ01 NEW

- 1/4"Torx head bits 25mm length

	Contents	kg	
1003TQ01	T20 T25 T30	0.02	24/576

1003TQ NEW

- 1/4"Torx head bits 25mm length

	Contents	kg	
1003TQ	T8 T10 T15	0.02	24/576

Bit Set

- Silicon chrome vanadium alloy steel (S2)
- Anti-rust oiled, sand-blasted.

1011MQ

- 11 PC. bit set

	Contents		kg	
1011MQ	1636M: 5 6 8 10 12 1680M: 5 6 8 10 12	414810M	0.82	1/20

1011MQ

Metal case size (mm)
- 198 x 105 x 37 (0.053 cuft)

1015MQ

- 15 PC. bit set

	Contents		kg	
1015MQ	1636H: 4 5 6 7 8 10 12 1680H: 4 5 6 7 8 10 12	414810M	0.96	1/20

1015MQ

Metal case size (mm)
- 198 x 105 x 37 (0.053 cuft)

1015PQ

- 15 PC. bit set

	Contents		kg	
1015PQ	1636T: T20 T25 T30 T40 T45 T50 T55 1680T: T20 T25 T30 T40 T45 T50 T55	414810M	0.92	1/20

1015PQ

Metal case size (mm)
- 198 x 105 x 37 (0.053 cuft)

1044CQ

- 44 PC. bit set

	Contents	
1044CQ	1636M: 5 6 8 10 12 1636H: 4 5 6 7 8 10 12 1636T: T20 T25 T27 T30 T40 T45 T50 T55 T60 1680H: 4 5 6 7 8 10 12 1680T: T20 T25 T27 T30 T40 T45 T50 T55 T60 1680M: 5 6 8 10 12	O 314810M 414810M

1044CQ

kg		Metal case size (mm)
2.5	10	296 x 130 x 41 (0.056 cuft)

10 PC. Interchangeable Ratchet Screwdriver Set

32810MR

- Non magnetic type.
- Handle of TPV+PP
- CONTENTS:
  16 TIPS:
  - 7PC. 1/4"x75 mm
    PH0 x SL 4 mm, PH1 x SL 5 mm, PH2 x SL 6 mm,
    Hex 3 mm x Hex 4 mm, Hex 5 mm x Hex 6 mm,
    Hex 2.0 mm x Hex 2.5 mm, T-10 x T-15
  - 1PC. 5/16"x75 mm
    PH3 x SL 8 mm
  - 1PC. Reversible ratchet
  - 1PC. 1/4" & 5/16" bit holder

KING TONY	Contents	kg	
32810MR		0.4	9 / 54

Bit Set

- Silicon chrome vanadium alloy steel (S2)
- Anti-rust oiled, sand-blasted.

1032CQ

- 32 PC. bit set

	Contents		
1032CQ	1025S	3.0 4.0 5.0 6.0	7702-25
	1025P	PH1 PH2 x 2 PH3	
	1025Z	PZ1 PZ2 x 2 PZ3	
	1025T	T10 T15 T20 T25 T27 T30 T40	753-63
	1025H	H3 H4 H5 H6	
	1025U	T10 T15 T20 T25 T27 T30 T40	

kg		Plastic case size (mm)
0.3	1/20	120 x 70 x 42 (0.01 cuft)

1050CQ

- 50 PC. bit set

	Contents		
1050CQ	1025S	4.0 x 2 5.5 x 2 6.5 x 2	750-60
	1025P	PH1 x 2 PH2 x 2 PH3 x 2	
	1025Z	PZ1x 2 PZ2 x 2 PZ3 x 2	
	1025T	T6 T7 T8 T9 T10 T15 T20 T25 T27 T30 T40 x 2	2141
	1025H	H2 H3 H4 H5 H6 H7 H8	
	1025U	T7 T8 T9 T10 T15 T20 T25 T27 T30 T40 x 2	

1050CQ

kg		Blow case size (mm)
0.5	1/20	224 x 110 x 54 (0.047 cuft)

2517MR

- 17 PC.Socket & bit set

	Contents		
2517MR	1025S	4.0 5.5 6.5	7702-25
	1025P	PH1 PH2 PH3	
	1025T	T10 T15 T20	753-63
	2335M	4 4.5 5 5.5 6 7mm	

kg		Blow case size (mm)
0.22	1/28	120 x 70 x 32 (0.01 cuft)

Power Bit

- Silicon chrome vanadium alloy steel (S2)
- Anti-rust oiled, sand-blasted

blister car

1/4" *Hex size shank driver*

⊕ 7100P

- PHILLIPS, short neck (9.5 mm) type
- DIN ISO 2351-2

KING TONY	No.	Overall Length (mm)	g	
715000P	0	50	8.5	10 / 100
715001P	1	50	9.0	10 / 100
715002P	2	50	11.0	10 / 100
715003P	3	50	11.0	10 / 100
716502P	2	65	15.5	10 / 100
717001P	1	70	16.5	10 / 100
717002P	2	70	17.0	10 / 100
717003P	3	70	17.0	10 / 100
719001P	1	90	18.0	10 / 100
719002P	2	90	20.0	10 / 100
719003P	3	90	20.0	10 / 100
711002P	2	100	24.0	10 / 100
711501P	1	150	23.0	10 / 100
711502P	2	150	33.0	10 / 100
711503P	3	150	33.0	10 / 100

◉ 7150H

- HEXAGON head
- DIN ISO 2351-3

KING TONY	(mm)	Overall Length (mm)	g	
715002H	2.0	50	6.0	10 / 100
715025H	2.5	50	6.5	10 / 100
715003H	3.0	50	6.5	10 / 100
715004H	4.0	50	9.5	10 / 100
715005H	5.0	50	10.0	10 / 100
715006H	6.0	50	11.0	10 / 100
715007H	7.0	50	13.0	10 / 100
715008H	8.0	50	17.0	10 / 100

⊖ 7150S

- SLOTTED head
- DIN ISO 2351-1

KING TONY	Tip width (mm)	Tip thickness (mm)	Overall Length (mm)	g	
715003S1	3.0	0.5	50	6.0	10 / 100
715035S1	3.5	0.5	50	6.5	10 / 100
715004S2	4.0	0.5	50	7.0	10 / 100
715004S1	4.0	0.8	50	7.0	10 / 100
715045S1	4.5	0.6	50	7.0	10 / 100
715005S1	5.0	0.8	50	8.0	10 / 100
715055S1	5.5	0.8	50	8.5	10 / 100
715055S2	5.5	1.0	50	8.5	10 / 100
715006S1	6.0	1.0	50	8.5	10 / 100
715065S1	6.5	1.2	50	9.0	10 / 100

▣ 7150R

- SQUARE head

KING TONY	SIZE No.	Overall Length (mm)	g	
715000R	0	50	7.5	10 / 100
715001R	1	50	8.0	10 / 100
715002R	2	50	8.5	10 / 100
715003R	3	50	8.5	10 / 100

✱ 7100T

- For TORX head screws
- 50 / 70 mm L

KING TONY	SIZE No.	Overall Length (mm)	g	
715006T	T6	50	5.0	10 / 100
717006T	T6	70	7.0	10 / 100
715007T	T7	50	5.0	10 / 100
717007T	T7	70	7.0	10 / 100
715008T	T8	50	5.5	10 / 100
717008T	T8	70	7.5	10 / 100
715009T	T9	50	5.5	10 / 100
717009T	T9	70	7.5	10 / 100
715010T	T10	50	6.0	10 / 100
717010T	T10	70	8.0	10 / 100
715015T	T15	50	6.0	10 / 100
717015T	T15	70	8.0	10 / 100
715020T	T20	50	7.5	10 / 100
717020T	T20	70	10.5	10 / 100
715025T	T25	50	8.0	10 / 100
717025T	T25	70	11.0	10 / 100
715027T	T27	50	9.5	10 / 100
717027T	T27	70	14.0	10 / 100
715030T	T30	50	9.5	10 / 100
717030T	T30	70	14.0	10 / 100
715040T	T40	50	10.0	10 / 100
717040T	T40	70	15.5	10 / 100

⊛ 7100Z

- POZIDRIV head
- DIN ISO 2351-2

KING TONY	No.	Overall Length (mm)	g	
715001Z	1	50	9.0	10 / 100
715002Z	2	50	11.0	10 / 100
715003Z	3	50	12.5	10 / 100
717001Z	1	70	11.0	10 / 100
717002Z	2	70	15.5	10 / 100
717003Z	3	70	15.5	10 / 100
719001Z	1	90	13.0	10 / 100
719002Z	2	90	19.5	10 / 100
719003Z	3	90	19.5	10 / 100

Power Bit Set

◉ 2138PR

- 7 PC. tamper resistant bits & L-type holder set

	Contents	kg	
2138PR	◉ 7150H; 1589-02 (2 3 4 5 6 7 8)	0.24	10/60

Power Bit

- Silicon chrome vanadium alloy steel (S2)
- Anti-rust oiled, sand-blasted.

5mm *Hex size shank driver*

order unit: one box

⊕⊕ 7200PP

- DOUBLE PHILLIPS head
- Long head type

KING TONY	No.	Total Length (mm)	g	
726502P	2	65	8.5	10 / 100
727502P	2	75	10.0	10 / 100
721102P	2	110	14.5	10 / 100

1/4" *Hex size shank driver*

⊕⊕ 7400PP

- DOUBLE PHILLIPS head
- Short head type

KING TONY	No.	Overall Length (mm)	g	
745002P	2	50	11.0	10 / 100
747502P	2	75	15.0	10 / 100
747503P	3	75	16.5	10 / 100
741002P	2	100	23.5	10 / 100
741502P	2	150	37.5	10 / 100

⊕⊕ 7300PP

- DOUBLE PHILLIPS head
- Long head type

KING TONY	No.	Overall Length (mm)	g	
734501P	1	45	9.0	10 / 100
734502P	2	45	9.0	10 / 100
734503P	3	45	10.0	10 / 100
736501P	1	65	14.0	10 / 100
736502P	2	65	14.0	10 / 100
736503P	3	65	14.5	10 / 100
731101P	1	110	26.0	10 / 100
731102P	2	110	26.0	10 / 100
731103P	3	110	26.5	10 / 100
731502P	2	150	32.0	10 / 100
731503P	3	150	33.0	10 / 100

Power Bit

- Silicon chrome vanadium alloy steel (S2)
- Nickel plated

order unit: one box

⊕⊕ 1300PN

- DOUBLE PHILLIPS head
- Long head type

KING TONY	No.	Overall Length (mm)	g	
134501P	1	45	8.5	10 / 300
134502P	2	45	9.0	10 / 300
134503P	3	45	9.0	10 / 300
136501P	1	65	14.0	10 / 200
136502P	2	65	14.0	10 / 200
136503P	3	65	14.0	10 / 200
131101P	1	110	26.0	10 / 150
131102P	2	110	26.0	10 / 150
131103P	3	110	26.5	10 / 150
131501P	1	150	36.0	10 / 100
131502P	2	150	36.5	10 / 100
131503P	3	150	37.0	10 / 100

⊕⊕ 1500PN

- DOUBLE PHILLIPS head
- Short head type

KING TONY	No.	Overall Length (mm)	g	
155001P	1	50	10.0	10 / 300
155002P	2	50	10.0	10 / 300
155003P	3	50	10.0	10 / 300
157501P	1	75	16.5	10 / 200
157502P	2	75	16.5	10 / 200
157503P	3	75	17.0	10 / 200
151001P	1	100	23.0	10 / 150
151002P	2	100	23.0	10 / 150
151003P	3	100	23.5	10 / 150
151501P	1	150	36.5	10 / 100
151502P	2	150	37.0	10 / 100
151503P	3	150	37.5	10 / 100

⊕⊖ 7300PN

- PHILLIPS / SLOTTED head
- Long head type

KING TONY	No.	Tip width (mm)	Tip thickness (mm)	Overall Length (mm)	g	
734551P	1	5.0	0.8	45	8.0	10 / 300
734552P	2	5.0	0.8	45	8.0	10 / 300
736552P	2	5.0	0.8	65	13.5	10 / 200
731152P	2	5.0	0.8	110	25.0	10 / 150
731552P	2	5.0	0.8	150	36.5	10 / 100

Bit Accessory

- Chrome vanadium & stainless alloy steel
- Anti-rust oiled , sand-blasted

1/4" *Hex size shank driver*

750

750

- Magnetic bit holder
- **2 PC.** type
- DIN 7427

KING TONY	(inch)	Total Lenght (mm)	g	
750-60	1/4	60	20.5	6 / 84

760

760 S

- Nut setter
- **Non magnetic** type
- DIN 3126

KING TONY	(inch)	Total Lenght (mm)	g	
7606508S	1/4	65	20	6 / 84
7606510S	5/16	65	30	6 / 84
7606512S	3/8	65	36	6 / 72

770

770

- Bit adapter
- **Ball** retainer type
- DIN 7428

KING TONY	(inch)	Total Lenght (mm)	g	
7702-25	1/4	25	6.0	20 / 200
7702-50	1/4	50	13.5	10 / 100
7703-50	3/8	50	23.5	6 / 84

751

751

- Magnetic bit holder
- **1 PC.** type
- With spring clip
- DIN 7427

KING TONY	(inch)	Total Lenght (mm)	g	
751-60	1/4	60	24	6 / 84
751-75	1/4	75	36	6 / 84

761

761 M
761 S

- Nut setter
- **Magnetic** type
- DIN 3126

KING TONY	mm / inch	Total Lenght (mm)	g	
7616507M	7	65	25	6 / 84
7616508M	8	65	30	6 / 84
7616510M	10	65	37	6 / 72
7614208S	1/4	42	15.0	6 / 90
7614210S	5/16	42	17.5	6 / 90
7614512S	3/8	45	22.5	6 / 84
7616508S	1/4	65	30.0	6 / 84
7616510S	5/16	65	31.5	6 / 84
7616512S	3/8	65	37.5	6 / 72
7616514S	7/16	65	39.5	6 / 72

771

771

- Bit adapter
- **Pin** retainer type
- DIN 7428

KING TONY	(inch)	Total Lenght (mm)	g	
7712-02	1/4	50	12.5	10 / 100
7712-03	1/4	75	33.5	10 / 100

752

752

- Magnetic bit holder
- **2 PC.** type
- With quick-release sleeve
- DIN 7427

KING TONY	(inch)	Total Lenght (mm)	g	
752-60	1/4	60	24.5	6 / 72
752-75	1/4	75	36.5	6 / 72

753

753

- Magnetic bit holder
- **2 PC.** type
- With quick-release sleeve
- DIN 7427

KING TONY	(inch)	Total Lenght (mm)	g	
753-63	1/4	63	33	6 / 72

Bicycle Compact Tool

20A16MR

- SPOKE WRENCHES : 14G
  EXTENSION BAR
  WRENCHES : 8/10/15 MM

	Contents	kg	
20A16MR	◉ H2 H2.5 H3 H4 H5 H6 ○ 8 9 10 mm ⊕ PH2 ⊖ 5.0	0.27	6/60

20A17MR

- SPOKE WRENCHES : 14G / 15G / 0.136"
  CHAIN TOOL
  SOCKET : 8MM

	Contents	kg	
20A17MR	◉ H2.5 H3 H4 H5 H6 ◉ 9 10 12 13 15 ⊕ PH2 ⊖ 5.0	0.28	6/60

Aluminum Folding Hex Key Wrench Set

20317MR

	PC./SET	Spec.	Contents	kg	
20317MR	7	knife type	◉ H1.5 H2 H2.5 H3 H4 H5 H6	0.09	10 / 200

Aluminum Folding Tool Set

20306PR

- Special design suitable for bike

	PC./SET	Spec.	Contents	kg	
20306PR	6	knife type	◉ H3 H4 H5 H6 ⊕ PH2 ⊖ 5.0	0.11	12 / 72

Hex Key

- MATERIAL - SNCM + V alloy steel
- FINISHING - chrome plated

1145 M

- Standard arm type
- Allen head
- Metric size - DIN ISO 2936

KING TONY	mm	ℓ (mm)	L (mm)	g	
114515M	1.5	15.5	46.5	0.9	20/400
114502M	2.0	18.0	52.0	1.8	20/400
114525M	2.5	20.5	58.5	3.0	20/400
114503M	3.0	23.5	66.0	5.0	20/400
114504M	4.0	29.5	74.0	10.0	20/400
114505M	5.0	33.0	85.0	18.0	20/400
114555M	5.5	35.5	90.5	24.0	10/400
114506M	6.0	38.0	96.5	30.0	10/200
114507M	7.0	41.0	102	45.0	10/200
114508M	8.0	44.0	108	60.0	10/200
114510M	10.0	50.0	122	105.0	10/200

1125 M
1125 S

- Extra long arm type
- Allen head
- Metric size - DIN ISO 2936
- Inch size

KING TONY	mm / inch	ℓ (mm)	L (mm)	g	
112515M	1.5	15.5	91.5	1.5	20/400
112502M	2.0	18.0	102	3.0	20/400
112525M	2.5	20.5	114.5	5.0	20/400
112503M	3.0	23.0	129	8.0	20/300
112504M	4.0	29.0	144	18.0	20/300
112505M	5.0	33.0	165	31.0	20/300
112506M	6.0	38.0	186	51.0	10/100
112507M	7.0	41.0	197	78.0	10/100
112508M	8.0	44.0	208	104.0	10/100
112510M	10.0	50.0	234	182.0	10/100
112512M	12.0	57.0	262	290.0	8/48
112514M	14.0	70.0	294	451.0	8/48
112517M	17.0	80.0	337	770.0	4/32
112519M	19.0	89.0	380	863.0	5/20
112522M	22.0	102.0	400	1590.0	4/16
112504S	1/8	23	129	8.0	20/400
112505S	5/32	29	144	18.0	20/300
112506S	3/16	33	165	31.0	20/300
112508S	1/4	38	186	51.0	10/100
112510S	5/16	44	208	104.0	10/100
112512S	3/8	50	234	182.0	10/100
112516S	1/2	57	262	290.0	8/48
112518S	9/16	70	294	451.0	8/48

Spline L- wrench

1126

- **Extra long** type
- For Spline head screws

KING TONY	SIZE	ℓ (mm)	L (mm)	g	
112605M	M5	33	165	28.2	20 / 300
112606M	M6	38	186	46.4	20 / 300
112608M	M8	44	208	90	10 / 100
112610M	M10	50	234	159.6	10 / 100
112612M	M12	53	264	237.8	10 / 80

1146

- **Standard** type
- For Spline head screws

KING TONY	SIZE	ℓ (mm)	L (mm)	g	
114605M	M5	29	83	15.6	20 / 320
114606M	M6	33	90	24.8	20 / 320
114608M	M8	39	98	47	10 / 300
114610M	M10	44	111	83.6	10 / 200
114612M	M12	53	126	127	10 / 180

Hex Key Set

- MATERIAL - SNCM + V alloy steel
- FINISHING - chrome plated

20218 MR
20219 MR
20208 MR
20209 MR

20218MR

20219MR

20208MR

20209MR

	PC./SET	Spec.	Contents	kg	
20218MR	8	knife type	2 2.5 3 4 5 6 8 10	0.33	8 / 64
20219MR	9	Standard arm plastic holder	1.5 2 2.5 3 4 5 6 8 10	0.33	6 / 48
20208MR	8	Extra long plastic holder	2 2.5 3 4 5 6 8 10	0.43	8 / 48
20209MR	9	Extra long plastic holder	1.5 2 2.5 3 4 5 6 8 10	0.44	8 / 48

20210 MR

	PC./SET	Spec.	Contents	kg	
20210MR	10	Extra long metal case	3 4 5 6 7 8 10 12 14 17	0.47	1 / 6

20208 MR 01
20208 SR 01

	PC./SET	Spec.	Contents	kg	
20208MR01	8	Extra long color box	3 4 5 6 8 10 12 14	1.25	1 / 20
20208SR01			1/8 5/32 3/16 1/4 5/16 3/8 1/2 9/16		

20208MR01 / 20208SR01

Spline L- wrench Set

20505 PR

	PC./SET	Spec.	Contents	kg	
20505PR	5	Standard type Plastic Tray	M5 M6 M8 M10 M12	0.317	56

20515 PR

	PC./SET	Spec.	Contents	kg	
20515PR	5	Extra long type Plastic Tray	M5 M6 M8 M10 M12	0.609	42

Ball Hex Key

- MATERIAL - SNCM + V alloy steel
- FINISHING - chrome plated

1130 M
1130 S

- **Long** arm with **ball point** type
- Metric size - DIN ISO 2936
- Inch size

KING TONY	mm / inch	ℓ (mm)	L (mm)	g	
113015M	1.5	15.5	63.5	1.4	20/400
113002M	2.0	18.0	77.0	2.0	20/400
113025M	2.5	20.5	87.5	4.0	20/400
113003M	3.0	23.0	93.0	7.0	20/400
113004M	4.0	29.0	104	14.0	20/400
113005M	5.0	33.0	120	25.0	20/300
113006M	6.0	38.0	141	41.0	10/150
113008M	8.0	44.0	158	84.0	10/150
113010M	10.0	50.0	180	145.0	10/150
113003S	3/32	20.5	87.5	3.6	20/400
113004S	1/8	23.0	93.0	7.4	20/400
113005S	5/32	29.0	104	14.0	20/400
113006S	3/16	33.0	120	24.0	10/300
113007S	7/32	35.5	130	33.0	10/150
113008S	1/4	38.0	141	44.0	10/150
113010S	5/16	44.0	158	82.0	10/150
113012S	3/8	50.0	180	138.0	10/150

1130M / 1130S

1120 M

- **Extra long** arm with **ball point** type
- Metric size - DIN ISO 2936

KING TONY	mm	ℓ (mm)	L (mm)	g	
112015M	1.5	15.5	91.5	1.5	20/400
112002M	2.0	18.0	102	3.0	20/400
112025M	2.5	20.5	114.5	5.0	20/400
112003M	3.0	23.0	129	8.0	20/300
112004M	4.0	29.0	144	18.0	20/300
112005M	5.0	33.0	165	31.0	20/300
112006M	6.0	38.0	186	51.0	10/100
112007M	7.0	41.0	197	78.0	10/100
112008M	8.0	44.0	208	104.0	10/100
112010M	10.0	50.0	234	182.0	10/100

Ball Hex Key Set

- MATERIAL - SNCM + V alloy steel
- FINISHING - chrome plated

20107 MR 01
20107 SR
20108 MR
20109 MR

	PC./SET	Spec.	Contents	kg	
20107MR01	7	Long arm /ball plastic holder	1130M 2.5 3 4 5 6 8 10	0.37	10 / 60
20107SR	7	Long arm /ball plastic holder	1130S 3/32 1/8 5/32 3/16 1/4 5/16 3/8	0.36	10 / 60
20108MR	8	Extra long /ball plastic holder	1120M 2 2.5 3 4 5 6 8 10	0.43	8 / 48
20109MR	9	Extra long /ball plastic holder	1120M 1.5 2 2.5 3 4 5 6 8 10	0.44	8 / 48

20107SR

20109MR

Star L- wrench

- MATERIAL - SNCM + V alloy steel
- FINISHING - chrome plated

1143

- **Standard** type
- For torx head screws

KING TONY	SIZE	ℓ (mm)	L (mm)	g	
114310	T10	18	50.0	3.5	20/400
114315	T15	20	55.5	5.5	20/400
114320	T20	24	61.5	8.0	20/400
114325	T25	26	67.5	11.0	20/400
114327	T27	30	75.5	15.0	20/400
114330	T30	36	85.5	24.5	10/200
114340	T40	41	96.5	39.0	10/200
114345	T45	46	107	57.0	10/200
114350	T50	52	122	80.0	10/200

1147

- **Standard** type
- **Tamper resistant** type
- For torx head screws

KING TONY	SIZE	ℓ (mm)	L (mm)	g	
114710	T10	18	50.0	3.5	20/400
114715	T15	20	55.5	5.5	20/400
114720	T20	24	61.5	8.0	20/400
114725	T25	26	67.5	11.0	20/400
114727	T27	30	75.5	15.0	20/400
114730	T30	36	85.5	24.5	10/200
114740	T40	41	96.5	39.0	10/200
114745	T45	46	107	57.0	10/200
114750	T50	52	122	80.0	10/200

1123

- **Extra long** type
- For torx head screws

KING TONY	SIZE	ℓ (mm)	L (mm)	g	
112310	T10	18	91.5	5.8	20/400
112315	T15	20	103	8.8	20/400
112320	T20	22	115	12.9	20/400
112325	T25	25	130	18.4	20/300
112327	T27	29	145.5	25.6	20/300
112330	T30	35	165	42.2	20/300
112340	T40	40	182	63.5	10/100
112345	T45	45	202	92.4	10/100
112350	T50	49	225	130.6	10/100

1127

- **Extra long** type
- Tamper resistant type
- For torx head screws

KING TONY	SIZE	ℓ (mm)	L (mm)	g	
112710	T10	18	91.5	5.6	20/400
112715	T15	20	103	8.6	20/400
112720	T20	22	115	12.4	20/400
112725	T25	25	130	17.8	20/300
112727	T27	29	145.5	24.6	20/300
112730	T30	35	165	40.4	20/300
112740	T40	40	182	61.6	10/100
112745	T45	45	202	89.0	10/100
112750	T50	49	225	126.2	10/100

Star L- wrench Set

- MATERIAL - SNCM + V alloy steel
- FINISHING - chrome plated

20307 PR
20407 PR

	PC./SET	Spec.		Contents	kg	
20307PR	7	Standard type plastic holder	1143	T10 T15 T20 T25 T27 T30 T40	0.13	18 / 144
20407PR	7	Standard type Tamper resistant plastic holder	1147	T10 T15 T20 T25 T27 T30 T40	0.13	18 / 144

20308 PR

	PC./SET	Spec.		Contents	kg	
20308PR	8	knife type	1143	T9 T10 T15 T20 T25 T27 T30 T40	0.20	12 / 72

20309 PR
20319 PR

	PC./SET	Spec.		Contents	kg	
20309PR	9	Standard type plastic holder	1143	T10 T15 T20 T25 T27 T30 T40 T45 T50	0.3	8 / 64
20319PR	9	Extra long type plastic holder	1123	T10 T15 T20 T25 T27 T30 T40 T45 T50	0.45	8 / 48

Star L- wrench Set

- MATERIAL - SNCM + V alloy steel
- FINISHING - chrome plated

20409 PR
20419 PR

	PC./SET	Spec.		Contents	kg	
20409PR	9	Standard type Tamper resistant plastic holder	1147	T10 T15 T20 T25 T27 T30 T40 T45 T50	0.34	8 / 64
20419PR	9	Extra long type Tamper resistant plastic holder	1127	T10 T15 T20 T25 T27 T30 T40 T45 T50	0.45	8 / 48

L- type Wrench

- MATERIAL - SNCM + V alloy steel
- FINISHING - chrome plated with black tip

1160

- Hexagon with **ball point** head
- Metric size

KING TONY	(mm)	ℓ (mm)	L (mm)	g	
116002M	2.0	100	150	19.0	10 / 200
116025M	2.5	100	150	21.5	10 / 200
116003M	3.0	100	150	25.0	10 / 200
116004M	4.0	100	150	32.5	10 / 200
116005M	5.0	150	215	74.0	10 / 200
116006M	6.0	150	215	92.0	10 / 200
116007M	7.0	150	215	120.0	10 / 200
116008M	8.0	200	280	212.5	10 / 80
116010M	10.0	200	280	289.5	10 / 80

1163

- For torx internal screws
- Tamper resistant type

KING TONY	SIZE	ℓ (mm)	L (mm)	g	
116310	T10	100	150	24.0	10 / 200
116315	T15	100	150	27.0	10 / 200
116320	T20	100	150	31.0	10 / 200
116325	T25	100	150	35.5	10 / 200
116327	T27	150	215	69.5	10 / 200
116330	T30	150	215	86.0	10 / 200
116340	T40	150	215	105.5	10 / 200
116345	T45	200	280	181.5	10 / 80
116350	T50	200	280	214.5	10 / 80

1165

- For hexagon head screws
- Metric size

KING TONY	(mm)	ℓ (mm)	L (mm)	g	
116502M	2.0	100	150	19.0	10 / 200
116525M	2.5	100	150	21.5	10 / 200
116503M	3.0	100	150	25.0	10 / 200
116504M	4.0	100	150	32.5	10 / 200
116505M	5.0	150	215	74.0	10 / 200
116506M	6.0	150	215	92.0	10 / 200
116507M	7.0	150	215	120.0	10 / 200
116508M	8.0	200	280	212.5	10 / 80
116510M	10.0	200	280	289.5	10 / 80

L- type Wrench Set

- MATERIAL - SNCM + V alloy steel
- FINISHING - chrome plated with black tip

22106MR

22306PR

22106 MR
22306 PR

	PC./SET	Spec.	Contents	kg	
22106MR	6	Ball & hex two way type	1160 3 4 5 6 7 8	0.68	20
22306PR	6	Torx head two way type	1163 T10 T15 T20 T25 T30 T40	0.46	20

22108MR

22208MR

22309PR

22108 MR
22208 MR
22309 PR

	PC./SET	Spec.	Contents	kg	
22108MR	8	Ball & hex two way type	1160 2 2.5 3 4 5 6 8 10	0.97	10
22208MR	8	Hex head two way type	1165 2 2.5 3 4 5 6 8 10	0.97	10
22309PR	9	Torx head two way type	1163 T10 T15 T20 T25 T27 T30 T40 T45 T50	1.0	10

22118MR

22218MR

22319PR

22118 MR
22218 MR
22319 PR

	PC./SET	Spec.	Contents	kg	
22118MR	8	Ball & hex two way type	1160 2 2.5 3 4 5 6 8 10	1.1	12
22218MR	8	Hex head two way type	1165 2 2.5 3 4 5 6 8 10	1.1	12
22319PR	9	Torx head two way type	1163 T10 T15 T20 T25 T27 T30 T40 T45 T50	1.2	12

T - type Wrench

- MATERIAL - SNCM + V alloy steel
- FINISHING - chrome plated with black tip

1150 M

- Hexagon with ball point head
- Metric size

KING TONY	(mm)	ℓ (mm)	L (mm)	g	
115002M	2.0	100	137	28	10 / 200
115025M	2.5	100	137	30	10 / 200
115003M	3.0	100	137	32	10 / 200
115004M	4.0	100	137	38	10 / 200
115005M	5.0	150	188	65	10 / 200
115006M	6.0	150	188	79	10 / 200
115008M	8.0	200	240	159	10 / 120
115010M	10.0	200	240	217	10 / 120

1155 M

- Hexagon head
- Metric size

KING TONY	(mm)	ℓ (mm)	L (mm)	g	
115502M	2.0	100	137	28	10 / 200
115525M	2.5	100	137	30	10 / 200
115503M	3.0	100	137	32	10 / 200
115504M	4.0	100	137	38	10 / 200
115505M	5.0	150	188	65	10 / 200
115506M	6.0	150	188	79	10 / 200
115508M	8.0	200	240	159	10 / 120
115510M	10.0	200	240	217	10 / 120

1153

- For torx head screws

KING TONY	SIZE	ℓ (mm)	L (mm)	g	
115310	T10	100	137	40	10 / 200
115315	T15	100	137	40	10 / 200
115320	T20	100	137	40	10 / 200
115325	T25	100	137	40	10 / 200
115327	T27	150	188	73	10 / 200
115330	T30	150	188	74	10 / 200
115340	T40	150	188	88	10 / 200
115345	T45	200	240	173	10 / 120
115350	T50	200	240	173	10 / 120

21108 MR
21208 MR
21309 PR

21108MR

21208MR

21309PR

	PC./SET	Spec.	Contents	kg	
21108MR	8	Ball hex Stand type	1150 2 2.5 3 4 5 6 8 10	1.1	1 / 12
21208MR	8	Hexagon Stand type	1155 2 2.5 3 4 5 6 8 10	1.1	1 / 12
21309PR	9	Torx head Stand type	1153 T10 T15 T20 T25 T27 T30 T40 T45 T50	1.2	1 / 12

Tee-Handle Wrench NEW

- MATERIAL - Chrome vanadium steel
- FINISHING - chrome plated

1195

- 6 Point
- Metric Size
- For gexagon head screws
- The handle pin can be removed for another wrench

KING TONY	(mm)	ℓ (mm)	L (mm)	g	
119502M	H2	64	126.5	22	10 / 200
119525M	H2.5	64	126.5	22	10 / 200
119503M	H3	64	126.5	23	10 / 200
119504M	H4	89.5	181	62	10 / 100
119505M	H5	89.5	182	65	10 / 100
119506M	H6	105	210	120	6 / 48
119508M	H8	124	250	224	4 / 32
119510M	H10	145	300	386	5 / 50

Notes

Other Tools

- Punch
- Second Cut File Set
- Flat Chisel
- Gear Puller & Sawing
- Hammer
- Saw & Riveter
- Measure Tape & Set
- Measuring
- Metric Feeler Gauge
- Blow Gun

KING TONY
GENUINE HICKORY
GENUINE HICKORY
KING TONY

Punch

- MATERIAL - chrome vanadium alloy steel
- FINISHING - phosphate sunk

761

761 Center punch	KING TONY	Ø x L	Overall Length (mm)	g	
	76103-04	3 x 100	100	34	12 / 336
	76104-05	4 x 120	120	59	12 / 336
	76105-06	5 x 150	150	116	12 / 144

762

762 Flat Chisel	KING TONY	Ø x L	Overall Length (mm)	g	
	76213-04	13 x 100	100	69	12 / 336
	76215-05	15 x 125	125	70	12 / 336
	76217-06	17 x 150	150	145	12 / 144
	76220-07	20 x 175	175	300	12 / 144
	76223-08	23 x 200	200	300	12 / 72
	76224-10	24 x 250	250	388	4 / 40
	76226-12	26 x 300	300	650	4 / 32

763

763 Starter punch	KING TONY	Ø x L	Overall Length (mm)	g	
	76301-05	1 x 120	120	57	12 / 336
	76302-05	2 x 120	120	58	12 / 336
	76303-05	3 x 120	120	60	12 / 336
	76304-05	4 x 120	120	60	12 / 336
	76305-05	5 x 120	120	64	12 / 336
	76306-05	6 x 120	120	64	12 / 336
	76307-05	7 x 120	120	100	12 / 240
	76308-05	8 x 120	120	100	12 / 240
	76309-06	9 x 150	150	130	12 / 144
	76310-06	10 x 150	150	132	12 / 144

764

764 Pin punch	KING TONY	Ø x L	Overall Length (mm)	g	
	76402-45	2 x 30	115	32	10 / 640
	76403-05	3 x 40	125	34	10 / 640
	76404-06	4 x 50	150	60	10 / 250
	76405-65	5 x 50	165	71	10 / 280
	76406-07	6 x 50	180	125	10 / 150
	76408-08	8 x 50	200	130	10 / 120
	76410-85	10 x 65	215	155	12 / 120
	76412-09	12 x 70	230	356	10 / 80
	76414-10	14 x 75	250	502	6 / 48

Pin Punch Set

KING TONY	Contents		kg	
1006PR	764	Ø 2 x 30 Ø 3 x 40 Ø 4 x 50 Ø 5 x 50 Ø 6 x 50 Ø 8 x 50	0.57	1/20
1009PR	764	Ø 2 x 30 Ø 3 x 40 Ø 4 x 50 Ø 5 x 50 Ø 6 x 50 Ø 8 x 50 Ø10 x 65 Ø12 x 70 Ø14 x 75	1.67	1/12
1010PR	761 763 764	Ø 3 x 100 Ø 4 x 120 Ø 5 x 150 Ø 3 x 120 Ø 6 x 120 Ø 8 x 120 Ø 3 x 40 Ø 4 x 50 Ø 5 x 50 Ø 6 x 50	0.86	1/24
1006PRN	764	Ø 2 x 30 Ø 3 x 40 Ø 4 x 50 Ø 5 x 50 Ø 6 x 50 Ø 8 x 50	0.57	1/20
1009PRN	764	Ø 2 x 30 Ø 3 x 40 Ø 4 x 50 Ø 5 x 50 Ø 6 x 50 Ø 8 x 50 Ø10 x 65 Ø12 x 70 Ø14 x 75	1.67	1/12

Tetoron pouch:

1006PR

1009PR

1010PR

Nylon pouch:

1006PRN

1009PRN

Flat Chisel & Punch Set

1090PR1

- 90 PC. flat chisel & punch set

KING TONY		Contents			Each Q'ty
1090PR1	1090PR	761 762 763	Ø 4 x 120 Ø 5 x 150 17 x 150 mm 20 x 150 mm 23 x 200 mm 24 x 250 mm 4 x 120 mm 8 x 120 mm	764 767	Ø 3 x 125 Ø 4 x 150 Ø 5 x 165 Ø 6 x 180 Ø 10 x 215 150 mm 200 mm	6
	8711B				

	kg	CUFT	Screwdriver shelf size (mm)
1090PR	13.5	0.34'	109 x 81 x 39
8711B	6.2	0.9'	650 x 250 x 210

Second Cut File

1005ZQ 1015ZQ

- 8" & 10" second cut files without handle
- Available with T2 cut for precision work

KING TONY	Contents	L (inch)	kg	
1005ZQ (for 8")	▮ 75102-08 ◖ 75202-08 ● 75302-08 ▲ 75402-08 ■ 75502-08	8"	0.6	1/20
1015ZQ (for 10")	▮ 75102-10 ◖ 75202-10 ● 75302-10 ▲ 75402-10 ■ 75502-10	10"	1.0	1/10

1005ZQ / 1015ZQ

1005GQ 1015GQ

- 8" &10" second cut files with handle
- Available with T2 cut for precision work

KING TONY	Contents	L (inch)	kg	
1005GQ (for 8")	▮ 75102-08G ◖ 75202-08G ● 75302-08G ▲ 75402-08G ■ 75502-08G	8"	0.9	1/20
1015GQ (for 10")	▮ 75102-10G ◖ 75202-10G ● 75302-10G ▲ 75402-10G ■ 75502-10G	10"	1.4	1/8

1005GQ / 1015GQ

91248 91249

- Spare handles for file

KING TONY	Contents	A (mm)	L (mm)	g		Spare handles for files	Second cut files without handles
91248 (for 8")	91240 ◖ 91245 ● 91246 ▮ 91244	32	123	65	80	◖ 91245	▮75102-08
						● 91246	●75402-08 ▲75302-08 / ■75502-08
						▮ 91244	◖75202-08
91249 (for 10")	91240 ▮ 91241 ● 91242					▮ 91241	▮75102-10 / ◖75202-10
						● 91242	●75402-10 ▲75302-10 / ■75502-10

91248 / 91249

Flat Chisel

767

- For flat chisel

KING TONY	A (mm)	B (mm)	L (mm)	g	
76717-05	17.1	12.6	125	88	12 / 240
76721-06	19.8	15.0	150	130	6 / 144
76724-08	25.0	18.5	200	275	12 / 72
76729-10	29.3	21.7	250	470	8 / 64

Flat Chisel Set

11104PR

KING TONY	Contents	kg	
11104PR	767: 76717-05 76721-06 76724-08 76729-10 87108	1.37	1/10

11104PR10

KING TONY	Contents	kg	
11104PR10	767: 76717-05 76721-06 76724-08 76729-10	1.0	1/10

Metal Holder

87108

- For flat chisel

KING TONY	H (mm)	L (mm)	g	
87108	140	160	410	12

Screw Extractor Set

11205SQ

- Quick and easy way to remove broken screws, pipes, bolts and studs.

KING TONY		Contents	Specification	g	
11205SQ	5PC.	2127-06M 2127-08M 2127-11M 2127-14M 2127-18M	1/8" - 1/4" 1/4" - 5/16" 5/16" - 7/16" 7/16" - 9/16" 9/16" - 3/4"	103	25 / 100

Gear Puller

Material - chrome vanadium alloy steel
Finishing - chrome plated & phosphate sunk

7962

Two-Jaw gear puller

KING TONY	SIZE (inch)	A (mm)	B (mm)	kg	
7962-03	3	75	60	0.44	1 / 40
7962-04	4	100	95	0.78	1 / 20
7962-06	6	150	150	1.65	1 / 10
7962-08	8	200	235	3.50	1 / 5
7962-12	12	300	280	7.00	1 / 2

7963

Three-Jaw gear puller

KING TONY	SIZE (inch)	A (mm)	B (mm)	kg	
7963-03	3	75	60	0.55	1 / 40
7963-04	4	100	95	1.06	1 / 20
7963-06	6	150	150	2.25	1 / 10
7963-08	8	200	235	4.50	1 / 5
7963-12	12	300	280	11.00	1 / 2

Hammer

- Material - high quality alloy steel
- Handle - high-safety hickory

CAUTION When using any hammer tool, always remember to protect your sight against the risk of flying chips.

7811

- American style.
- Forged and hardened steel
- Wood and metal wedge
- GGG, H86C

KING TONY	H.W (g)	H.W (LB)	H.W (oz)	A (mm)	H (mm)	L (mm)	g	
7811-08	245	1/2	8	25	80	300	375	6 / 60
7811-12	370	3/4	12	29	93	300	485	6 / 48
7811-16	485	1	16	32.5	103	353	640	6 / 36
7811-24	765	1-1/2	24	35.5	122	405	975	1 / 24
7811-32	925	2	32	40.5	125	405	1200	6 / 24
7811-40	1125	2-1/2	40	42.2	133	405	1395	4 / 12

7821

- German style
- Forged and hardened steel
- Wood and metal wedge
- DIN 1041

KING TONY	H.W (g)	A (mm)	H (mm)	L (mm)	g	
7821-30	395	23	103	300	400	12 / 48
7821-50	615	27	120.5	320	660	6 / 36
7821-80	990	33	130	350	960	12 / 24

7823

- Engineer's hammer
- DIN1041

KING TONY	H.W (g)	A (mm)	H (mm)	L (mm)	g	
7823-10	1000	36	135	360	1121	9/18
7823-15	1500	42	145	380	1606	6/12
7823-20	2000	47	155	400	2106	6/12

Hammer

- Material - high quality alloy steel
- Handle - high-safety hickory

CAUTION When using any hammer tool, always remember to protect your sight against the risk of flying chips.

7822

- Riveting hammer
- NF E71-016

KING TONY	H.W (g)	A (mm)	B (mm)	H (mm)	L (mm)	g	
7822-25	315	25	22	85	315	489	10/40
7822-30	400	30	26	95	323	650	10/40
7822-35	630	35	31	105	353	1000	9/18
7822-40	800	40	35	115	362	1330	8/16
7822-45	1250	45	40	124	385	1790	8/16
7822-50	1600	50	44	135	400	2458	6/12

7822

7833

- Lump hammer
- DIN6475

KING TONY	H.W (g)	A (mm)	H (mm)	L (mm)	g	
7833-10	1000	40	95	260	1065	7/14
7833-12	1250	43	100	260	1425	6/12
7833-15	1500	45	110	280	1778	6/12
7833-20	2000	50	120	300	2142	4/8

7833

7851

- Dead blow hammer

KING TONY	H.W (g)	A (mm)	H (mm)	L (mm)	g	
7851-08	227	43	81	272	585	6/24
7851-16	454	46	100	304	849	6/24
7851-24	680	49	100	322	884	6/24
7851-32	907	55	100	342	1090	6/24
7851-40	1134	58	110	342	1218	6/24
7851-48	1361	61	123	355	1511	6/12
7851-64	1814	67	136	368	1874	6/12

7851

7842

- Soft face hammer (changable head)
- Material : Polyurethane

KING TONY	A (mm)	H (mm)	L (mm)	g	
7842-22	22	74	260	102	10/40
7842-28	28	88	300	160	10/40
7842-35	38	100	320	312	8/32
7842-45	45	112	320	468	8/32
7842-60	60	136	380	882	6/12

7842

915

- Spare faces for item 7842
- H : Hard / S : Soft
- Material : Polyurethane

KING TONY	Hardness (shore A)	A (mm)	g	
91522H/S	90°/75°	22	11	10/160
91528H/S	90°/75°	28	24	10/100
91535H/S	90°/75°	38	36	6/120
91545H/S	90°/75°	45	65	6/36
91560H/S	90°/75°	60	125	6/24

915

Saw

7911-12

- Sliding metal bow
- Lightweight, resistant to anti oxidization
- Two blade positions 45° and 90° including flush cut
- Ergonomics handle with hand stop oil resistant, moisture-resistant

KING TONY	Adjustable Blade Length(mm)	Overall Length (mm)	g	
7911-12	305	400	628	6 / 36

7911-12

7921-12

- Sliding metal bow
- Handle material : ABS+TPR.
- Lightweight & anti-slippery.
- Four blade positions 45°, 90°, 135°, 180° including flush cut
- Spare blades can be stored.

KING TONY	Adjustable Blade Length(mm)	Overall Length (mm)	g	
7921-12	300	510	555	1 / 50

7921-12

Way to replace the blade

1.

To loosen the button.

2.

To press the button then pull the tube to take out the blade.

3.

Replace the new blade.

Riveter

21-20-101

- Capacity Ø 4.8mm
- Stainless Steel Riveter
- Drop-forged aluminum body

KING TONY	L (mm)	L (inch)	g		Nosepiece (mm)	Nosepiece (inch)
21-20-101	260	10-1/4	588	12/24	Ø 2.4	3/32
					Ø 3.2	1/8
					Ø 4.0	5/32
					Ø 4.8	3/16

Ø 2.4~4.8mm

21-20-102

- 4 size quickly and easily to change
- The drive can be used in 90° and 180°

KING TONY	L (mm)	L (inch)	g		Nosepiece (mm)	Nosepiece (inch)
21-20-102	278	11	778	6 / 24	Ø 2.4	3/32
					Ø 3.2	1/8
					Ø 4.0	5/32
					Ø 4.8	3/16

Riveter Set

21-20-07MR

KING TONY	Contents	Each Q'ty
21-20-07MR	4 x 8 mm, 4 x 10 mm, 4 x 10 mm, 4.8 x 8 mm, 4 x 8 mm, 4.8 x 10 mm	20
	21-20-101	

kg		Plastic case size (mm)
1.06	1 / 16	276 x 160 x 46 (0.122 cuft)

Riveter

79711

- Capacity Ø 6.4mm
- Stainless Steel Riveter
- Drop-forged aluminum body

KING TONY	L (mm)	L (inch)	g		Nosepiece (mm)	Nosepiece (inch)
79711	460	18	1488	1/12	Ø 3.2	1/8
					Ø 4	5/32
					Ø 4.8	3/16
					Ø 6.4	1/4

Ø 3.2~6.4mm

Measuring Tape

- Material:ABS
- Metric/inch system
- Side and bottom Tape-lock-buttom

79083

KING TONY	L (M)	B (mm)	g	
79083-03C	3	13	116	12 / 72
79083-05C	5	19	210.4	12 / 72

79084

- Magnet hook

KING TONY	L (M)	B (mm)	g	
79084-03C	3	16	116.6	12 / 72
79084-05C	5	19	210.4	12 / 72

Measuring Tape Set

- Material:ABS
- Metric/inch system
- Side and bottom Tape-lock-buttom

790831CQ

- 12 PC. measuring tape set

	PC/SET	Contents	kg	
79083-03C	6		12.2	1 / 6
79083-05C	6			

790841CQ

- 12 PC. measuring tape set
- Magnet hook

	PC/SET	Contents	kg	
79084-03C	6		12.2	1 / 6
79084-05C	6			

Measuring

79061

- 1 side both edges photo-engraved mm-scale
- Flexible stainless graduated rule

KING TONY	L (mm)	W (mm)	T (mm)	g	
79061-12	300	23.7	1.0	65	20 / 400
79061-20	500	28.5	1.2	145	10 / 160
79061-40	1000	35.0	1.2	360	10 / 20

77121

- Made of stainless steel with fine adjustment
- Vernier calipers with external upper jaw

KING TONY	A (mm)	B max (mm)	Vernier (mm)	H X S (mm)	g	
77121-08	60	200	0.02	20 x 4	860	1/10

77131

- Parallax free bevel vernier calipers

KING TONY	A (mm)	B max (mm)	Vernier (mm)	H X S (mm)	g	
77131-06	40	150	0.02	16 x 3	320	1/50
77131-08	50	200	0.02	20 x 4	450	1/50

77141

- Open slider digital calipers
- Manual power on / off
- Metric / inch system interchange at any position with data output interface

KING TONY	A (mm)	B (mm)	Accuracy (mm)	Vernier (mm)	g	
77141-06	40	150	0.01	0.01	320	1/20
77141-08	50	200	0.01	0.01	485	1/50

Metric Feeler Gauge

- Material: Blade material of stainless steel

77340-20

- 20 BLADES METRIC FEELER GAUGE

KING TONY	Number of Blades	Width x Length of Blades (mm)	Contents:	g	
77340-20	20	10 x 100	0.05, 0.10, 0.15, 0.20, 0.25, 0.30, 0.35, 0.40, 0.45, 0.50, 0.55, 0.60, 0.65, 0.70, 0.75, 0.80, 0.85, 0.90, 0.95, 1.00 mm	105	50 / 200

Metric Feeler Gauge

• Material: Blade material of stainless steel

77335-25

▪ 25 BLADES METRIC FEELER GAUGE

KING TONY	Number of Blades	Width x Length of Blades (mm)	Contents:	g	
77335-25	25	13 x 85	0.04, 0.05, 0.06, 0.07, 0.08, 0.09, 0.10, 0.15, 0.20, 0.25, 0.30, 0.35, 0.40, 0.45, 0.50, 0.55, 0.60, 0.65, 0.70, 0.75, 0.80, 0.85, 0.90, 0.95, 1.00 mm	110	50 / 200

Blow Gun

79900

- High pressure nozzle
- Sure grip handle design
- Ideal for cleaning surfaces

KING TONY	L (mm)	g	
79900-04	242	200	2 / 60
79900-10	402	240	2 / 50
79900-13	472	260	2 / 50
79900-20	652	300	2 / 50

Specification:

Body material	nylon fiber	Air consumption (90psi)	1/4" hose-13cfm-350l/min 3/8" hose-15cfm-430l/min
Nozzle material	steel		
Working pressure	75~120psi/5.0~8.0kgs		
Max pressure	220psi/15kgs	Air inlet thread	Sae size : 1/4" npt Metric size : 1/4" pt
Sound pressure	85-90db		

Blow Gun Set

799001DQ NEW

- 18 PC. blow gun set

	PC./SET	Contents	kg	
79900-04	8		2.8	1 / 6
79900-10	6			
79900-13	4			
SY-211M	18	(European type)		

360° Cast Steel Beach Vice

9TZ11 NEW

- Cast steel body and silde ideal for heavy duty applications
- Ductile cast iron screw pitched acme thread ensures long life and positive action
- Serrated jaws design provide good grip
- 360 ° degree swivel base allow operator to approach any directions

KING TONY	JAW OPENING inch / mm	THROAT DEPTH	g	/
9TZ11-04	4" / 100	2-1/4"	7500	1 / 1
9TZ11-05	5" / 125	2-5/8"	11000	1 / 1
9TZ11-06	6" / 150	3"	14500	1 / 1
9TZ11-08	8" / 200	3-1/2"	18000	1 / 1

Automotive Tools

- Engine Series
- Undercar Series
- Body Series
- Battery & Electrical
- General Tools

ISO

CE Certificate

G.S. Approval

VDE Certificate

Q'ty / Carton

Engine Series

Q'ty / Box

Undercar Series

Weight (g)

Battery & Electrical

Diameter

Body Series

External Circlip

General Tools

Internal Circlip

Circlip Pliers Head Size

Bolt

Ribe Bit Socket

Tool Trolley Set

936-003 MR 03 NEW

- 183 PC. tool trolley set

936-003MR03

Tray No.	Set	Use Drawer
Tray # 4	375 x 265 mm 9-1219MR01 34 9-1709MR 35 9-31919MR 42 9-4328MR 32 9-5575MR 33 9-40207GP01 36	 B3
	 1006PR 282 84700612B	

Tool trolley:

87432-5B 3

	Spec.	kg	CUFT
936-003MR03-A	87432-5B	56	12.24
936-003MR03-D	183 PC. trolley contents	17.4	2.41

Curved Hose Clamp Pliers

9AA21

- Designed to remove and install flat band hose clamp in hard-to reach areas.
- Locking latch securely holds clamp in position.
- 45° designed to fit some clamps in deep position.

KING TONY	L (mm)	L (inch)	Ø (mm)	g	
9AA21	220	8-1/2	18~53	224	12 / 48

Flexible Hose Clamp

9AA31

- For replacement of fuel, oil and water hose.
- Hose clamps with flexible 630mm wire.
- Convenient for working hidden areas and long distance.

KING TONY	L1 (mm)	L1 (inch)	L2 (mm)	L2 (inch)	Ø (mm)	g	
9AA31	630	25	225	9	12~53	528	12 / 36

Valve Stem Seal Pliers

9AD11

- For removing valve stem seals in multi-valves engines.
- Jaw longitudinal toothed - avoids slipping down.
- For deeply leveled valve stem seals.

KING TONY	L (mm)	L (inch)	Ø (mm)	g	
9AD11	275	11	9.5	400	12 / 48

Piston Ring Compressor

9AC

- The square adjustment key wrench forces the rings into the grooves and cluch controls prevent them from expanding.

KING TONY	H (mm)	H (inch)	Ø (mm)	Ø (inch)	g	
9AC125-32	80	3-1/4	57~125	2-1/4~5	260	1/60
9AC125-40	100	4	57~125	2-1/4~5	280	1/60
9AC175-32	80	3-1/4	90~175	3-1/2~7	300	1/60
9AC175-40	100	4	90~175	3-1/2~7	320	1/60
9AC175-66	165	6-3/4	90~175	3-1/2~7	530	1/40

Piston Ring Pliers

9AP

- Special steel
- Nickle - plated
- For removing and mounting piston rings

KING TONY	L (mm)	L (inch)	Capacity (mm)	g	
9AP100	212	8-11/32	50~100	323	12 / 48
9AP120	227	8-15/16	80~120	354	12 / 48
9AP160	253	9-61/64	110~160	458	12 / 48

16 PC. Cup Type Oil Filter Wrench Kit

9AE2016

- Withstands up to 85 ft.lbs
- Coated with electro-black oxide finish for protection against rust.
- 1PC. 1/2(F)x3/8"(M) adapter
- 1PC. 3 legged oil filter wrench(65-120mm)

9AE2-6606	66mm(2-19/32")-6 flutes-1 step Fiat(Punto, 1.2), Renault(Clio 1.2 Express, Kangoo. Rapid. Twingo), etc....
9AE2-7476	74 to 76mm(2-29/32" to 3")-15 flutes-2 step Fits Fram, AC, Saturn, Opel, VW, Audi, Mercedes, etc....
9AE2-7608	76mm(3")-8 flutes-1 step Fiat(z.B. Marea), Lancia(z.B. Delta), etc....
9AE2-7612	76mm(3")-12 flutes-1step Fiat(z.B. Ducato, Scudo, Ulysee),Renault, (Megane, Laguna, Espace III.), etc....
9AE2-7614	76mm(3")-14 flutes-1step Fits Champion, Champ Lee, Purolator, Mopar, VW, Porsche,Mercedes, BMW, Audi, Toyota, Opel, etc....
9AE2-8616	86mm(3-3/8")-16 flutes-1step Volvo(S40, S60, S70, S80) etc....
9AE2-8618	86mm(3-3/8")-18 flutes-1step VW. Golf.(MKIII. Tdi, Passat Tdi), Audi A6 Tdi, Renault(Clio, Rapid 1.9D, Laguna.Safrane. Espace 2.1D). Citroen, Peugeot, Renault, etc..
9AE2-9210	92mm(3-40/64")-10 flutes-1step Fiat, Cinquecento, Coupe, Croma, Fiat, Panda. Regata, Ritmo Fiat, Seicento. Tempra, Tipo, Lancia(Beta. Dedra. Kappa. Monte. Carlo. Prisma. Thema. Trevi), etc....
9AE2-9315	93mm(3-21/32")-15 flutes-1step Fits Casite, Champ, Champion, GM, Fram, Hastings,Purolator, Wix, Nissan, Volvo, Mazda, Audi, VW, Porsche, Renault, etc....
9AE2-9345	93mm(3-21/32")-45 flutes-1step VW-Audi.(TDi 2.4, 2.6, 2.8L), etc....
9AE2-9618	96mm(3-3/4")-18 flutes-1step Audi(A4 Tdi, VW Passat,97 Tdi), Renault (Laguna 2.2d. Safrane2.2D. Espace 2.2D. R19 2.2D. Rapid, Megane,1.9/2.1D. Tdi) etc..
9AE2-10615	106mm(4-11/64")-15 flutes-1step Fiat(Ducato 2.5D. Td), etc....
9AE2-10815	108mm(4-8/32")-15 flutes-1step Volvo(C70. S70. V70. Tdi. TD)(850 Tdi. TD) etc....
9AE2-10818	108mm(4-8/32")-18 flutes-1step Renault(Espace, Laguna, Master, Safrane, Traffic 2.4, 2.5, 2.8D. TD), etc....
9AE423	3 legged oil Filter Tool 63-102mm(2-1/2" to 4")
9AE221	1/2" drive adaptor 1/2" F x 3/8" M

KING TONY	kg	
9AE2016	3.6	1 / 5

Three-Legs Oil Filter Wrench

9AE41

- The claw-type filter is available for removing all oil filters from 2-1/2" to 4"-3/4" (63-120mm) in diameter.
- Suitable for use with 3/8" or 1/2" square drive tool.
- Coated with electro-black oxide finish for protection against rust.

KING TONY	A (inch)	B (inch)	Ø (mm)	Ø (inch)	g	
9AE41	1/2	3/8	63~120	2-1/2~4-3/4	597	6 / 36

Three-Legs Oil Filter Wrench

9AE42

- The claw-type filter is available for removing all oil filters from 2-1/2" to 4" (63-102mm) in diameter.
- Suitable for use with 3/8" or 1/2" square drive tool.
- Coated with electro-black oxide finish for protection against rust.

9AE42

9AE221

9AE423

KING TONY	A (inch)	B (inch)	Ø (mm)	Ø (inch)	g	
9AE221	1/2	3/8	-	-	39	-
9AE42	1/2	3/8	63~102	2-1/2~4	395	12 / 48
9AE423	-	3/8	63~102	2-1/2~4	356	12 / 48

Two Jaws Oil Filter Wrench

9AE52

- The claw-type filter is available for removing all oil filters from 2-3/8" to 3-1/8" (60-80mm) in diameter.
- Suitable for use with 1/2" square drive tool.
- Coated with electro-black oxide finish for protection against rust.

KING TONY	A (inch)	Ø (mm)	Ø (inch)	g	
9AE52	1/2	60~80	2-3/8~3-1/8	470	6 / 36

10 PC. Valve Spring Compressor Set

9AH11

- Complete Service tool kit for OHV & OHC petrol or diesel engines on Audi, Nissan, Toyota, Chrysler, Honda, Mazda, Mitsubishi, Saturn, Lexus, Hyundai, Infiniti, Porsche, Volvo, VW.

KING TONY	L (mm)	L1 (mm)	H (mm)	kg	
9AH11	515	275	95	3.39	1/ 5

5 PC. Valve Spring Compressor Set

9AH025

- Suitable for use on large engines & diesel engines.
- Capacity: 35~140mm
- Unique direct action compressor lever gives improved visibility & ease of use in areas of difficult access. Dual size in 25 and 30mm adapter.

KING TONY	A (mm)	B (mm)	L (mm)	kg	
9AH025	35~140	280	390	2.7	1/ 5

Universal Clutch Aligner Set

9AK11

- Designed to make alignment and assembly of cluth.
- Specially designed for those vehicles equipped with late-model front wheel drives-without pilot bearing in flywheel.

KING TONY	Ø (mm)	kg	
9AK11	15.5~27	0.19	1/ 20

COMPLETE KIT FOR ASSEMBLY AND DISASSEMBLY OF SELF ADJUSTING CLUTCHES

9AK21 NEW

- Allows operations on clutch equipped with this device in order to prevent any damage to system and to keep adapter ring in right position.
- Istallation avoiding clutch deformation.
- Prevents plate distortion which may prevent the clutch from disengaging or cause dragging.
- Features a refitting tool, allowing the clutch adjuster to be wound back, to disk pushing plate.
- Suitable for most SAC(Self Adjusting Clutches 3 and 4 holes)

KING TONY	kg	
9AK12	10.75	1/ 2

Pulley Removing Wrench

9AL

- To lock the pulley during removing or assembling any type of pulley retaining bolt.

KING TONY	L (mm)	L (inch)	Ø (mm)	g	
9AL11	365	(14-3/8)	40-140	540	12 / 36
9AL12	365	(14-3/8)	40-140	540	12 / 36

1.
Compressors

2.
Water pump pulley

3.
Alternator pump pulley

4.
Oil filter removing & assembling

21 PC. Oil Drain Plug Key Set

9AR11 NEW

- Suitable for sump plugs on engine, gearbox and back axle
- Contents:
  Hex key socket: 8, 9, 10, 12, 13, 14, 17 mm
  Square socket : 5/16", 3/8", 7, 8, 10, 11, 12, 13, 14 mm
  Torx socket : T45
  Triangular socket : 10mm
  Spline (TAMPER) socket : M16
  Square drive socket : 10mm
  3/8"drive sliding T-handle

KING TONY	kg	
9AR11	1.7	1 / 10

10 PC. Bearing Race and Seal Driver Set

9BA11

- Quickly and easily to insert bearing race.
- Collars fit most standard wheel bearing size.
- Helps reduce damage to both race and axle housing.
- 9 collar sizes:
  (1)1.555"/39.5mm (2)1.752"/44.5mm
  (3)1.968"/50mm (4)2.322"/59mm
  (5)2.480"/63mm (6)2.559"/65mm
  (7)2.834"/72mm (8)2.992"/76mm
  (9)3.189"/81mm

9BA11	1800	1 / 10

12 PC. Two Sets Bearing Separator Assembly

9BA21

- 2 Sets Bearing Separator & Bolts
  Capacity 30mm-50mm
  (Bolt ∅ 3/8" x L 120mm x 24t 415 Hardened 42°-45°)
  Capacity 50mm-75mm
  (Bolt ∅ 1/2" x L 135mm x 20t 415 Hardened 42°-45°)
- 4 PC. Main Rod (Hex Bar 17mm 3/8" x L 127mm x 16t)
- 4 PC. Extension Rod (Hex Bar 14mm 3/8" x L 102mm x 16t)
- 1 PC. Beam (Carbon Steel)
- 1 PC. Central Bolt (9/16" x L 175 x 10t/inch Carbon Steel)

9BA21	5400	1 / 2

8 PC. Pressure Screw Bearing Separator Puller Set

9BA22

- Set Bearing Separator & Bolts
  Capacity 75mm-105mm
  (Bolt ∅ 5/8" x 18t 415 Hardened 42°-45°)
- 2 PC. Main Rod (8" x 1.75P Carbon Steel)
- 2 PC. Extension Rod (8" x 1.75P Carbon Steel)
- 1 PC. Beam (Carbon Steel)
- 1 PC. Central Bolt (∅18.65mm x L 11.5 " x 10t)
- 1 PC. Nut (Carbon Steel)

9BA22	8950	1 / 2

Handbrake Cable Pliers

9BC11

- For hand brake cable removing and replacing.
- Suitable for Audi, Bmw, Citroen, Nissan, Peugeot, Seat, Renault, Rover, etc.

KING TONY	L (mm)	L (inch)	A Max(mm)	B (mm)	g	
9BC11	230	9	35	5	198	12 / 48

Drum Brake Spring Pliers

9BC121

- Designed to remove and replace brake retaining spring on drum brakes.

KING TONY	L (mm)	L (inch)	g	
9BC121	215	8-1/2	230	12 / 72

9BC122

- Designed to remove and replace brake retaining spring on drum brakes.

KING TONY	L (mm)	L (inch)	g	
9BC122	320	12-1/2	426	6 / 36

HGV Drum Brake Spring Pliers

9BC124

- Designed to remove and replace brake retaining spring on drum brakes.
- Extra strong version for HGV air or hydraulic drum brakes.

KING TONY	L (mm)	L (inch)	g	
9BC124	525	20-5/8	1246	3 / 6

Disc Brake Piston Separator

9BC21

- Heavy duty drop forged construction.
- Fit in brake caliper to push back pistons for new brake pads installation.

KING TONY	Max Capacity (mm)	Max Capacity (inch)	g	
9BC21	75	2-7/8	1125	1 / 20

11 PC. Universal Disc Brake Wind-Back Tool Kit

9BC22

- Magnetic socket adapter.
- Including 9 adapters for brake assemblage.
- For rotating pistons back into caliper to provide clearance for new pads.
- Prevents damage to the piston and boot.
- Suitable for V.W.-audi, Ford, Nissan, Alfa romeo, Rover, Saab, Subaru, Toyota, Jaguar, and most of the general motors.

KING TONY	g	
9BC22	3000	1 / 6

31 PC. Universal Disc Brake Wind-Back Tool Kit

9BC23 NEW

- For rotating pistons back into caliper to provide clearance for new pads.
- Prevents damage to the piston and boot.
- Suitable for
  Bmw,Ford,Vw,Audi,Porsche,Saab,Opel,Volvo,Jaguar,Citroen,Peugeot,Renault,Lauxhall,Lancia,Alfa romeo,Fiat, Nissan,Honda,Subaru,Toyota,Mitsubishi
- Contents:
  21pcs adapters for brake assemblage
  3pcs backing pads
  2pcs rotating caliper with 3/8"DR (right/left side threaded)
  2pcs hex key: 7, 8mm
  2pcs pin punch : Ø5.5, 6mm
  1pc 3/8"DR x 12mm hex key socket

KING TONY	kg	
9BC23	4.76	1 / 4

18PC. Pneumatic Disc Brake Wind-back Tool Kit

9BC25 NEW

- Air operated ram applies pressure to caliper piston, while the handle is rotated by hand.
- Easy to use- works on standard workshop air supply.
- Reversible- works on both RH and LH applications.
- Can be used on wind back and push back piston.
- Supplied with adaptor , which covers a wide range of popular vehicles.
- Full range of additional specialist adaptors available.
- Suitable for
  Mercedes-Benz, Bmw, Audi, Vw, Opel, Volvo, Jaguar, Citroen, Fiat, Peugeot, Alfa romeo,Saab, Lancia, Toyota,Honda, Nissan, Mitsubishi, Isuzu, Mazda,Subaru, Gm, Ford, Rover

KING TONY	kg	
9BC25	3.2	1 / 5

Ball Joint Extractor

9BE11

- Drop forged steel body.
- Max jaw opening: 50mm

KING TONY	A (mm)	min B (mm)	max B (mm)	C (mm)	D (mm)	E (mm)	g	
9BE11	160	12	50	19	19	25	1083	1 / 12

9BE21

- Special design 2-stage operating suits most cars and light trucks ball joints in steering & suspension.
- Jaw open: 22mm.
- Suitable for V.W.-Audi, Fiat, Ford, Nissan, Saab, Opel, Peugeot, Volvo, Renault, Toyota, Mercedes, etc.

KING TONY	A (mm)	min B (mm)	max B (mm)	C (mm)	D (mm)	E (mm)	g	
9BE21	160	12	50	20	22	32	1270	1 / 12

Drop Forged Coil Spring Compressor

■ 9BF11

■ 9BF21

- Drop forged SCM435 jaws & leaded screws.
- Both 21m/m 6-point sockets and 1/2" wrench are available.
- Suitable design for use in limited space under wheel arch.

9BF11

9BF21

KING TONY	L (mm)	(mm)	g	
9BF11	85 / 370	19	3510	1 / 6
9BF21	85 / 270	19	3360	1 / 6

8 PC. Coil Spring Compressor Set

■ 9BF31

- Developed for "Macpherson" suspensions, using a range of 3 sets interchangeable monobloc forks
- Spring specification / use:
  A:φ80～115mm
  B:φ110～150mm
  C:φ140～195mm
- Suitable for : Bmw, Ford, Vw, Audi, Porsche, Saab, Opel, Volvo, Nissan, Honda, Mitsubishi, Subaru, Toyota

KING TONY	L (mm)	Capacity (mm)	kg	
9BF31	460	40~300	15	1 / 3

18 PC. Steering Wheel Puller Set

■ 9BG11

With hex on the puller for easier to fix the puller.
With deep thread to make the bolt powerful to remove or install the pulley.

- Two pulling flange plates in one set.
- Small Plate Dia:
  1" to 3-11/16"(25 to 95mm)
- Large Plate Dia:
  1-1/8" to 5"(28 to 125mm)
- Bolt Size:
  3 PC. 5/16" UNC x 3- 1/2" long puller bolts
  3 PC. 5/16" UNF x 3" long puller bolts
  3 PC. 3/8" UNC x 3" long puller bolts
  3 PC. 3/8" UNF x 3" long puller bolts

KING TONY	g	
9BG11	4100	1 / 4

15 PC. Multi-steering Knuckle Spreader Tool Set

9BJ11 NEW

- This kit is used to spread the steering knuckle to enable the removal and fitting of shock absorbers without the risk of damaging the aluminum or cast iron knuckle.
- The tool is adjustable and suitable for steering knuckles with either a centralized slot or a non centralized slot.
- Wide range of vehicle applications.
- Designed for twin ball joints as fitted to Audi and Vw control arms.
- Suitable for strut clamping bores on Audi,Vw,Bmw,Ford,Peugeot,Citroen,Renault,Seat,Skoda.

KING TONY	kg	
9BJ11	1.05	1 / 10

Wheel Balancing Weight Tool

9BK11

- Ideal for wheel balance weights fitting and removing.

KING TONY	L (mm)	L (inch)	A (mm)	B (mm)	g	
9BK11	250	10	22	86	420	10 / 50

Tyre Lever

9BK41-53

- Professional quality, forged from CR-V steel.
- Straight pattern with profiled shank.

KING TONY	L (mm)	L (inch)	A (mm)	B (mm)	g	
9BK41-53	530	21	28	11	928	10 / 20

Auto Body Repair Tool

9CF110

- 1PC. Standard Bumping Hammer

	A (mm)	B (mm)	C (mm)	L (mm)	g	
9CF110	98.5	38	40.5	325	440	6 / 36

9CF120

- 1PC. Light Shrinking Hammer

	A (mm)	B (mm)	C (mm)	L (mm)	g	
9CF120	98	40.6	39.6	325	467	6 / 36

9CF130

- 1PC. Straight Pick & Finishing Hammer

	A (mm)	B (mm)	L (mm)	g	
9CF130	138	40	325	467	6 / 36

9CF131

- 1PC. Curved Pein & Finishing Hammer

	A (mm)	B (mm)	L (mm)	g	
9CF131	140	40	325	467	6 / 36

9CF132

- 1PC. Curved Pein & Finishing Hammer

	A (mm)	B (mm)	L (mm)	g	
9CF132	141	40	325	-	6 / 36

9CF210

- 1PC. Utility Dolly

	A (mm)	B (mm)	L (mm)	g	
9CF210	69	64	42.3	1375	6 / 12

9CF220

- 1PC. Curved Dolly

	A (mm)	B (mm)	L (mm)	g	
9CF220	58.6	45	133	1625	6 / 12

Auto Body Repair Tool

9CF230

- 1PC. Heel Dolly

KING TONY	A (mm)	B (mm)	L (mm)	g	
9CF230	60	30	79.3	1125	6 / 12

9CF240

- 1PC. Toe Dolly

KING TONY	A (mm)	B (mm)	L (mm)	g	
9CF240	58.5	29.1	121	1400	6 / 12

9CF241

- 1PC. Thin Toe Dolly

KING TONY	A (mm)	B (mm)	L (mm)	g	
9CF241	55	24	118	963	6 / 24

7PC. Auto Body Repair Tool Set

9CF-107
9CF-207
9CF-307

- All drop forged medium(SAE/AISI 1045,1055) carbon steel.
- Hammers are hardened and tempered, including 3 hardwood handled hammers and 4 dollies.

9CF-107

9CF-207

9CF-307

KING TONY	Contents			
9CF-107	9CF110, 9CF120	9CF130, 9CF240		
9CF-207	9CF210, 9CF220	9CF241	9CF131	
NEW 9CF-307	9CF230		9CF132	

KING TONY	kg	
9CF-107	7.5	1 / 4
9CF-207	7.1	
9CF-307	7.1	

3 PC. Stainless Steel Putty Knife Set

9CJ013

- 9CJ1112 1PC. 1-1/4" Putty Knife
- 9CJ1120 1PC. 2" Putty Knife
- 9CJ1130 1PC. 3" Putty Knife

	kg	
9CJ013	0.2	10 / 40

1-1/4" Putty Knife

9CJ1112

	A		L			
	(mm)	(inch)	(mm)	(inch)	g	
9CJ1112	32	1-1/4	218	8-1/2	60	6 / 72

2" Putty Knife

9CJ1120

	A		L			
	(mm)	(inch)	(mm)	(inch)	g	
9CJ1120	50	2	218	8-1/2	70	6 / 72

3" Putty Knife

9CJ1130

	A		L			
	(mm)	(inch)	(mm)	(inch)	g	
9CJ1130	76	3	218	8-1/2	82	6 / 72

3 PC. Stainless Steel Bolstered Scraper Set

9CJ023

- 9CJ2112 1PC. 1-1/4" Bolstered Scraper
- 9CJ2212 1PC. 1-1/4" Bent Bolstered Scraper
- 9CJ2120 1PC. 2" Bolstered Scraper

9CJ023	0.4	10 / 40

1-1/4" Bolstered Scraper

9CJ2112

	A		L			
	(mm)	(inch)	(mm)	(inch)		
9CJ2112	32	1-1/4	218	8-1/2	120	6 / 72

1-1/4" Bent Bolstered Scraper

9CJ2212

	A		L			
	(mm)	(inch)	(mm)	(inch)		
9CJ2212	32	1-1/4	218	8-1/2	120	6 / 72

2" Bolstered Scraper

9CJ2120

	A		L			
	(mm)	(inch)	(mm)	(inch)		
9CJ2120	50	2	218	8-1/2	140	6 / 72

3 PC. Stainless Steel Pinchweld Scraper Set

9CJ033

- 9CJ3104 1PC. 1/2" Pinchweld Scraper
- 9CJ3105 1PC. 5/8" Pinchweld Scraper
- 9CJ3106 1PC. 3/4" Pinchweld Scraper

	kg	
9CJ033	0.3	10 / 40

1/2" Pinchweld Scraper

9CJ3104

	A		L			
	(mm)	(inch)	(mm)	(inch)	g	
9CJ3104	12	1/2	168	6-1/2	75	6 / 72

5/8" Pinchweld Scraper

9CJ3105

	A		L			
	(mm)	(inch)	(mm)	(inch)	g	
9CJ3105	15	5/8	218	8-1/2	108	6 / 72

3/4" Pinchweld Scraper

9CJ3106

	A		L			
	(mm)	(inch)	(mm)	(inch)	g	
9CJ3106	19	3/4	168	6-1/2	75	6 / 72

Multi Purpose Single Edge Razor Scraper

9CJ61-40

- Ideal for scraping labels and decals.
- Comfortable TPR handle for maximum grip.
- Accepts all standard single edge razor blades.

	A		L			
	(mm)	(inch)	(mm)	(inch)	g	
9CJ61-40	40	1-1/2	235	9	145	6 / 72

Spark Plug Boot Pliers

9DB201

- Safe remove spark plug cables and prevent cable damge.
- Pliers' handles and jaws are coated with a heavy-duty plastic for a sure grip.

KING TONY	L (mm)	Ø (mm)	L1 (mm)	g	
9DB201	260	14~18	20	266	12 / 48

Circuit Tester

9DC22

- Bronze body housing.
- Cover cap for contact needle
- Bulb of 24V/3W interchangeable.
- Test voltage 6~24V
- For application of D.C. circuits only.

KING TONY	L (mm)	Test Range	g	
9DC22	107	6~24V	50	20 / 200

Automotive Voltage Tester

9DC23

- Insulated alligator clip with 110 cm cable.
- 2 LEDs indicate positive(+)/negative(-) polarity.
- Test voltage 3~48V
- For application of D.C. circuits only.
- Two testing methods as illustration.

1.

2.

KING TONY	L (mm)	Test Range	g	
9DC23	138	3~48V	52	12 / 144

Lubrication-Grease Gun(Grip Type)

9BU1

- Ideal for machine, automobile, farm and garden equipments other vehicles etc.

KING TONY	L (mm)	L (inch)	Screw Thread	Working Pressure (psi)	Working Pressure (bar)	Burst Pressure	Burst Pressure	Capacity (c.c.)	Capacity (oz)	g	
9BU111	267	(10-5/8)	1/8" x 28 PT	2900	(200)	4000	(275)	120	(3)	605	1 / 30
9BU112	267	(10-5/8)	10 x 1.0 Mertric	2900	(200)	4000	(275)	120	(3)	605	1 / 30

9BU111 for general market except North America,Germany, South Africa, Egypt
9BU112 for Germany, South Africa, Egypt, etc.

9BU1T

- Ideal for machine, automobile, farm and garden equipments other vehicles etc.

KING TONY	L (mm)	L (inch)	Screw Thread	Working Pressure (psi)	Working Pressure (bar)	Burst Pressure	Burst Pressure	Capacity (c.c.)	Capacity (oz)	g	
9BU111T	267	(10-5/8)	1/8" x 28 PT	2900	(200)	4000	(275)	120	(3)	677	1 / 30
9BU112T	267	(10-5/8)	10 x 1.0 Mertric	2900	(200)	4000	(275)	120	(3)	677	1 / 30

9BU111T for general market except North America,Germany, South Africa, Egypt
9BU112T for Germany, South Africa, Egypt, etc.

Lubrication-Grease Gun(Lever Type)

9BU2

- Ideal for machine, automobile, farm and garden equipments other vehicles etc.

KING TONY	L (mm)	L (inch)	Screw Thread	Working Pressure (psi)	Working Pressure (bar)	Burst Pressure	Burst Pressure	Capacity (c.c.)	Capacity (oz)	g	
9BU241	360	(14.5)	1/8" x 28 PT	4500	(310)	10000	(700)	400	(14)	1180	1 / 16
9BU242	360	(14.5)	1/8" x 28 PT	4500	(310)	10000	(700)	400	(14)	1180	1 / 16
9BU251	355	(14)	10 x 1.0 Metric	4500	(310)	10000	(700)	500	(16)	1518	1 / 16
9BU252	355	(14)	10 x 1.0 Metric	4500	(310)	10000	(700)	500	(16)	1518	1 / 16

9BU241 for general market except North America,Germany, South Africa, Egypt
9BU251 for general market except North America,Germany, South Africa, Egypt
9BU242 for Germany, South Africa, Egypt, etc.
9BU252 for Germany, South Africa, Egypt, etc.

Lubrication-Grease Gun with 12" Tube(Lever Type)

9BU2T

- Ideal for machine, automobile, farm and garden equipments other vehicles etc.

KING TONY	L (mm)	L (inch)	Screw Thread	Working Pressure (psi)	Working Pressure (bar)	Burst Pressure	Burst Pressure	Capacity (c.c.)	Capacity (oz)	g	
9BU241T	360	(14.5)	1/8" x 28 PT	4500	(310)	10000	(700)	400	(14)	1240	1 / 16
9BU242T	360	(14.5)	1/8" x 28 PT	4500	(310)	10000	(700)	400	(14)	1240	1 / 16
9BU251T	355	(14)	10 x 1.0 Metric	4500	(310)	10000	(700)	500	(16)	1625	1 / 16
9BU252T	355	(14)	10 x 1.0 Metric	4500	(310)	10000	(700)	500	(16)	1625	1 / 16

9BU241T for general market except North America,Germany, South Africa, Egypt
9BU251T for general market except North America,Germany, South Africa, Egypt
9BU242T for Germany, South Africa, Egypt, etc.
9BU252T for Germany, South Africa, Egypt, etc.

Oil Suction Gun

9BT250 NEW

- Designed for all purpose quickly draining and filling device oil and other fluids for clutches, agricultural, and industrial chemical, additives, transmission on differentials, brake master cylinders, oil filters or other type of sumps or sampling engine oil. Features 11" flexible plastic hose

KING TONY	L (mm)	L (inch)	Capacity (c.c.)	Capacity (oz)	g	
9BT250	340	(13.4)	500	(16)	770	1 / 20

Fluorescent Lamp

9TA21A

- Wire Length : 33ft (10M)
- Euro.version : 220V 9W 12A

KING TONY	A (mm)	B (mm)	g	
9TA21A	310	55x45	1100	1 / 12

30+6LED Rechargeable Working Lamp

9TA23

- 30+6LED
- BRIGHTNESS:150 lux in 1m
- ANTI-IMPACT ABS HOUSING + TPR COATING
- RECHARGEABLE 3.6V 3300mAh NIMH BATTERY
- AC & DC CHARGERS INCLUDED
- SWIVEL NYLON HANGING HOOK PROVIDES 360DEGREES OF ROTATION FOR PRECISE POSITION
- WITH PROGRAMMED IC CHIP ON PCB FOR RELIABILITY
- BUILT-IN OVERLOAD/UNDERLOAD PROTECTION
- BATTERY POWER STATUS INDICATOR
- UP TO 6 HOURS OF CONTINUOUS LIGHTING
- EURO.VERSION:100-240V 50/60Hz
- CE/ROHS COMPLIANT
- I=6LED II=30LED

Contents:

1. 30+6LED RECHARGEABLE WORKING LAMP x 1PC.
2. AC ADAPTOR x 1PC.
3. DC CAR CHARGER x 1PC.

KING TONY	Charger	Suitable country	
9TA23A	CE	European & America & Asia	1 / 8

Optional Model of Charger :

CE UL

Roller Stud Extractor Socket

9TD401

- Turned by means of the hexagonal drive or a 1/2" - 12.7 mm ratchet which has a through-hole for a bar.
- For tightening or loosening studs.

KING TONY	mm	D1 (mm)	D2 (mm)	L (mm)	g	
9TD401-06M	6	24.5	21	60	150	10/180
9TD401-08M	8	24.5	21	60	150	10/180
9TD401-10M	10	27.5	21	69.5	190	12/120
9TD401-12M	12	27.5	21	69.5	190	12/120

4PC. Roller Stud Extractor Socket Set

9TD014MR

- Roller Stud Extractor Socket Set
- 4 stud drivers for sizes M6, M8, M10 and M12
- Supplied in a box

KING TONY	g	
9TD014MR	1100	1 / 8

1/2"DR Damaged Nuts Remover Socket

9TD403 NEW

- Made of top quality SNCM alloy Steel provide good wear resistance and durability.
- Ideal for the removal of rounded, damaged or corroded nuts, bolts, oil drain plugs, marine nuts and bolts, exhaust manifold nuts, pipe nipples, and studs.
- No more pounding, chisels or torches.

CAUTION

Can Not with pneumatic wrench

KING TONY	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	g	
9TD403-12M	18	22	11	12	77	10/180
9TD403-13M	20	22	11	12	84	10/180
9TD403-14M	21	22	11	12	85	10/180
9TD403-17M	24.5	25	15	16	117	10/180
9TD403-19M	27	27	15	16	135	8/80

Clip Removal Pliers

9TC101

- For removal of door inner-linings and other trim items held in place by plastic rivets.

KING TONY	L (mm)	L (inch)	g	
9TC101	230	9	241	12 / 72

15PC. 10-1/2" Heavy Duty Replaceable Tip Circlip Pliers Set

45115PP

- Ideal for Internal-External circlip removing and replacment .
- Ratcheting locking action handles.

68GS-11 1PC. Internal Straight Circlip Pliers
68RS-11 1PC.External Straight Circlip Pliers
68GR-01 2PC. 15° Internal interchangeable
68GQ-01 2PC. 45° Internal interchangeable
68GB-01 2PC. 90° Internal interchangeable
68RR-01 2PC. 15° External interchangeable
68RQ-01 2PC. 45° External interchangeable
68RB-01 2PC. 90° External interchangeable
68ZZ-01 6PC. Screw(M5x0.8)

KING TONY	L (mm)	L (inch)	Spread (mm)	Spread (inch)	ø (mm)	ø (mm)	kg	
45115PP	267	(10-1/2)	50	2"	-	-	1.30	1 / 10
68GS-11	267	(10-1/2)	50	2"	85～100	3	0.31	12 / 24
68GR-11	267	(10-1/2)	50	2"	85～100	3	0.31	12 / 24
68GQ-11	267	(10-1/2)	50	2"	85～100	3	0.31	12 / 24
68GB-11	267	(10-1/2)	50	2"	85～100	3	0.31	12 / 24
68RS-11	267	(10-1/2)	50	2"	40～100	2.75	0.32	12 / 24
68RR-11	267	(10-1/2)	50	2"	40～100	2.75	0.32	12 / 24
68RQ-11	267	(10-1/2)	50	2"	40～100	2.75	0.32	12 / 24
68RB-11	267	(10-1/2)	50	2"	40～100	2.75	0.32	12 / 24

11PC. 16"Internal-External Heavy Duty Circlip Pliers Set

45211PP

- Ideal for Internal-External circlip removing and replacment .
- Ratcheting locking action handles.

68GS-16 1PC. Internal Straight Circlip Pliers
68RS-16 1PC. External Straight Circlip Pliers
68GQ-02 2PC. 45° Internal interchangeable
68GB-02 2PC. 90° Internal interchangeable
68RQ-02 2PC. 45° External interchangeable
68RB-02 2PC. 90° External interchangeable
68ZZ-02 6PC. Screw(M6)

KING TONY	L (mm)	L (inch)	Spread (mm)	Spread (inch)	ø (mm)	ø (mm)	kg	
45211PP	406	(16)	85	3-1/4"	-	-	3.32	1 / 6
68GS-16	406	(16)	85	3-1/4"	82～175	3	0.93	1 / 12
68GQ-16	406	(16)	85	3-1/4"	82～175	3	0.93	1 / 12
68GB-16	406	(16)	85	3-1/4"	82～175	3	0.93	1 / 12
68RS-16	406	(16)	85	3-1/4"	82～165	3	0.97	1 / 12
68RQ-16	406	(16)	85	3-1/4"	82～165	3	0.97	1 / 12
68RB-16	406	(16)	85	3-1/4"	82～165	3	0.97	1 / 12

Magnetic Flexible Handle

2121

- Grip Material-PP+TPR.
- Enhanced flexible conduit for perfect shaping.
- More powerful magnetizing force.

For longer life, please don't shake or wave it.

KING TONY	SIZE	Diax Length(mm)		Magnetic power(kg)	g	/
		L1	L2			
2121-12	12"	Ø 5x305	415	0.5	100	1 / 100
2121-18	18"	Ø 5x455	565	0.5	120	1 / 80

Magnetic Pickup Tool

2124

- Compact and ergonomic design for comfortable holding.
- Enhanced flexible conduit for perfect shaping.
- Solid crimping for holding tube and flexible conduit.
- More powerful magnetizing force.
- Comfortable pushing strength.

For longer life, please don't shake or wave it.

KING TONY	SIZE	Diax Length(mm)		Magnetic power(kg)	g	/
		L1	L2			
2124-13	13"	Ø 11x330	490	0.8	152	1/36
2124-18	18"	Ø 13.5x450	610	1.5	181	1/36

Claw Pickup Tool

2126

- Compact and ergonomic design for comfortable holding.
- Enhanced flexible conduit for perfect shaping.
- Solid crimping for holding tube and flexible conduit.
- Maximum claw width 1-1/4".
- Comfortable pushing strength.

For longer life, please don't shake or wave it.

KING TONY	SIZE	Diax Length(mm)		Maximum Size	g	/
		L1	L2			
2126-18	18"	Ø 11x450	610	1-1/4"	181	1/36

3 in 1 Pickup Tool

2129-24 NEW

- Compact and ergonomic design for comfortable holding
- Enhanced flexible conduit for perfect shaping
- Solid crimping for holding tube and flexible conduit
- More powerful magnetizing force
- Hook type claw
- Clamp light
- Comfortable pushing strength
- Lithium cell:LR521x3

For longer life, please don't shake or wave it.

KING TONY	Size	Diax Length (mm) L1	L2	Magnetice power (kg)	Maximum	g	
2129-24	24"	⌀ 13x470	570	1.0	1-1/4"	280	12/48

Double size "L" handle

1586

- Material : Chrome vanadium alloy steel.
- For oil plug.

KING TONY	Total Length (inch)	(mm)	Size (inch)	(mm)	g	
1586-09	9	230	5/16 x 3/8	8 x 10	320	6 / 60

Door Upholstery Remover

43280212

Tip size:

KING TONY	SIZE	Dia x Length (mm) L1	L2	g	
43280212	5"	8 x 120	240	140	12 / 144

Pry Bar

9TK

- Chrome vanadium alloy steel
- PP+TPR handls
- Packaged in plastic tray
- Pry bars are for prying and levering
- Sturdy blade minimizing lever spring effect
- It's hardened and tempered for maximum durability

KING TONY	L (mm)	g	
9TK108	204	140.4	6 / 72
9TK112	312	286.0	6 / 48
9TK118	458	547.0	6 / 48
9TK124	608	677.2	6 / 36

4PC. Pry Bar Set

9TK014

- 9TK108 pry bar
- 9TK112 pry bar
- 9TK118 pry bar
- 9TK124 pry bar

KING TONY	kg	
9TK014	1.85	5 / 10

Round Magnetic Tool Holder

9TE11

- Stainless steel tray resists corrosion
- Can be used horizontally, vertically, and upside down
- Convenient for collecting small parts and tools

KING TONY	SIZE (mm)	g	
9TE11	Ø150	433	1 / 30

Wing Protector

9TP11

- Protection from unwanted scratches, dents and dirt
- Magnetic attachment keeps paintwork safe from damage
- Rugged, padded imitation leather and reinforced edges provide a perfect, cushioned working area

KING TONY	SIZE (mm)	g	
9TP11	1050x650	649	1 / 8

7PC. AUTO INSPECTION TOOL KIT

9TQ01 NEW

- 1PC Stainless steel telescopic bar
- 1PC 3.5 lbs. magnet pick-up with LED light
- 1PC Strong 8.0 lbs. magnet pick-up
- 1PC Flexible claw pick-up tool
- 1PC Round magnetic dish Dia. 100mm
- 1PC Round inspection mirror-Dia. 50mm
- 1PC Rectangular inspection mirror 89 x 50mm

KING TONY	kg	
9TQ01	1.52	1/5

Safety Goggle

9CK-101

- Soft pvc frame & lens high impact clear polycarbonate.
- Anti-dust and anti-impact vents.

KING TONY	L1		L2		g	
	(mm)	(inch)	(mm)	(inch)		
9CK-101	74	2-7/8	153	6	70	20 / 200

Plastic Pressure Oil can

9TB225

KING TONY	Capacity C.C.	g	
9TB225	225	103	60

10xxx

1001MR 54
1003MQ 263
1003LQ 263
1003PQ 263
1003ZQ 263
1003TQ 263
1003TQ01 263
1005GQ 285
1005ZQ 285
1006PR 284
1006PRN 284
1009PR 284
1009PRN 284
1010PR 284
1011MQ 264
1015GQ 285
1015MQ 264
1015PQ 264
1015ZQ 285
1020-08 205
1020-09 205
1020-10 205
1020-11 205
1020-12 205
1020-13 205
1020-14 205
1020-15 205
1020-16 205
1020-17 205
1020-18 205
1020-19 205
102500P 259
102500P.B 259
102500R 222
102500R.B 222
102501P 259
102501P.B 259
102501R 260
102501R.B 260
102501Z 260
102501Z.B 260
102502P 259
102502P.B 259
102502H 260
102502H.B 260
102502R 260
102502R.B 260
102502Z 260
102502Z.B 260
102503H 260
102503H.B 260
102503P 259
102503P.B 259
102503R 260
102503R.B 260
102503S1 260
102503S1.B 260
102503Z 260
102503Z.B 260
102504H 260
102504H.B 260
102504S1 260
102504S1.B 260
102504S2 260
102504S2.B 260
102505H 260
102505H.B 260
102505S1 260
102505S1.B 260
102506H 260
102506H.B 260
102506S1 260
102506S1.B 260
102506T 260
102506T.B 260
102507H 260
102507H.B 260
102507S1 260
102507S1.B 260
102507T 260
102507T.B 260
102507U 260
102507U.B 260
102508H 260
102508H.B 260
102508S1 260
102508S1.B 260
102508S2 260
102508S2.B 260
102508T 260
102508T.B 260
102508U 260
102508U.B 260
102508V 260
102509T 260
102509T.B 260
102509U 260
102509U.B 260
102509V 260
102510H 260
102510H.B 260
102510T 260
102510T.B 260
102510U 260
102510U.B 260
102510V 260
102512P 259
102512P.B 259
102515H 260
102515H.B 260
102515T 260
102515T.B 260
102515U 260
102515U.B 260
102515V 260
102520T 260
102520T.B 260
102520U 260
102520U.B 260
102520V 260
102525H 260
102525H.B 260
102525T 260
102525T.B 260
102525U 260
102525U.B 260
102525V 260
102527T 260
102527T.B 260
102527U 260
102527U.T 260
102527V 260
102530T 260
102530T.B 260
102530U 260
102530U.B 260
102530V 260
102535S1 260
102535S1.B 260
102540T 260
102540T.B 260
102540U 260
102540U.B 260
102540V 260
102545S1 260
102545S1.B 260
102555S1 260
102555S1.B 260
102555S2 260
102555S2.B 260
102565S1 260
102565S1.B 260
1032CQ 266
1044CQ 264
1050CQ 266
1060-06 193
1060-07 193
1060-08 193
1060-09 193
1060-10 193
1060-11 193
1060-12 193
1060-13 193
1060-14 193
1060-15 193
1060-16 193
1060-17 193
1060-18 193
1060-19 193
1060-20 193
1060-21 193
1060-22 193
1060-23 193
1060-24 193
1060-25 193
1060-26 193
1060-27 193
1060-28 193
1060-29 193
1060-30 193
1060-32 193
1060-55 193
1063-06 197
1063-07 197
1063-08 197
1063-09 197
1063-10 197
1063-11 197
1063-12 197
1063-13 197
1063-14 197
1063-15 197
1063-16 197
1063-17 197
1063-18 197
1063-19 197
1063-21 197
1063-22 197
1063-24 197
1063-27 197
1063-30 197
1063-32 197
1071-33 193
1071-34 193
1071-35 193
1071-36 193
1071-38 193
1071-41 193
1071-42 193
1071-44 193
1071-46 193
1071-48 193
1071-50 193
1080-06 214
1080-07 214
1080-08 214
1080-09 214
1080-10 214
1080-11 214
1080-12 214
1080-13 214
1080-14 214
1080-15 214
1080-16 214
1080-17 214
1080-18 214
1080-19 214
1080-20 214
1080-21 214
1080-22 214
1080-23 214
1080-24 214
1080-25 214
1080-26 214
1080-27 214
1080-28 214
1080-29 214
1080-30 214
1080-32 214
1081-06 215
1081-07 215
1081-08 215
1081-09 215
1081-10 215
1081-11 215
1081-12 215
1081-13 215
1081-14 215
1081-15 215
1081-16 215
1081-17 215
1081-18 215
1081-19 215
1081-20 215
1081-21 215
1081-22 215
1081-23 215
1081-24 215
1081-25 215
1081-26 215
1081-27 215
1081-28 215
1081-29 215
1081-30 215
1081-32 215
1084-08 216
1084-09 216
1084-10 216
1084-11 216
1084-12 216
1084-13 216
1084-14 216
1084-15 216
1084-16 216
1084-17 216
1084-18 216
1084-19 216
1090PR1 284
10A0-24 206
10A0-27 206
10A0-30 206
10A0-32 206
10A0-36 206
10A0-41 206
10A0-46 206
10A0-50 206
10A0-55 206
10A0-60 206
10A0-65 206
10A0-70 206
10A0-75 206
10A0-80 206
10A0-85 206
10A0-90 206
10A0-95 206
10A0-A0 206
10A0-A5 206
10A0-B0 206
10A0-B5 206
10A0-C0 206
10B0-24 206
10B0-27 206
10B0-30 206
10B0-32 206
10B0-36 206
10B0-41 206
10B0-46 206
10B0-50 206
10B0-55 206
10B0-60 206
10B0-65 206
10B0-70 206
10B0-75 206
10B0-80 206
10B0-85 206
10B0-90 206
10B0-95 206
10B0-A0 206
10B0-A5 206
10B0-B0 206
10B0-B5 206
10B0-C0 206
10C0-24 207
10C0-27 207
10C0-30 207
10C0-32 207
10C0-36 207
10C0-41 207
10C0-46 207
10C0-50 207
10C0-55 207
10C0-60 207
10C0-65 207
10D0-08 196
10D0-09 196
10D0-10 196
10D0-11 196
10D0-12 196
10D0-13 196
10D0-14 196
10D0-15 196
10D0-16 196
10D0-17 196
10D0-18 196
10D0-19 196

11xxx

1108MR 198
1108SR 198
11104PR 286
11104PR10 286
1110MR 198
1110SR 198
1112MR 198
1112MRN 198
1112SR 198
111946 207
112002M 273
112003M 273
112004M 273
112005M 273
112006M 273
112007M 273
112008M 273
112010M 273
112015M 273
112025M 273
11205SQ 286
112261 207
112310 274
112315 274
112320 274
112325 274
112327 274
112330 274
112340 274
112345 274
112350 274
112502M 271
112503M 271
112504M 271
112504S 271

Index

112505M ---- 271
112505S ---- 271
112506M ---- 271
112506S ---- 271
112507M ---- 271
112508M ---- 271
112508S ---- 271
112510M ---- 271
112510S ---- 271
112512M ---- 271
112512S ---- 271
112514M ---- 271
112516S ---- 271
112517M ---- 271
112518S ---- 271
112519M ---- 271
112522M ---- 271
112576 ---- 207
112605M ---- 271
112606M ---- 271
112608M ---- 271
112610M ---- 271
112612M ---- 271
112710 ---- 274
112715 ---- 274
112720 ---- 274
112725 ---- 274
112727 ---- 274
112730 ---- 274
112740 ---- 274
112745 ---- 274
112750 ---- 274
113002M ---- 273
113003M ---- 273
113003S ---- 273
113004M ---- 273
113004S ---- 273
113005M ---- 273
113005S ---- 273
113006M ---- 273
113006S ---- 273
113007S ---- 273
113008M ---- 273
113008S ---- 273
113010M ---- 273
113010S ---- 273
113012S ---- 273
113015M ---- 273
113025M ---- 273
113086 ---- 207
114310 ---- 274
114315 ---- 274
114320 ---- 274
114325 ---- 274
114327 ---- 274
114330 ---- 274
114340 ---- 274
114345 ---- 274
114350 ---- 274
114502M ---- 271
114503M ---- 271
114504M ---- 271
114505M ---- 271
114506M ---- 271
114507M ---- 271
114508M ---- 271
114510M ---- 271
114515M ---- 271
114525M ---- 271
114555M ---- 271
114605M ---- 271
114606M ---- 271
114608M ---- 271
114610M ---- 271
114612M ---- 271
114710 ---- 274
114715 ---- 274
114720 ---- 274
114725 ---- 274
114727 ---- 274
114730 ---- 274
114740 ---- 274
114745 ---- 274
114750 ---- 274
115002M ---- 278
115003M ---- 278
115004M ---- 278
115005M ---- 278
115006M ---- 278
115008M ---- 278
115010M ---- 278
115025M ---- 278
115310 ---- 278
115315 ---- 278
115320 ---- 278
115325 ---- 278
115327 ---- 278
115330 ---- 278
115340 ---- 278
115345 ---- 278
115350 ---- 278
115502M ---- 278
115503M ---- 278
115504M ---- 278
115505M ---- 278
115506M ---- 278
115508M ---- 278
115510M ---- 278
115525M ---- 278
116002M ---- 276
116003M ---- 276
116004M ---- 276
116005M ---- 276
116006M ---- 276
116007M ---- 276
116008M ---- 276
116010M ---- 276
116025M ---- 276
116310 ---- 276
116315 ---- 276
116320 ---- 276
116325 ---- 276
116327 ---- 276
116330 ---- 276
116340 ---- 276
116345 ---- 276
116350 ---- 276
116502M ---- 276
116525M ---- 276
116503M ---- 276
116504M ---- 276
116505M ---- 276
116506M ---- 276
116507M ---- 276
116508M ---- 276
116510M ---- 276
118406M ---- 219
118407M ---- 219
118408M ---- 219
118409M ---- 219
118410M ---- 219
118411M ---- 219
118412M ---- 219
118413M ---- 219
118414M ---- 219
118417M ---- 219
118508M ---- 218
118509M ---- 218
118510M ---- 218
118511M ---- 218
118512M ---- 218
118513M ---- 218
118514M ---- 218
118517M ---- 218
118519M ---- 218
119502M ---- 279
119525M ---- 279
119503M ---- 279
119504M ---- 279
119505M ---- 279
119506M ---- 279
119508M ---- 279
119510M ---- 279

12xxx

1207MR ---- 194
1207SR ---- 194
1208MR ---- 194
12107MR ---- 211
1210MR ---- 194
12112MR ---- 211
12114MR ---- 211
1211MR ---- 194
1211MRN ---- 195
1211SR ---- 194
1211SR01 ---- 194
1212MR ---- 194
1214MR ---- 194
1214MR01 ---- 194
1214MRN01 ---- 195
1214SR ---- 194
1214SR01 ---- 194
1215MR ---- 194
1215MRN01 ---- 194
1215MRN ---- 195
1216SR ---- 194
1218MR01 ---- 194
1218MRN ---- 195
12207MR ---- 211
12212MR ---- 211
12214MR ---- 211
1226MR ---- 194
1226MRN ---- 195
12706MR ---- 211
12709MR ---- 211
1272MR ---- 197
1282MR ---- 196
1296MRN ---- 195

13xxx

13012MR ---- 211
13013MR ---- 212
1306MR ---- 203
1306MRN ---- 203
1306SR ---- 203
131101P ---- 268
131102P ---- 268
131103P ---- 268
13113MR ---- 213
131501P ---- 268
131502P ---- 268
131503P ---- 268
1317012PN ---- 253
1317012ZN ---- 253
1317046SN ---- 253
1317057SN ---- 253
1317115TN ---- 253
1317225TN ---- 253
1317340TN ---- 253
1317401PN ---- 253
131744BHN ---- 253
1317501ZN ---- 253
131755BHN ---- 253
1317602PN ---- 253
131766BHN ---- 253
1317702ZN ---- 253
13213MR ---- 213
134501P ---- 268
134502P ---- 268
134503P ---- 268
1360012P ---- 261
1360012Z ---- 261
1360022P ---- 261
1360022Z ---- 261
1360023P ---- 261
1360023Z ---- 261
1360451P ---- 261
1360451Z ---- 261
1360552P ---- 261
1360552Z ---- 261
1360703P ---- 261
1360703Z ---- 261
136501P ---- 268
136502P ---- 268
136503P ---- 268

14xxx

1406PR ---- 202
14103GP ---- 161
14108SR ---- 212
14111MR ---- 212
14110003 ---- 247
14110104 ---- 247
14110204 ---- 247
14110204-E* ---- 247
14110205-E* ---- 247
14110206 ---- 247
14110206-E* ---- 247
14110208-E* ---- 247
14110214 ---- 247
14110306 ---- 247
14110308 ---- 247
14120303 ---- 247
14120404 ---- 247
14120806 ---- 247
14120808 ---- 247
14125504 ---- 247
14126504 ---- 247
14126504-E* ---- 247
14126506 ---- 247
14126506-E* ---- 247
14126514 ---- 247
14210023 ---- 248
14210104 ---- 248
14210112 ---- 248
14210116 ---- 248
14210132 ---- 248
14210204 ---- 248
14210206 ---- 248
14210212 ---- 248
14210214 ---- 248
14210216 ---- 248
14210306 ---- 248
14220303 ---- 248
14220404 ---- 248
14220503 ---- 248
14220504 ---- 248
14220512 ---- 248
14220516 ---- 248
14220806 ---- 248
14220807 ---- 248
14220808 ---- 248
14225503 ---- 248
14225504 ---- 248
14225505 ---- 248
14225506 ---- 248
14226504 ---- 248
14226506 ---- 248
14226512 ---- 248
14226514 ---- 248
14226516 ---- 248
14230803 ---- 249
14230903 ---- 249
14231003 ---- 249
14231503 ---- 249
14232004 ---- 249
14232504 ---- 249
14232704 ---- 249
14233005 ---- 249
14234006 ---- 249
14240105 ---- 249
14240206 ---- 249
14270803 ---- 249
14270903 ---- 249
14271003 ---- 249
14271503 ---- 249
14272004 ---- 249
14272504 ---- 249
14272704 ---- 249
14273005 ---- 249
14274006 ---- 249
14280023 ---- 249
14280104 ---- 249
14280132 ---- 249
14280204 ---- 249
14280306 ---- 249
14311003 ---- 257
14311015 ---- 257
14311103 ---- 257
14311115 ---- 257
14312003 ---- 257
14312015 ---- 257
14313003 ---- 257
14313015 ---- 257
14320615 ---- 257
14320815 ---- 257
14321003 ---- 257
14321015 ---- 257
14321503 ---- 257
14321515 ---- 257
14321803 ---- 257
14321815 ---- 257
14322003 ---- 257
14322015 ---- 257
14322503 ---- 257
14322515 ---- 257
14323003 ---- 257
14323015 ---- 257
14323503 ---- 257
14323515 ---- 257
14324003 ---- 257
14324015 ---- 257
14330403 ---- 257
14330415 ---- 257
14330503 ---- 257
14330515 ---- 257
14330603 ---- 257
14330615 ---- 257
14330703 ---- 257
14330715 ---- 257
14330803 ---- 257
14330815 ---- 257
14330902 ---- 257
14330903 ---- 257
14331002 ---- 257
14331003 ---- 257
14331502 ---- 257
14331503 ---- 257
14332002 ---- 257
14332003 ---- 257
1450-04 ---- 252
1450-05 ---- 252
1450-06 ---- 252
1450-07 ---- 252
1450-08 ---- 252
1450-09 ---- 252
1450-10 ---- 252
1450-11 ---- 252
1450-12 ---- 252
1450-13 ---- 252
1450-45 ---- 252
1450-55 ---- 252
14610103 ---- 252
14610204 ---- 252
14610306 ---- 252

14620807 ------ 252
14625504 ------ 252
14626504 ------ 252
14626506 ------ 252
14710003 ------ 256
14710104 ------ 256
14710204 ------ 256
14710306 ------ 256
14720303 ------ 256
14720404 ------ 256
14720807 ------ 256
14725505 ------ 256
14726506 ------ 256
14780003 ------ 256
14780104 ------ 256
14780204 ------ 256
14780306 ------ 256
14810103 ------ 251
14810204 ------ 251
14810204-E* -- 251
14810205 ------ 251
14810205-E* -- 251
14810306 ------ 251
14810412 ------ 251
14825503 ------ 251
14826504 ------ 251
14826504-E* -- 251
14826506 ------ 251
14826505-E* 251
14820806 ------ 251
14821012 ------ 251

15xxx

151001P ------ 268
151002P ------ 268
151003P ------ 268
151501P ------ 268
151502P ------ 268
151503P ------ 268
155001P ------ 268
155002P ------ 268
155003P ------ 268
15631612 ------ 219
15631615 ------ 219
15631618 ------ 219
15632112 ------ 219
15632115 ------ 219
15632118 ------ 219
15661612 ------ 220
15661615 ------ 220
15661618 ------ 220
15662112 ------ 220
15662115 ------ 220
15662118 ------ 220
157501P ------ 268
157502P ------ 268
157503P ------ 268
1586-09 ------- 322

16xxx

1606MR ------- 199
1609MR ------- 199
163604H ------ 262
163605H ------ 262
163605M ------ 262
163606H ------ 262
163606M ------ 262
163607H ------ 262
163608H ------ 262
163608M ------ 262
163610H ------ 262
163610M ------ 262
163610T ------ 262
163610U ------ 262
163612H ------ 262
163612M ------ 262
163615T ------ 262
163615U ------ 262
163620T ------ 262
163620U ------ 262
163625T ------ 262
163625U ------ 262
163627T ------ 262
163627U ------ 262
163630T ------ 262
163630U ------ 262
163640T ------ 262
163640U ------ 262
163645T ------ 262
163645U ------ 262
163650T ------ 262
163650U ------ 262
163655T ------ 262
163655U ------ 262
163660T ------ 262
163660U ------ 262
168004H ------ 262
168005H ------ 262
168005M ------ 262
168006H ------ 262
168006M ------ 262
168007H ------ 262
168008H ------ 262
168008M ------ 262
168010H ------ 262
168010M ------ 262
168010T ------ 262
168010U ------ 262
168012H ------ 262
168012M ------ 262
168015T ------ 262
168015U ------ 262
168020T ------ 262
168020U ------ 262
168025T ------ 262
168025U ------ 262
168027T ------ 262
168027U ------ 262
168030T ------ 262
168030U ------ 262
168040T ------ 262
168040U ------ 262
168045T ------ 262
168045U ------ 262
168050T ------ 262
168050U ------ 262
168055T ------ 262
168055U ------ 262
168060T ------ 262
168060U ------ 262

17xxx

1706MR ------- 200
1707SR ------- 200
1708MR ------- 200
1710MR ------- 200
1712MR ------- 200
1712MRN ------ 200
174010H ------ 143
174012H ------ 143
174014H ------ 143
174017H ------ 143
174019H ------ 143
174022H ------ 143

18xxx

1805MR ------- 214
1808MR ------- 214
1812MR ------- 214
181202P ------ 261
181203P ------ 261
1826MR ------- 214
183215T ------ 261
183220T ------ 261
183225T ------ 261
183227T ------ 261
183230T ------ 261
183240T ------ 261
183245T ------ 261
183250T ------ 261
183602P ------ 261
183603P ------ 261
183604P ------ 261
183608S ------ 261
183609S ------ 261
183610S ------ 261
183611S ------ 261
183612S ------ 261
187015T ------ 261
187020T ------ 261
187025T ------ 261
187027T ------ 261
187030T ------ 261
187040T ------ 261
187045T ------ 261
187050T ------ 261
188002P ------ 261
188003P ------ 261
188004P ------ 261
188008S ------ 261
188010S ------ 261
188012S ------ 261

19xxx

19005507 ------ 198
19000607 ------ 198
19000708 ------ 198
19000809 ------ 198
19000810 ------ 198
19000911 ------ 198
19001011 ------ 198
19001012 ------ 198
19001113 ------ 198
19001213 ------ 198
19001214 ------ 198
19001314 ------ 198
19001317 ------ 198
19001415 ------ 198
19001417 ------ 198
19001617 ------ 198
19001618 ------ 198
19001719 ------ 198
19001819 ------ 198
19001921 ------ 198
19001922 ------ 198
19002022 ------ 198
19002123 ------ 198
19002224 ------ 198
19002326 ------ 198
19002426 ------ 198
19002427 ------ 198
19002528 ------ 198
19002632 ------ 198
19002730 ------ 198
19002732 ------ 198
19003032 ------ 198
19005507 ------ 198
19100607 ------ 205
19100809 ------ 205
19100810 ------ 205
19101011 ------ 205
19101012 ------ 205
19101213 ------ 205
19101214 ------ 205
19101415 ------ 205
19101617 ------ 205
19101819 ------ 205
19102022 ------ 205
19102123 ------ 205
19102427 ------ 205
1912MR -------- 215
19200608 ------ 202
19200711 ------ 202
19201012 ------ 202
19201418 ------ 202
19201622 ------ 202
19202024 ------ 202
1926MR -------- 215
19300810 ------ 203
19300911 ------ 203
19301011 ------ 203
19301012 ------ 203
19301113 ------ 203
19301213 ------ 203
19301214 ------ 203
19301417 ------ 203
19301719 ------ 203
19301922 ------ 203
19312224 ------ 203
19312427 ------ 203
19313032 ------ 203
19500810 ------ 201
19501012 ------ 201
19501113 ------ 201
19501214 ------ 201
19501315 ------ 201
19501417 ------ 201
19501618 ------ 201
19501719 ------ 201
19501922 ------ 201
19510810 ------ 202
19511012 ------ 202
19511113 ------ 202
19511214 ------ 202
19511517 ------ 202
19511719 ------ 202
19511922 ------ 202
195419H ------- 144
195422H ------- 144
195424H ------- 144
195427H ------- 144
195432H ------- 144
19600607 ------ 199
19600809 ------ 199
19600810 ------ 199
19601012 ------ 199
19601113 ------ 199
19601214 ------ 199
19601417 ------ 199
19601719 ------ 199
19601921 ------ 199
19602224 ------ 199
19602326 ------ 199
19602427 ------ 199
19602732 ------ 199
19603032 ------ 199
19610809 ------ 199
19611011 ------ 199
19611213 ------ 199
19611415 ------ 199
19611617 ------ 199
19611819 ------ 199
19700607 ------ 200
19700809 ------ 200
19700810 ------ 200
19701011 ------ 200
19701012 ------ 200
19701113 ------ 200
19701213 ------ 200
19701214 ------ 200
19701314 ------ 200
19701415 ------ 200
19701417 ------ 200
19701617 ------ 200
19701719 ------ 200
19701819 ------ 200
19701921 ------ 200
19702022 ------ 200
19702123 ------ 200
19702224 ------ 200
19702326 ------ 200
19702426 ------ 200
19702427 ------ 200
19702528 ------ 200
19703032 ------ 200
199104R ------- 218
19911722 ------ 218
19932427 ------ 218
19961721 ------ 218
19A00607 ------ 207
19A00809 ------ 207
19A01011 ------ 207
19A01213 ------ 207
19A01415 ------ 207
19A01617 ------ 207
19A01819 ------ 207
19A02022 ------ 207
19A02123 ------ 207
19A02426 ------ 207
19A02528 ------ 207
19A02729 ------ 207
19A03032 ------ 207
19A0-09 -------- 207
19A0-15 -------- 207
19C00607 ------ 201
19C00809 ------ 201
19C01011 ------ 201
19C01213 ------ 201
19C01415 ------ 201
19C01617 ------ 201
19C01819 ------ 201
19C02022 ------ 201
19C02123 ------ 201
19C02426 ------ 201
19C02528 ------ 201
19C03032 ------ 201

1A/1B/1Cxx

1A06MR ------- 205
1B06MR ------- 205
1C08MR ------- 201
1C12MR ------- 201

20xxx

20107MR01 ---- 273
20107SR ------- 273
20108MR ------- 273
20109MR ------- 273
2019MR -------- 57
2019SR -------- 57
20208MR ------- 272
20208MR01 ---- 272
20208SR01 ---- 272
20209MR ------- 272
2021MR -------- 57
20210MR ------- 272
20218MR ------- 272
20219MR ------- 272
2030CR -------- 58
20306PR ------- 270
20307PR ------ 275
20308PR ------ 275
20309PR ------ 275
2031MR -------- 58
203101 -------- 51
203102 -------- 51
203103 -------- 51
203104 -------- 51
20317PR ------- 270
20319PR ------ 270
203204 -------- 51
203208 -------- 51
203210 -------- 51
203235 -------- 51
203255 -------- 51
203265 -------- 51
203308 -------- 51

Index

203309 ---------- 51
203310 ---------- 51
203315 ---------- 51
203320 ---------- 51
203325 ---------- 51
203327 ---------- 51
203330 ---------- 51
203340 ---------- 51
203503 ---------- 51
203504 ---------- 51
203505 ---------- 51
203506 ---------- 51
203507 ---------- 51
203508 ---------- 51
203510 ---------- 51
203708 ---------- 51
203709 ---------- 51
203710 ---------- 51
203715 ---------- 51
203720 ---------- 51
203725 ---------- 51
203727 ---------- 51
203730 ---------- 51
203740 ---------- 51
20407PR ------- 275
20409PR ------- 275
20419PR ------- 275
20505PR ------- 272
20515PR ------- 272
20A16MR ------ 270
20A17MR ------ 270

21xxx

21108MR ------ 278
21-20-07MR--- 290
21-20-101------ 289
21-20-102------ 289
21208MR ------ 278
2121-12 ------- 321
2121-18 ------- 321
2124-13 ------- 321
2124-18 ------- 321
2126-18 ------- 321
2127PR --------- 60
2129-24 ------- 322
21309PR ------ 278
213312DF ------ 56
2138PR ------- 267
2177DF---------- 56
2178AE---------- 56
2178DF---------- 56
21A107-------- 222

22xxx

22106MR ------ 277
22108MR ------ 277
22118MR ------ 277
22208MR ------ 277
22218MR ------ 277
2221-02 --------- 55
2221-03 --------- 55
2221-04 --------- 55
2221-06 --------- 55
2221-10 --------- 55
2221-12 --------- 55
2223-02 --------- 55
2223-04 --------- 55
22306PR ------ 277
22309PR ------ 277
22319PR ------ 277
223504M ------- 50
223505M ------- 50
223505S ------- 50
223506M ------- 50
223506S ------- 50
223507M ------- 50
223507S ------- 50
223508M ------- 50
223508S ------- 50
223509M ------- 50
223509S ------- 50
223510M ------- 50
223510S ------- 50
223511M ------- 50
223511S ------- 50
223512M ------- 50
223512S ------- 50
223513M ------- 50
223514M ------- 50
223514S ------- 50
223516S ------- 50
223545M ------- 50
223555M ------- 50
227504M ------- 51
227505M ------- 51
227506M ------- 51
227507M ------- 51
227508M ------- 51
2293-02 --------- 55
2293-04 --------- 55
2293-06 --------- 55

23xxx

231008M ------- 50
231010M ------- 50
231010S ------- 50
231012S ------- 50
2311-06 --------- 55
2311-12 --------- 55
2311-18 --------- 55
233004M ------- 49
233005M ------- 49
233005S ------- 49
233006M ------- 49
233006S ------- 49
233007M ------- 49
233007S ------- 49
233008M ------- 49
233008S ------- 49
233009M ------- 49
233009S ------- 49
233010M ------- 49
233010S ------- 49
233011M ------- 49
233011S ------- 49
233012M ------- 49
233012S ------- 49
233013M ------- 49
233014M ------- 49
233014S ------- 49
233015S ------- 49
233016S ------- 49
233045M ------- 49
233055M ------- 49
233504M ------- 49
233505M ------- 49
233505S ------- 49
233506M ------- 49
233506S ------- 49
233507M ------- 49
233507S ------- 49
233508M ------- 49
233508S ------- 49
233509M ------- 49
233509S ------- 49
233510M ------- 49
233510S ------- 49
233511M ------- 49
233511S ------- 49
233512M ------- 49
233512S ------- 49
233513M ------- 49
233514M ------- 49
233514S ------- 49
233515S ------- 49
233516S ------- 49
233532M ------- 49
233545M ------- 49
233555M ------- 49
237504M ------- 50
237505M ------- 50
237506M ------- 50
237507M ------- 50
237508M ------- 50

24xxx

24110204 ------ 247
24110214 ------ 247
24311030 ------ 258
24311140 ------ 258
24312020 ------ 258
24330610 ------ 258
24330715 ------ 258
24330820 ------ 258
24330915 ------ 258
2452-05F-------- 56
2452DK---------- 56

25xxx

2509MR --------- 60
2509SR---------- 60
2510SR---------- 57
2511MR --------- 57
2515MR --------- 54
2516MR --------- 57
2516SR---------- 57
2517MR -------- 266
2519MR --------- 57
2519SR---------- 57
2521MR --------- 57
2526CR --------- 59
2526MR --------- 58
2526SR---------- 58
2530CR --------- 58
2531MR---------- 58
253504M ------ 119
253505M ------ 119
253506M ------ 119
253507M ------ 119
253508M ------ 119
253509M ------ 119
253510M ------ 119
253511M ------ 119
253512M ------ 119
253513M ------ 119
253514M ------ 119
253545M ------ 119
253555M ------ 119
2539MR---------- 59
2540MR---------- 59
2551MR---------- 60
2571-45--------- 56
2575MR---------- 59

27xxx

2752-06G-------- 52
2752-06P -------- 52
2752DK---------- 52
2755-55G ------- 52
2755DK---------- 52
2760-04--------- 53
2760DK---------- 53
2761-55F -------- 52
2761-55P -------- 52
2761DK---------- 52
2765-04G-------- 54
2765DK---------- 54
276A-04G ------- 54
276ADK---------- 54
2769-55F -------- 52
2769-55P -------- 52
2769DK---------- 52
2771-55F -------- 53
2771-55G ------- 53
2771DK---------- 53
2779-55F -------- 53
2779-55G-------- 53
2779DK---------- 53
2781-06F -------- 53
2781-06P -------- 53
2781DK---------- 53
2789-06F -------- 53
2789-06P -------- 53
2789DK---------- 53
2792 ---------- 55

28xxx

2813 ---------- 55

30xxx

3007MR01 ------ 71
30115MR ------ 250
30117MR ------ 250
30118MR ------ 250
30127MR ------ 250
3013MR--------- 71
3013SR--------- 71
30206MR ------ 252
3020MR02 ------ 73
3020SR02 ------ 73
302102---------- 65
302103---------- 65
302104---------- 65
302205---------- 65
302208---------- 65
302210---------- 65
302308---------- 65
302309---------- 65
302310---------- 65
302315---------- 65
302320---------- 65
302325---------- 65
302327---------- 65
302330---------- 65
302340---------- 65
302345---------- 65
302350---------- 65
3023MR --------- 73
3023MR04 ------ 73
3024MR --------- 74
3024SR---------- 74
302503---------- 65
302504---------- 65
302505---------- 65
302506---------- 65
302507---------- 65
302508---------- 65
302510---------- 65
302512---------- 65
302708---------- 66
302709---------- 66
302710---------- 66
302715---------- 66
302720---------- 66
302725---------- 66
302727---------- 66
302730---------- 66
302740---------- 66
302745---------- 66
302750---------- 66
3027MR --------- 74
3027SR---------- 74
302D08---------- 66
302D09---------- 66
302D10---------- 66
302D15---------- 66
302D20---------- 66
302D25---------- 66
302D27---------- 66
302D30---------- 66
302D40---------- 66
302D45---------- 66
302D50---------- 66
302D55---------- 66
302D60---------- 66
30307PR ------ 250
30309PR ------ 250
30317PR ------ 250
30319PR ------ 250
3034MR --------- 75
3036CR --------- 75
303904---------- 66
303905---------- 66
303906---------- 66
303907---------- 66
303908---------- 66
303909---------- 66
303910---------- 66
3050MR--------- 75
305310 --------- 121
305315 --------- 121
305320 --------- 121
305325 --------- 121
305327 --------- 121
305330 --------- 121
305340 --------- 121
305345 --------- 121
305350 --------- 121
305504M ------- 121
305505M ------- 121
305506M ------- 121
305506S ------- 121
305507S ------- 121
305508M ------- 121
305508S ------- 121
305510M ------- 121
305510S ------- 121
305512M ------- 121
305512S ------- 121
305516S ------- 121
30607MR ------ 256
30617MR ------ 256
306504 --------- 121
306505 --------- 121
306506 --------- 121
306508 --------- 121
306510 --------- 121

31xxx

3103PR --------- 71
3105PR --------- 72
3106PR --------- 72
31116MR ------ 250
3113PR --------- 71
3116PR --------- 72
31216MR ------ 250
31416MR ------ 254
31416MR-A ---- 254
31416MR-D ---- 254
31419MR ------ 259
314708S ------ 122
314710M ------ 122
314710S ------ 122
314808S -------- 70
314810S -------- 70
314810M -------- 70
31512MR ------ 254
31512MR01 ---- 254
31512MR-A ---- 254
31512MR-D ---- 254
31516MR ------ 254
31516MR-A ---- 254
31516MR-D ---- 254
31519MR ------ 254
31519MR-A ---- 254
31519MR-D ---- 254

32xxx

3203 ---------- 217
3203A0 -------- 217
3204 ---------- 217
32108MR ------ 259
32118MR ------ 259
321510M -------- 64
321512M -------- 64
32209MR ------ 259
3221-03 -------- 69
3221-06 -------- 69
3221-10 -------- 69
3221-16 -------- 69
3221-18 -------- 69
3221-24 -------- 69
3223-03 -------- 69
3223-06 -------- 69
3223-10 -------- 69
32218MR ------ 259
323007M -------- 62
323008M -------- 62
323009M -------- 62
323010M -------- 62
323010S -------- 62
323011M -------- 62
323012M -------- 62
323012S -------- 62
323013M -------- 62
323014M -------- 62
323014S -------- 62
323015M -------- 62
323016M -------- 62
323016S -------- 62
323017M -------- 62
323018M -------- 62
323018S -------- 62
323019M -------- 62
323020S -------- 62
323021M -------- 62
323022M -------- 62
323022S -------- 62
323024M -------- 62
323024S -------- 62
323026S -------- 62
32309PR ------ 259
323507M -------- 63
323508M -------- 63
323509M -------- 63
323510M -------- 63
323510S -------- 63
323511M -------- 63
323512M -------- 63
323512S -------- 63
323513M -------- 63
323514M -------- 63
323514S -------- 63
323515M -------- 63
323516M -------- 63
323516S -------- 63
323517M -------- 63
323518M -------- 63
323518S -------- 63
323519M -------- 63
323520S -------- 63
323521M -------- 63
323522M -------- 63
323522S -------- 63
323524M -------- 63
323524S -------- 63
323526S -------- 63
32518MR ------ 255
32518MR01 --- 255
32518MR02 --- 255
3260-03 -------- 122
3260-03P ------ 122
3260-06 -------- 122
3260-06P ----- 122
32607MR ------ 259
327504M -------- 63
327505M -------- 63
327506M -------- 63
327507M -------- 63
327508M -------- 63
327510M -------- 63
327511M -------- 63
327512M -------- 63
327514M -------- 63
327516M -------- 63
327518M -------- 63
32810MR ------ 265
3293-03 -------- 69
3293-06 -------- 69
3293-10 -------- 69

33xxx

3311-06 -------- 69
3311-12 -------- 69
33111 ---------- 171
333006M -------- 61
333007M -------- 61
333008M -------- 61
333008S -------- 61
333009M -------- 61
333010M -------- 61
333010S -------- 61
333011M -------- 61
333011S -------- 61
333012M -------- 61
333012S -------- 61
333013M -------- 61
333014M -------- 61
333014S -------- 61
333015M -------- 61
333015S -------- 61
333016M -------- 61
333016S -------- 61
333017M -------- 61
333018M -------- 61
333018S -------- 61
333019M -------- 61
333019S -------- 61
333020M -------- 61
333020S -------- 61
333021M -------- 61
333022M -------- 61
333022S -------- 61
333024M -------- 61
333024S -------- 61
333026S -------- 61
333028S -------- 61
33311-020 ----- 159
333506M -------- 61
333507M -------- 61
333508M -------- 61
333508S -------- 62
333509M -------- 61
333510M -------- 61
333510S -------- 62
333511M -------- 61
333511S -------- 62
333512M -------- 61
333512S -------- 62
333513M -------- 61
333514M -------- 61
333514S -------- 62
333515M -------- 61
333515S -------- 62
333516M -------- 61
333516S -------- 62
333517M -------- 61
333518M -------- 61
333518S -------- 62
333519M -------- 61
333519S -------- 62
33351-030 ----- 168
333520M -------- 61
333520S -------- 62
333521M -------- 61
333522M -------- 61
333522S -------- 62
333523M -------- 61
333524M -------- 61
333524S -------- 62
333526S -------- 62
333528S -------- 62
333530S -------- 62
333532S -------- 62
33411-020 ----- 161
33411-040 ----- 161
33411-050 ----- 161
33412-040 ----- 161
33412-050 ----- 161
33421-040 ----- 160
33451-030 ----- 168
33451-045 ----- 159
33461-060 ----- 168
33462-060 ----- 168
335008M ------ 204
335009M ------ 204
335010M ------ 204
335011M ------ 204
335012M ------ 204
335013M ------ 204
335014M ------ 204
335016M ------ 204
335017M ------ 204
335018M ------ 204
335019M ------ 204
335108M ------ 204
335109M ------ 204
335110M ------ 204
335111M ------ 204
335112M ------ 204
335113M ------ 204
335114M ------ 204
335115M ------ 204
335116M ------ 204
335117M ------ 204
335118M ------ 204
335119M ------ 204
33611-055 ----- 162
33612-055 ----- 162
33621-075 ----- 162
33622-075 ----- 162
33631-110 ----- 162
33632-110 ----- 162
337504M ------- 63
337505M ------- 63
337506M ------- 63
337507M ------- 63
337508M ------- 63
337510M ------- 63
337511M ------- 63
337512M ------- 63
337514M ------- 63
337516M ------- 63
337518M ------- 63
33811-150 ----- 164
33812-150 ----- 164
33831-180 ----- 164
33832-180 ----- 164
33841-180 ----- 163
33842-180 ----- 163
33851-120 ----- 163
33851-250 ----- 165
33852-120 ----- 163
33852-250 ----- 165
33861-200 ----- 165
33862-200 ----- 165
33911-250 ----- 166
33912-250 ----- 166
33921-300 ----- 166
33922-300 ----- 166

34xxx

3406MP -------- 123
34111-1DG ----- 187
34111-1EG ----- 187
34111-2DG ----- 187
34111-2EG ----- 187
341118-17M ---- 187
341142-22M --- 187
341155-26M --- 187
3411B5-29M --- 187
3411003MR ---- 187
3419PP ------- 123
34207-1A ------ 186
34223-1A ------ 184
34223-1B ------ 184
34223-1C ------ 184
34262-1CG ---- 177
34262-1DG ---- 177
34262-1EG ---- 177
34262-2DG ---- 177
34262-3DG ---- 177
3426A-1DG ---- 179
3426A-1EG ---- 179
3426A-2DG ---- 179
3426A-2EG ---- 179
3426C-1DF ---- 178
3426C-2DF ---- 178
34307-1A ------ 186
34323-1A ------ 184
34323-1B ------ 184
34323-2A ------ 184
34323-2B ------ 184
343506M ------- 120
343507M ------- 120
343508M ------- 120
343508S ------- 120
343509M ------- 120
343510M ------- 120
343510S ------- 120
343511M ------- 120
343512M ------- 120
343512S ------- 120
343513M ------- 120
343514M ------- 120
343514S ------- 120
343515M ------- 120
343516M ------- 120
343516S ------- 120
343517M ------- 120
343518M ------- 120
343518S ------- 120
343519M ------- 120
343520M ------- 120
343520S ------- 120
343521M ------- 120
343522M ------- 120
343522S ------- 120
343523M ------- 120
343524M ------- 120
343524S ------- 120
343526S ------- 120
343528S ------- 120
34362-1CG ---- 177
34362-1DG ---- 177
34362-1EG ---- 177
34362-2CG ---- 177
34362-2DG ---- 177
34362-2EG ---- 177
34362-3DG ---- 177
34367-2AG ---- 185
3436A-2DG ---- 179
3436A-2EG ---- 179
3436C-1DF ---- 178
3436C-2DF ---- 178
34387-2AG ---- 185
34422-1GG ---- 177
34422-3GG ---- 177
34423-1A ------ 184
34423-1B ------ 184
34423-1C ------ 184
34423-2A ------ 184
34423-2B ------ 184
34440 ---------- 188
34407-1A ------ 186
34462-1CG ---- 177
34462-1DG ---- 177
34462-1EG ---- 177
34462-1FG ---- 177
34462-2CG ---- 177
34462-2DG ---- 177
34462-2EG ---- 177
34462-2FG ---- 177
34467-1AG ---- 185
3446A-1DG ---- 179
3446A-1EG ---- 179
3446A-2DG ---- 179
3446A-2EG ---- 179
34487-1AG ---- 185
34501107M ---- 181
34501108M ---- 181
34501108S ---- 181
34501109M ---- 181
34501110M ---- 181
34501110S ---- 181
34501111M ---- 181
34501112M ---- 181
34501112S ---- 181
34501113M ---- 181
34501114M ---- 181
34501114S ---- 181
34501115M ---- 181
34501116M ---- 181
34501116S ---- 181
34501117M ---- 181
34501118M ---- 181
34501118S ---- 181
34501119M ---- 181
34501120S ---- 181
34501122S ---- 181
34501124S ---- 181
34501213M ---- 181
34501214M ---- 181
34501215M ---- 181
34501216M ---- 181
34501217M ---- 181
34501218M ---- 181
34501219M ---- 181
34501221M ---- 181
34501222M ---- 181
34501224M ---- 181
34501227M ---- 181
34501230M ---- 181
34501232M ---- 181
34501234M ---- 181
34501236M ---- 181
34501238M ---- 181
34501241M ---- 181
34502107M ---- 182
34502108M ---- 182
34502108S ---- 182
34502110M ---- 182
34502110S ---- 182
34502111M ---- 182
34502112M ---- 182
34502112S ---- 182
34502113M ---- 182
34502114M ---- 182
34502114S ---- 182
34502115M ---- 182
34502116M ---- 182
34502116S ---- 182

Index

34502117M---- 182
34502118M---- 182
34502118S---- 182
34502119M---- 182
34502120S---- 182
34502121M --- 182
34502122M --- 182
34502122S---- 182
34502124S---- 182
34502213M --- 182
34502214M --- 182
34502215M --- 182
34502216M --- 182
34502217M --- 182
34502218M --- 182
34502219M --- 182
34502221M --- 182
34502222M --- 182
34502224M --- 182
34502227M --- 182
34502230M --- 182
34502232M --- 182
34502234M --- 182
34502236M --- 182
34502241M --- 182
34503102R---- 181
34503103R---- 181
34503203R---- 181
34503204R---- 181
34503206R---- 181
345101E08MR 183
345102D08MR 183
345102E08MR 183
345104D08MR 183
34512-1CG---- 180
34512-1DG---- 180
34512-1EG---- 180
34512-1FG---- 180
34512-2CG---- 180
34512-2DG---- 180
34512-2EG---- 180
34512-2FG---- 180
34512-3CG---- 180
34512-3DG---- 180
34512-3EG---- 180
34512-3FG---- 180
34512-4DG---- 180
3452-08F ------ 70
3452-08G------ 70
3452-10F ------ 70
3452-10G------ 70
345201D11MR 183
345201E11MR 183
345202D11MR 183
345202E11MR 183
345203D11MR 183
345203E11MR 183
34522-1CG---- 180
34522-1DG---- 180
34522-1EG---- 180
34522-1FG---- 180
34522-2CG---- 180
34522-2DG---- 180
34522-2EG---- 180
34522-2FG----- 180
34522-3CG ---- 180
34522-3DG ---- 180
34522-3EG ---- 180
34522-3FG----- 180
34607-1A------ 186
34660---------- 188
34662-1CG ---- 177
34662-1DG ---- 177
34662-1EG ---- 177
34662-2CG ---- 177
34662-2DG ---- 177
34662-2EG ---- 177
34662-3CG ---- 177
34662-3DG ---- 177
34662-3EG ---- 177
34688---------- 188
34862-1CG ---- 177
34862-1DG ---- 177
34862-1EG ---- 177
34862-2CF ---- 178
34862-2CG ---- 178
34862-2DF ---- 178
34862-2DG ---- 178
34862-2EF ---- 178
34862-2EG ---- 178
34862-2FF ---- 178
34862-2FG----- 178

35xxx

3508MR-------- 73
3508SR -------- 73
3511-06 -------219
3511-10 -------219
35114MR ------251
3513MR-------- 71
3520MR02 ----- 73
3523MR-------- 73
3523MR04 ----- 73
3524MR-------- 74
3527MR-------- 74
3534MR-------- 75
353506M ------ 119
353507M ------ 119
353508M ------ 119
353508S------ 119
353509M ------ 119
353510M ------ 119
353510S------ 119
353511M------ 119
353512M ------ 119
353512S------ 119
353513M ------ 119
353514M ------ 119
353514S------ 119
353515M ------ 119
353516M ------ 119
353516S------ 119
353517M ------ 119
353518M ------ 119
353518S------ 119
353519M ------ 119
353520S------ 119
353522S------ 119
353524S ------ 119
3571-08 -------- 70
357505M------ 121
357506M------ 121
357507M------ 121
357508M------ 121
357510M------ 121
357512M------ 121
357514M------ 121

36xxx

3611-06------- 216
3611-08------- 216
3611-10------- 216
3611-12------- 216
3611-15------- 216
3611-18------- 216
3611-24------- 216
363016 --------- 64
363021 --------- 64
3631-10R ------ 216
363516 -------- 64
363521 -------- 64
366016 -------- 64
366021 -------- 64
366516 -------- 64
366521 -------- 64
36A014 -------- 64
36A018 -------- 64
36A514 -------- 64
36A518 -------- 64

37xxx

372108M------ 211
372110M------ 211
372110S------ 211
372111M------ 211
372112M------ 211
372112S------ 211
372113M------ 211
372114M------ 211
372114S------ 211
372115M------ 211
372116M------ 211
372116S------ 211
372117M------ 211
372118M------ 211
372118S------ 211
372119M------ 211
372120S------ 211
372122S------ 211
372124S------ 211
37221-030----- 170
373008M------ 209
373009M------ 209
373010M------ 209
373011M------ 209
373012M------ 209
373013M------ 209
373014M------ 209
373015M------ 209
373016M------ 209
373017M------ 209
373018M------ 209
373019M------ 209
373108M ------209
373109M ------209
373110M------209
373111M------209
373112M------209
373113M------209
373114M------209
373115M------209
373116M------209
373117M------209
373118M------209
373119M------209
373121M ------209
373122M ------209
373124M ------209
373202H------208
3732225H-----208
373202R------208
373203R------208
373204R------208
373208M ------210
373209M ------210
373210M ------210
373211M------210
373212M ------210
373213M ------210
373214M ------210
373215M ------210
373216M ------210
373217M ------210
373218M ------210
373219M ------210
37321-050-----170
373221M ------210
373222M ------210
373224M ------210
373225H------208
37323-080-----170
37360809M ---210
37361011M ---210
37361213M ---210
37361415M ---210
37361618M ---210
37361719M ---210
37370607M ---210
37370809M ---210
37371011M ---210
37371213M ---210
37371415M ---210
37371618M ---210
37371719M ---210
37372123M ---210
37372224M ---210
37423-080-----170
375010M ------ 65
375011M------- 65
375012M ------ 65
375013M ------ 65
375014M ------ 65
375015M ------ 65
375016M ------ 65
375017M ------ 65
375018M ------ 65
375019M ------ 65
3752-09G------- 67
3752-09P------- 67
3752DK--------- 67
3755-08G ------67
3755DK---------67
3760-45 --------67
3760DK --------67
3761-08F--------67
3761-08P ------67
3761DK --------67
3769-08F--------68
3769-08P ------68
3769DK --------68
3771-08F--------68
3771-08G ------68
3771DK --------68
3779-08F--------68
3779-08G ------68
3779DK---------68
3781-11F--------68
3781-11P--------68
3781DK --------68
3789-11F ------68
3789-11P ------68
3789DK---------68
3792----------70
3795-15 ------ 220
3795-18 ------ 220
3795-24 ------ 220
3795-30 ------ 220
3796 -------- 123
3796P-------- 123

38xxx

3812----------70
3814----------70
3862--------- 122
3862P-------- 122
3864--------- 122
3864P-------- 122

40xxx

4010MR -------91
4010SR---------91
4012MR --------95
4012SR---------95
401408M--------81
401409M--------81
401410M--------81
401411M--------81
401412M--------81
401413M--------81
401414M--------81
401419M--------81
401505M ----- 132
401506M------ 132
401507M ----- 132
401508M ----- 132
401508S ------ 132
401509M ----- 132
401510M ----- 132
401512M ----- 132
401512S ------ 132
401513M ----- 132
401514M ----- 132
401516S -------132
401517M -----132
401519M -----132
402102 -------- 82
402103 -------- 82
402104 -------- 82
402208 -------- 82
402210 -------- 82
402212 -------- 82
402214 -------- 82
402216 -------- 82
402320 -------- 83
402325 -------- 83
402327 -------- 83
402330 -------- 83
402340 -------- 83
402345 -------- 83
402350 -------- 83
402355 -------- 83
402360 -------- 83
402365 -------- 83
402370 -------- 83
4024MR-------- 95
4024SR -------- 95
402503 -------- 82
402504 -------- 82
402505 -------- 82
402506 -------- 82
402507 -------- 82
402508 -------- 82
402510 -------- 82
402512 -------- 82
402514 -------- 82
402517 -------- 82
402519 -------- 82
402605 -------- 82
402606 -------- 82
402608 -------- 82
402610 -------- 82
402612 -------- 82
402614 -------- 82
4026MR ------ 96
4026MR03 ----- 96
4026MR04 ----- 96
4026SR -------- 96
4026SR03 ----- 96
402720 -------- 83
402725 -------- 83
402727 -------- 83
402730 -------- 83
402740 -------- 83
402745 -------- 83
402750 -------- 83
402755 -------- 83
402760 -------- 83
4028MR-------- 97
4028MR02 ----- 97
4028SR -------- 97
402B16-------- 83
402B18-------- 83
4032MR ------ 97
4032SR ------ 97
403320 -------- 83
403325 -------- 83

403327 ---------- 83
403330 ---------- 83
403340 ---------- 83
403345 ---------- 83
403350 ---------- 83
403355 ---------- 83
403360 ---------- 83
403365 ---------- 83
403370 ---------- 83
4033MR -------- 95
4033SR -------- 95
4034MR -------- 98
403504 ---------- 82
403505 ---------- 82
403506 ---------- 82
403507 ---------- 82
403508 ---------- 82
403510 ---------- 82
403512 ---------- 82
403514 ---------- 82
403517 ---------- 82
403519 ---------- 82
403606 ---------- 82
403608 ---------- 82
403610 ---------- 82
403612 ---------- 82
403720 ---------- 83
403725 ---------- 83
403727 ---------- 83
403730 ---------- 83
403740 ---------- 83
403745 ---------- 83
403750 ---------- 83
403755 ---------- 83
403760 ---------- 83
404108 ---------- 83
4042CR -------- 98
4042CR02 ---- 98
4044CR -------- 96
404904 ---------- 83
404905 ---------- 83
404906 ---------- 83
404907 ---------- 83
404908 ---------- 83
404909 ---------- 83
404910 ---------- 83
404912 ---------- 83
404913 ---------- 83
404914 ---------- 83
404916 ---------- 83
404925 ---------- 83
405325 -------- 131
405327 -------- 131
405330 -------- 131
405340 -------- 131
405345 -------- 131
405350 -------- 131
405355 -------- 131
405360 -------- 131
405504M------ 131
405505M------ 131
405506M------ 131
405506S ------ 131
405507M------ 131
405508M ------131
405508S------131
405510M ------131
405510S------131
405512M ------131
405512S------131
405513M ------131
405514M ------131
405514S------131
405516S------131
405608M ------131
405610M ------131
405612M ------131
406325--------131
406327--------131
406330--------131
406340--------131
406345--------131
406350--------131
406355--------131
406360--------131
406504M ------132
406505M ------132
406506M ------132
406508M ------132
406510M ------132
406512M ------132
406514M ------132
406608-------- 82
406610-------- 82
406612-------- 82
4066MR ------- 90
4066SR ------- 90
4072MR ------- 90
4072SR ------- 90
407505M ------132
407506M ------132
407508M ------132
407510M ------132
407512M ------132
407514M ------132

41xxx

41026MR ---- 98
41026SR ------ 98
4104PR -------- 92
4105PR -------- 92
4106PR -------- 91
4108FR -------- 99
4109PR -------- 93
4110PR -------- 93
4111FR-------- 99
4112FR -------- 99
4116PR -------- 91
4118MR-------- 91
4119PR -------- 93
4120PR -------- 93
4121-11GR------ 87
4126PR -------- 92
4128PR -------- 94
4136PR -------- 92
414708S------132
414710M ------132
414710S------132
414808S -------81
414810M-------81
414810S -------81
414A08S ------ 132
41526MR -------98
41526SR-------98

42xxx

4208MR --------93
4208SR---------93
42104GP------ 229
42104GP01 --- 229
42114GP ---- 229
42116GP ---- 229
4215MR -------93
4220MR -------94
4221-18 --------87
4221-24 --------87
4221-30 --------87
4221-36 --------87
4223-02 --------87
4223-05 --------87
4223-10 --------87
423008M ------78
423009M ------78
423010M ------78
423010S -------78
423011M -------78
423012M-------78
423012S -------78
423013M ------78
423014M ------78
423014S -------78
423015M ------78
423016M ------78
423016S -------78
423017M ------78
423018M ------78
423018S -------78
423019M ------78
423020M ------78
423020S -------78
423021M ------78
423022M ------78
423022S -------78
423023M ------78
423024M ------78
423024S -------78
423025M ------78
423026M ------78
423026S -------78
423027M ------78
423028M ------78
423028S -------78
423029M-------78
423030M ------78
423030S -------78
423032M ------78
423032S -------78
423033M ------78
423034S -------78
423036M ------78
423036S -------78
423038S -------78
423040S-------- 78
423508M ------ 79
423509M ------ 79
423510M -------- 79
423510S ------ 79
423511M ------ 79
423512M -------- 79
423512S ------ 79
423513M ------ 79
423514M -------- 79
423514S ------ 79
423515M ------ 79
423516M -------- 79
423516S ------ 79
423517M ------ 79
423518M -------- 79
423518S ------ 79
423519M ------ 79
423520M -------- 79
423520S ------ 79
423521M ------ 79
423522M -------- 79
423522S-------- 79
423523M ------ 79
423524M -------- 79
423524S ------ 79
423525M ------ 79
423526M -------- 79
423526S ------ 79
423527M -------- 79
423528M -------- 79
423528S ------ 79
423529M ------ 79
423530M -------- 79
423530S ------ 79
423532M -------- 79
423532S ------ 79
423533M -------- 79
423534S ------ 79
423536M -------- 79
423536S-------- 79
423538M -------- 79
423538S-------- 79
423540S-------- 79
423541M -------- 79
423542S-------- 79
423544S-------- 79
423546S-------- 79
423548S-------- 79
424508M ---- 80
424509M ---- 80
424510M --- 80
424512M -------- 80
424513M -------- 80
424514M -------- 80
4251-02-------- 87
4251-03-------- 87
4251-04-------- 87
4251-05-------- 87
4251-06-------- 87
4251-08-------- 87
4251-10-------- 87
425508M -------- 80
425509M -------- 80
425510M--------80
425512M--------80
425513M--------80
425514M--------80
4260-03 ------ 133
4260-03P ----- 133
4260-04 ------ 133
4260-04P ----- 133
4260-05 ------ 133
4260-05P ----- 133
4260-06 ------ 133
4260-06P ----- 133
4260-10 ------ 133
4260-10P ----- 133
4260-12 ------ 133
4260-12P ----- 133
427510M ------80
427512M ------80
427514M--------80
427516M--------80
427518M--------80
427520M--------80
427522M--------80
427524M--------80
4293-02 --------87
4293-05 --------87
4293-10 --------87

43xxx

4308MR -------93
4311-16F-------88
4311-16G ------88
4311MR -------91
4315MR -------93
4320MR -------94
4322MR -------94
4325MR -------94
43280212 ----- 322
433008M--------76
433009M ------76
433010M ------76
433010S -------76
433011M -------76
433012M ------76
433012S -------76
433013M--------76
433013S -------76
433014M ------76
433014S -------76
433015M ------76
433015S -------76
433016M ------76
433016S -------76
433017M ------76
433018M ------76
433018S -------76
433019M ------76
433019S -------76
433020M ------76
433020S -------76
433021M ------76
433022M ------76
433022S -------76
433023M ------76
433024M ------76
433024S -------76
433025M ------76
433025S -------76
433026M ------76
433026S -------76
433027M ------76
433028M ------76
433028S -------76
433029M ------76
433030M ------76
433030S -------76
433032M ------76
433032S -------76
433033M ------76
433034S -------76
433036M ------76
433036S -------76
433038S -------76
433040S -------76
433506M-------77
433507M-------77
433508M ------77
433509M-------77
433510M ------77
433510S -------77
433511M-------77
433512M-------77
433512S -------77
433513M ------77
433514M ------77
433514S -------77
433515M ------77
433515S -------77
433516M ------77
433516S -------77
433517M ------77
433518M ------77
433518S -------77
433519M-------77
433519S -------77
433520M ------77
433520S -------77
433521M ------77
433522M ------77
433522S -------77
433523M-------77
433524M ------77
433524S -------77
433525M-------77
433525S -------77
433526M-------77
433526S -------77
433527M ------77
433528M-------77
433528S -------77
433529M-------77
433530M-------77
433530S -------77
433532M-------77
433532S -------77
433533M-------77
433534M-------77
433534S -------77

Index

433536M 77
433536S 77
433538M 77
433538S 77
433539M 77
433540S 77
433541M 77
433546M 77
437510M 80
437512M 80
437514M 80
437516M 80
437518M 80
437520M 80
437522M 80
437524M 80

44xxx

4407MP 137
4408MP 135
4408SP 135
4410MP 135
4410SP 135
44116MP 172
44118MP 172
4412MP 135
4413MP 136
4414SP 135
441517M 129
441519M 129
441521M 129
4415MP 136
4415MP03 136
4416SP 136
4417PP 137
443008M 126
443009M 126
443010M 126
443011M 126
443012M 126
443013M 126
443014M 126
443015M 126
443016M 126
443017M 126
443018M 126
443019M 126
443020M 126
443021M 126
443022M 126
443023M 126
443024M 126
443027M 126
443030M 126
443032M 126
443036M 126
443508M 126
443509M 126
443510M 126
443510S 126
443511M 126
443512M 126
443512S 127
443513M 126
443514M 126
443514S 127
443515M 126
443516M 126
443516S 127
443517M 126
443518M 126
443518S 127
443519M 126
443520M 126
443520S 127
443521M 126
443522M 126
443522S 127
443523M 126
443524M 126
443524S 127
443525M 126
443526M 126
443526S 127
443527M 126
443528M 126
443528S 127
443529M 126
443530M 126
443530S 127
443532M 126
443532S 127
443533M 126
443534M 126
443534S 127
443536M 126
443536S 127
443538M 126
443538S 127
443540S 127
443541M 126
443546M 126
4440SP 130
4450SP 130
44504MP 171
44504MPB 171
4452-15F 88
4452-18F 88
4452-24F 88
4452DK 88
4452DK1 88
4457MP 137
4462-18 88
4462-24 88
4462DK 88
4466MP 138
4466SP 138
4467PP 137
4472MP 138
4472SP 138
4476MP 137

45xxx

4501MR 95
4505MR 99
4505SR 99
4510MR 91
4510SR 91
4511-06 219
4511-10 219
45115PP 320
4512MR 95
4512SR 95
45211PP 320
4524MR 95
4524SR 95
452517M 124
452519M 124
452521M 124
452522M 124
452524M 124
4526MR 96
4526MR03 96
4526MR04 96
4526SR 96
4526SR03 96
4528MR 97
4528MR02 97
4528SR 97
453008M 124
453009M 124
453010M 124
453011M 124
453012M 124
453013M 124
453014M 124
453015M 124
453016M 124
453017M 124
453018M 124
453019M 124
453020M 124
453021M 124
453022M 124
453023M 124
453024M 124
453025M 124
453026M 124
453027M 124
453028M 124
453029M 124
453030M 124
453032M 124
453033M 124
453034M 124
453036M 124
453038M 124
453041M 124
4532MR 97
4532SR 97
4533MR 95
4533SR 95
4534MR 98
453508M 125
453509M 125
453510M 125
453510S 125
453511M 125
453512M 125
453512S 125
453513M 125
453514M 125
453514S 125
453515M 125
453516M 125
453516S 125
453517M 125
453518M 125
453518S 125
453519M 125
453520M 125
453520S 125
453521M 125
453522M 125
453522S 125
453523M 125
453524M 125
453524S 125
453525M 125
453526M 125
453526S 125
453527M 125
453528M 125
453528S 125
453529M 125
453530M 125
453530S 125
453532M 125
453532S 125
453533M 125
453534M 125
453534S 125
453536M 125
453536S 125
453538M 125
453538S 125
453539M 125
453540S 125
453541M 125
453546M 125
4542CR 98
4542CR02 98
4544CR 96
4566MR 90
4572-10 88
4572-12 88
4572DK 88
4572MR 90
4572SR 90
4573-10 88
4573DK 88
457510M 129
457512M 129
457514M 129
457516M 129
457518M 129
457520M 129
4581-10 89
4583-12 89
4584-12 89

46xxx

463016 81
463021 81
463516 81
463521 81
466016 81
466021 81
466516 81
466521 81

47xxx

4725-10F 84
4725-10G 84
4725-12B 84
4725-12F 84
4725-12G 84
4725DKR01 84
4752-12G 84
4752-12P 84
4752DK 84
4755-10G 84
4755DK 84
4760-05 84
4760-05G 85
4760DK 85
4762-10F 85
4762-10G 85
4762-10P 85
4762-15F 85
4762-15G 85
4762-15P 85
4762DK 85
4767-10F 85
4767-10G 85
4767-15F 85
4767-15G 85
4767DK 85
4768-10F 85
4768-10G 85
4768-10P 85
4768-15F 85
4768-15G 85
4768-15P 85
4768DK 85
4771-10B 86
4771-10F 86
4771-10G 86
4771DK 86
4779-10B 86
4779-10F 86
4779-10G 86
4779DK01 86
4781-12F 86
4781-12P 86
4781DK 86
4789-12F 86
4789-12P 86
4789DK 86
4791 89
4795-18 220
4795-24 220
4795-30 220
4795-36 220
4796 133
4796P 133
4797 133
4797P 133
4798 133
4798P 133
479AP 133

48xxx

4813 89
4816 89
483510M 127
483511M 127
483512M 127
483513M 127
483514M 127
483516M 127
483517M 127
483519M 127
483521M 127
483522M 127
483523M 127
483524M 127
483526M 127
483527M 127
483530M 127
4863 134
4863P 134
4866 134
4866P 134
4873 134
4873P 134

49xxx

493008M 128
493009M 128
493010M 128
493011M 128
493012M 128
493013M 128
493014M 128
493015M 128
493016M 128
493017M 128
493018M 128
493019M 128
493020M 128
493021M 128
493022M 128
493023M 128
493024M 128
493027M 128
493030M 128
493032M 128
493036M 128
493510M 128
493510S 128
493511M 128
493512M 128
493512S 128
493513M 128
493514M 128
493514S 128
493516M 128
493516S 128
493517M 128
493518S 128
493519M 128
493520S 128
493521M 128
493522M 128

493522S ------ 128
493523M ------ 128
493524M ------ 128
493524S ------ 128
493526M ------ 128
493526S ------ 128
493527M ------ 128
493528S ------ 128
493530M ------ 128
493530S ------ 128
493532S ------ 128
493534S ------ 128
493536S ------ 128
493538S ------ 128
493540S ------ 128
4A5510M ------ 129
4A5511M ------ 129
4A5512M ------ 129
4A5512S ------ 129
4A5513M ------ 129
4A5514M ------ 129
4A5514S ------ 129
4A5515M ------ 129
4A5516M ------ 129
4A5516S ------ 129
4A5517M ------ 129
4A5518M ------ 129
4A5518S ------ 129
4A5519M ------ 129
4A5520S ------ 129
4A5521M ------ 129
4A5522M ------ 129
4A5522S ------ 129
4A5524M ------ 129
4A5524S ------ 129
4A5526S ------ 129
4A5528S ------ 129
4A5530S ------ 129
4B5510M ------ 130
4B5511M ------ 130
4B5512M ------ 130
4B5512S ------ 130
4B5513M ------ 130
4B5514M ------ 130
4B5514S ------ 130
4B5515M ------ 130
4B5516M ------ 130
4B5516S ------ 130
4B5517M ------ 130
4B5518M ------ 130
4B5518S ------ 130
4B5519M ------ 130
4B5520S ------ 130
4B5521M ------ 130
4B5522M ------ 130
4B5522S ------ 130
4B5524M ------ 130
4B5524S ------ 130
4B5526S ------ 130
4B5528S ------ 130
4B5530S ------ 130

50xxx

5022MR ------ 107
5022SR ------ 107
5039CR ------ 97
5060-08 ------ 193
5060-10 ------ 193
5060-12 ------ 193
5060-14 ------ 193
5060-16 ------ 193
5060-18 ------ 193
5060-20 ------ 193
5060-22 ------ 193
5060-24 ------ 193
5060-26 ------ 193
5060-28 ------ 193
5060-30 ------ 193
5060-32 ------ 193
5060-34 ------ 193
5060-36 ------ 193
5060-40 ------ 193
5063-14 ------ 197
5063-16 ------ 197
5063-18 ------ 197
5071-42 ------ 193
5071-44 ------ 193
5071-46 ------ 193
5071-48 ------ 193
5071-50 ------ 193
5071-52 ------ 193
5071-54 ------ 193
5071-56 ------ 193
5071-58 ------ 193
5071-60 ------ 193
5071-62 ------ 193
5071-64 ------ 193

54xxx

5450-08 ------ 253
5450-10 ------ 253

55xxx

5522MR ------ 107
553417M ------ 156
553421M ------ 156
553426S ------ 156
553430S ------ 156
553533M ------ 156
553534S ------ 156
553535M ------ 156
553536S ------ 156
553538M ------ 156
553540S ------ 156
553541M ------ 156
553542S ------ 156
553546S ------ 156

57xxx

572210M ------ 220
572212M ------ 220
574208M ------ 221
574210M ------ 221
574212M ------ 221
574213M ------ 221
574214M ------ 221
574217M ------ 221
575208M ------ 221
575210M ------ 221
575212M ------ 221
575213M ------ 221
575214M ------ 221
575217M ------ 221
575510M ------ 221
575512M ------ 221
576208M ------ 221
576210M ------ 221
576212M ------ 221
576213M ------ 221
576214M ------ 221
576217M ------ 221
577208M ------ 222
577210M ------ 222
577212M ------ 222
577213M ------ 222
577214M ------ 222
577217M ------ 222
577406M ------ 222
577407M ------ 222
577408M ------ 222
577409M ------ 222
577410M ------ 222
577411M ------ 222
577412M ------ 222
577413M ------ 222
577414M ------ 222
577415M ------ 222
577416M ------ 222
577417M ------ 222
577418M ------ 222
577419M ------ 222

59xxx

59000810 ------ 171
59001012 ------ 171
59001214 ------ 171
59001416 ------ 171
59001618 ------ 171
59001820 ------ 171
59002022 ------ 171
59002224 ------ 171
59002628 ------ 171
59003032 ------ 171
59003034 ------ 171
59003236 ------ 171
59003640 ------ 171
59301012 ------ 203
59301214 ------ 203
59301618 ------ 203
59301820 ------ 203
59302224 ------ 203
59302428 ------ 203
59601214 ------ 199
59601618 ------ 199
59602022 ------ 199
59602428 ------ 199
59603032 ------ 199
59700810 ------ 200
59701012 ------ 200
59701214 ------ 200
59701416 ------ 200
59701618 ------ 200
59701820 ------ 200
59702022 ------ 200
59702224 ------ 200
59702428 ------ 200
59702628 ------ 200
59703032 ------ 200
59703436 ------ 200
59703640 ------ 200

60xxx

6011-05R ------ 232
6011-07N ------ 232
6011-07R ------ 232
6011-10N ------ 232
6011-10R ------ 232
601514M ------ 143
601517M ------ 143
601519M ------ 143
601521M ------ 143
601522M ------ 143
601524M ------ 143
601527M ------ 143
6016MR ------ 104
6016SR ------ 104
6023MR ------ 104
6023SR ------ 104
6031-07N ------ 232
6031-07R ------ 232
6031-10N ------ 232
6031-10R ------ 232
608510 ------ 143
608512 ------ 143
608514 ------ 143
608517 ------ 143
608519 ------ 143
608522 ------ 143
609519 ------ 144
609522 ------ 144
609524 ------ 144
609527 ------ 144
609532 ------ 144
609616M ------ 143
609622M ------ 144

61xxx

6111-06 ------ 225
6111-07 ------ 225
6111-08 ------ 225
6112-09A ------ 225
6112-09C ------ 225
6114-05 ------ 225
6116-07A ------ 230
6116-08A ------ 230
6131-12 ------ 242
6131-12P01 ------ 242
6131-14 ------ 242
6131-14P01 ------ 242
6131-18 ------ 242
6131-18P01 ------ 242
6131-24 ------ 242
6131-24P01 ------ 242
6131-30 ------ 242
6131-30P01 ------ 242
6131-36 ------ 242
6131-36P01 ------ 242
6131-42 ------ 242
6131-42P01 ------ 242
6146-08A ------ 230

62xxx

6211-06 ------ 226
6213-06 ------ 226
6214-05 ------ 226
6214-45 ------ 226
6216-06A ------ 230
6224CR ------ 104
6226CR ------ 104
6231-07 ------ 226
6231-08 ------ 226
623517M ------ 102
623518M ------ 102
623519M ------ 102
623520M ------ 102
623521M ------ 102
623522M ------ 102
623523M ------ 102
623524M ------ 102
623525M ------ 102
623526M ------ 102
623527M ------ 102
623528M ------ 102
623529M ------ 102
623530M ------ 102
623531M ------ 102
623532M ------ 102
623533M ------ 102
623534M ------ 102
623535M ------ 102
623536M ------ 102
623537M ------ 102
623538M ------ 102
623539M ------ 102
623540M ------ 102
623541M ------ 102
623542M ------ 102
623543M ------ 102
623544M ------ 102
623545M ------ 102
623546M ------ 102
623547M ------ 102
623548M ------ 102
623549M ------ 102
623550M ------ 102
623551M ------ 102
623552M ------ 102
623553M ------ 102
623554M ------ 102
623555M ------ 102
623556M ------ 102
623557M ------ 102
623558M ------ 102
623559M ------ 102
623560M ------ 102
6236-07A ------ 230
6251-04 ------ 103
6251-08 ------ 103
6251-16 ------ 93
6260-04 ------ 144
6260-04P ------ 144
6260-07 ------ 144
6260-07P ------ 144
6260-10 ------ 144
6260-10P ------ 144
6260-13 ------ 144
6260-13P ------ 144

63xxx

6311-06 ------ 225
6311-08 ------ 225
6313-06 ------ 225
6314-05 ------ 225
6315-06 ------ 232
6315-09 ------ 232
6316MR ------ 104
6318-08A ------ 230
6323MR ------ 104
633017M ------ 100
633019M ------ 100
633021M ------ 100
633022M ------ 100
633022S ------ 100
633023M ------ 100
633024M ------ 100
633024S ------ 100
633026M ------ 100
633026S ------ 100
633027M ------ 100
633028M ------ 100
633028S ------ 100
633029M ------ 100
633030M ------ 100
633030S ------ 100
633032M ------ 100
633032S ------ 100
633033M ------ 100
633034M ------ 100
633034S ------ 100
633035M ------ 100
633036M ------ 100
633036S ------ 100
633038M ------ 100
633038S ------ 100
633040S ------ 100
633041M ------ 100
633042M ------ 100
633042S ------ 100
633044S ------ 100
633046M ------ 100
633046S ------ 100
633048M ------ 100
633048S ------ 100
633050M ------ 100
633050S ------ 100
633052S ------ 100
633054M ------ 100
633054S ------ 100
633056S ------ 100
633058M ------ 100
633058S ------ 100
633060M ------ 100
633060S ------ 100
633062S ------ 100
633063M ------ 100
633064S ------ 100

Index

633065M 100
633066S 100
633068S 100
633070M 100
633070S 100
633072S 100
633074S 100
633076S 100
633078S 100
633080S 100
633082S 100
633084S 100
633086S 100
633088S 100
6331-06 226
6331-08 226
6334-05 226
633517M 101
633518M 101
633519M 101
633520M 101
633521M 101
633522M 101
633523M 101
633524M 101
633525M 101
633526M 101
633527M 101
633528M 101
633529M 101
633530M 101
633531M 101
633532M 101
633533M 101
633534M 101
633535M 101
633536M 101
633537M 101
633538M 101
633539M 101
633540M 101
633541M 101
633542M 101
633543M 101
633544M 101
633545M 101
633546M 101
633547M 101
633548M 101
633549M 101
633550M 101
633551M 101
633552M 101
633553M 101
633554M 101
633555M 101
633556M 101
633557M 101
633558M 101
633559M 101
633560M 101
633563M 101
633565M 101
633570M 101
6336-08A 230

64xxx

6408MP 146
6408MP10 146
6408SP10 146
6409MP 146
6409MP10 146
6409SP10 146
6410MP 146
6410SP 146
6411-06 227
64111MP 173
64115MP 17
6411MP 173
6431-10 227
6431-11 227
643519M 141
643521M 141
643522M 141
643523M 141
643524M 141
643524S 141
643525M 141
643526M 141
643526S 141
643527M 141
643528M 141
643528S 141
643529M 141
643530M 141
643530S 141
643532M 141
643532S 141
643533M 141
643534M 141
643534S 141
643535M 141
643536M 141
643536S 141
643538M 141
643538S 141
643540M 141
643540S 141
643541M 141
643542M 141
643542S 141
643543M 141
643544M 141
643544S 141
643546M 141
643546S 141
643548M 141
643548S 141
643550M 141
643550S 141
643552S 141
643554S 141
643555M 141
643556S 141
643558S 141
643560M 141
643560S 141
643562S 141
643564S 141
643565M 141
6452-18F 103
6452-30F 103
6452DK 103
6463-08C 228

65xxx

651017M 139
651018M 139
651019M 139
651021M 139
651022M 139
651023M 139
651024M 139
651026M 139
651027M 139
651028M 139
651029M 139
651030M 139
6511-10A 227
6511-10C 227
6511-13C 227
6511-17C 227
651417M 143
651419M 143
651420M 143
651421M 143
651514M 139
651515M 139
651516M 139
651517M 139
651518M 139
651519M 139
651521M 139
651522M 139
651523M 139
651524M 139
651525M 139
651526M 139
651527M 139
651528M 139
651529M 139
651530M 139
6516-10 195
6516-10A 199
653017M 139
653019M 139
653021M 139
653022M 139
653023M 139
653024M 139
653026M 139
653027M 139
653028M 139
653029M 139
653030M 139
653032M 139
653033M 139
653034M 139
653035M 139
653036M 139
653038M 139
653040M 139
653041M 139
653042M 139
653046M 139
653063M 139
653065M 139
653070M 139
6531-10 217
6531-12 217
6531-14 217
6531-18 217
6531-24 217
6531-36 217
6531-48 217
653517M 140
653518M 140
653519M 140
653521M 140
653522M 140
653522S 140
653523M 140
653524M 140
653524S 140
653526M 140
653526S 140
653527M 140
653528M 140
653528S 140
653529M 140
653530M 140
653530S 140
653532M 140
653532S 140
653533M 140
653534M 140
653534S 140
653535M 140
653536M 140
653536S 140
653538M 140
653538S 140
653540M 140
653540S 140
653541M 140
653542M 140
653542S 140
653543M 140
653544M 140
653544S 140
653546M 140
653546S 140
653548M 140
653548S 140
653550M 140
653550S 140
653552M 140
653552S 140
653554M 140
653554S 140
653555M 140
653556S 140
653557M 140
653558M 140
653558S 140
653560M 140
653560S 140
653562S 140
653563M 140
653564S 140
653565M 140
653566S 140
653568S 140
653570S 140
653572S 140
653574S 140
653576S 140
6572-20 103
6572DK 103
657524M 142
657526M 142
657528M 142
657530M 142
657532M 142
6581-12 103
6581-18 103

66xxx

6605-08 232
6615-06 233
6615-11 233
6615-18 233
6625-06 233
6625-11 233
6625-18 233
6655-09 233
6665-09 233

67xxx

6711-06 227
6716-06A 230
6721-10 234
6731-09 234
6741-06 234
6779-20F 103
6779DK 103
6791 103
6797 144
6797P 144
6798 144
6798P 144
67HB-07 228
67HS-07 228
67SB-07 228
67SS-07 228

68xxx

6814 103
6818 103
683517M 142
683519M 142
683521M 142
683522M 142
683523M 142
683524M 142
683526M 142
683527M 142
683529M 142
683530M 142
683532M 142
6864 145
6864P 145
6868 145
6868P 145
6874 145
6874P 145
68GB-01 320
68GB-02 320
68GB-11 320
68GB-16 320
68GR-01 320
68GR-11 320
68GS-11 320
68GS-16 320
68GQ-01 320
68GQ-02 320
68GQ-11 320
68GQ-16 320
68HB-05 228
68HB-07 228
68HB-10 228
68HS-05 228
68HS-07 228
68HS-10 228
68RB-01 320
68RB-02 320
68RB-11 320
68RB-16 320
68RR-01 320
68RR-11 320
68RS-11 320
68RS-16 320
68RQ-01 320
68RQ-02 320
68RQ-11 320
68RQ-16 320
68SB-05 228
68SB-07 228
68SB-10 228
68SS-05 228
68SS-07 228
68SS-10 228
68ZZ-01 320
68ZZ-02 320

69xxx

6921-05A 228
6921-05C 228
6921-06A 228
6921-06C 228
6921-07A 228
6921-07C 228
693519M 142
693521M 142
693522M 142
693523M 142
693524M 142
693524S 142
693526M 142
693526S 142
693527M 142
693528S 142
693529M 142
683530M 142
693530S 142

693532M 142
693532S 142
693534S 142
693536S 142
693538S 142
693540S 142
6AB12-55 240

70xxx

7075MR 110
7075MR01 110
7085MR 111

71xxx

711002P 267
7112PR 114
7113PR 114
711501P 267
711502P 267
711503P 267
7120PR 107
7120PR01 107
715000P 267
715001P 267
715002P 267
715003P 267
715000R 267
715001R 267
715001Z 267
715002H 267
715002R 267
715002Z 267
715003H 267
715003R 267
715003S1 267
715003Z 267
715004H 267
715004S1 267
715004S2 267
715005H 267
715005S1 267
715006H 267
715006S1 267
715006T 267
715007H 267
715007T 267
715008H 267
715008T 267
715009T 267
715010T 267
715015T 267
715020T 267
715025H 267
715025T 267
715027T 267
715030T 267
715035S1 267
715040T 267
715045S1 267
715055S1 267
715055S2 267
715065S1 267
716502P 267
717001P 267
717001Z 267
717002P 267
717002Z 267
717003P 267
717003Z 267
717006T 267
717007T 267
717008T 267
717009T 267
717010T 267
717015T 267
717020T 267
717025T 267
717027T 267
717030T 267
717040T 267
719001P 267
719001Z 267
719002P 267
719002Z 267
719003P 267
719003Z 267

72xxx

721102P 268
726502P 268
727502P 268

73xxx

731101P 268
731102P 268
731103P 268
731152P 268
731502P 268
731503P 268
731552P 268
734501P 268
734502P 268
734503P 268
734551P 268
734552P 268
736501P 268
736502P 268
736503P 268
736552P 268

74xxx

74010 237
74020 237
74030 237
74040 237
74060 237
741002P 268
74150 237
741502P 268
74160 237
74250 238
74260 238
74270 238
74350 238
74360 238
74407 239
74408 239
74410 239
74412 239
74414 239
74416 239
745002P 268
74508 239
74510 239
74512 239
74514 239
74607 240
74610 240
74613 240
747502P 268
747503P 268
74900 240

75xxx

750-60 269
751-60 269
751-75 269
75102-08 285
75102-10 285
75102-08G 285
75102-10G 285
752-60 269
752-75 269
75202-08 285
75202-10 285
75202-08G 285
75202-10G 285
753-63 269
75302-08 285
75302-10 285
75302-08G 285
75302-10G 285
75402-08 285
75402-10 285
75402-08G 285
75402-10G 285
75502-08 285
75502-08G 285
75502-10 285
75502-10G 285
7553MR 113
7558MR 108
7572MR 110
7597MR 112

76xxx

7606508S 269
7606510S 269
7606512S 269
76103-04 283
76104-05 283
76105-06 283
7614208S 269
7614210S 269
7614512S 269
7616507M 269
7616508M 269
7616508S 269
7616510M 269
7616510S 269
7616512S 269
7616514S 269
76213-04 283
76215-05 283
76217-06 283
76220-07 283
76223-08 283
76224-10 283
76226-12 283
76301-05 283
76302-05 283
76303-05 283
76304-05 283
76305-05 283
76306-05 283
76307-05 283
76308-05 283
76309-06 283
76310-06 283
76402-45 283
76403-05 283
76404-06 283
76405-65 283
76406-07 283
76408-08 283
76410-85 283
76412-09 283
76414-10 283
76717-05 286
76721-06 286
76724-08 286
76729-10 286

77xxx

7702-25 269
7702-50 269
7703-50 269
7712-02 269
7712-03 269
77121-08 292
77131-06 292
77131-08 292
77141-06 292
77141-08 292
77340-20 292
77335-25 293

78xxx

7811-08 287
7811-12 287
7811-16 287
7811-24 287
7811-32 287
7811-40 287
7821-30 287
7821-50 287
7821-80 287
7822-25 287
7822-30 287
7822-35 287
7822-40 287
7822-45 287
7822-50 287
7823-10 287
7823-15 287
7823-20 287
7833-10 288
7833-12 288
7833-15 288
7833-20 288
7842-22 288
7842-28 288
7842-35 288
7842-45 288
7842-60 288
7851-08 288
7851-16 288
7851-24 288
7851-32 288
7851-40 288
7851-48 288
7851-64 288

79xxx

79061-12 292
79061-20 292
79061-40 292
79083-03C 291
79083-05C 291
790831CQ 291
79084-03C 291
79084-05C 291
790841CQ 291
7911-12 289
7912-21 242
7912-22 242
7912-23 243
7921-12 289
7962-03 287
7962-04 287
7962-06 287
7962-08 287
7962-12 287
7963-03 287
7963-04 287
7963-06 287
7963-08 287
7963-12 287
79711 290
7971-07 241
7976-65 241
79900-04 293
79900-10 293
79900-13 293
79900-20 293
799001DQ 293

80xxx

8015MR 106
8015SR 106

82xxx

8251-08 106
8251-16 106
8260-07 152
8260-07P 152
8260-10 152
8260-10P 152
8260-13 152
8260-13P 152

83xxx

833036M 105
833038M 105
833041M 105
833046M 105
833046S 105
833048S 105
833050M 105
833054M 105
833054S 105
833055M 105
833058M 105
833060M 105
833060S 105
833063M 105
833064S 105
833065M 105
833067M 105
833070M 105
833071M 105
833072S 105
833075M 105
833076S 105
833077M 105
833080M 105
833084S 105
833094S 105
8330A0S 105

84xxx

8408MP 154
8409MP 154
8410MP 154
8410SP 154
843524M 150
843527M 150
843528M 150
843530M 150
843530S 150
843532M 150
843532S 150
843533M 150
843534M 150
843534S 150
843535M 150
843536M 150
843536S 150
843538M 150
843538S 150
843540M 150
843540S 150
843541M 150
843542M 150
843542S 150
843544S 150
843546M 150
843546S 150
843548M 150
843548S 150
843550M 150
843550S 150
843552M 150
843552S 150
843554M 150
843554S 150
843555M 150
843556S 150
843558M 150
843558S 150

Index

843560M ---- 150
843560S ---- 150
843562S ---- 150
843564S ---- 150
843566S ---- 150
843568S ---- 150
843570S ---- 150
843572S ---- 150

85xxx

851417M ---- 151
851419M ---- 151
851420M ---- 151
851421M ---- 151
851422M ---- 151
851426S ---- 151
852421M ---- 151
853417M ---- 151
853419M ---- 151
853421M ---- 151
853519M ---- 148
853521M ---- 148
853522M ---- 148
853523M ---- 148
853524M ---- 148
853524S ---- 149
853525M ---- 148
853526M ---- 148
853526S ---- 149
853527M ---- 148
853528M ---- 148
853528S ---- 149
853529M ---- 148
853530M ---- 148
853530S ---- 149
853532M ---- 148
853532S ---- 149
853533M ---- 148
853534M ---- 148
853534S ---- 149
853535M ---- 148
853536M ---- 148
853536S ---- 149
853538M ---- 148
853538S ---- 149
853540M ---- 148
853540S ---- 149
853541M ---- 148
853542M ---- 148
853542S ---- 149
853544M ---- 148
853544S ---- 149
853546M ---- 148
853546S ---- 149
853548M ---- 148
853548S ---- 149
853550M ---- 148
853550S ---- 149
853552M ---- 148
853552S ---- 149
853553M ---- 148
853554M ---- 148
853554S ---- 149
853555M ---- 148
853556S ---- 149
853558M ---- 148
853558S ---- 149
853560M ---- 148
853560S ---- 149
853562S ---- 149
853563M ---- 148
853564S ---- 149
853565M ---- 148
853566M ---- 148
853566S ---- 149
853568M ---- 148
853568S ---- 149
853570M ---- 148
853570S ---- 149
853571M ---- 148
853572S ---- 149
853574S ---- 149
853575M ---- 148
853576S ---- 149
853578S ---- 149
853580M ---- 148
853580S ---- 149
853582S ---- 149
853584S ---- 149
853585M ---- 148
853586S ---- 149
853588S ---- 149
853590M ---- 148
853590S ---- 149
853595M ---- 148
853592S ---- 149
853594S ---- 149
853596S ---- 149
8535A0S ---- 149
8535A0M ---- 148
8535A4S ---- 149
8535A8S ---- 149
8535B2S ---- 149
8572-25 ---- 106
8572DK ---- 106
8581-26 ---- 106

87xxx

870208 ---- 60
870311 ---- 72
870322 ---- 72
870406 ---- 92
870410 ---- 92
870422 ---- 60
87103 ---- 4
87105 ---- 3
87106 ---- 3
87108 ---- 286
87110 ---- 3
87111 ---- 3
8711B ---- 4
87151 ---- 5
87160 ---- 6
8720 ---- 60
87203 ---- 3
8730 ---- 72
87301 ---- 3
87301-494A ---- 3
87301-496A ---- 3
87301-498A ---- 3
87352 ---- 4
8740 ---- 92
87401-2 ---- 23
87401-3 ---- 23
87401-3H ---- 23
87402 ---- 23
87404 ---- 23
87407 ---- 24
87411-6B ---- 22
87411-9B ---- 22
87421-3B ---- 22
87432-15 ---- 9
87432-22 ---- 9
87432-23 ---- 9
87432-24 ---- 9
87432-26 ---- 9
87432-52 ---- 9
87432-5B ---- 7
87432-5G ---- 7
87434-7B ---- 7
87434-7G ---- 7
87438-3B ---- 7
87441-1B ---- 8
87441-3B ---- 8
87501P01 ---- 11
87501P02 ---- 11
87501P03 ---- 11
87502 ---- 9
87502-01 ---- 12
87502-02 ---- 12
87502-050 ---- 12
87502-051 ---- 12
87502-054 ---- 12
87502-058 ---- 12
87502-061 ---- 12
87502-064 ---- 12
87502-068 ---- 12
87502-11 ---- 12
87502-12 ---- 12
87502P01 ---- 10
87502P011 ---- 10
87502P012 ---- 10
87502P90 ---- 10
87502P91 ---- 10
87711C ---- 24
8772KT ---- 3
8773KT ---- 3
8774KT ---- 3
8776KT ---- 3
8779-32F ---- 105
8779DK ---- 105
8781007KT ---- 4
8781012KT ---- 4
8781013KT ---- 4
8781032KT ---- 4
8797 ---- 152
8797P ---- 152

88xxx

8816 ---- 106
883524M ---- 151
883527M ---- 151
883529M ---- 151
883530M ---- 151
883532M ---- 151
883533M ---- 151
883534M ---- 151
883535M ---- 151
883536M ---- 151
883538M ---- 151
883541M ---- 151
8866 ---- 153
8866P ---- 153
8869 ---- 153
8869P ---- 153

9-xxx

9-10112MR ---- 40
9-10115MR ---- 40
9-10212MR ---- 40
9-10215MR ---- 40
9-1216MR ---- 34
9-1216MR01 ---- 34
9-1217MR ---- 44
9-1218MR ---- 34
9-1219MR01 ---- 34
9-1282MR ---- 41
9-1303MR ---- 39
9-1606MR ---- 44
9-1606MR01 ---- 44
9-1609MR ---- 38
9-1709MR ---- 35
9-1711MR ---- 35
9-1716MR ---- 44
9-1905MR ---- 40
9-1C08MR ---- 41
9-20110MR ---- 39
9-22108MR ---- 35
9-22308PR ---- 35
9-2526MR ---- 39
9-2548CR ---- 30
9-2548CR01 ---- 30
9-30106MR ---- 45
9-30206MR ---- 45
9-31006MR ---- 43
9-31106MR ---- 39
9-30110CR ---- 35
9-31110MR ---- 36
9-31909PR ---- 38
9-31919MR ---- 42
9-3523MR ---- 37
9-40102GP ---- 31
9-40103GP ---- 40
9-40203GP ---- 45
9-40207GP ---- 36
9-40207GP01 ---- 36
9-40604GP ---- 37
9-4116FR ---- 44
9-4119PR ---- 39
9-4120PR ---- 39
9-4128FR ---- 39
9-42114GP ---- 31
9-42144GP ---- 38
9-4319MR ---- 44
9-4319MR01 ---- 44
9-4328MR ---- 32
9-4333MR ---- 32
9-4338MR ---- 42
9-4338MR01 ---- 42
9-4338MR03 ---- 42
9-4516MR ---- 32
9-4522MR ---- 33
9-4526MR ---- 30
9-5575MR ---- 33
9-7069CR ---- 30
9-7069CR01 ---- 30
9-7540MR ---- 30
9-90103PP ---- 36
9-90103PP01 ---- 36
9-90104GP ---- 43
9-90106SR ---- 38
9-90109MN ---- 35
9-90115MR ---- 45
9-90120MR ---- 45
9-90121MR ---- 43
9-90125MR ---- 45
9-90126MR ---- 43
9-90128SR ---- 31
9-90129CR ---- 31
9-90131MR ---- 37
9-90138CR ---- 32
9-90205GN ---- 37
9-90205GN01 ---- 37
9-90310MR ---- 36
9-90315MR ---- 34
9-90408TQ ---- 42
9-91120MR ---- 35

90xxx

901-068MR ---- 26
901-069MR ---- 26
901-073MR ---- 26
902-062MR ---- 27
902-065MR ---- 27
902-065MR04 ---- 27
902-068MR ---- 26
902-089MR01 ---- 28
902-103MR ---- 29
9033CR ---- 108
90401 ---- 134
90402 ---- 134
90403 ---- 145
90404 ---- 145
90405 ---- 153
90406 ---- 153
90408 ---- 123
90409 ---- 123
90601 ---- 134
90602 ---- 134
90603 ---- 145
90604 ---- 145
90605 ---- 153
90606 ---- 153
90607 ---- 145
90608 ---- 123
90609 ---- 123
9063MR ---- 109
9063MR01 ---- 109

91xxx

911-000CR ---- 25
911-000CR01 ---- 25
911-000CR02 ---- 25
91162MR ---- 213
91168MR ---- 213
91230 ---- 258
91232 ---- 253
91248 ---- 285
91249 ---- 285
91262MR ---- 213
91268MR ---- 213
91403 ---- 4
91404 ---- 4
91406 ---- 4
91408 ---- 4
91421-01 ---- 4
91421-11 ---- 4
91431 ---- 3
91522H/S ---- 288
91528H/S ---- 288
91535H/S ---- 288
91545H/S ---- 288
91560H/S ---- 288

92xxx

92543MR ---- 102

93xxx

932-000MR ---- 16
932-008MR ---- 17
932-009MR ---- 20
932-010MR ---- 19
934-001MR ---- 18
936-003MR03 ---- 297
938-001MR ---- 21

94xxx

941-000MR ---- 15
9415GR ---- 115

95xxx

9507MR ---- 112
953532M ---- 155
953533M ---- 155
953534M ---- 155
953536M ---- 155
953538M ---- 155
953541M ---- 155
953542M ---- 155
953546M ---- 155
953550M ---- 155
953555M ---- 155
953560M ---- 155
953565M ---- 155
953570M ---- 155
953575M ---- 155
953580M ---- 155
953585M ---- 155
953590M ---- 155
953595M ---- 155
9535A0M ---- 155
9535A5M ---- 155
9535B0M ---- 155
9535B5M ---- 155
9535C0M ---- 155
9535C5M ---- 155
9535D0M ---- 155

9535D5M ---- 155
9535E0M ---- 155
9535F0M ---- 155
9563MR ---- 109
9563MR01 ---- 109

98xxx

9868 ---- 155
9868P ---- 155

9Axxx

9AA21 ---- 298
9AA31 ---- 298
9AC125-32 ---- 299
9AC125-40 ---- 299
9AC175-32 ---- 299
9AC175-40 ---- 299
9AC175-66 ---- 299
9AD11 ---- 298
9AE2-6606 ---- 300
9AE2-7476 ---- 300
9AE2-7612 ---- 300
9AE2-7614 ---- 300
9AE2-8616 ---- 300
9AE2-8618 ---- 300
9AE2-9210 ---- 300
9AE2-9315 ---- 300
9AE2-9345 ---- 300
9AE2-9618 ---- 300
9AE2-10615 ---- 300
9AE2-10815 ---- 300
9AE2-10818 ---- 300
9AE221 ---- 301
9AE41 ---- 300
9AE42 ---- 301
9AE423 ---- 301
9AE52 ---- 301
9AH11 ---- 301
9AH025 ---- 302
9AK11 ---- 302
9AL11 ---- 303
9AL12 ---- 303
9AR11 ---- 303
9AP100 ---- 299
9AP120 ---- 299
9AP160 ---- 299

9Bxxx

9BA11 ---- 304
9BA21 ---- 304
9BA22 ---- 304
9BC11 ---- 305
9BC121 ---- 305
9BC122 ---- 305
9BC124 ---- 305
9BC21 ---- 306
9BC22 ---- 306
9BC23 ---- 306
9BC25 ---- 307
9BE11 ---- 307
9BE21 ---- 307
9BF11 ---- 308
9BF21 ---- 308
9BF31 ---- 308
9BG11 ---- 308
9BJ11 ---- 309
9BK11 ---- 309
9BK41-53 ---- 309
9BT250 ---- 311
9BU111 ---- 316
9BU111T ---- 316
9BU112 ---- 316
9BU112T ---- 316
9BU241 ---- 317
9BU241T ---- 317
9BU242 ---- 317
9BU242T ---- 317
9BU251 ---- 317
9BU251T ---- 317
9BU252 ---- 317
9BU252T ---- 317

9Cxxx

9CF-107 ---- 311
9CF110 ---- 310
9CF-207 ---- 311
9CF120 ---- 310
9CF130 ---- 310
9CF131 ---- 310
9CF132 ---- 310
9CF210 ---- 310
9CF220 ---- 310
9CF230 ---- 311
9CF240 ---- 311
9CF241 ---- 311
9CF-307 ---- 311
9CJ013 ---- 312
9CJ023 ---- 313
9CJ033 ---- 314
9CJ1112 ---- 312
9CJ1120 ---- 312
9CJ1130 ---- 312
9CJ2112 ---- 313
9CJ2120 ---- 313
9CJ2212 ---- 313
9CJ3104 ---- 314
9CJ3105 ---- 314
9CJ3106 ---- 314
9CJ61-40 ---- 314
9CK-101 ---- 324

9Dxxx

9DB201 ---- 315
9DC22 ---- 315
9DC23 ---- 315

9Txxx

9TA21A ---- 318
9TA23A ---- 318
9TB225 ---- 324
9TC101 ---- 319
9TD014MR ---- 319
9TD401-06M ---- 318
9TD401-08M ---- 318
9TD401-10M ---- 318
9TD401-12M ---- 318
9TD403-12M ---- 319
9TD403-13M ---- 319
9TD403-14M ---- 319
9TD403-17M ---- 319
9TD403-19M ---- 319
9TE11 ---- 323
9TK014 ---- 323
9TK108 ---- 323
9TK112 ---- 323
9TK118 ---- 323
9TK124 ---- 323
9TP11 ---- 323
9TQ01 ---- 324
9TZ11-04 ---- 294
9TZ11-05 ---- 294
9TZ11-06 ---- 294
9TZ11-08 ---- 294

Axxx

ADFLAG ---- A15
ADFLAG1 ---- A15
ADHSTK-KT ---- A15
ADSTK-A ---- A15
ADSTK-H ---- A15
ADSTK-P ---- A15
ADSTK-T ---- A15
ADVT-A ---- A15
ADVT-H ---- A15
ADVT-P ---- A15
ADVT-T ---- A15

Cxxx

CPSTK-G1 ---- A16
CPSTK-G2 ---- A16
CPSTK-G3 ---- A16

Zxxx

ZS104 ---- A13
ZS105 ---- A13
ZS106 ---- A13
ZS107 ---- A13
ZS108 ---- A13
ZS109 ---- A14
ZS110 ---- A14
ZS111 ---- A14
ZS112 ---- A14
ZS113 ---- A13
ZS203 ---- A13
ZS208 ---- A16
ZS402 ---- A13
ZS403 ---- A13
ZS405 ---- A13
ZS510 ---- A16
ZS511 ---- A16
ZS512 ---- A16
ZS520 ---- A14
ZS521 ---- A14
ZS522 ---- A15
ZS524 ---- A15
ZS526 ---- A15
ZS529 ---- A16
ZS531 ---- A16
ZS533 ---- A15
ZS534 ---- A16
ZS535 ---- A16
ZV001 ---- 189

Notes

KING TONY TOOLS CO.,LTD.

http://www.kingtony.com
sales department e-mail: sales@kingtony.com.tw
customer service e-mail: service@kingtony.com.tw

CAT2012-0FG