

ComTrac®

Adjustable Speed Drives



Speed Control Made Simple!

STANDARD
3-DAY
DELIVERY

"Geared to a higher standard!"



www.stober.com





ComTrac® Adjustable Speed Drives

Company Profile

STÖBER was first established in Germany in 1934, and has been a pioneer in the gearing industry ever since. Through constant innovation, STÖBER today is known for high precision, high efficiency and low noise in their various gearing technologies. STÖBER® Drives Inc., located in Maysville, KY, manufactures products to serve the North American market.

Beginning with the ComTrac® Mechanical Variable Speed Reducers, STÖBER established itself as a technology leader, later adding the innovative MGS® Modular Gear System to the product offering. MGS® Food and Beverage Reducers excel in the harshest of washdown environments.

STÖBER next introduced ServoFit® Precision Planetary Gearheads, establishing the standard for low noise and low backlash in the servo industry. The recent introduction of the SMS® ServoFit Modular System gearheads adds a high precision, cost effective alternative to the servo market.

STÖBER has the broadest offering of speed reducers available, providing one stop shopping for both the industrial market and the rapidly growing motion control market.

On behalf of the worldwide family of STÖBER employees, we thank you for trying our products and pledge to continue to meet your product and service needs with the newest solutions.

Sincerely,

Bernd Stöber, Chairman
Stöber Antriebstechnik GmbH

Peter Feil, VP/General Manager
STOBER Drives, Inc.



Table of Contents

ComTrac Adjustable Speed Drives

Advantages and Features	2
Performance	3
Washdown Duty	4
Operating Characteristics	5
Ratings and Dimension	
.50 HP	6
.75 HP	7
1.0 HP	8
1.5 HP	9
2.0 HP	10
3.0 HP	11
5.0 HP	12
Electric Remote Control (ERC)	13
Selection and Performance Characteristics	14
Installation Instructions	16
Maintenance and Lubrication	18

"C" Series MGS Adjustable Speed Drives

Performance Specifications.....	19
Ratings	20
Dimensions.....	34
Mounting Positions	70

"F" Series MGS Adjustable Speed Drives

Performance Specifications.....	37
Ratings	38
Dimension	44
Mounting Positions	70

"K" Series MGS Adjustable Speed Drives

Performance Specifications.....	47
Ratings	48
Dimensions.....	64
Mounting Positions	71
Mounting Hollow Output Units	68
Mounting Positions	69
Terms and Conditions.....	72

ComTrac® Adjustable Speed Drives



Advantages:

You're probably already aware of the many common-sense advantages offered by traction-type adjustable speed drives like the ComTrac drive. When compared to mechanical belt-type, or electrical adjustable speed drives, traction type drives offer:

- Often, a lower initial cost.
- Few worries about motor overheating during low speed operation.
- No motor brushes to replace.
- Very compact and lightweight when compared to other mechanical drives.
- Simple design with few rotating components to wear or replace.
- Easily serviced by semiskilled personnel
- Low maintenance – doesn't need to be cycled through its speed range to prevent component damage.
- 2 year warranty—your assurance of satisfactory product performance.

Features:

Drive cone – The drive cone is made from ductile iron and is precision ground for long service life. It contains inner air chambers for efficient heat dissipation. It is independently supported by a shielded bearing mounted into the motor adapter/slide – not just by the motor bearing.

Traction ring – ComTrac's self-lubrication traction ring is made from a proprietary material that provides exceptional resistance to wear and high temperatures. When replacement is necessary, only the ring and not the entire friction ring mounting flange is replaced.

Speed adjustment – ComTrac's rack and pinion speed adjustment system features stainless steel components to resist corrosion and is dust resistant by design. The stainless steel pinion shaft and ductile iron rack are designed to provide assured speed adjustments in the wettest, dirtiest environments.

Handwheel control – Handwheel control with a position indicator is standard on every ComTrac drive. Remote speed controls and overspeed protection is also available.

All ComTrac drives are shipped with the handwheel positioned on the left as viewed from the output shaft end of the drive. The handwheel can be quickly and easily moved to the right side by using the tools and instructions included with the drive.

Mounting position – ComTrac drives can be mounted in virtually any position.

NEMA C-face input – All ComTrac drives feature a NEMA C-face input – that means standard off-the-shelf motors, available locally. ComTrac's patented corrosion resistant collet clamp ring makes motor shaft attachment fast and simple. The proper hex wrenches are included with each unit in the motor access cover. When the motor must be replaced, it can be done easily and quickly without disassembly of the entire drive.

In addition, the OF unit is standard with a NEMA C-face output flange. It enables you to add adjustable speed capability to new or existing applications.

Torque compensator – The torque compensator assembly features high-capacity cylindrical roller bearings – not needle bearings – for long life and quiet operation. The design allows speed changes during operation or while the drive is at rest. The load compensating cams precisely match the pressure between the drive cone and the traction ring in proportion to the load torque.

Cast iron housing – High tensile strength cast iron housing for long service life in demanding applications.

Stainless steel nameplate.

Two year warranty – Every ComTrac unit is backed by a two-year warranty.


Delivery – ComTrac units are shipped in 3 days or less.

Selection:

In general, proper selection of a ComTrac drive is as easy as the drive is to operate.

1. Establish the maximum horsepower required by the driven machine at maximum speed.
2. Select the drive which meets or exceeds the maximum HP rating of the driven machine at maximum speed.

Part No. Example:



Speed Control Made Simple!




ComTrac® Adjustable Speed Drives

Performance Specifications:

- Horsepower ratings – from 1/2 to 10
- Output speeds – available from 2180 to 311 RPM
- Speed range – 5:1 to 7:1
- Output torques – up to 496 in.lbs.
- NEMA frames – from 56C to 215TC

**STANDARD
3-DAY
DELIVERY**



Footed unit shown for illustration only.
This style is no longer available.

ComTrac® Adjustable Speed Drives

Washdown/Outdoor Service/ Severe Duty



Advantages:

STÖBER has developed a severe duty protection package for ComTrac drives which significantly improves the drives' ability to withstand the effects of outdoor use, exposure to excessively humid or acidic environments, or spray washed with water or caustic fluids.

The ComTrac severe duty package includes corrosion protection for all functional components and housings including:

- Drive cone
- Motor clamping ring
- Motor slide and rack
- Bearing housing
- Main housing cover

To prevent corrosion, these components are protected by a special heat treatment process similar to chrome plating.

Features:

Drive cone – Corrosion protected drive cone extends cone and ring life.

Speed adjustment – The protected motor slide, stainless steel control shaft with pinion, and greased rack and slideway assure the proper speed adjustment.

NEMA C-face input – ComTrac's patented corrosion resistant collet clamp ring assures ease of motor replacement.

External surface – All external surfaces are protected with a special acid-resistant epoxy paint to prevent corrosion and lubricant contamination.

Internal surface – All internal surfaces and bearing housing are protected with a special anticorrosion paint.

Double seals – Double output seals can be provided for maximum protection in very harsh environments.

Mounting position – ComTrac drives in a vertical mounting position (output shaft down) must be adapted to allow water to drain.

Stainless steel nameplate – Other features of the severe duty unit are: stainless steel nameplate, rivets, and chrome plated bolts.

Two year warranty – Like the standard drive, this ComTrac unit is also backed by a two-year warranty.

Delivery – ComTrac units are shipped in 3 days or less.


**STANDARD
3-DAY
DELIVERY**



Footed unit shown for illustration only.
This style is no longer available.



ComTrac® Adjustable Speed Drives Operating Characteristics



Footed unit shown for illustration only.
This style is no longer available.

Operation:

The ComTrac drive is an adjustable speed traction drive. Its operation is based upon the transfer of power between the motor mounted **drive cone** and the **traction ring**. The **drive cone** and the **traction ring** are forced together to transmit torque through the use of a **spring loaded torque compensator assembly**.

At rest, the **spring** inside the **torque compensator** produces only a small contact pressure between the **drive cone** and **traction ring**. Unlike other mechanical drives, the minimal spring pressure allows speed changes to be made while the drive is at rest.


As the drive is started, the **load compensating cams** move against each other to increase pressure between the **drive cone** and **traction ring**. During operation, the **load compensating cams** maintain the proper amount of pressure between the **drive cone** and **traction ring** in proportion to the output load torque required.

Speed changes are made by changing the relative running diameters of the **drive cone** and the **traction ring**. As the motor and **drive cone** are moved upward, the contact point between the **cone** and **ring** moves to the faster running outer diameter of the **drive cone** and output speed increases. As the motor and **drive cone** are lowered, the contact point between the **cone** and **ring** moves to the slower running center of the **drive cone** and output speed decreases.



Movement of the motor and **drive cone** are accomplished through the use of a **handwheel** attached to a **rack and pinion**. By turning the **handwheel**, the motor is easily raised or lowered on the **dust resistant motor slide**. Speed changes can also be made through the use of an optional electric remote control which replaces the **handwheel**.

Speed Control Made Simple!


- Turn the handwheel – pinion moves the rack on the motor slide – up or down.



Maximum speed – motor slide up.



Minimum speed – motor slide down.






ComTrac® Adjustable Speed Drives

.50 HP @ 1750 RPM

All TD27 units are available with 56C and 143TC input.



Constant Horsepower Range			Constant Torque Range					
RPM ⁽¹⁾	MAXIMUM		TRANSITION ⁽²⁾			MINIMUM		
	in.lbs.	HP	RPM	in.lbs.	HP	RPM	in.lbs.	HP
2,180	12.2	0.42	334	66	0.35	311	66	0.33

All ratings shown are based on 1750 RPM motor speed and are rated to provide constant torque through the entire speed range. Contact STOBER for constant horsepower applications. **MOTOR MUST BE ORDERED SEPARATELY.**

¹⁾ Speed tolerance at rated load is $\pm 3\%$. At less than rated load, minimum speed may increase 5%.


²⁾ The ComTrac drive operates at constant horsepower above transition values and at constant torque below transition values. Note shaded area. Engineering advances may cause slight changes to the information shown.



ComTrac® Adjustable Speed Drives

.75 HP @ 1750 RPM

All TD27 units are available with 56C and 143TC input.



Constant Horsepower Range			Constant Torque Range		
MAXIMUM	TRANSITION ⁽²⁾		MINIMUM		
RPM ⁽¹⁾	in.lbs.	HP	RPM ⁽¹⁾	in.lbs.	HP
2,180	18.3	0.63	582	66	0.61
			311	66	0.33

All ratings shown are based on 1750 RPM motor speed and are rated to provide constant torque through the entire speed range. Contact STOBER for constant horsepower applications. **MOTOR MUST BE ORDERED SEPARATELY.**

¹⁾ Speed tolerance at rated load is $\pm 3\%$. At less than rated load, minimum speed may increase 5%.


²⁾ The ComTrac drive operates at constant horsepower above transition values and at constant torque below transition values. Note shaded area. Engineering advances may cause slight changes to the information shown.



ComTrac® Adjustable Speed Drives

1.0 HP @ 1750 RPM

All TD27 units are available with 56C and 143TC input.



Constant Horsepower Range			Constant Torque Range					
RPM ⁽¹⁾	MAXIMUM		TRANSITION ⁽²⁾		MINIMUM			
	in.lbs.	HP	RPM	in.lbs.	HP	RPM	in.lbs.	HP
2,180	24.4	0.84	821	66	0.86	311	66	0.33

All ratings shown are based on 1750 RPM motor speed and are rated to provide constant torque through the entire speed range. Contact STOBER for constant horsepower applications. **MOTOR MUST BE ORDERED SEPARATELY.**


¹⁾ Speed tolerance at rated load is $\pm 3\%$. At less than rated load, minimum speed may increase 5%.

²⁾ The ComTrac drive operates at constant horsepower above transition values and at constant torque below transition values. Note shaded area. Engineering advances may cause slight changes to the information shown.



ComTrac® Adjustable Speed Drives

1.5 HP @ 1750 RPM



Constant Horsepower Range			Constant Torque Range		
MAXIMUM	TRANSITION ⁽²⁾		MINIMUM		
RPM ⁽¹⁾	in.lbs.	HP	RPM ⁽¹⁾	in.lbs.	HP
2,100	38	1.27	856	97	1.31
			420	97	0.64

All ratings shown are based on 1750 RPM motor speed and are rated to provide constant torque through the entire speed range. Contact STOBER for constant horsepower applications. **MOTOR MUST BE ORDERED SEPARATELY.**


¹⁾ Speed tolerance at rated load is $\pm 3\%$. At less than rated load, minimum speed may increase 5%.

²⁾ The ComTrac drive operates at constant horsepower above transition values and at constant torque below transition values. Note shaded area. Engineering advances may cause slight changes to the information shown.



ComTrac® Adjustable Speed Drives

2.0 HP @ 1750 RPM



Constant Horsepower Range			Constant Torque Range		
RPM ⁽¹⁾	in.lbs.	HP	TRANSITION ⁽²⁾		
			RPM ⁽¹⁾	in.lbs.	HP
2,100	51	1.70	1,162	97	1.79
			420	97	0.65

All ratings shown are based on 1750 RPM motor speed and are rated to provide constant torque through the entire speed range. Contact STOBER for constant horsepower applications. **MOTOR MUST BE ORDERED SEPARATELY.**


¹⁾ Speed tolerance at rated load is $\pm 3\%$. At less than rated load, minimum speed may increase 5%.

²⁾ The ComTrac drive operates at constant horsepower above transition values and at constant torque below transition values. Note shaded area. Engineering advances may cause slight changes to the information shown.



ComTrac® Adjustable Speed Drives

3.0 HP @ 1750 RPM



Constant Horsepower Range			Constant Torque Range					
MAXIMUM		TRANSITION ⁽²⁾			MINIMUM			
RPM ⁽¹⁾	in.lbs.	HP	RPM ⁽¹⁾	in.lbs.	HP	RPM ⁽¹⁾	in.lbs.	HP
2,100	81	2.70	970	177	2.72	420	177	1.18

All ratings shown are based on 1750 RPM motor speed and are rated to provide constant torque through the entire speed range. Contact STOBER for constant horsepower applications. **MOTOR MUST BE ORDERED SEPARATELY.**


¹⁾ Speed tolerance at rated load is $\pm 3\%$. At less than rated load, minimum speed may increase 5%.

²⁾ The ComTrac drive operates at constant horsepower above transition values and at constant torque below transition values. Note shaded area. Engineering advances may cause slight changes to the information shown.



ComTrac® Adjustable Speed Drives

5.0 HP @ 1750 RPM



Part No. – 88 lbs.
TD570FK184
Flange Style
184TC Input
182TC Output

Constant Horsepower Range			Constant Torque Range		
RPM ⁽¹⁾	in.lbs.	HP	TRANSITION ⁽²⁾		
			RPM ⁽¹⁾	in.lbs.	HP
2,100	137	4.56	1,102	266	4.65
					420
				266	1.77

All ratings shown are based on 1750 RPM motor speed and are rated to provide constant torque through the entire speed range. Contact STOBER for constant horsepower applications. **MOTOR MUST BE ORDERED SEPARATELY.**

¹⁾ Speed tolerance at rated load is $\pm 3\%$. At less than rated load, minimum speed may increase 5%.

²⁾ The ComTrac drive operates at constant horsepower above transition values and at constant torque below transition values. Note shaded area. Engineering advances may cause slight changes to the information shown.



ComTrac® Adjustable Speed Drives

Electric Remote Control





The STOBER Electric Remote Control (ERC) is a compact double reduction gearmotor which is pinion mounted to the motor slide track in place of the handwheel. A mechanical clutch within the unit indicates the end of vertical motor travel in both directions by making a clicking noise.



The ERC can be operated by push button or other type of control (not included) to adjust the drive's speed. In many applications it is advisable to use a limit switch with the ERC to prevent overspeed or underspeed conditions.

Features:

- Speed changes can be made when the unit is stationary or running.
- STOBER ERC can be quickly and easily added to existing ComTrac drives without special tools.
- All STOBER ERC units are designed for washdown/severe duty applications and are available from stock.
- Available voltages:
 - 115V, single phase, 60 Hz
 - 230/460V, three phase, 60 Hz



ERC for ComTrac sizes: TD27, TD37, and TD47.



ERC for ComTrac sizes: TD57

Table No. 1

ERC – Dimensions (Inches)

ComTrac	Model Number		A	B	C
	Single Phase	Three Phase			
TD27	ERC27-1	ERC27-2	6.18	7.09	9.72
TD37	ERC37-1	ERC37-3	6.14	7.05	9.68
TD47	ERC47-1	ERC47-3	7.12	8.03	10.67
TD57	ERC57-1	ERC57-3	7.56	9.06	11.10


Motor dimensions may vary slightly from values shown.

● Reference point for handwheel center.

Motor Clearance

On some TD27 ComTrac units, the motor can be lower than the base of the unit when adjusted to the slowest setting. The following formula will determine a value based on the length of the motor to be installed.

$$XX = .055 \times B \text{ (When "B" = motor length)}$$



Footed unit shown for illustration only.
This style is no longer available.

ComTrac® Adjustable Speed Drives

Selection and Performance Characteristics



Selection:

The ComTrac drives shown in the selection tables are rated for constant torque operation – where required horsepower varies directly in proportion to the speed of the driven machine. All ratings shown are based upon standard NEMA C-face motor designs with 1750 RPM input speed. Contact STOBER technical support for selection assistance for motor speeds other than 1750 RPM.

Basic selection procedure is as follows:

1. Establish the maximum horsepower required by the driven machine at maximum speed.

If only the driven equipment's maximum torque (T) requirement is known, use the following formula to convert the torque value to horsepower:

$$\text{HP} = \frac{T \times \text{RPM}}{63,025}$$

2. Select the drive which meets or exceeds the maximum HP rating of the driven machine at maximum speed.

Since the typical ComTrac application requires constant torque over the entire speed range, there will be an adequate service factor to protect the traction ring from damage.

Use the output speed ratings shown in the tables to select an output speed which meets or exceeds the requirement of the driven machine. Read across the table to determine if the drive's actual minimum and maximum speed, torque, and horsepower ratings meet the requirements of the driven equipment.

If the maximum output speed shown in the table is too low, go to the next higher speed. Should the torque or horsepower ratings shown be below the driven equipment's requirements, consult the next higher horsepower rating in the selection data.

Motor Performance

The ratings shown in the ComTrac selection tables are based on standard NEMA motors with the following specifications:

- 1750 RPM speed
- 60 Hz operation

Application Matched Options

Several options for ComTrac drives, such as remote controls, are included in this catalog. In addition, the following options are also available:

- 50 Hz operation for export
- Motor enclosures

For application and selection assistance for these options and others, contact your local STOBER distributor.

Non-Standard Application Conditions

For constant horsepower applications, or any of the nonstandard application conditions shown below, contact STOBER technical support.

Unusual Loading Conditions:

- Heavy shock load
- High inertia load
- Load reversals or overhauling loads
- More than ten starts per hour

Unusual Environmental Conditions:

- High altitudes – above 5000 feet
- Corrosive chemicals
- Excessively dusty or abrasive environments
- Ambient temperatures below 25° F or above 125° F

Nonstandard Motors:

- Motor frame sizes other than those shown in the tables

Nonstandard Mounting:

- Output shaft up or down (V5 or V6 mounting)

Not Recommended for Mounting:

- Explosive environment of any type

Performance Characteristics

Because of its mechanical operation, the ComTrac drive generally produces constant output torque. While the induction motor produces constant horsepower and constant speed, the two are combined in a manner that provides optimum utility and economy. As the ComTrac Performance Chart shows, the drive has two operating regions.

1. Constant torque between the drive's absolute minimum speed and transition speed.
2. Constant horsepower between the transition speed and maximum speed.

When selecting a ComTrac drive, it is important to choose a unit which will not allow the cone and ring system to be over powered by the motor. As shown in the ComTrac Performance Chart, ComTrac drives should always be selected so that the output torque required is well below the torque capability of the cone and the ring system.



ComTrac® Adjustable Speed Drives Selection and Performance Characteristics

Graph No. 1 ComTrac Performance Chart

Overhung Loads





Table No. 1

ComTrac Series 0F Specifications

Motor HP	NEMA Frame	Output Torque in.lbs.	Model Number	C-Face Output Flange	Output Speed Range (RPM)		
					Range	Max.	Min.
.50	56C	16	TD270F	56C	7:1	2180	311
.75	56C	24	TD270F	56C	7:1	2180	311
1.00	143TC	32	TD270F	56C	7:1	2180	311
1.50	145TC	48	TD370F	143/145TC	5:1	2100	420
2.00	145TC	64	TD370F	143/145TC	5:1	2100	420
3.00	182TC	99	TD470F	143/145TC	5:1	2100	420
5.00	184TC	168	TD570F	182/184TC	5:1	2100	420

Minimum output torque rating based on 1750 RPM maximum input speed.

Graph No. 2 ComTrac Series 0F Output HP



ComTrac® Adjustable Speed Drives

Installation Instructions



ComTrac Series 0F


Units with C-face input and output are designed to attach to any speed reducer with a NEMA C-face input. Care must be taken to follow the speed reducer manufacturer's recommended mounting instructions.



NOTE: ComTrac Series 0F drives do not have mounting feet. The drive and motor assembly is mounted on the speed reducer which must support the reducer, ComTrac, and the motor. If there is concern for the ability of the reducer mounting feet to support the entire assembly, a larger speed reducer may be required.

The output shaft of the ComTrac drive is shipped from the factory with a protective coating. Remove this coating with a suitable nonflammable solvent. Precaution must be taken not to allow the solvent to contact the output shaft oil seal, since damage to the seal may occur.

Motor Installation



Step 1 – Remove the access cover.



Step 2 – Lubricate and insert keyed motor shaft into the slotted bore of the drive cone shaft.

NOTE: For ease of installation, secure the key to the motor shaft. (Staking near the end of the keyway or a temporary adhesive works well.)



Step 3 – Tighten the four motor flange bolts.

IMPORTANT: Jog the motor several revolutions before tightening the motor clamp to assure proper position of the drive cone on the motor shaft. See Page 5 for illustration.

Step 4 – Through the access hole, tighten the hex socket screw on the motor clamp hub to the tightening torque shown in the table below. The correct size hex wrench is provided. **DO NOT OVERTIGHTEN.**


SHOWN WITHOUT MOTOR FOR DEMONSTRATION.



Table No. 1

Clamp Ring Setscrew Tightening Torque

ComTrac Size	in. lbs.
TD27	88.5
TD37	88.5
TD47	221
TD57	434



Step 5 – Reattach access cover.

When couplings, gears, sprockets or pulleys are mounted on the output shaft, be sure to mount them as close as possible to the housing to minimize the effects of overhung loads on shafts and bearings.

CAUTION: Do not drive couplings, sprockets, gears or pulleys onto the output shaft with hard hammer blows, since damage to internal gears or bearings will result. All output shafts have a metric centering thread for attachment of transmission devices. They can be pulled on gently with a bolt and plate.




ComTrac® Adjustable Speed Drives

Installation Instructions

Handwheel Position

ComTrac drives are furnished with the speed control handwheel on the left, as viewed from the output shaft end of the drive. If it is necessary that the handwheel be moved to the opposite side, this can be accomplished very easily with the hex wrenches provided with each drive.


Procedure for Changing Handwheel Position:



Step 1 – Remove the three (3) plastic plugs in the housing on the side opposite the handwheel.



Step 2 – Remove the handwheel and indicator assembly by removing the two (2) socket-head capscrews which secure the handwheel indicator assembly to the housing.



Step 3 – Turn the yellow numbered position indicator wheel around by removing the slotted screw. (Be sure to remove the tape covering to expose position numbers on the other side of the wheel.)

Step 4 – Replace the slotted screw.



Step 5 – Place pinion, handwheel and indicator on desired side of the drive's housing (from where the three plastic plugs were removed), and secure with the two socket-head capscrews removed previously.



Step 6 – Relocate the plastic plugs to the holes where the handwheel was originally mounted.

Lubricate the motor slide and rack (both sides) with **one** (1) stroke with a grease gun through the fittings provided in the housing.

IMPORTANT: Do not over lubricate the motor slide. Under normal conditions, maintenance of the motor slide and rack should only be required one time per year.

Electric Remote Control (ERC) Installation

The Electric Remote Control consists of a small gearmotor mounted on the ComTrac drive in place of the manual handwheel control.

Procedure

Attaching the ERC is accomplished by simply removing the two (2) socket-head capscrews that secure the handwheel and indicator assembly to the drive's housing.

Replace the handwheel/indicator assembly with the ERC and secure it to the housing with the same two screws.

Lubricate the motor slide and rack (both sides) with one (1) stroke with a grease gun through fittings in the housing.

The ERC is operated by pushbutton or other form of contact (furnished by customer). A mechanical clutch is contained within the gearmotor which indicates the end position of travel, in either direction, by making a clicking noise. Also, the ERC can be operated while the drive is stationary.

Power required for the ERC is 230 volt, 3 phase, 60 hertz, or 115 volt, single phase, 60 hertz.

The wiring diagram for the ERC is inside the motor's conduit box.

The ERC motor and drive should be protected from excessive dust, flying chips, and oil splashes.

ComTrac® Adjustable Speed Drives

Maintenance and Lubrication Instructions



In order to obtain long life and trouble-free operation from your ComTrac® drive, it is essential that proper installation and operating procedures be followed.

The torque required by the application must not exceed the reducer torque capacity shown on the nameplate. For safety purposes a safety coupling should be installed between the reducer and the driven load. Otherwise, overload may cause damage to the interior parts of the reducer which may result in breaking the reducer housing. As a result, persons could be injured by flying parts or splashing hot gear oil.

This catalog includes basic directions for mounting and start-up of the ComTrac® drive, as well as lubrication information. Failure to follow these instructions will void the drive's warranty.

If you have questions about the installation, operation or maintenance of your ComTrac® drive, please contact your local STOBER distributor for assistance.

WARNING:

Safety is the most important consideration when operating any type of drive. Through proper application, safe handling methods, and wearing appropriate clothing, you can prevent accidents and injury to yourself and fellow workers.

The shafts of ComTrac® drives rotate at very high speeds and can cut off or severely injure hands, fingers, and arms. Use appropriate guards for shafts and other rotating parts at all times. Follow all directions in the service instruction manual.

Obey all federal, state and local safety regulations when operating the drive.



- Always be sure electrical power is off while making electrical connections and during installation and maintenance of the unit.
- Keep clothing, hands, and tools away from ventilation openings on motors and from all rotating parts during operation.
- Lift drive with a double rope sling or other proper lifting equipment of adequate strength. Make sure load is secured and balanced to prevent shifting when unit is being moved. Lifting heavy drives by hand may be dangerous and should be avoided.
- The intended use of lifting lugs is to handle the weight of the unit only. Never use a lifting lug to lift attached assemblies.
- Never operate drive at speeds higher than those shown on the nameplate, or personal injury may result. Contact STOBER Drives Inc., if there is any change of operating conditions from those for which the unit was originally sold (as stamped on the nameplate). Failure to comply could result in personal injury and/or machinery damage.
- Always follow good safety practices at all times.

Each drive is tested before delivery. Before installation, however, it is advisable to examine the unit for possible damage which might have occurred during transit. If damage is discovered, it should be immediately reported to the transport agent.

If installation is delayed after receipt of the MGS speed reducer, the drive should be stored in a clean, dry place until put into service. Long term storage requires special procedures. If not kept in a heated, dry area, consult STOBER Drives, Inc. for storage instructions.

NOTE: If it is necessary to clean drive shafts, take care to protect the oil seals.

IMPORTANT: Do not use any device to hammer the unit onto the output shaft during installation since the bearing races could be damaged.

Maintenance and Lubrication

WARNING: Before beginning any work on the ComTrac drive system, disconnect the power source (lock-out the motor starter, and unload breakers, backstops, etc.). Failure to do so may cause serious personal injury and/or machinery damage.

Series 0F

These units require lubricant only in the cam and bearing chamber and are shipped with the lubricant in them. There is a sufficient quantity of lubricant to allow mounting the non-gearied ComTrac Drive in any position.

Table No. 1

Series "0" – Bearing and Cam Chamber Oil Quantity

ComTrac Size	fluid oz.
TD27-0	1.5
TD37-0	1.7
TD47-0	1.9
TD57-0	4.4

For normal indoor installations the handwheel or ERC control pinion and motor slide rack should be lubricated through the grease fitting every six months using NLGI No. 2 grease. One stroke of a grease gun is sufficient. When the drive is operating under wet conditions, increase the frequency of lubrication to once a month.

Under normal operating conditions the synthetic oil in the cam and bearing chamber does not need to be replaced. If for any reason some quantity of lubricant is lost, remove the rest of the lubricant from the cam and bearing chamber and replace it with the type and quantity of oil listed in the lubrication table shown.

Table No. 2 Bearing and Cam Oil Manufacturers

Lubricant Manufacturer	AGMA Lubricant (No. 5EP)
Darmex	9140
Exxon	Spartan 220
Mobil *	Mobilgear 630
Gulf	HD220
Keystone	KSL-366
Lubriplate	APG90

* Mobile SHC626 is used for the initial fill. If refill is necessary, any of the above products may be used.

For installations in the food, dairy, beverage and baking industries, where special lubricants are required, a suitable grease of the user's preference should be used.

When a ComTrac Drive with C-face output (Series 0F) is attached to a speed reducer, follow the manufacturer's lubrication instructions for the reducer mounting before start-up.



"C" Series – Concentric Helical MGS® Adjustable Speed Drives

Performance Specifications:

- Horsepower ratings – from 1/2 to 5
- Output speeds – available from 1139 to 8 RPM
- Speed range – 5:1 to 7:1
- Output torques – up to 59,782 in.lbs.
- NEMA frames – from 56C to 215TC

STOBER can offer a wider variety of sizes, ratios, and mounting positions than ever before by utilizing MGS Reducers and Com-Trac Adjustable Speed Drives.

These versatile gear drives offer you performance, durability, and economy for a wide range of variable speed applications. High efficiency helical gearing keeps motor size to a minimum while conserving energy.




Table No. 1 "C" Series – Output Shaft Diameter

Base Module	Inches		Metric ⁽¹⁾
	Standard	Stainless Steel	
C002	.750	.750	20
C102/C103	1.000	1.000	25
C202/C203	1.250	1.250	30
C302/C303	1.250	1.250	40
C402/C403	1.625	1.625	40
C512/C513	1.625	1.625	40
C612/C613	2.125	2.125	50
C712/C713	2.375	–	60
C812/C813	2.875	–	70

⁽¹⁾ Contact STOBER Drives for availability.



"C" Series – MGS Adjustable Speed Drive Selection Data




Speed Range		Part Number		Maximum		Transition (2)		Minimum	
Max.	Min.			RPM	Torque in.lbs.	RPM	Torque in.lbs.	RPM	Torque in.lbs.
.50 HP, 1750 RPM Motor Continued on next page									
1,139	163	C002_0020	TD270K 050-050	1,139	22	163	129	163	129
1,045	149	C102_0022	TD270K 050-050	1,045	25	149	140	149	140
822	117	C002_0028	TD270K 050-050	822	31	117	178	117	178
742	106	C002_0031	TD270K 050-050	742	35	106	198	106	198
686	98	C002_0033	TD270K 050-050	686	37	98	214	98	214
593	85	C002_0038	TD270K 050-050	593	43	85	247	85	247
586	84	C102_0039	TD270K 050-050	586	44	84	250	84	250
548	78	C002_0041	TD270K 050-050	548	47	78	267	78	267
543	78	C102_0042	TD270K 050-050	543	47	78	270	78	270
486	69	C002_0047	TD270K 050-050	486	53	69	302	69	302
453	65	C102_0050	TD270K 050-050	453	57	65	324	65	324
449	64	C002_0051	TD270K 050-050	449	57	64	326	64	326
391	56	C002_0058	TD270K 050-050	391	66	56	375	56	375
387	55	C102_0059	TD270K 050-050	387	66	55	379	55	379
361	52	C002_0063	TD270K 050-050	361	71	52	406	52	406
295	42	C002_0077	TD270K 050-050	295	87	42	497	42	497
292	42	C102_0078	TD270K 050-050	292	88	42	502	42	502
276	39	C002_0082	TD270K 050-050	276	93	39	531	39	531
275	39	C102_0083	TD270K 050-050	275	93	39	532	39	532
247	35	C002_0092	TD270K 050-050	247	104	42	531	35	531
244	35	C102_0093	TD270K 050-050	244	105	35	601	35	601
221	32	C002_0105	TD270K 050-050	221	116	44	531	32	531
197	28	C002_0115	TD270K 050-050	197	130	45	531	28	531
181	26	C002_0125	TD270K 050-050	181	141	46	531	26	531
162	23	C002_0140	TD270K 050-050	162	159	48	531	23	531
145	21	C002_0155	TD270K 050-050	145	176	49	531	21	531
130	19	C002_0175	TD270K 050-050	130	197	49	531	19	531
110	16	C002_0210	TD270K 050-050	110	233	50	531	16	531
98	14	C002_0230	TD270K 050-050	98	261	51	531	14	531
97	14	C102_0240	TD270K 050-050	97	265	23	1,063	14	1,063
91	13	C002_0250	TD270K 050-050	91	281	51	531	13	531
91	13	C102_0250	TD270K 050-050	91	283	23	1,063	13	1,063
81	12	C002_0280	TD270K 050-050	81	315	51	531	12	531
80	11	C102_0280	TD270K 050-050	80	319	24	1,063	11	1,063
73	10	C002_0310	TD270K 050-050	73	352	50	531	10	531
73	10	C102_0310	TD270K 050-050	73	350	24	1,063	10	1,063
65	9.3	C002_0350	TD270K 050-050	65	394	50	531	9.3	531
65	9.3	C102_0350	TD270K 050-050	65	395	25	1,063	9.3	1,063
56	8.0	C202_0410	TD270K 050-050	56	460	14	1,772	8.0	1,772

1) Speed tolerance at rated load is $\pm 3\%$. At less than rated load, minimum speed may increase 5%.


2) The ComTrac drive operates at constant horsepower above transition values and at constant torque below transition values. Note shaded area. Engineering advances may cause slight changes to the information shown.

Housing Styles


N – Foot Mounted




F – Round Flange



Q – Square Flange



G – Tapped Holes



See page 78 for mounting positions.

Housing Style Q is available on special order.

Output Shaft Diameter (inches)
See Page 21 for other options.

Base Module	Dia.	Base Module	Dia.
C002	.7500	C512/C513	1.6250
C102/C103	1.0000	C612/C613	2.1250
C202/C203	1.2500	C712/C713	2.3750
C302/C303	1.2500	C812/C813	2.8750
C402/C403	1.6250		



"C" Series – MGS Adjustable Speed Drive Selection Data




Speed Range		Part Number	Maximum		Transition (2)		Minimum	
Output RPM (1)			RPM	Torque in.lbs.	RPM	Torque in.lbs.	RPM	Torque in.lbs.
Max.	Min.							

.50 HP, 1750 RPM Motor

Continued

55	7.8	C102_0420	TD270K 050-050	55	468	25	1,063	7.8	1,063
48	6.9	C102_0470	TD270K 050-050	48	528	25	1,063	6.9	1,063
46	6.6	C202_0490	TD270K 050-050	46	554	14	1,772	6.6	1,772
46	6.5	C302_0500	TD270K 050-050	46	560	7	3,100	6.5	3,100
40	5.8	C202_0560	TD270K 050-050	40	635	15	1,772	5.8	1,772
37	5.2	C302_0620	TD270K 050-050	37	697	8	2,932	5.2	2,932
36	5.2	C402_0630	TD270K 050-050	36	704	5	4,029	5.2	4,029
33	4.7	C302_0700	TD270K 050-050	33	786	8	3,100	4.7	3,100
30	4.3	C613_0760	TD270K 050-050	30	841	4	4,815	4.3	4,815
29	4.1	C203_0800	TD270K 050-050	29	883	15	1,772	4.1	1,772
28	4.0	C403_0810	TD270K 050-050	28	896	4	4,872	4.0	4,872
26	3.7	C613_0880	TD270K 050-050	26	972	4	5,566	3.7	5,566
25	3.6	C203_0910	TD270K 050-050	25	1,012	15	1,772	3.6	1,772
25	3.6	C303_0910	TD270K 050-050	25	1,007	8	3,100	3.6	3,100
25	3.6	C403_0900	TD270K 050-050	25	1,002	5	4,872	3.6	4,872
21	3.0	C203_1090	TD270K 050-050	21	1,211	15	1,772	3.0	1,772
21	3.0	C303_1080	TD270K 050-050	21	1,200	8	3,100	3.0	3,100
21	3.0	C503_1090	TD270K 050-050	21	1,205	3	6,900	3.0	6,900
21	3.1	C613_1060	TD270K 050-050	21	1,176	3	6,736	3.1	6,736
17	2.4	C203_1360	TD270K 050-050	17	1,509	15	1,772	2.4	1,772
17	2.4	C303_1350	TD270K 050-050	17	1,502	9	3,100	2.4	3,100
13	1.8	C303_1800	TD270K 050-050	13	2,002	9	3,100	1.8	3,100
13	1.8	C403_1800	TD270K 050-050	13	2,002	5	4,872	1.8	4,872
13	1.8	C503_1810	TD270K 050-050	13	2,004	3	7,086	1.8	7,086
13	1.9	C613_1750	TD270K 050-050	13	1,944	2	11,133	1.9	11,133
11	1.5	C503_2160	TD270K 050-050	11	2,395	4	7,086	1.5	7,086
11	1.5	C613_2130	TD270K 050-050	11	2,364	2	11,515	2.5	11,515
10	1.5	C303_2170	TD270K 050-050	10	2,408	8	3,100	1.5	3,100
10	1.5	C403_2170	TD270K 050-050	10	2,406	5	4,872	1.5	4,872
9	1.2	C613_2660	TD270K 050-050	9	2,955	2	11,515	1.2	11,515
8	1.2	C403_2700	TD270K 050-050	8	2,997	5	4,872	1.2	4,872
8	1.2	C503_2710	TD270K 050-050	8	3,001	4	7,086	1.2	7,086

Part No. Explanation



Selection Procedure:

- Determine the MGS/ComTrac combination according to the Input HP of the application and the Output RPM nearest the required **maximum** speed.
- Verify that the output torque will sufficiently meet the application requirements.
- Complete the Part No. per the example by adding the Housing Style letter ("N", "F", "Q" or "G") as required.



"C" Series – MGS Adjustable Speed Drive Selection Data



Speed Range		Part Number	Maximum		Transition (2)		Minimum	
Output RPM (1)	Max.		Min.	RPM	Torque in.lbs.	RPM	Torque in.lbs.	RPM

.75 HP, 1750 RPM Motor

Continued on next page

1,139	163	C002_0020	TD270K	050-075	1,139	33	282	129	163	129
1,045	149	C102_0022	TD270K	050-075	1,045	36	259	140	149	140
822	117	C002_0028	TD270K	050-075	822	46	204	178	117	178
742	106	C002_0031	TD270K	050-075	742	51	184	198	106	198
686	98	C002_0033	TD270K	050-075	686	55	170	214	98	214
593	85	C002_0038	TD270K	050-075	593	64	147	247	85	247
586	84	C102_0039	TD270K	050-075	586	65	145	250	84	250
548	78	C002_0041	TD270K	050-075	548	69	136	267	78	267
543	78	C102_0042	TD270K	050-075	543	70	135	270	78	270
486	69	C002_0047	TD270K	050-075	486	78	120	302	69	302
453	65	C102_0050	TD270K	050-075	453	84	112	324	65	324
449	64	C002_0051	TD270K	050-075	449	85	111	326	64	326
391	56	C002_0058	TD270K	050-075	391	97	97	375	56	375
387	55	C102_0059	TD270K	050-075	387	98	96	379	55	379
361	52	C002_0063	TD270K	050-075	361	105	89	406	52	406
295	42	C002_0077	TD270K	050-075	295	129	73	497	42	497
292	42	C102_0078	TD270K	050-075	292	130	72	502	42	502
276	39	C002_0082	TD270K	050-075	276	138	68	531	39	531
275	39	C102_0083	TD270K	050-075	275	138	68	532	39	532
247	35	C002_0092	TD270K	050-075	247	154	70	531	35	531
244	35	C102_0093	TD270K	050-075	244	156	60	601	35	601
221	32	C002_0105	TD270K	050-075	221	172	72	531	32	531
197	28	C002_0115	TD270K	050-075	197	193	73	531	28	531
181	26	C002_0125	TD270K	050-075	181	210	74	531	26	531
162	23	C002_0140	TD270K	050-075	162	235	75	531	23	531
145	21	C002_0155	TD270K	050-075	145	261	75	531	21	531
130	19	C002_0175	TD270K	050-075	130	293	75	531	19	531
128	18	C102_0175	TD270K	050-075	128	296	35	1,063	18	1,063
110	16	C002_0210	TD270K	050-075	110	346	75	531	16	531
109	16	C102_0210	TD270K	050-075	109	348	36	1,063	16	1,063
98	14	C002_0230	TD270K	050-075	98	388	74	531	14	531
97	14	C102_0240	TD270K	050-075	97	393	37	1,063	14	1,063
91	13	C002_0250	TD270K	050-075	91	417	74	531	13	531
91	13	C102_0250	TD270K	050-075	91	420	37	1,063	13	1,063
81	12	C002_0280	TD270K	050-075	81	468	73	531	12	531
80	11	C102_0280	TD270K	050-075	80	474	37	1,063	11	1,063
73	10	C002_0310	TD270K	050-075	73	522	72	531	10	531
73	10	C102_0310	TD270K	050-075	73	519	37	1,063	10	1,063
65	9.3	C102_0350	TD270K	050-075	65	586	38	1,063	9.3	1,063


1) Speed tolerance at rated load is $\pm 3\%$. At less than rated load, minimum speed may increase 5%.

2) The ComTrac drive operates at constant horsepower above transition values and at constant torque below transition values. Note shaded area.


Engineering advances may cause slight changes to the information shown.

Housing Styles


N – Foot Mounted




F – Round Flange



Q – Square Flange



G – Tapped Holes



See page 78 for mounting positions.

Housing Style Q is available on special order.

Output Shaft Diameter (inches)
See Page 21 for other options.

Base Module	Dia.	Base Module	Dia.
C002	.7500	C512/C513	1.6250
C102/C103	1.0000	C612/C613	2.1250
C202/C203	1.2500	C712/C713	2.3750
C302/C303	1.2500	C812/C813	2.8750
C402/C403	1.6250		



"C" Series – MGS Adjustable Speed Drive Selection Data



Speed Range		Part Number	Maximum		Transition ⁽²⁾		Minimum	
Output RPM ⁽¹⁾	Max.		RPM	Torque in.lbs.	RPM	Torque in.lbs.	RPM	Torque in.lbs.
Min.								

.75 HP, 1750 RPM Motor

Continued

65	9.2	C202_0350	TD270K 050-075	65	588	22	1,772	9.2	1,772
56	8.0	C202_0410	TD270K 050-075	56	683	22	1,772	8.0	1,772
55	7.8	C102_0420	TD270K 050-075	55	695	38	1,063	7.8	1,063
48	6.9	C102_0470	TD270K 050-075	48	784	37	1,063	6.9	1,063
49	6.9	C202_0470	TD270K 050-075	49	783	22	1,772	6.9	1,772
46	6.6	C202_0490	TD270K 050-075	46	823	22	1,772	6.6	1,772
46	6.5	C302_0500	TD270K 050-075	46	832	12	3,100	6.5	3,100
40	5.8	C202_0560	TD270K 050-075	40	943	23	1,772	5.8	1,772
41	5.8	C302_0560	TD270K 050-075	41	938	12	3,100	5.8	3,100
37	5.2	C302_0620	TD270K 050-075	37	1,035	13	2,932	5.2	2,932
36	5.2	C402_0630	TD270K 050-075	36	1,045	9	4,029	5.2	4,029
33	4.7	C302_0700	TD270K 050-075	33	1,168	13	3,100	4.7	3,100
30	4.3	C613_0760	TD270K 050-075	30	1,249	7	4,815	4.3	4,815
29	4.1	C203_0800	TD270K 050-075	29	1,311	22	1,772	4.1	1,772
28	4.0	C303_0800	TD270K 050-075	28	1,325	13	3,100	4.0	3,100
28	4.0	C403_0810	TD270K 050-075	28	1,331	7	4,872	4.0	4,872
26	3.7	C613_0880	TD270K 050-075	26	1,444	6	5,566	3.7	5,566
25	3.6	C203_0910	TD270K 050-075	25	1,503	22	1,772	3.6	1,772
25	3.6	C303_0910	TD270K 050-075	25	1,495	13	3,100	3.6	3,100
25	3.6	C403_0900	TD270K 050-075	25	1,488	8	4,872	3.6	4,872
21	3.0	C303_1080	TD270K 050-075	21	1,783	13	3,100	3.0	3,100
21	3.0	C403_1080	TD270K 050-075	21	1,774	8	4,872	3.0	4,872
21	3.0	C503_1090	TD270K 050-075	21	1,790	5	6,900	3.0	6,900
21	3.1	C613_1060	TD270K 050-075	21	1,747	5	6,736	3.1	6,736
17	2.4	C303_1350	TD270K 050-075	17	2,231	13	3,100	2.4	3,100
17	2.4	C403_1350	TD270K 050-075	17	2,218	8	4,872	2.4	4,872
13	1.8	C303_1800	TD270K 050-075	13	2,973	12	3,100	1.8	3,100
13	1.8	C403_1800	TD270K 050-075	13	2,973	8	4,872	1.8	4,872
13	1.8	C503_1810	TD270K 050-075	13	2,976	5	7,086	1.8	7,086
13	1.9	C613_1750	TD270K 050-075	13	2,888	3	11,133	1.9	11,133
11	1.5	C503_2160	TD270K 050-075	11	3,557	6	7,086	1.5	7,086
11	1.8	C613_2130	TD270K 050-075	11	3,511	3	11,515	1.5	11,515
10	1.5	C403_2170	TD270K 050-075	10	3,574	8	4,872	1.5	4,872
9	1.2	C613_2660	TD270K 050-075	9	4,388	3	11,515	1.2	11,515
8	1.2	C403_2700	TD270K 050-075	8	4,451	8	4,872	1.2	4,872
8	1.2	C503_2710	TD270K 050-075	8	4,457	6	7,086	1.2	7,086

Part No. Explanation

C	5	0	2	N	0620	TD370K140 – 200 W	
Housing Style	Ratio of MGS Unit (0620 = 62.0:1)	Washdown, when required					
No. of Gear Reductions	Non-gearred TD37 ComTrac Unit, 145TC Input						
Generation No.							
Unit No.							
Concentric Helical							

Selection Procedure:

- Determine the MGS/ComTrac combination according to the Input HP of the application and the Output RPM nearest the required **maximum** speed.
- Verify that the output torque will sufficiently meet the application requirements.
- Complete the Part No. per the example by adding the Housing Style letter ("N", "F", "Q" or "G") as required.



"C" Series – MGS Adjustable Speed Drive Selection Data



Speed Range		Part Number	Maximum		Transition (2)		Minimum	
Output RPM (1)	Max.		Min.	RPM	Torque in.lbs.	RPM	Torque in.lbs.	RPM

1.0 HP, 1750 RPM Motor

Continued on next page

1,139	163	C002_0020	TD270K	140-100	1,139	46	411	129	163	129
1,045	149	C102_0022	TD270K	140-100	1,045	50	377	140	149	140
822	117	C002_0028	TD270K	140-100	822	63	296	178	117	178
742	106	C002_0031	TD270K	140-100	742	70	267	198	106	198
686	98	C002_0033	TD270K	140-100	686	76	247	214	98	214
593	85	C002_0038	TD270K	140-100	593	87	214	247	85	247
586	84	C102_0039	TD270K	140-100	586	88	211	250	84	250
548	78	C002_0041	TD270K	140-100	548	95	198	267	78	267
543	78	C102_0042	TD270K	140-100	543	95	196	270	78	270
486	69	C002_0047	TD270K	140-100	486	107	175	302	69	302
453	65	C102_0050	TD270K	140-100	453	115	163	324	65	324
449	64	C002_0051	TD270K	140-100	449	115	162	326	64	326
391	56	C002_0058	TD270K	140-100	391	133	141	375	56	375
387	55	C102_0059	TD270K	140-100	387	134	140	379	55	379
361	52	C002_0063	TD270K	140-100	361	144	130	406	52	406
295	42	C002_0077	TD270K	140-100	295	176	106	497	42	497
292	42	C102_0078	TD270K	140-100	292	178	105	502	42	502
276	39	C002_0082	TD270K	140-100	276	188	100	531	39	531
275	39	C102_0083	TD270K	140-100	275	188	99	532	39	532
247	35	C002_0092	TD270K	140-100	247	210	101	531	35	531
244	35	C102_0093	TD270K	140-100	244	213	88	601	35	601
221	32	C002_0105	TD270K	140-100	221	235	102	531	32	531
197	28	C002_0115	TD270K	140-100	197	263	102	531	28	531
181	26	C002_0125	TD270K	140-100	181	286	103	531	26	531
183	26	C102_0125	TD270K	140-100	183	284	66	803	26	803
162	23	C002_0140	TD270K	140-100	162	321	103	531	23	531
162	23	C102_0140	TD270K	140-100	162	320	58	906	23	906
145	21	C002_0155	TD270K	140-100	145	356	102	531	21	531
145	21	C102_0155	TD270K	140-100	145	358	52	1,012	21	1,012
130	19	C002_0175	TD270K	140-100	130	399	101	531	19	531
128	18	C102_0175	TD270K	140-100	128	404	50	1,063	18	1,063
110	16	C002_0210	TD270K	140-100	110	472	99	531	16	531
109	16	C102_0210	TD270K	140-100	109	475	51	1,063	16	1,063
98	14	C002_0230	TD270K	140-100	98	529	98	531	14	531
97	14	C102_0240	TD270K	140-100	97	536	51	1,063	14	1,063
96	14	C202_0240	TD270K	140-100	96	538	35	1,520	14	1,520
91	13	C102_0250	TD270K	140-100	91	573	51	1,063	13	1,063
92	13	C202_0250	TD270K	140-100	92	562	33	1,588	13	1,588
80	11	C102_0280	TD270K	140-100	80	646	51	1,063	11	1,063
81	12	C202_0280	TD270K	140-100	81	644	30	1,772	12	1,772
73	10	C102_0310	TD270K	140-100	73	708	51	1,063	10	1,063
74	11	C202_0310	TD270K	140-100	74	699	30	1,772	11	1,772


1) Speed tolerance at rated load is $\pm 3\%$. At less than rated load, minimum speed may increase 5%.

2) The ComTrac drive operates at constant horsepower above transition values and at constant torque below transition values. Note shaded area.


Engineering advances may cause slight changes to the information shown.

Housing Styles


N – Foot Mounted



F – Round Flange



Q – Square Flange



G – Tapped Holes



See page 78 for mounting positions.

Housing Style Q is available on special order.

Output Shaft Diameter (inches)

See Page 21 for other options.

Base Module	Dia.	Base Module	Dia.
C002	.7500	C512/C513	1.6250
C102/C103	1.0000	C612/C613	2.1250
C202/C203	1.2500	C712/C713	2.3750
C302/C303	1.2500	C812/C813	2.8750
C402/C403	1.6250		



"C" Series – MGS Adjustable Speed Drive Selection Data



Speed Range Output RPM ⁽¹⁾		Part Number	Maximum		Transition ⁽²⁾		Minimum	
Max.	Min.		RPM	Torque in.lbs.	RPM	Torque in.lbs.	RPM	Torque in.lbs.
1.0 HP, 1750 RPM Motor Continued								
65	9.3	C102_0350	TD270K 140-100	65	799	51	1,063	9.3
65	9.2	C202_0350	TD270K 140-100	65	802	31	1,772	9.2
56	8.0	C202_0410	TD270K 140-100	56	931	31	1,772	8.0
55	7.9	C302_0410	TD270K 140-100	55	942	20	2,665	7.9
55	7.8	C102_0420	TD270K 140-100	55	947	50	1,063	7.8
49	6.9	C202_0470	TD270K 140-100	49	1,067	31	1,772	6.9
49	7.0	C302_0470	TD270K 140-100	49	1,063	18	3,007	7.0
46	6.6	C202_0490	TD270K 140-100	46	1,122	31	1,772	6.6
46	6.5	C302_0500	TD270K 140-100	46	1,134	17	3,100	6.5
40	5.8	C202_0560	TD270K 140-100	40	1,286	30	1,772	5.8
41	5.8	C302_0560	TD270K 140-100	41	1,279	17	3,100	5.8
37	5.2	C302_0620	TD270K 140-100	37	1,411	19	2,932	5.2
36	5.2	C402_0630	TD270K 140-100	36	1,425	13	4,029	5.2
33	4.7	C302_0700	TD270K 140-100	33	1,592	18	3,100	4.7
33	4.7	C402_0700	TD270K 140-100	33	1,592	12	4,503	4.7
30	4.3	C613_0760	TD270K 140-100	30	1,703	11	4,815	4.3
28	4.0	C303_0800	TD270K 140-100	28	1,806	17	3,100	4.0
28	4.0	C403_0810	TD270K 140-100	28	1,815	11	4,872	4.0
26	3.7	C613_0880	TD270K 140-100	26	1,968	9	5,566	3.7
25	3.6	C303_0910	TD270K 140-100	25	2,038	17	3,100	3.6
25	3.6	C403_0900	TD270K 140-100	25	2,029	11	4,872	3.6
21	3.0	C303_1080	TD270K 140-100	21	2,430	17	3,100	3.0
21	3.0	C403_1080	TD270K 140-100	21	2,419	11	4,872	3.0
21	3.0	C503_1090	TD270K 140-100	21	2,440	8	6,900	3.0
21	3.1	C613_1060	TD270K 140-100	21	2,382	8	6,736	3.1
17	2.4	C303_1350	TD270K 140-100	17	3,042	17	3,100	2.4
17	2.4	C403_1350	TD270K 140-100	17	3,024	11	4,872	2.4
17	2.4	C503_1350	TD270K 140-100	17	3,040	7	7,086	2.4
13	1.8	C403_1800	TD270K 140-100	13	4,053	11	4,872	1.8
13	1.8	C503_1810	TD270K 140-100	13	4,057	8	7,086	1.8
13	1.9	C613_1750	TD270K 140-100	13	3,937	5	11,133	1.9
11	1.5	C503_2160	TD270K 140-100	11	4,849	8	7,086	1.5
11	1.5	C613_2130	TD270K 140-100	11	4,786	5	11,515	1.5
10	1.5	C403_2170	TD270K 140-100	10	4,872	10	4,872	1.5
9	1.2	C613_2660	TD270K 140-100	9	5,983	5	11,515	1.2
8	1.2	C503_2710	TD270K 140-100	8	6,076	7	7,086	1.2

Part No. Explanation

C 5 0 2 N 0620 TD370K140 – 200 W

Washdown, when required
Rated for HP (200 = 2.00)
Non-gearred TD37 ComTrac Unit, 145TC Input
Ratio of MGS Unit (0620 = 62.0:1)
Housing Style
No. of Gear Reductions
Generation No.
Unit No.
Concentric Helical

Selection Procedure:

- Determine the MGS/ComTrac combination according to the Input HP of the application and the Output RPM nearest the required **maximum** speed.
- Verify that the output torque will sufficiently meet the application requirements.
- Complete the Part No. per the example by adding the Housing Style letter ("N", "F", "Q" or "G") as required.



"C" Series – MGS Adjustable Speed Drive Selection Data



Speed Range		Part Number	Maximum		Transition (2)		Minimum	
Output RPM (1)	Max.		Min.	RPM	Torque in.lbs.	RPM	Torque in.lbs.	RPM

1.5 HP, 1750 RPM Motor

Continued on next page

1,095	219	C002_0020	TD370K	140-150	1,095	70	419	189	219	189
1,005	201	C102_0022	TD370K	140-150	1,005	77	384	206	201	206
914	183	C102_0024	TD370K	140-150	914	84	349	226	183	226
847	169	C102_0026	TD370K	140-150	847	91	324	244	169	244
790	158	C002_0028	TD370K	140-150	790	97	302	262	158	262
713	143	C002_0031	TD370K	140-150	713	108	273	290	143	290
659	132	C002_0033	TD370K	140-150	659	117	252	314	132	314
649	130	C202_0034	TD370K	140-150	649	119	248	319	130	319
570	114	C002_0038	TD370K	140-150	570	135	218	362	114	362
563	113	C102_0039	TD370K	140-150	563	137	215	367	113	367
527	105	C002_0041	TD370K	140-150	527	146	202	392	105	392
522	104	C102_0042	TD370K	140-150	522	147	200	396	104	396
467	93	C002_0047	TD370K	140-150	467	165	179	442	93	442
435	87	C102_0050	TD370K	140-150	435	177	166	475	87	475
432	86	C002_0051	TD370K	140-150	432	178	165	479	86	479
376	75	C002_0058	TD370K	140-150	376	205	158	504	75	504
378	76	C202_0058	TD370K	140-150	378	204	144	547	76	547
372	74	C102_0059	TD370K	140-150	372	207	142	555	74	555
347	69	C002_0063	TD370K	140-150	347	222	159	503	69	503
345	69	C102_0063	TD370K	140-150	345	223	132	599	69	599
281	56	C102_0078	TD370K	140-150	281	274	107	737	56	737
266	53	C002_0082	TD370K	140-150	266	290	153	531	53	531
267	53	C202_0082	TD370K	140-150	267	288	102	774	53	774
265	53	C102_0083	TD370K	140-150	265	291	101	781	53	781
237	47	C002_0092	TD370K	140-150	237	325	152	531	47	531
235	47	C102_0093	TD370K	140-150	235	328	90	881	47	881
233	47	C202_0094	TD370K	140-150	233	330	89	887	47	887
212	42	C002_0105	TD370K	140-150	212	362	151	531	42	531
211	42	C102_0105	TD370K	140-150	211	365	81	981	42	981
190	38	C002_0115	TD370K	140-150	190	406	150	531	38	531
187	37	C102_0115	TD370K	140-150	187	412	75	1,063	37	1,063
186	37	C202_0120	TD370K	140-150	186	414	71	1,111	37	1,111
174	35	C002_0125	TD370K	140-150	174	442	148	531	35	531
176	35	C102_0125	TD370K	140-150	176	438	75	1,063	35	1,063
155	31	C002_0140	TD370K	140-150	155	495	146	531	31	531
156	31	C102_0140	TD370K	140-150	156	494	76	1,063	31	1,063
139	28	C102_0155	TD370K	140-150	139	553	76	1,063	28	1,063
143	29	C202_0155	TD370K	140-150	143	538	55	1,444	29	1,444
123	25	C102_0175	TD370K	140-150	123	624	76	1,063	25	1,063
125	25	C202_0175	TD370K	140-150	125	616	48	1,656	25	1,656
105	21	C102_0210	TD370K	140-150	105	733	76	1,063	21	1,063
106	21	C202_0210	TD370K	140-150	106	724	45	1,772	21	1,772
93	19	C302_0230	TD370K	140-150	93	826	36	2,218	19	2,218
93	19	C102_0240	TD370K	140-150	93	828	75	1,063	19	1,063
93	19	C202_0240	TD370K	140-150	93	830	45	1,772	19	1,772
87	17	C102_0250	TD370K	140-150	87	884	74	1,063	17	1,063

1) Speed tolerance at rated load is $\pm 3\%$. At less than rated load, minimum speed may increase 5%.

2) The ComTrac drive operates at constant horsepower above transition values and at constant torque below transition values. Note shaded area.


Engineering advances may cause slight changes to the information shown.

Housing Styles


N – Foot Mounted



F – Round Flange



Q – Square Flange



G – Tapped Holes



See page 78 for mounting positions.

Housing Style Q is available on special order.

Output Shaft Diameter (inches)

See Page 21 for other options.

Base Module	Dia.	Base Module	Dia.
C002	.7500	C512/C513	1.6250
C102/C103	1.0000	C612/C613	2.1250
C202/C203	1.2500	C712/C713	2.3750
C302/C303	1.2500	C812/C813	2.8750
C402/C403	1.6250		



"C" Series – MGS Adjustable Speed Drive Selection Data



Speed Range		Part Number	Maximum		Transition ⁽²⁾		Minimum	
Output RPM ⁽¹⁾	Max.		RPM	Torque in.lbs.	RPM	Torque in.lbs.	RPM	Torque in.lbs.
Min.								

1.5 HP, 1750 RPM Motor

Continued

89	18	C202_0250	TD370K 140-150	89	867	45	1,772	18	1,772
77	15	C102_0280	TD370K 140-150	77	998	73	1,063	15	1,063
77	15	C202_0280	TD370K 140-150	77	994	46	1,772	15	1,772
78	16	C302_0280	TD370K 140-150	78	985	30	2,645	16	2,645
71	14	C202_0310	TD370K 140-150	71	1,080	46	1,772	14	1,772
70	14	C302_0310	TD370K 140-150	70	1,092	27	2,934	14	2,934
62	12	C202_0350	TD370K 140-150	62	1,238	45	1,772	12	1,772
62	12	C302_0350	TD370K 140-150	62	1,232	26	3,100	12	3,100
54	11	C202_0410	TD370K 140-150	54	1,437	45	1,772	11	1,772
53	11	C302_0410	TD370K 140-150	53	1,455	26	3,100	11	3,100
52	10	C402_0420	TD370K 140-150	52	1,469	20	3,946	10	3,946
47	9.3	C202_0470	TD370K 140-150	47	1,647	44	1,772	9.3	1,772
47	9.4	C302_0470	TD370K 140-150	47	1,642	26	3,100	9.4	3,100
47	9.4	C402_0470	TD370K 140-150	47	1,642	18	4,411	9.4	4,411
44	8.8	C302_0500	TD370K 140-150	44	1,750	26	3,100	8.8	3,100
44	8.7	C402_0500	TD370K 140-150	44	1,766	17	4,744	8.7	4,744
39	7.8	C302_0560	TD370K 140-150	39	1,975	26	3,100	7.8	3,100
39	7.8	C402_0560	TD370K 140-150	39	1,974	16	4,872	7.8	4,872
35	7.0	C402_0630	TD370K 140-150	35	2,199	18	4,440	7.0	4,440
35	7.0	C502_0620	TD370K 140-150	35	2,196	13	5,901	7.0	5,901
31	6.3	C402_0700	TD370K 140-150	31	2,458	17	4,872	6.3	4,872
31	6.3	C502_0700	TD370K 140-150	31	2,461	12	6,613	6.3	6,613
29	5.8	C613_0760	TD370K 140-150	29	2,629	11	7,062	5.8	7,062
27	5.4	C303_0800	TD370K 140-150	27	2,789	25	3,100	5.4	3,100
27	5.4	C403_0810	TD370K 140-150	27	2,802	16	4,872	5.4	4,872
27	5.4	C503_0810	TD370K 140-150	27	2,794	11	7,086	5.4	7,086
25	5.0	C613_0880	TD370K 140-150	25	3,039	10	8,164	5.0	8,164
24	4.8	C403_0900	TD370K 140-150	24	3,132	16	4,872	4.8	4,872
24	4.8	C503_0900	TD370K 140-150	24	3,132	11	7,086	4.8	7,086
21	4.1	C613_1060	TD370K 140-150	21	3,677	8	9,879	4.1	9,879
20	4.1	C403_1080	TD370K 140-150	20	3,735	16	4,872	4.1	4,872
20	4.0	C503_1090	TD370K 140-150	20	3,767	11	7,086	4.0	7,086
16	3.2	C403_1350	TD370K 140-150	16	4,668	16	4,872	3.2	4,872
16	3.2	C503_1350	TD370K 140-150	16	4,692	11	7,086	3.2	7,086
16	3.2	C613_1350	TD370K 140-150	16	4,675	7	11,515	3.2	11,515
12	2.5	C613_1750	TD370K 140-150	12	6,078	7	11,515	2.5	11,515
12	2.4	C503_1810	TD370K 140-150	12	6,263	11	7,086	2.4	7,086
10	2.1	C613_2130	TD370K 140-150	10	7,389	7	11,515	2.1	11,515
8	1.6	C613_2660	TD370K 140-150	8	9,236	7	11,515	1.6	11,515

Part No. Explanation

C 5 0 2 N 0620 TD370K140 – 200 W

Washdown, when required
Rated for HP (200 = 2.00)
Non-gearred TD37 ComTrac Unit, 145TC Input
Ratio of MGS Unit (0620 = 62.0:1)
Housing Style
No. of Gear Reductions
Generation No.
Unit No.
Concentric Helical

Selection Procedure:

- Determine the MGS/ComTrac combination according to the Input HP of the application and the Output RPM nearest the required **maximum** speed.
- Verify that the output torque will sufficiently meet the application requirements.
- Complete the Part No. per the example by adding the Housing Style letter ("N", "F", "Q" or "G") as required.



"C" Series – MGS Adjustable Speed Drive Selection Data



Speed Range		Part Number	Maximum		Transition (2)		Minimum	
Output RPM (1)	Max.		Min.	RPM	Torque in.lbs.	RPM	Torque in.lbs.	RPM

2.0 HP, 1750 RPM Motor

Continued on next page

1,095	219	C002_0020	TD370K 140-200	1,095	96	584	189	219	189
1,005	201	C102_0022	TD370K 140-200	1,005	105	536	206	201	206
914	183	C102_0024	TD370K 140-200	914	115	487	226	183	226
847	169	C102_0026	TD370K 140-200	847	124	452	244	169	244
790	158	C002_0028	TD370K 140-200	790	133	421	262	158	262
713	143	C002_0031	TD370K 140-200	713	147	380	290	143	290
659	132	C002_0033	TD370K 140-200	659	159	351	314	132	314
656	131	C102_0033	TD370K 140-200	656	160	350	315	131	315
649	130	C202_0034	TD370K 140-200	649	162	346	319	130	319
570	114	C002_0038	TD370K 140-200	570	184	304	362	114	362
563	113	C102_0039	TD370K 140-200	563	186	300	367	113	367
527	105	C002_0041	TD370K 140-200	527	199	281	392	105	392
522	104	C102_0042	TD370K 140-200	522	201	278	396	104	396
467	93	C002_0047	TD370K 140-200	467	225	258	428	93	428
470	94	C102_0047	TD370K 140-200	470	224	250	440	94	440
435	87	C102_0050	TD370K 140-200	435	241	232	475	87	475
432	86	C002_0051	TD370K 140-200	432	243	259	427	86	427
431	86	C202_0051	TD370K 140-200	431	244	230	479	86	479
376	75	C002_0058	TD370K 140-200	376	280	257	429	75	429
378	76	C202_0058	TD370K 140-200	378	278	201	547	76	547
372	74	C102_0059	TD370K 140-200	372	282	198	555	74	555
347	69	C002_0063	TD370K 140-200	347	303	255	430	69	430
345	69	C102_0063	TD370K 140-200	345	304	184	599	69	599
281	56	C102_0078	TD370K 140-200	281	374	150	737	56	737
266	53	C002_0082	TD370K 140-200	266	395	205	531	53	531
267	53	C202_0082	TD370K 140-200	267	393	142	774	53	774
265	53	C102_0083	TD370K 140-200	265	397	141	781	53	781
237	47	C002_0092	TD370K 140-200	237	443	203	531	47	531
235	47	C102_0093	TD370K 140-200	235	448	125	881	47	881
233	47	C202_0094	TD370K 140-200	233	451	124	887	47	887
212	42	C002_0105	TD370K 140-200	212	494	200	531	42	531
211	42	C102_0105	TD370K 140-200	211	499	112	981	42	981
187	37	C102_0115	TD370K 140-200	187	563	104	1,063	37	1,063
186	37	C202_0120	TD370K 140-200	186	565	99	1,111	37	1,111
176	35	C102_0125	TD370K 140-200	176	598	104	1,063	35	1,063
178	36	C202_0125	TD370K 140-200	178	591	95	1,164	36	1,164
156	31	C102_0140	TD370K 140-200	156	675	104	1,063	31	1,063
155	31	C202_0140	TD370K 140-200	155	678	83	1,334	31	1,334
139	28	C102_0155	TD370K 140-200	139	754	103	1,063	28	1,063
143	29	C202_0155	TD370K 140-200	143	734	76	1,444	29	1,444
123	25	C102_0175	TD370K 140-200	123	851	102	1,063	25	1,063
125	25	C202_0175	TD370K 140-200	125	841	67	1,656	25	1,656
105	21	C102_0210	TD370K 140-200	105	1,001	100	1,063	21	1,063
106	21	C202_0210	TD370K 140-200	106	988	63	1,772	21	1,772
105	21	C302_0210	TD370K 140-200	105	999	56	1,966	21	1,966
93	19	C302_0230	TD370K 140-200	93	1,127	50	2,218	19	2,218
93	19	C202_0240	TD370K 140-200	93	1,133	62	1,772	19	1,772
89	18	C202_0250	TD370K 140-200	89	1,183	62	1,772	18	1,772


1) Speed tolerance at rated load is $\pm 3\%$. At less than rated load, minimum speed may increase 5%.

2) The ComTrac drive operates at constant horsepower above transition values and at constant torque below transition values. Note shaded area.


Engineering advances may cause slight changes to the information shown.

Housing Styles


N – Foot Mounted



F – Round Flange



Q – Square Flange



G – Tapped Holes



See page 78 for mounting positions.

Housing Style Q is available on special order.

Output Shaft Diameter (inches)

See Page 21 for other options.

Base Module	Dia.	Base Module	Dia.
C002	.7500	C512/C513	1.6250
C102/C103	1.0000	C612/C613	2.1250
C202/C203	1.2500	C712/C713	2.3750
C302/C303	1.2500	C812/C813	2.8750
C402/C403	1.6250		



"C" Series – MGS Adjustable Speed Drive Selection Data



Speed Range		Part Number	Maximum		Transition (2)		Minimum	
Output RPM (1)			RPM	Torque in.lbs.	RPM	Torque in.lbs.	RPM	Torque in.lbs.
Max.	Min.							

2.0 HP, 1750 RPM Motor

Continued

88	18	C302_0250	TD370K 140-200	88	1,191	47	2,344	18	2,344
77	15	C202_0280	TD370K 140-200	77	1,356	61	1,772	15	1,772
78	16	C302_0280	TD370K 140-200	78	1,344	42	2,645	16	2,645
71	14	C202_0310	TD370K 140-200	71	1,474	61	1,772	14	1,772
70	14	C302_0310	TD370K 140-200	70	1,491	38	2,934	14	2,934
62	12	C202_0350	TD370K 140-200	62	1,689	60	1,772	12	1,772
62	12	C302_0350	TD370K 140-200	62	1,682	36	3,100	12	3,100
63	13	C402_0350	TD370K 140-200	63	1,672	33	3,291	13	3,291
53	11	C302_0410	TD370K 140-200	53	1,986	36	3,100	11	3,100
52	10	C402_0420	TD370K 140-200	52	2,005	28	3,946	10	3,946
47	9.4	C302_0470	TD370K 140-200	47	2,241	35	3,100	9.4	3,100
47	9.4	C402_0470	TD370K 140-200	47	2,241	25	4,411	9.4	4,411
44	8.8	C302_0500	TD370K 140-200	44	2,389	35	3,100	8.8	3,100
44	8.7	C402_0500	TD370K 140-200	44	2,410	23	4,744	8.7	4,744
39	7.8	C302_0560	TD370K 140-200	39	2,696	35	3,100	7.8	3,100
39	7.8	C402_0560	TD370K 140-200	39	2,694	23	4,872	7.8	4,872
39	7.8	C502_0560	TD370K 140-200	39	2,681	21	5,277	7.8	5,277
35	7.0	C402_0630	TD370K 140-200	35	3,002	25	4,440	7.0	4,440
35	7.0	C502_0620	TD370K 140-200	35	2,998	19	5,901	7.0	5,901
31	6.3	C402_0700	TD370K 140-200	31	3,355	22	4,872	6.3	4,872
31	6.3	C502_0700	TD370K 140-200	31	3,360	17	6,613	6.3	6,613
29	5.8	C613_0760	TD370K 140-200	29	3,588	15	7,062	5.8	7,062
27	5.4	C403_0810	TD370K 140-200	27	3,825	22	4,872	5.4	4,872
27	5.4	C503_0810	TD370K 140-200	27	3,814	15	7,086	5.4	7,086
25	5.0	C613_0880	TD370K 140-200	25	4,148	13	8,164	5.0	8,164
24	4.8	C403_0900	TD370K 140-200	24	4,275	22	4,872	4.8	4,872
24	4.8	C503_0900	TD370K 140-200	24	4,275	15	7,086	4.8	7,086
21	4.1	C613_1060	TD370K 140-200	21	5,019	11	9,879	4.1	9,879
20	4.0	C503_1090	TD370K 140-200	20	5,142	15	7,086	4.0	7,086
16	3.2	C503_1350	TD370K 140-200	16	6,405	15	7,086	3.2	7,086
16	3.2	C613_1350	TD370K 140-200	16	6,382	9	11,515	3.2	11,515
12	2.5	C613_1750	TD370K 140-200	12	8,296	9	11,515	2.5	11,515
10	2.1	C613_2130	TD370K 140-200	10	10,085	9	11,515	2.1	11,515

3.0 HP, 1750 RPM Motor

Continued on next page

1,084	217	C102_0020	TD470K 180-300	1,084	150	470	347	217	347
1,005	201	C102_0022	TD470K 180-300	1,005	161	436	374	201	374
914	183	C102_0024	TD470K 180-300	914	178	396	411	183	411
884	177	C202_0025	TD470K 180-300	884	184	384	425	177	425
847	169	C102_0026	TD470K 180-300	847	191	368	444	169	444
813	163	C202_0027	TD470K 180-300	813	199	353	462	163	462
708	142	C102_0031	TD470K 180-300	708	229	307	531	142	531
656	131	C102_0033	TD470K 180-300	656	247	285	573	131	573
649	130	C202_0034	TD470K 180-300	649	250	281	580	130	580
563	113	C102_0039	TD470K 180-300	563	288	244	667	113	667
522	104	C102_0042	TD470K 180-300	522	311	227	720	104	720
498	100	C402_0044	TD470K 180-300	498	326	216	755	100	755

Part No. Explanation

C	5	0	2	N	0620	TD370K140 – 200 W
						Washdown, when required
						Rated for HP (200 = 2.00)
						Non-gearred TD37 ComTrac Unit, 145TC Input
						Ratio of MGS Unit (0620 = 62.0:1)
						Housing Style
						No. of Gear Reductions
						Generation No.
						Unit No.
						Concentric Helical

Selection Procedure:

- Determine the MGS/ComTrac combination according to the Input HP of the application and the Output RPM nearest the required maximum speed.
- Verify that the output torque will sufficiently meet the application requirements.
- Complete the Part No. per the example by adding the Housing Style letter ("N", "F", "Q" or "G") as required.



"C" Series – MGS Adjustable Speed Drive Selection Data



Speed Range		Part Number	Maximum		Transition (2)		Minimum	
Output RPM (1)	Max.		Min.	RPM	Torque in.lbs.	RPM	Torque in.lbs.	RPM

3.0 HP, 1750 RPM Motor

Continued on next page

473	95	C502_0046	TD470K 180-300	473	343	205	795	95	795
470	94	C102_0047	TD470K 180-300	470	345	204	800	94	800
435	87	C102_0050	TD470K 180-300	435	373	189	864	87	864
434	87	C302_0050	TD470K 180-300	434	374	188	866	87	866
431	86	C202_0051	TD470K 180-300	431	376	187	872	86	872
414	83	C402_0053	TD470K 180-300	414	392	180	908	83	908
378	76	C202_0058	TD470K 180-300	378	429	164	995	76	995
372	74	C102_0059	TD470K 180-300	372	436	164	996	74	996
373	75	C302_0059	TD470K 180-300	373	434	162	1,007	75	1,007
345	69	C102_0063	TD470K 180-300	345	470	166	992	69	992
347	70	C202_0063	TD470K 180-300	347	467	151	1,082	70	1,082
329	66	C402_0066	TD470K 180-300	329	493	143	1,142	66	1,142
329	66	C502_0067	TD470K 180-300	329	493	143	1,144	66	1,144
281	56	C102_0078	TD470K 180-300	281	578	169	985	56	985
280	56	C202_0078	TD470K 180-300	280	578	122	1,340	56	1,340
267	53	C202_0082	TD470K 180-300	267	607	116	1,407	53	1,407
265	53	C102_0083	TD470K 180-300	265	613	157	1,063	53	1,063
265	53	C302_0083	TD470K 180-300	265	612	115	1,418	53	1,418
235	47	C102_0093	TD470K 180-300	235	692	158	1,063	47	1,063
235	47	C302_0093	TD470K 180-300	235	690	102	1,600	47	1,600
233	47	C202_0094	TD470K 180-300	233	696	101	1,613	47	1,613
211	42	C102_0105	TD470K 180-300	211	770	158	1,063	42	1,063
213	43	C202_0105	TD470K 180-300	213	761	93	1,763	43	1,763
187	37	C102_0115	TD470K 180-300	187	869	156	1,063	37	1,063
188	38	C302_0115	TD470K 180-300	188	861	82	1,995	38	1,995
186	37	C202_0120	TD470K 180-300	186	872	93	1,772	37	1,772
176	35	C102_0125	TD470K 180-300	176	924	155	1,063	35	1,063
178	36	C202_0125	TD470K 180-300	178	913	93	1,772	36	1,772
176	35	C302_0125	TD470K 180-300	176	920	77	2,131	35	2,131
156	31	C102_0140	TD470K 180-300	156	1,042	153	1,063	31	1,063
155	31	C202_0140	TD470K 180-300	155	1,047	94	1,772	31	1,772
156	31	C302_0140	TD470K 180-300	156	1,038	68	2,405	31	2,405
143	29	C202_0155	TD470K 180-300	143	1,133	95	1,772	29	1,772
141	28	C302_0155	TD470K 180-300	141	1,153	61	2,671	28	2,671
139	28	C402_0160	TD470K 180-300	139	1,168	60	2,707	28	2,707
125	25	C202_0175	TD470K 180-300	125	1,299	94	1,772	25	1,772
125	25	C302_0175	TD470K 180-300	125	1,301	54	3,014	25	3,014
112	22	C612_0195	TD470K 180-300	112	1,454	48	3,369	22	3,369
106	21	C202_0210	TD470K 180-300	106	1,526	93	1,772	21	1,772
105	21	C302_0210	TD470K 180-300	105	1,542	53	3,100	21	3,100
93	19	C302_0230	TD470K 180-300	93	1,741	54	3,100	19	3,100
94	19	C402_0230	TD470K 180-300	94	1,732	41	4,014	19	4,014
93	19	C202_0240	TD470K 180-300	93	1,750	92	1,772	19	1,772
88	18	C302_0250	TD470K 180-300	88	1,839	54	3,100	18	3,100
88	18	C402_0250	TD470K 180-300	88	1,848	38	4,283	18	4,283
80	16	C612_0270	TD470K 180-300	80	2,034	35	4,714	16	4,714
78	16	C302_0280	TD470K 180-300	78	2,075	54	3,100	16	3,100
79	16	C402_0280	TD470K 180-300	79	2,066	34	4,787	16	4,787


1) Speed tolerance at rated load is ±3%. At less than rated load, minimum speed may increase 5%.

2) The ComTrac drive operates at constant horsepower above transition values and at constant torque below transition values. Note shaded area.


Engineering advances may cause slight changes to the information shown.

Housing Styles


N – Foot Mounted



F – Round Flange



Q – Square Flange



G – Tapped Holes



See page 78 for mounting positions.

Housing Style Q is available on special order.

Output Shaft Diameter (inches)

See Page 21 for other options.

Base Module	Dia.	Base Module	Dia.
C002	.7500	C512/C513	1.6250
C102/C103	1.0000	C612/C613	2.1250
C202/C203	1.2500	C712/C713	2.3750
C302/C303	1.2500	C812/C813	2.8750
C402/C403	1.6250		



"C" Series – MGS Adjustable Speed Drive Selection Data



Speed Range		Part Number	Maximum		Transition ⁽²⁾		Minimum	
Output RPM ⁽¹⁾	Max.		RPM	Torque in.lbs.	RPM	Torque in.lbs.	RPM	Torque in.lbs.
Min.								

3.0 HP, 1750 RPM Motor

Continued

70	14	C302_0310	TD470K 180-300	70	2,302	54	3,100	14	3,100
70	14	C402_0310	TD470K 180-300	70	2,310	34	4,872	14	4,872
68	14	C612_0320	TD470K 180-300	68	2,403	29	5,569	14	5,569
65	13	C712_0340	TD470K 180-300	65	2,506	28	5,808	13	5,808
62	12	C302_0350	TD470K 180-300	62	2,597	53	3,100	12	3,100
63	13	C402_0350	TD470K 180-300	63	2,582	34	4,872	13	4,872
63	13	C502_0350	TD470K 180-300	63	2,595	27	6,015	13	6,015
56	11	C612_0390	TD470K 180-300	56	2,921	24	6,770	11	6,770
53	11	C712_0410	TD470K 180-300	53	3,042	23	7,048	11	7,048
52	10	C402_0420	TD470K 180-300	52	3,096	34	4,872	10	4,872
52	10	C502_0420	TD470K 180-300	52	3,091	23	7,086	10	7,086
48	10	C612_0450	TD470K 180-300	48	3,362	21	7,790	10	7,790
47	9.4	C402_0470	TD470K 180-300	47	3,461	34	4,872	9.4	4,872
47	9.4	C502_0470	TD470K 180-300	47	3,464	23	7,086	9.4	7,086
44	8.9	C613_0490	TD470K 180-300	44	3,601	19	8,346	8.9	8,346
44	8.8	C502_0500	TD470K 180-300	44	3,694	23	7,086	8.8	7,086
40	7.9	C612_0550	TD470K 180-300	40	4,087	17	9,471	7.9	9,471
39	7.8	C502_0560	TD470K 180-300	39	4,140	24	7,086	7.8	7,086
39	7.7	C712_0570	TD470K 180-300	39	4,213	17	9,764	7.7	9,764
34	6.9	C613_0630	TD470K 180-300	34	4,638	15	10,748	6.9	10,748
32	6.4	C612_0690	TD470K 180-300	32	5,108	14	11,515	6.4	11,515
31	6.3	C712_0700	TD470K 180-300	31	5,157	14	11,951	6.3	11,951
28	5.7	C613_0770	TD470K 180-300	28	5,613	13	12,844	5.7	12,844
28	5.5	C813_0790	TD470K 180-300	28	5,798	12	13,437	5.5	13,437
27	5.4	C713_0810	TD470K 180-300	27	5,917	12	13,713	5.4	13,713
25	4.9	C613_0890	TD470K 180-300	25	6,488	14	11,515	4.9	11,515
24	4.8	C813_0910	TD470K 180-300	24	6,638	10	15,382	4.8	15,382
22	4.5	C613_0980	TD470K 180-300	22	7,136	13	12,844	4.5	12,844
22	4.4	C713_0990	TD470K 180-300	22	7,246	10	16,791	4.4	16,791
20	4.1	C613_1070	TD470K 180-300	20	7,851	14	11,515	4.1	11,515
20	4.1	C813_1080	TD470K 180-300	20	7,862	9	18,220	4.1	18,220
17	3.4	C613_1270	TD470K 180-300	17	9,276	13	12,844	3.4	12,844
17	3.3	C713_1320	TD470K 180-300	17	9,674	8	21,259	3.3	21,259
16	3.2	C613_1370	TD470K 180-300	16	9,982	14	11,515	3.2	11,515
16	3.2	C713_1370	TD470K 180-300	16	10,037	9	17,716	3.2	17,716
16	3.2	C813_1380	TD470K 180-300	16	10,114	7	23,438	3.2	23,438
12	2.4	C713_1830	TD470K 180-300	12	13,402	9	17,716	2.4	17,716
12	2.5	C813_1780	TD470K 180-300	12	13,035	5	30,208	2.5	30,208
10	2.1	C813_2120	TD470K 180-300	10	15,501	5	31,889	2.1	31,889
10	2.0	C713_2230	TD470K 180-300	10	16,264	9	17,716	2.0	17,716
8	1.6	C813_2700	TD470K 180-300	8	19,719	5	31,889	1.6	31,889

Part No. Explanation

C 5 0 2 N 0620 TD370K140 – 200 W
 C 5 0 2 N 0620 TD370K140 – 200 W
 Housing Style No. of Gear Reductions Generation No.
 Unit No. Concentric Helical

Washdown, when required
 Rated for HP (200 = 2.00)
 Non-gearred TD37 ComTrac Unit, 145TC Input

Ratio of MGS Unit (0620 = 62.0:1)

Selection Procedure:

- Determine the MGS/ComTrac combination according to the Input HP of the application and the Output RPM nearest the required maximum speed.
- Verify that the output torque will sufficiently meet the application requirements.
- Complete the Part No. per the example by adding the Housing Style letter ("N", "F", "Q" or "G") as required.



"C" Series – MGS Adjustable Speed Drive Selection Data



Speed Range		Part Number	Maximum		Transition (2)		Minimum	
Output RPM (1)	Max.		Min.	RPM	Torque in.lbs.	RPM	Torque in.lbs.	RPM

5.0 HP, 1750 RPM Motor

Continued on next page

1,089	218	C202_0020	TD570K	180-500	1,089	255	543	518	218	518
1,002	200	C202_0022	TD570K	180-500	1,002	277	499	563	200	563
884	177	C202_0025	TD570K	180-500	884	314	441	638	177	638
813	163	C202_0027	TD570K	180-500	813	342	405	693	163	693
705	141	C202_0031	TD570K	180-500	705	394	351	800	141	800
649	130	C202_0034	TD570K	180-500	649	428	323	869	130	869
563	113	C202_0039	TD570K	180-500	563	494	281	1,002	113	1,002
518	104	C202_0042	TD570K	180-500	518	537	258	1,089	104	1,089
523	105	C302_0042	TD570K	180-500	523	531	261	1,077	105	1,077
498	100	C402_0044	TD570K	180-500	498	558	248	1,133	100	1,133
473	95	C502_0046	TD570K	180-500	473	588	236	1,193	95	1,193
469	94	C202_0047	TD570K	180-500	469	593	234	1,203	94	1,203
468	94	C302_0047	TD570K	180-500	468	594	233	1,205	94	1,205
434	87	C302_0050	TD570K	180-500	434	640	216	1,299	87	1,299
431	86	C202_0051	TD570K	180-500	431	644	215	1,307	86	1,307
414	83	C402_0053	TD570K	180-500	414	671	206	1,362	83	1,362
378	76	C202_0058	TD570K	180-500	378	735	197	1,431	76	1,431
373	75	C302_0059	TD570K	180-500	373	744	186	1,510	75	1,510
347	70	C202_0063	TD570K	180-500	347	799	198	1,427	70	1,427
346	69	C302_0063	TD570K	180-500	346	802	173	1,628	69	1,628
329	66	C402_0066	TD570K	180-500	329	844	164	1,714	66	1,714
329	66	C502_0067	TD570K	180-500	329	845	164	1,715	66	1,715
280	56	C202_0078	TD570K	180-500	280	990	201	1,422	56	1,422
279	56	C302_0078	TD570K	180-500	279	996	139	2,021	56	2,021
267	53	C202_0082	TD570K	180-500	267	1,040	160	1,772	53	1,772
265	53	C302_0083	TD570K	180-500	265	1,048	132	2,127	53	2,127
235	47	C302_0093	TD570K	180-500	235	1,182	117	2,400	47	2,400
233	47	C202_0094	TD570K	180-500	233	1,192	161	1,772	47	1,772
213	43	C202_0105	TD570K	180-500	213	1,303	161	1,772	43	1,772
213	43	C302_0105	TD570K	180-500	213	1,306	106	2,651	43	2,651
188	38	C302_0115	TD570K	180-500	188	1,474	94	2,992	38	2,992
188	38	C402_0115	TD570K	180-500	188	1,478	94	2,999	38	2,999
186	37	C202_0120	TD570K	180-500	186	1,493	159	1,772	37	1,772
178	36	C202_0125	TD570K	180-500	178	1,564	159	1,772	36	1,772
176	35	C302_0125	TD570K	180-500	176	1,575	91	3,100	35	3,100
175	35	C402_0125	TD570K	180-500	175	1,590	87	3,227	35	3,227
156	31	C302_0140	TD570K	180-500	156	1,777	91	3,100	31	3,100
156	31	C402_0140	TD570K	180-500	156	1,777	78	3,607	31	3,607
141	28	C302_0155	TD570K	180-500	141	1,974	92	3,100	28	3,100
139	28	C502_0155	TD570K	180-500	139	1,995	69	4,049	28	4,049
139	28	C402_0160	TD570K	180-500	139	2,000	69	4,060	28	4,060
125	25	C302_0175	TD570K	180-500	125	2,227	92	3,100	25	3,100
124	25	C402_0175	TD570K	180-500	124	2,235	62	4,538	25	4,538
112	22	C612_0195	TD570K	180-500	112	2,490	56	5,054	22	5,054
105	21	C302_0210	TD570K	180-500	105	2,641	91	3,100	21	3,100
105	21	C402_0210	TD570K	180-500	105	2,654	58	4,872	21	4,872
105	21	C502_0210	TD570K	180-500	105	2,647	52	5,373	21	5,373
93	19	C302_0230	TD570K	180-500	93	2,981	90	3,100	19	3,100


1) Speed tolerance at rated load is $\pm 3\%$. At less than rated load, minimum speed may increase 5%.

2) The ComTrac drive operates at constant horsepower above transition values and at constant torque below transition values. Note shaded area.


Engineering advances may cause slight changes to the information shown.

Housing Styles

N – Foot Mounted



F – Round Flange



Q – Square Flange



G – Tapped Holes



See page 78 for mounting positions.

Housing Style Q is available on special order.

Output Shaft Diameter (inches)

See Page 21 for other options.

Base Module	Dia.	Base Module	Dia.
C002	.7500	C512/C513	1.6250
C102/C103	1.0000	C612/C613	2.1250
C202/C203	1.2500	C712/C713	2.3750
C302/C303	1.2500	C812/C813	2.8750
C402/C403	1.6250		



"C" Series – MGS Adjustable Speed Drive Selection Data



Speed Range		Part Number	Maximum		Transition ⁽²⁾		Minimum	
Output RPM ⁽¹⁾	Max.		RPM	Torque in.lbs.	RPM	Torque in.lbs.	RPM	Torque in.lbs.
Min.								

5.0 HP, 1750 RPM Motor

Continued

94	19	C402_0230	TD570K 180-500	94	2,966	58	4,872	19	4,872
94	19	C502_0230	TD570K 180-500	94	2,966	47	6,021	19	6,021
88	18	C402_0250	TD570K 180-500	88	3,165	59	4,872	18	4,872
87	17	C502_0250	TD570K 180-500	87	3,184	43	6,463	17	6,463
80	16	C612_0270	TD570K 180-500	80	3,483	40	7,070	16	7,070
79	16	C402_0280	TD570K 180-500	79	3,537	59	4,872	16	4,872
78	16	C502_0280	TD570K 180-500	78	3,568	40	7,086	16	7,086
70	14	C402_0310	TD570K 180-500	70	3,956	58	4,872	14	4,872
70	14	C502_0310	TD570K 180-500	70	3,966	40	7,086	14	7,086
68	14	C612_0320	TD570K 180-500	68	4,115	34	8,353	14	8,353
65	13	C712_0340	TD570K 180-500	65	4,292	32	8,712	13	8,712
63	13	C402_0350	TD570K 180-500	63	4,422	58	4,872	13	4,872
63	13	C502_0350	TD570K 180-500	63	4,445	40	7,086	13	7,086
63	13	C612_0350	TD570K 180-500	63	4,428	31	8,989	13	8,989
56	11	C612_0390	TD570K 180-500	56	5,003	28	10,155	11	10,155
53	11	C712_0410	TD570K 180-500	53	5,208	27	10,573	11	10,573
52	10	C502_0420	TD570K 180-500	52	5,294	40	7,086	10	7,086
48	10	C612_0450	TD570K 180-500	48	5,757	24	11,515	10	11,515
47	9.4	C502_0470	TD570K 180-500	47	5,933	40	7,086	9.4	7,086
47	9.3	C712_0470	TD570K 180-500	47	5,945	23	12,068	9.3	12,068
44	8.9	C613_0490	TD570K 180-500	44	6,167	22	12,519	8.9	12,519
44	8.8	C502_0500	TD570K 180-500	44	6,327	40	7,086	8.8	7,086
40	7.9	C612_0550	TD570K 180-500	40	6,998	25	11,515	7.9	11,515
39	7.7	C712_0570	TD570K 180-500	39	7,215	19	14,646	7.7	14,646
34	6.9	C613_0630	TD570K 180-500	34	7,942	22	12,844	6.9	12,844
32	6.4	C612_0690	TD570K 180-500	32	8,748	25	11,515	6.4	11,515
31	6.3	C712_0700	TD570K 180-500	31	8,831	16	17,716	6.3	17,716
28	5.7	C613_0770	TD570K 180-500	28	9,611	22	12,844	5.7	12,844
28	5.5	C813_0790	TD570K 180-500	28	9,930	14	20,156	5.5	20,156
27	5.4	C713_0810	TD570K 180-500	27	10,133	13	20,569	5.4	20,569
25	4.9	C613_0890	TD570K 180-500	25	11,111	24	11,515	4.9	11,515
24	4.8	C813_0910	TD570K 180-500	24	11,367	12	23,073	4.8	23,073
22	4.5	C613_0980	TD570K 180-500	22	12,219	21	12,844	4.5	12,844
22	4.4	C713_0990	TD570K 180-500	22	12,408	13	21,259	4.4	21,259
20	4.1	C813_1080	TD570K 180-500	20	13,464	10	27,330	4.1	27,330
17	3.3	C713_1320	TD570K 180-500	17	16,567	13	21,259	3.3	21,259
16	3.2	C713_1370	TD570K 180-500	16	17,188	16	17,716	3.2	17,716
16	3.2	C813_1380	TD570K 180-500	16	17,320	9	31,889	3.2	31,889
12	2.5	C813_1780	TD570K 180-500	12	22,322	9	31,889	2.5	31,889
10	2.1	C813_2120	TD570K 180-500	10	26,545	9	31,889	2.1	31,889

Part No. Explanation

C 5 0 2 N 0620 TD370K140 – 200 W

Washdown, when required
Rated for HP (200 = 2.00)
Non-gearred TD37 ComTrac Unit, 145TC Input
Ratio of MGS Unit (0620 = 62.0:1)
Housing Style
No. of Gear Reductions
Generation No.
Unit No.
Concentric Helical

Selection Procedure:

- Determine the MGS/ComTrac combination according to the Input HP of the application and the Output RPM nearest the required **maximum** speed.
- Verify that the output torque will sufficiently meet the application requirements.
- Complete the Part No. per the example by adding the Housing Style letter ("N", "F", "Q" or "G") as required.



"C" Series – MGS® Adjustable Speed Drives Dimensional Data



Drawing for Units
C002N — C503N




Table No. 1 "C" Series with ComTrac – Foot Mounting Unit Dimensions (Inches) – "N" Housing Style

Base Module	A	B	D	F	G	H	J	M	N	O	P	Q	R	S	T	V	Z ₁
C002	5.20	3.74	5.67	4.33	2.44	3.23	.28	1.38	.79	2.24	1.73	.16	2.17	.43	3.62	1.57	—
C102/C103	6.93	4.65	6.97	5.91	2.76	4.02	.35	1.65	.98	2.72	2.13	.16	2.64	.51	4.88	1.97	—
C202/C203	7.87	5.31	7.68	6.69	3.35	4.53 ¹⁾	.43	1.97	1.18	3.39	2.56	.16	3.11	.55	5.43	2.36	—
C302/C303	8.46	6.06	8.46	7.28	4.13	5.12 ¹⁾	.43	1.97	1.18	3.35	2.56	.16	3.11	.55	5.91	2.36	—
C402/C403	10.04	7.09	9.65	8.66	4.33	5.71	.55	2.36	1.38	4.17	3.39	.16	4.13	.75	6.89	3.15	—
C502/C503	11.42	7.76	11.42	9.65	5.12	6.69	.71	2.76	1.57	4.21	3.39	.16	4.25	.87	7.56	3.15	—
C612/C613	11.81	10.43	12.40	9.65	8.46	7.87 ¹⁾	.71	2.95	1.57	6.02	4.17	.20	5.12	.98	6.97	3.94	6.57
C712/C713	14.37	11.22	14.76	11.81	9.25	9.25 ¹⁾	.71	3.54	1.97	7.28	5.00	.20	6.42	.98	7.56	4.72	7.91
C812/C813	17.13	14.17	17.72	13.39	11.81	11.42	.87	3.74	2.17	8.58	5.83	.39	7.48	1.14	8.78	5.51	8.70

¹⁾ See Table No. 2. These sizes are not coaxial. H=Output Height, H₁=Input Height.

Table No. 2 H₁ Dimension (Inches)

Base Module	TD27	TD37	TD47	TD57
C203	3.07	—	—	—
C303	3.66	3.66	—	—
C612	—	—	7.64	7.64
C613	7.64	7.64	7.64	7.64
C713	—	—	—	—

These sizes are not coaxial.

H=Output Height, H₁=Input Height.

Table No. 3 "C" Series Shaft Dimensions (Inches)

Base Module	U	Tolerance	UA – Key	UB
C002	.7500	+.0000/-0.0006	3/16 x 3/16 x 17/32	.83
C102/C103	1.0000	+.0000/-0.0006	1/4 x 1/4 x 19/16	1.11
C202/C203	1.2500	+.0000/-0.0007	1/4 x 1/4 x 115/16	1.36
C302/C303	1.2500	+.0000/-0.0007	1/4 x 1/4 x 115/16	1.36
C402/C403	1.6250	+.0000/-0.0007	3/8 x 3/8 x 27/8	1.79
C502/C503	1.6250	+.0000/-0.0007	3/8 x 3/8 x 27/8	1.79
C612/C613	2.1250	+.0000/-0.0008	1/2 x 1/2 x 35/32	2.35
C712/C713	2.3750	+.0000/-0.0008	5/8 x 5/8 x 315/16	2.65
C812/C813	2.8750	+.0000/-0.0008	3/4 x 3/4 x 45/16	3.21

Table No. 4

"C" Series with ComTrac Dimensions (Inches)

ComTrac Part No.	NEMA C-Flange	DH	HL	TL	X	Y	Z
TD270K050	56C	4.92	5.67	7.87	2.09	5.55	4.41
TD270K140	143/145TC	4.92	5.67	7.87	2.09	5.55	4.41
TD370K140	143/145TC	4.92	5.91	8.50	2.17	5.67	4.37
TD470K180	182/184TC	6.30	6.81	8.94	2.80	7.20	5.59
TD570K180	182/184TC	7.87	8.31	11.89	3.11	8.11	6.30



"C" Series – MGS® Adjustable Speed Drives

Dimensional Data



Drawing for Units
C612N — C813N




Table No. 5 "C" Series with ComTrac – Foot Mounting Unit Dimensions
(Inches) – "N" Housing Style

Base	TD270K050 ⁽²⁾			TD370K140			TD470K180			TD570K180		
	H ₂	I	L	H ₂	I	L	H ₂	I	L	H ₂	I	L
C002	1.65	12.40	6.22	1.18	13.07	6.22	—	—	—	—	—	—
C102	2.44	13.70	7.52	1.97	14.37	7.52	1.42	14.49	7.60	—	—	—
C202	2.95	14.80	8.62	2.48	15.47	8.62	1.93	15.59	8.70	1.18	18.23	8.70
C203⁽¹⁾	1.50	16.50	10.31	—	—	—	—	—	—	—	—	—
C302	3.54	15.55	9.37	3.07	16.22	9.37	2.52	16.34	9.45	1.77	18.98	9.45
C303⁽¹⁾	2.09	17.24	11.06	1.61	17.91	11.06	—	—	—	—	—	—
C402	4.13	17.44	11.24	3.66	18.11	11.26	3.11	18.23	11.34	2.36	20.87	11.34
C403	4.13	19.13	12.95	3.66	19.80	12.95	—	—	—	—	—	—
C502	—	—	—	4.65	18.94	12.09	4.09	19.06	12.17	3.35	21.69	12.17
C503	5.12	19.96	13.78	4.65	20.63	13.78	—	—	—	—	—	—
C612⁽¹⁾	—	—	—	—	—	—	5.04	20.00	13.11	4.29	22.64	13.11
C613⁽¹⁾	6.06	20.94	14.76	5.59	21.61	14.76	5.04	22.44	15.55	4.29	25.08	15.55
C712	—	—	—	—	—	—	6.65	22.09	15.20	5.91	24.72	15.20
C713⁽¹⁾	—	—	—	—	—	—	6.65	24.49	17.60	5.91	27.13	17.60
C812	—	—	—	—	—	—	—	—	—	—	—	—
C813	—	—	—	—	—	—	8.82	27.13	20.24	8.07	29.76	20.24

⁽¹⁾ See Table No. 2. These sizes are not coaxial. H=Output Height, H₁=Input Height.

⁽²⁾ Also TD270FK140 for a NEMA 143TC frame motor.

Table No. 6
"C" Series with ComTrac – Approximate Weight (lbs.)

Part Number	C002	C102	C202	C203	C302	C303	C402	C403	C502	C503	C612	C613	C712	C713	C812	C813
TD270K050 ⁽²⁾	51	62	71	78	82	89	104	111	128	144	—	148	—	—	—	—
TD370K140	69	80	89	—	100	107	122	129	146	162	—	210	—	—	—	—
TD470K180	—	88	97	—	108	—	130	—	154	—	174	218	258	280	—	401
TD570K180	—	—	126	—	137	—	159	—	183	—	203	247	287	309	—	430

⁽²⁾Also TD270FK140 for a NEMA 143TC frame motor.

Part No. Example

Foot Mounting with ComTrac, 56C Input, .75 HP motor
C302N0620 TD270K050-075

The STOBER Difference . . .
...equals VALUE for you



3 Rings

To get competent,
“one-stop” shopping!

**STANDARD
3-DAY
DELIVERY**



3 WAY After Sale Service

5 Day Factory Service
Field Service
Training Support

2 YEAR WARRANTY

TROUBLE

Few Rotating Parts
Fit Standard NEMA C-face Motor



Industrial Coatings:
Standard Severe Duty Gray
White Washdown (FDA approved)
Stainless Steel (FDA/USDA approved)

Additional Product Offering

- MGS® Speed Reducers
- Food and Beverage Duty Speed Reducers
- Poultry Duty Speed Reducers
- ServoFit® Precision Planetary Gearheads
- ServoFit® Modular System Gearheads



"F" Series – Offset Helical MGS® Adjustable Speed Drives

Performance Specifications:

- Horsepower ratings – from 1/2 to 5
- Output speeds – available from 528 to .6 RPM
- Speed range – 5:1 to 7:1
- Output torques – up to 9,744 in.lbs.
- NEMA frames – from 56C to 215TC

STOBER's versatility continues with MGS Reducers and ComTrac Adjustable Speed Drives when using the Offset Helical Series.

Compact size and flexibility make these gear drives a popular choice for applications that require high performance, efficiency, and durability.




Table No. 1 "F" Series – Output Diameter Options

Base Module	Stainless Bushing Bores Sizes – inches													Hollow			Shaft	
	3/4	1	1 3/16	1 1/4	1 3/8	1 7/16	1 1/2	1 5/8	1 11/16	1 3/4	1 7/8	1 15/16	2	Standard	Stainless	Metric ⁽¹⁾	Standard	Metric ⁽¹⁾
F102	X	—	—	—	—	—	—	—	—	—	—	—	—	.750	—	20	1.000	25
F202/F203	—	X	X	—	—	—	—	—	—	—	—	—	—	1.000	1.000	25	1.250	30
F302/F303	—	X	X	X	X	X	X	—	—	—	—	—	—	1.250	1.250	30	1.375	35
F402/F403	—	X	X	X	X	X	X	—	—	—	—	—	—	1.500	—	40	1.625	40
F602/F603	—	—	X	—	—	X	X	X	X	X	X	X	X	2.000	—	50	2.125	50

⁽¹⁾ Contact STOBER Drives for availability.



"F" Series – MGS Adjustable Speed Drive Selection Data



Speed Range		Part Number		Maximum		Transition (2)		Minimum	
Output RPM (1)	Max.			RPM	Torque in.lbs.	RPM	Torque in.lbs.	RPM	Torque in.lbs.
.50 HP, 1750 RPM Motor									
528	75	F102_0043	TD270K 050-050	528	48	75	278	75	278
486	69	F202_0047	TD270K 050-050	486	53	69	302	69	302
352	50	F102_0065	TD270K 050-050	352	73	50	416	50	416
318	45	F102_0072	TD270K 050-050	318	81	45	461	45	461
254	36	F102_0089	TD270K 050-050	254	101	36	577	36	577
253	36	F202_0090	TD270K 050-050	253	101	36	580	36	580
208	30	F102_0110	TD270K 050-050	208	123	30	704	30	704
167	24	F102_0135	TD270K 050-050	167	153	24	876	24	876
123	18	F102_0185	TD270K 050-050	123	208	21	1,063	18	1,063
99	14	F102_0230	TD270K 050-050	99	260	23	1,063	14	1,063
81	12	F102_0280	TD270K 050-050	81	317	24	1,063	12	1,063
65	9.3	F102_0350	TD270K 050-050	65	394	25	1,063	9.3	1,063
49	7.0	F102_0460	TD270K 050-050	49	523	25	1,063	7.0	1,063
48	6.9	F202_0470	TD270K 050-050	48	529	11	2,126	6.9	2,126
41	5.8	F102_0560	TD270K 050-050	41	630	25	1,063	5.8	1,063
40	5.8	F302_0560	TD270K 050-050	40	636	5.9	3,543	5.8	3,543
40	5.7	F202_0570	TD270K 050-050	40	638	12	2,126	5.7	2,126
32	4.6	F102_0700	TD270K 050-050	32	788	25	1,063	4.6	1,063
32	4.6	F202_0700	TD270K 050-050	32	789	12	2,126	4.6	2,126
24	3.5	F202_0940	TD270K 050-050	24	1,056	13	2,126	3.5	2,126
24	3.5	F402_0930	TD270K 050-050	24	1,050	3.5	6,015	3.5	6,015
20	2.9	F302_1130	TD270K 050-050	20	1,270	7.4	3,543	2.9	3,543
20	2.9	F402_1120	TD270K 050-050	20	1,264	3.6	6,201	2.9	6,201
16	2.3	F402_1400	TD270K 050-050	16	1,573	3.9	6,201	2.3	6,201
12	1.8	F303_1820	TD270K 050-050	12	2,024	7.5	3,543	1.8	3,543
13	1.8	F403_1820	TD270K 050-050	13	2,013	4.1	6,201	1.8	6,201
13	1.8	F603_1810	TD270K 050-050	13	2,004	2.3	9,744	1.8	9,744
11	1.5	F403_2160	TD270K 050-050	11	2,401	4.2	6,201	1.5	6,201
11	1.5	F603_2150	TD270K 050-050	11	2,390	2.4	9,744	1.5	9,744
10	1.5	F303_2180	TD270K 050-050	10	2,423	7.4	3,543	1.5	3,543
8	1.2	F603_2690	TD270K 050-050	8	2,987	2.6	9,744	1.2	9,744
8	1.2	F303_2720	TD270K 050-050	8	3,018	7.3	3,543	1.2	3,543
8	1.2	F403_2710	TD270K 050-050	8	3,005	4.3	6,201	1.2	6,201
6	0.9	F403_3610	TD270K 050-050	6	4,003	4.3	6,201	0.9	6,201
6	0.9	F603_3610	TD270K 050-050	6	4,003	2.7	9,744	0.9	9,744
5	0.7	F403_4340	TD270K 050-050	5	4,815	4.2	6,201	0.7	6,201
5	0.7	F603_4340	TD270K 050-050	5	4,812	2.7	9,744	0.7	9,744
4	0.6	F603_5400	TD270K 050-050	4	5,994	2.7	9,744	0.6	9,744

.75 HP, 1750 RPM Motor

Continued on next page

528	75	F102_0043	TD270K 050-075	528	72	131	278	75	278
486	69	F202_0047	TD270K 050-075	486	78	120	302	69	302
352	50	F102_0065	TD270K 050-075	352	108	87	416	50	416
318	45	F102_0072	TD270K 050-075	318	120	79	461	45	461
254	36	F102_0089	TD270K 050-075	254	150	63	577	36	577
253	36	F202_0090	TD270K 050-075	253	151	63	580	36	580
208	30	F102_0110	TD270K 050-075	208	183	52	704	30	704
167	24	F102_0135	TD270K 050-075	167	227	41	876	24	876

1) Speed tolerance at rated load is ±3%. At less than rated load, minimum speed may increase 5%.

2) The ComTrac drive operates at constant horsepower above transition values and at constant torque below transition values. Note shaded area.


Engineering advances may cause slight changes to the information shown.

Housing Styles

F – Round Flange



G – Tapped Holes



Housing Style "F" is available as Hollow (A) or Solid (V) Output.

See page 78 for mounting positions.

Output Shaft Diameter and
Hollow Output (inches)

See Page 43 for other options.

Base Module	Output Shaft	Hollow Output
F102	1.0000	.7500
F202/F203	1.2500	1.0000
F302/F303	1.3750	1.2500
F402/F403	1.6250	1.5000
F602/F603	2.1250	2.0000



"F" Series – MGS Adjustable Speed Drive Selection Data



Speed Range		Part Number	Maximum		Transition ⁽²⁾		Minimum	
Output RPM ⁽¹⁾	Max.		RPM	Torque in.lbs.	RPM	Torque in.lbs.	RPM	Torque in.lbs.
.75 HP, 1750 RPM Motor								
123	18	F102_0185	TD270K 050-075	123	309	35	1,063	18
99	14	F102_0230	TD270K 050-075	99	386	37	1,063	14
81	12	F102_0280	TD270K 050-075	81	471	37	1,063	12
65	9.3	F102_0350	TD270K 050-075	65	586	38	1,063	9.3
64	9.2	F202_0350	TD270K 050-075	64	593	17	2,126	9.2
49	7.0	F102_0460	TD270K 050-075	49	776	37	1,063	7.0
48	6.9	F202_0470	TD270K 050-075	48	786	18	2,126	6.9
41	5.8	F102_0560	TD270K 050-075	41	936	36	1,063	5.8
40	5.8	F302_0560	TD270K 050-075	40	944	10	3,543	5.8
40	5.7	F202_0570	TD270K 050-075	40	948	19	2,126	5.7
32	4.6	F202_0700	TD270K 050-075	32	1,172	19	2,126	4.6
32	4.6	F302_0700	TD270K 050-075	32	1,176	11	3,543	4.6
24	3.5	F202_0940	TD270K 050-075	24	1,568	19	2,126	3.5
24	3.5	F302_0940	TD270K 050-075	24	1,565	11	3,543	3.5
24	3.5	F402_0930	TD270K 050-075	24	1,560	6.0	6,015	3.5
20	2.9	F302_1130	TD270K 050-075	20	1,886	11	3,543	2.9
20	2.9	F402_1120	TD270K 050-075	20	1,877	6.1	6,201	2.9
16	2.3	F402_1400	TD270K 050-075	16	2,336	6.3	6,201	2.3
12	1.8	F303_1820	TD270K 050-075	12	3,006	11	3,543	1.8
13	1.8	F403_1820	TD270K 050-075	13	2,990	6.3	6,201	1.8
13	1.8	F603_1810	TD270K 050-075	13	2,976	3.8	9,744	1.8
11	1.5	F403_2160	TD270K 050-075	11	3,565	6.4	6,201	1.5
11	1.5	F603_2150	TD270K 050-075	11	3,549	3.9	9,744	1.5
8.4	1.2	F603_2690	TD270K 050-075	8.4	4,436	4.0	9,744	1.2
8.4	1.2	F403_2710	TD270K 050-075	8.4	4,462	6.3	6,201	1.2
6.3	0.9	F403_3610	TD270K 050-075	6.3	5,945	6.1	6,201	0.9
6.3	0.9	F603_3610	TD270K 050-075	6.3	5,945	4.0	9,744	0.9
5.2	0.7	F603_4340	TD270K 050-075	5.2	7,147	4.0	9,744	0.7
4.2	0.6	F603_5400	TD270K 050-075	4.2	8,902	3.9	9,744	0.6
528	75	F102_0043	TD270K 140-100	528	98	190	278	75
486	69	F202_0047	TD270K 140-100	486	107	175	302	69
352	50	F102_0065	TD270K 140-100	352	147	127	416	50
318	45	F102_0072	TD270K 140-100	318	163	115	461	45
254	36	F102_0089	TD270K 140-100	254	204	92	577	36
253	36	F202_0090	TD270K 140-100	253	205	91	580	36
208	30	F102_0110	TD270K 140-100	208	249	75	704	30
167	24	F102_0135	TD270K 140-100	167	310	60	876	24
123	18	F102_0185	TD270K 140-100	123	421	50	1,063	18
122	17	F202_0185	TD270K 140-100	122	425	44	1,202	17
99	14	F102_0230	TD270K 140-100	99	526	51	1,063	14
97	14	F202_0230	TD270K 140-100	97	534	35	1,510	14
81	12	F102_0280	TD270K 140-100	81	642	51	1,063	12
81	12	F202_0280	TD270K 140-100	81	641	29	1,812	12
65	9.3	F102_0350	TD270K 140-100	65	799	51	1,063	9.3
64	9.2	F202_0350	TD270K 140-100	64	808	25	2,126	9.2
49	7.0	F102_0460	TD270K 140-100	49	1,058	49	1,063	7.0
48	6.9	F202_0470	TD270K 140-100	48	1,072	26	2,126	6.9

Part No. Explanation

E 2 0 2 A F 0620 TD370K140 - 200 W
 Washdown, when required
 Rated for HP (200 = 2.00)
 Non-gearred TD37 ComTrac Unit, 145TC Input
 Ratio of MGS Unit (0620 = 62.0:1)
 Housing Style – F (Output Flange)
 Hollow Output Style – A
 No. of Gear Reductions
 Generation No.
 Unit No.
 Offset Helical

Selection Procedure:

- Determine the MGS/ComTrac combination according to the Input HP of the application and the Output RPM nearest the required **maximum speed**.
- Verify that the output torque will sufficiently meet the application requirements.
- Complete the Part No. per the example by adding "A" or "V" for the Output Style and the Housing Style letter ("B", "F", or "G") as required. "V" output is only available with the "F" housing style.



"F" Series – MGS Adjustable Speed Drive Selection Data



Speed Range		Part Number		Maximum		Transition (2)		Minimum	
Output RPM (1)	Max.			RPM	Torque in.lbs.	RPM	Torque in.lbs.	RPM	Torque in.lbs.
.75 HP, 1750 RPM Motor Continued									
48	6.9	F302_0470	TD270K 140-100	48	1,075	17	3,041	6.9	3,041
40	5.8	F302_0560	TD270K 140-100	40	1,287	15	3,543	5.8	3,543
40	5.7	F202_0570	TD270K 140-100	40	1,293	26	2,126	5.7	2,126
32	4.6	F202_0700	TD270K 140-100	32	1,598	25	2,126	4.6	2,126
32	4.6	F302_0700	TD270K 140-100	32	1,603	15	3,543	4.6	3,543
24	3.5	F302_0940	TD270K 140-100	24	2,134	15	3,543	3.5	3,543
24	3.5	F402_0930	TD270K 140-100	24	2,127	8.8	6,015	3.5	6,015
20	2.9	F302_1130	TD270K 140-100	20	2,572	15	3,543	2.9	3,543
20	2.9	F402_1120	TD270K 140-100	20	2,559	8.7	6,201	2.9	6,201
16	2.3	F402_1400	TD270K 140-100	16	3,185	8.8	6,201	2.3	6,201
16	2.3	F602_1400	TD270K 140-100	16	3,185	5.9	9,006	2.3	9,006
13	1.8	F403_1820	TD270K 140-100	13	4,077	8.6	6,201	1.8	6,201
13	1.8	F603_1810	TD270K 140-100	13	4,057	5.4	9,744	1.8	9,744
11	1.5	F403_2160	TD270K 140-100	11	4,861	8.5	6,201	1.5	6,201
11	1.5	F603_2150	TD270K 140-100	11	4,838	5.5	9,744	1.5	9,744
8.4	1.2	F603_2690	TD270K 140-100	8.4	6,048	5.5	9,744	1.2	9,744
8.4	1.2	F403_2710	TD270K 140-100	8.4	6,084	8.3	6,201	1.2	6,201
6.3	0.9	F603_3610	TD270K 140-100	6.3	8,105	5.4	9,744	0.9	9,744
5.2	0.7	F603_4340	TD270K 140-100	5.2	9,744	5.2	9,744	0.7	9,744

1.0 HP, 1750 RPM Motor Continued on next page									
508	102	F102_0043	TD370K 140-150	508	152	194	407	102	407
471	94	F302_0046	TD370K 140-150	471	163	180	439	94	439
467	93	F202_0047	TD370K 140-150	467	165	179	442	93	442
394	79	F202_0056	TD370K 140-150	394	195	151	525	79	525
339	68	F102_0065	TD370K 140-150	339	227	129	611	68	611
306	61	F102_0072	TD370K 140-150	306	252	117	676	61	676
244	49	F102_0089	TD370K 140-150	244	315	93	846	49	846
243	49	F202_0090	TD370K 140-150	243	317	93	851	49	851
200	40	F102_0110	TD370K 140-150	200	384	83	956	40	956
202	40	F202_0110	TD370K 140-150	202	380	77	1,021	40	1,021
161	32	F102_0135	TD370K 140-150	161	478	85	950	32	950
161	32	F202_0135	TD370K 140-150	161	479	61	1,288	32	1,288
119	24	F102_0185	TD370K 140-150	119	649	84	952	24	952
117	23	F202_0185	TD370K 140-150	117	656	45	1,763	23	1,763
117	23	F302_0190	TD370K 140-150	117	660	45	1,774	23	1,774
95	19	F102_0230	TD370K 140-150	95	812	82	962	19	962
93	19	F202_0230	TD370K 140-150	93	824	37	2,126	19	2,126
93	19	F302_0240	TD370K 140-150	93	827	36	2,223	19	2,223
78	16	F202_0280	TD370K 140-150	78	989	38	2,126	16	2,126
77	15	F302_0280	TD370K 140-150	77	993	30	2,668	15	2,668
62	12	F202_0350	TD370K 140-150	62	1,247	38	2,126	12	2,126
62	12	F302_0350	TD370K 140-150	62	1,233	24	3,311	12	3,311
46	9.3	F202_0470	TD370K 140-150	46	1,655	37	2,126	9.3	2,126
46	9.3	F302_0470	TD370K 140-150	46	1,660	23	3,543	9.3	3,543
39	7.7	F302_0560	TD370K 140-150	39	1,987	23	3,543	7.7	3,543
39	7.8	F402_0560	TD370K 140-150	39	1,969	15	5,290	7.8	5,290
39	7.7	F202_0570	TD370K 140-150	39	1,996	37	2,126	7.7	2,126

1) Speed tolerance at rated load is ±3%. At less than rated load, minimum speed may increase 5%.

2) The ComTrac drive operates at constant horsepower above transition values and at constant torque below transition values. Note shaded area.


Engineering advances may cause slight changes to the information shown.

Housing Styles

F – Round Flange



G – Tapped Holes



Housing Style "F" is available as Hollow (A) or Solid (V) Output.

See page 78 for mounting positions.

Output Shaft Diameter and
Hollow Output (inches)

See Page 43 for other options.

Base Module	Output Shaft	Hollow Output
F102	1.0000	.7500
F202/F203	1.2500	1.0000
F302/F303	1.3750	1.2500
F402/F403	1.6250	1.5000
F602/F603	2.1250	2.0000



"F" Series – MGS Adjustable Speed Drive Selection Data



Speed Range		Part Number	Maximum		Transition ⁽²⁾		Minimum		
Output RPM ⁽¹⁾	Max.		RPM	Torque in.lbs.	RPM	Torque in.lbs.	RPM	Torque in.lbs.	
1.0 HP, 1750 RPM Motor Continued									
31	6.2	F302_0700	TD370K 140-150	31	2,475	23	3,543	6.2	3,543
31	6.2	F402_0700	TD370K 140-150	31	2,465	13	6,201	6.2	6,201
23	4.7	F402_0930	TD370K 140-150	23	3,283	13	6,201	4.7	6,201
23	4.7	F602_0930	TD370K 140-150	23	3,283	9.0	8,821	4.7	8,821
23	4.7	F302_0940	TD370K 140-150	23	3,294	22	3,543	4.7	3,543
19	3.9	F402_1120	TD370K 140-150	19	3,950	13	6,201	3.9	6,201
19	3.9	F602_1120	TD370K 140-150	19	3,947	8.2	9,744	3.9	9,744
16	3.1	F602_1400	TD370K 140-150	16	4,916	8.3	9,744	3.1	9,744
12	2.4	F603_1810	TD370K 140-150	12	6,263	8.2	9,744	2.4	9,744
10	2.0	F603_2150	TD370K 140-150	10	7,469	8.0	9,744	2.0	9,744
8.1	1.6	F603_2690	TD370K 140-150	8.1	9,337	7.8	9,744	1.6	9,744
2.0 HP, 1750 RPM Motor									
508	102	F102_0043	TD370K 140-200	508	207	271	407	102	407
471	94	F302_0046	TD370K 140-200	471	223	251	439	94	439
467	93	F202_0047	TD370K 140-200	467	225	249	442	93	442
394	79	F202_0056	TD370K 140-200	394	267	210	525	79	525
339	68	F102_0065	TD370K 140-200	339	310	180	611	68	611
306	61	F102_0072	TD370K 140-200	306	344	163	676	61	676
305	61	F202_0072	TD370K 140-200	305	344	163	677	61	677
244	49	F102_0089	TD370K 140-200	244	430	136	812	49	812
243	49	F202_0090	TD370K 140-200	243	432	129	851	49	851
200	40	F102_0110	TD370K 140-200	200	524	136	813	40	813
202	40	F202_0110	TD370K 140-200	202	519	108	1,021	40	1,021
161	32	F102_0135	TD370K 140-200	161	653	132	821	32	821
161	32	F202_0135	TD370K 140-200	161	654	86	1,288	32	1,288
117	23	F202_0185	TD370K 140-200	117	896	63	1,763	23	1,763
117	23	F302_0190	TD370K 140-200	117	902	62	1,774	23	1,774
93	19	F202_0230	TD370K 140-200	93	1,125	52	2,126	19	2,126
93	19	F302_0240	TD370K 140-200	93	1,129	50	2,223	19	2,223
78	16	F202_0280	TD370K 140-200	78	1,350	52	2,126	16	2,126
77	15	F302_0280	TD370K 140-200	77	1,356	41	2,668	15	2,668
62	12	F202_0350	TD370K 140-200	62	1,703	51	2,126	12	2,126
62	12	F302_0350	TD370K 140-200	62	1,682	33	3,311	12	3,311
46	9.3	F302_0470	TD370K 140-200	46	2,266	31	3,543	9.3	3,543
47	9.3	F402_0470	TD370K 140-200	47	2,254	25	4,437	9.3	4,437
39	7.7	F302_0560	TD370K 140-200	39	2,713	31	3,543	7.7	3,543
39	7.8	F402_0560	TD370K 140-200	39	2,688	21	5,290	7.8	5,290
31	6.2	F302_0700	TD370K 140-200	31	3,379	30	3,543	6.2	3,543
31	6.2	F402_0700	TD370K 140-200	31	3,364	18	6,201	6.2	6,201
31	6.3	F602_0700	TD370K 140-200	31	3,344	17	6,582	6.3	6,582
23	4.7	F402_0930	TD370K 140-200	23	4,482	18	6,201	4.7	6,201
23	4.7	F602_0930	TD370K 140-200	23	4,482	12	8,821	4.7	8,821
19	3.9	F402_1120	TD370K 140-200	19	5,391	17	6,201	3.9	6,201
19	3.9	F602_1120	TD370K 140-200	19	5,388	11	9,744	3.9	9,744
16	3.1	F602_1400	TD370K 140-200	16	6,711	11	9,744	3.1	9,744
12	2.4	F603_1810	TD370K 140-200	12	8,550	11	9,744	2.4	9,744

Part No. Explanation

E 2 0 2 A F 0620 TD370K140 - 200 W

Washdown, when required
Rated for HP (200 = 2.00)
Non-greased TD37 ComTrac Unit, 145TC Input
Ratio of MGS Unit (0620 = 62.0:1)
Housing Style – F (Output Flange)
Hollow Output Style – A
No. of Gear Reductions
Generation No.
Unit No.
Offset Helical

Selection Procedure:

- Determine the MGS/ComTrac combination according to the Input HP of the application and the Output RPM nearest the required maximum speed.
- Verify that the output torque will sufficiently meet the application requirements.
- Complete the Part No. per the example by adding "A" or "V" for the Output Style and the Housing Style letter ("B", "F", or "G") as required. "V" output is only available with the "F" housing style.



"F" Series – MGS Adjustable Speed Drive Selection Data



Speed Range		Part Number		Maximum		Transition (2)		Minimum	
Output RPM (1)	Max.			RPM	Torque in.lbs.	RPM	Torque in.lbs.	RPM	Torque in.lbs.
Min.									
3.0 HP, 1750 RPM Motor									
471	94	F302_0046	TD470K	180-300	471	344	204	798	94
467	93	F202_0047	TD470K	180-300	467	347	203	804	93
394	79	F202_0056	TD470K	180-300	394	412	171	954	79
382	76	F302_0057	TD470K	180-300	382	424	166	983	76
376	75	F402_0058	TD470K	180-300	376	431	163	999	75
305	61	F202_0072	TD470K	180-300	305	531	132	1,232	61
243	49	F202_0090	TD470K	180-300	243	668	105	1,548	49
243	49	F302_0090	TD470K	180-300	243	666	106	1,544	49
202	40	F202_0110	TD470K	180-300	202	801	88	1,856	40
203	41	F302_0110	TD470K	180-300	203	800	88	1,853	41
161	32	F202_0135	TD470K	180-300	161	1,010	89	1,860	32
163	33	F302_0135	TD470K	180-300	163	992	71	2,300	33
117	23	F202_0185	TD470K	180-300	117	1,383	90	1,853	23
117	23	F402_0185	TD470K	180-300	117	1,381	51	3,200	23
117	23	F302_0190	TD470K	180-300	117	1,392	51	3,226	23
93	19	F202_0230	TD470K	180-300	93	1,738	88	1,872	19
94	19	F402_0230	TD470K	180-300	94	1,721	41	3,989	19
93	19	F302_0240	TD470K	180-300	93	1,744	46	3,543	19
77	15	F302_0280	TD470K	180-300	77	2,093	47	3,543	15
78	16	F402_0280	TD470K	180-300	78	2,075	34	4,809	16
62	12	F302_0350	TD470K	180-300	62	2,598	47	3,543	12
62	12	F402_0350	TD470K	180-300	62	2,601	27	6,028	12
46	9.3	F302_0470	TD470K	180-300	46	3,499	46	3,543	9.3
47	9.3	F402_0470	TD470K	180-300	47	3,481	27	6,201	9.3
47	9.4	F602_0470	TD470K	180-300	47	3,464	20	8,028	9.4
39	7.8	F402_0560	TD470K	180-300	39	4,151	27	6,201	7.8
39	7.9	F602_0560	TD470K	180-300	39	4,131	17	9,574	7.9
31	6.2	F402_0700	TD470K	180-300	31	5,195	27	6,201	6.2
31	6.3	F602_0700	TD470K	180-300	31	5,164	17	9,744	6.3
23	4.7	F602_0930	TD470K	180-300	23	6,921	17	9,744	4.7

5.0 HP, 1750 RPM Motor

Continued on next page

471	94	F302_0046	TD570K	180-500	471	590	235	1,197	94	1,197
467	93	F202_0047	TD570K	180-500	467	594	233	1,206	93	1,206
468	94	F402_0047	TD570K	180-500	468	594	233	1,206	94	1,206
394	79	F202_0056	TD570K	180-500	394	705	197	1,429	79	1,429
382	76	F302_0057	TD570K	180-500	382	726	191	1,474	76	1,474
376	75	F402_0058	TD570K	180-500	376	738	188	1,498	75	1,498
305	61	F202_0072	TD570K	180-500	305	910	201	1,419	61	1,419
305	61	F302_0072	TD570K	180-500	305	911	152	1,849	61	1,849
243	49	F202_0090	TD570K	180-500	243	1,144	199	1,423	49	1,423
243	49	F302_0090	TD570K	180-500	243	1,141	121	2,316	49	2,316
244	49	F402_0090	TD570K	180-500	244	1,140	121	2,315	49	2,315
202	40	F202_0110	TD570K	180-500	202	1,372	195	1,434	40	1,434
203	41	F302_0110	TD570K	180-500	203	1,370	101	2,780	41	2,780
202	40	F402_0110	TD570K	180-500	202	1,375	101	2,790	40	2,790
163	33	F302_0135	TD570K	180-500	163	1,700	93	3,058	33	3,058
161	32	F402_0135	TD570K	180-500	161	1,723	80	3,498	32	3,498

1) Speed tolerance at rated load is ±3%. At less than rated load, minimum speed may increase 5%.

2) The ComTrac drive operates at constant horsepower above transition values and at constant torque below transition values. Note shaded area.


Engineering advances may cause slight changes to the information shown.

Housing Styles

F – Round Flange



G – Tapped Holes



Housing Style "F" is available as Hollow (A) or Solid (V) Output.

See page 78 for mounting positions.

Output Shaft Diameter and
Hollow Output (inches)

See Page 43 for other options.

Base Module	Output Shaft	Hollow Output
F102	1.0000	.7500
F202/F203	1.2500	1.0000
F302/F303	1.3750	1.2500
F402/F403	1.6250	1.5000
F602/F603	2.1250	2.0000



"F" Series – MGS Adjustable Speed Drive Selection Data



Speed Range		Part Number	Maximum		Transition ⁽²⁾		Minimum		
Output RPM ⁽¹⁾			RPM	Torque in.lbs.	RPM	Torque in.lbs.	RPM	Torque in.lbs.	
Max.	Min.								
5.0 HP, 1750 RPM Motor Continued									
117	23	F402_0185	TD570K 180-500	117	2,364	59	4,800	23	4,800
117	23	F302_0190	TD570K 180-500	117	2,384	93	3,054	23	3,054
94	19	F402_0230	TD570K 180-500	94	2,948	47	5,984	19	5,984
94	19	F602_0230	TD570K 180-500	94	2,955	47	5,999	19	5,999
93	19	F302_0240	TD570K 180-500	93	2,987	90	3,082	19	3,082
78	16	F402_0280	TD570K 180-500	78	3,554	46	6,201	16	6,201
78	16	F602_0280	TD570K 180-500	78	3,554	39	7,214	16	7,214
62	12	F402_0350	TD570K 180-500	62	4,455	46	6,201	12	6,201
62	12	F602_0350	TD570K 180-500	62	4,471	31	9,075	12	9,075
47	9.3	F402_0470	TD570K 180-500	47	5,961	45	6,201	9.3	6,201
47	9.4	F602_0470	TD570K 180-500	47	5,933	29	9,744	9.4	9,744
39	7.9	F602_0560	TD570K 180-500	39	7,075	29	9,744	7.9	9,744
31	6.3	F602_0700	TD570K 180-500	31	8,844	29	9,744	6.3	9,744

Part No. Explanation


E 2 0 2 A F 0620 TD370K140 - 200 W
 Washdown, when required
 Rated for HP (200 = 2.00)
 Non-gearred TD37 ComTrac Unit, 145TC Input
 Ratio of MGS Unit (0620 = 62.0:1)
 Housing Style – F (Output Flange)
 Hollow Output Style – A
 No. of Gear Reductions
 Generation No.
 Unit No.
 Offset Helical

Selection Procedure:

- Determine the MGS/ComTrac combination according to the Input HP of the application and the Output RPM nearest the required **maximum speed**.
- Verify that the output torque will sufficiently meet the application requirements.
- Complete the Part No. per the example by adding "A" or "V" for the Output Style and the Housing Style letter ("B", "F", or "G") as required. "V" output is only available with the "F" housing style.



"F" Series – MGS® Adjustable Speed Drives Dimensional Data



Drawing for Units

F102AG — F603AG

Part No. Example

Basic Unit with ComTrac

F302AG0620 TD270K140

Table No. 1 "F" Series – Tapped Holes Unit Dimensions (Inches) – "G" Housing Style

Base Module	CD	B	D	F	G	H	H ₁	J ₁	J ₂ *	M	Tolerance	P	T	V	BC	BP	DP
F102	4.02	3.74	9.37	5.91	.79	2.91	6.93	.43		M8	2.756 ^{+.0007/-0.005}	.10	5.71	.26	3.35	3.43	.51
F202/F203	5.16	4.53	11.77	7.13	.87	3.66	8.82	.43		M8	3.740 ^{+.0007/-0.005}	.12	7.09	.31	4.53	4.13	.51
F302/F303	5.89	5.12	13.23	8.07	1.18	4.17	10.06	.55		M10	4.331 ^{+.0007/-0.005}	.14	8.11	.33	5.12	4.72	.63
F402/F403	6.65 ¹⁾	5.71	14.57	8.98	1.18	4.57	11.22	.55		M10	4.331 ^{+.0007/-0.005}	.14	9.06	.33	5.12	5.31	.63
F602/F603	7.72	7.09	17.64	10.63	1.38	5.39	13.11	.87		M10	5.118 ^{+.0008/-0.006}	.14	10.43	.41	6.50	6.54	.63

* F602 and F603 has 8 tapped holes instead of 4 as shown on drawing.

¹⁾ "CD" is 5.20 for a F403 with TD27.

Table No. 2 "F" Series Bore Dimensions (Inches)

Base Module	U	Tolerance	UA	UB	UC	UL	1
F102	.750	^{+.0008/-0.000}	.187	.84	1.38	2.87	^{3/8-16}
F202	1.000	^{+.0008/-0.000}	.250	1.12	1.77	3.62	^{1/2-13}
F302	1.250	^{+.0010/-0.000}	.250	1.37	1.97	4.06	^{1/2-13}
F402/F403	1.500	^{+.0010/-0.000}	.375	1.67	2.17	4.49	^{3/4-10}
F602/F603	2.000	^{+.0012/-0.000}	.500	2.23	2.76	5.63	^{3/4-10}

Table No. 3 "F" Series – Unit Dimensions (Inches)

ComTrac Part No.	NEMA C-Flange	DH	HL	TL	X	Y	Z
TD270K050	56C	4.92	5.67	7.87	2.09	5.55	4.41
TD270K140	143/145TC	4.92	5.67	7.87	2.09	5.55	4.41
TD370K140	143/145TC	4.92	5.91	8.50	2.17	5.67	4.37
TD470K180	182/184TC	6.30	6.81	8.94	2.80	7.20	5.59
TD570K180	182/184TC	7.87	8.31	11.89	3.11	8.11	6.30

1. Removal Bolt — not supplied.

2. Mounting Bolt — must be smaller than removal bolt.

All weights are approximate.

Table No. 4 "F" Series – Unit Dimensions (Inches)


Base Module	TD270K050 ⁽²⁾			Wt. lbs.	TD370K140			Wt. lbs.	TD470K180			Wt. lbs.	TD570K180			Wt. lbs.
	H ₂	I	L		H ₂	I	L		H ₂	I	L		H ₂	I	L	
F102	5.35	10.43	4.25	71	4.88	11.10	4.25	89	—	—	—	—	—	—	—	—
F202	7.24	11.18	5.08	84	6.77	11.85	5.08	102	6.22	11.97	5.08	110	—	—	—	—
F302	8.48	11.77	5.67	100	8.01	12.52	5.67	118	7.46	12.56	5.67	126	6.20	15.20	5.67	155
F402	9.65	12.36	6.38	117	9.17	13.03	6.38	135	8.62	13.15	6.38	143	7.87	15.79	6.38	172
F403	8.19	14.06	7.87	124	—	—	—	—	—	—	—	—	—	—	—	—
F602	11.54	13.85	7.48	198	11.06	14.33	7.68	216	10.51	14.45	7.68	224	9.76	17.09	7.68	253
F603	11.54	15.35	9.17	210	11.06	16.02	9.17	228	—	—	—	—	—	—	—	—

⁽²⁾ Also available for a NEMA 143TC frame motor.



"F" Series – MGS® Adjustable Speed Drives

Dimensional Data



Part No. Example

Basic Unit with ComTrac
F302VF0620 TD270K140

Table No. 1 "F" Series – Round Flange Dimensions (Inches) – "F" Housing Style

Base Module	CD	A	D	F	G	H	H ₁	J	M	Tolerance	N	O	P	Q	T	V
F102	4.02	6.30	9.37	5.12	.79	2.91	6.93	.35	4.331	+.0008/-0.0006	.14	.39	3.80	.16	5.71	1.97
F202/F203	5.16	7.87	11.77	6.50	.87	3.66	8.82	.43	5.118	+.0008/-0.0006	.14	.55	4.53	.16	7.09	2.36
F302/F303	5.89	9.84	13.23	8.46	1.18	4.17	10.06	.55	7.087	+.0008/-0.0006	.16	.59	5.10	.16	8.11	2.76
F402/F403	6.65 ¹⁾	9.84	14.57	8.46	1.18	4.57	11.22	.55	7.087	+.0008/-0.0006	.16	.59	5.49	.16	9.06	3.15
F602/F603	7.72	11.81	17.64	10.43	1.38	5.39	13.11	.55	9.055	+.0012/-0.0008	.16	.67	6.44	.20	10.43	3.94

¹⁾ "CD" is 5.20 for a F403 with TD27.

Table No. 2 "F" Series Shaft Dimensions (Inches)

Base Module	U	Tolerance	UA – Key	UB
F102	1.000	+.0000/-0.0006	1/4 x 1/4 x 1 ⁹ / ₁₆	1.11
F202	1.250	+.0000/-0.0007	1/4 x 1/4 x 1 ¹⁵ / ₁₆	1.36
F302	1.375	+.0000/-0.0007	5/16 x 5/16 x 2 ⁵ / ₁₆	1.51
F402/F403	1.625	+.0000/-0.0007	3/8 x 3/8 x 2 ⁷ / ₈	1.79
F602/F603	2.125	+.0000/-0.0008	1/2 x 1/2 x 3 ⁵ / ₃₂	2.35

Table No. 3 "F" Series – Unit Dimensions (Inches)

ComTrac Part No.	NEMA C-Flange	DH	HL	TL	X	Y	Z
TD270K050	56C	4.92	5.67	7.87	2.09	5.55	4.41
TD270K140	143/145TC	4.92	5.67	7.87	2.09	5.55	4.41
TD370K140	143/145TC	4.92	5.91	8.50	2.17	5.67	4.37
TD470K180	182/184TC	6.30	6.81	8.94	2.80	7.20	5.59
TD570K180	182/184TC	7.87	8.31	11.89	3.11	8.11	6.30

Table No. 4

"F" Series – Unit Dimensions (Inches)

Base Module	TD270K050 ⁽²⁾			Wt. lbs.	TD370K140			Wt. lbs.	TD470K180			Wt. lbs.	TD570K180			Wt. lbs.
	H ₂	I	L		H ₂	I	L		H ₂	I	L		H ₂	I	L	
F102	5.35	11.46	7.24	71	4.88	12.13	7.24	89	—	—	—	—	—	—	—	—
F202	7.24	12.44	8.54	84	6.77	13.11	8.54	102	6.22	13.15	8.62	110	—	—	—	—
F302	8.48	13.11	9.61	100	8.01	13.78	9.61	118	7.46	13.81	9.69	126	6.20	16.45	9.69	155
F402	9.65	13.82	10.59	117	9.17	14.49	10.59	135	8.62	14.53	10.67	143	7.87	17.17	10.67	172
F403	8.19	15.31	12.28	124	—	—	—	—	—	—	—	—	—	—	—	—
F602	11.54	15.03	12.60	198	11.06	15.75	12.60	216	10.51	15.71	12.68	224	9.76	18.39	12.68	253
F603	11.54	15.35	14.29	210	11.06	16.02	14.29	228	—	—	—	—	—	—	—	—

⁽²⁾ Also available for a NEMA 143TC frame motor.

All weights are approximate.

Personalized Mailer Available Free!



The above mailer provides introductory information on industrial products. The back of this one page mailer describes the performance data for ComTrac and MGS products.

Contact your STOBER representative for more information or to request a quantity for your mailing. We will imprint them with your logo and send them to you – free!

* Logo should be in a high resolution tif format for best printing results.



"K" Series – Right Angle Helical/Bevel MGS® Adjustable Speed Drives

Performance Specifications:

- Horsepower ratings – from 1/2 to 5
- Output speeds – available from 569 to .9 RPM
- Speed range – 5:1 to 7:1
- Output torques – up to 99,227 in.lbs.
- NEMA frames – from 56C to 215TC

With the many mounting options available, ComTrac Adjustable Speed Drives and MGS Helical/Bevel Speed Reducers offer consistent, higher input-to-output efficiencies and a configurations for almost any application situation. This added efficiency reduces your costs today through smaller gear drive and motor sizing. Tomorrow, you'll benefit through optimum energy savings.




Table No. 1

"K" Series Output Diameters

Module	Hollow		Shaft		Stainless Steel Bushing Bores																mm				
	inches		mm	inches		mm	inches																		
	Std	SS		Std	SS		(1)	(1)	1	1 3/16	1 1/4	1 3/8	1 7/16	1 1/2	1 5/8	1 11/16	1 3/4	1 7/8	1 15/16	2	2 3/16	2 3/8	2 7/16	2 3/4	40
K102	1	1	25	1	1	25	x	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
K202/K203	1 3/16	1 1/4	30	1 1/4	1 1/4	30	x	x	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
K302/K303	1 3/8	1 1/4 & 1 3/8	30	1 1/4	1 1/4	30	x	x	x	x	x	x	—	—	—	—	—	—	—	—	—	—	—	—	—
K402/K403	1 1/2	—	40	1 3/8	1 3/8	40	x	x	x	x	x	x	—	—	—	—	—	—	—	—	—	—	—	—	x
K513/K514	2	—	50	1 3/4	1 3/4	45	—	—	—	—	x	x	x	x	x	x	x	x	x	x	—	—	—	—	x
K613/K614	2	—	50	1 3/4	1 3/4	50	—	—	—	—	x	x	x	x	x	x	—	x	x	x	x	—	—	—	x
K713/K714	2 3/8	—	60	2 3/8	2 3/8	60	—	—	—	—	—	—	—	—	—	—	—	x	x	x	x	x	—	—	—
K813/K814	2 3/4	—	70	2 7/8	2 7/8	70	—	—	—	—	—	—	—	—	—	—	—	—	x	x	x	x	x	x	—
K913/K914	3 1/4	—	90	3 5/8	—	90	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

⁽¹⁾ Contact STOBER Drives for availability.

⁽²⁾ "K" Series stainless steel shaft are single side ONLY.



"K" Series – MGS Adjustable Speed Drive Selection Data



Speed Range		Part Number	Maximum		Transition (2)		Minimum	
Output RPM (1)	Max.		Min.	RPM	Torque in.lbs.	RPM	Torque in.lbs.	RPM
.50 HP, 1750 RPM Motor Continued on next page								
569	81	K102_0040	TD270K 050-050	569	45	81	258	81
521	74	K202_0044	TD270K 050-050	521	49	74	281	74
409	58	K102_0056	TD270K 050-050	409	63	58	359	58
379	54	K102_0060	TD270K 050-050	379	68	54	387	54
342	49	K102_0066	TD270K 050-050	342	75	49	428	49
340	49	K202_0067	TD270K 050-050	340	75	49	431	49
274	39	K102_0083	TD270K 050-050	274	94	39	535	39
271	39	K202_0084	TD270K 050-050	271	95	39	541	39
246	35	K102_0092	TD270K 050-050	246	104	35	596	35
224	32	K102_0100	TD270K 050-050	224	114	32	653	32
197	28	K102_0115	TD270K 050-050	197	130	28	745	28
180	26	K102_0125	TD270K 050-050	180	142	26	813	26
161	23	K102_0140	TD270K 050-050	161	159	23	910	23
136	19	K102_0165	TD270K 050-050	136	188	23	974	19
135	19	K202_0170	TD270K 050-050	135	190	19	1,086	19
130	19	K102_0175	TD270K 050-050	130	198	20	1,063	19
113	16	K102_0200	TD270K 050-050	113	227	24	974	16
98	14	K102_0230	TD270K 050-050	98	262	23	1,063	14
90	13	K102_0250	TD270K 050-050	90	284	30	851	13
81	12	K102_0280	TD270K 050-050	81	316	24	1,063	12
70	10	K403_0320	TD270K 050-050	70	359	10	2,057	10
70	10	K303_0330	TD270K 050-050	70	362	10	2,074	10
68	10	K202_0340	TD270K 050-050	68	378	18	1,364	10
65	9.3	K102_0350	TD270K 050-050	65	395	25	1,063	9.3
63	9.1	K303_0360	TD270K 050-050	63	397	9.1	2,276	9.1
58	8.3	K303_0390	TD270K 050-050	58	435	8.3	2,489	8.3
56	8.0	K302_0410	TD270K 050-050	56	456	14	1,705	8.0
51	7.2	K303_0450	TD270K 050-050	51	498	7.2	2,851	7.2
49	7.0	K202_0460	TD270K 050-050	49	520	14	1,772	7.0
47	6.7	K303_0490	TD270K 050-050	47	539	6.7	3,089	6.7
45	6.4	K402_0500	TD270K 050-050	45	568	10	2,387	6.4
46	6.6	K403_0490	TD270K 050-050	46	543	6.6	3,109	6.6
42	6.0	K303_0540	TD270K 050-050	42	598	7.0	3,100	6.0
41	5.8	K302_0560	TD270K 050-050	41	627	11	2,345	5.8
35	5.0	K303_0650	TD270K 050-050	35	727	7.5	3,100	5.0
34	4.9	K303_0670	TD270K 050-050	34	742	7.6	3,100	4.9
33	4.7	K402_0690	TD270K 050-050	33	780	7.3	3,283	4.7
32	4.6	K513_0700	TD270K 050-050	32	777	4.6	4,451	4.6
29	4.1	K303_0780	TD270K 050-050	29	870	7.9	3,100	4.1
27	3.8	K514_0850	TD270K 050-050	27	928	3.8	5,316	3.8
27	3.9	K614_0840	TD270K 050-050	27	915	3.9	5,241	3.9
26	3.7	K513_0870	TD270K 050-050	26	968	3.7	5,544	3.7
25	3.6	K303_0900	TD270K 050-050	25	999	8.2	3,100	3.6
24	3.5	K514_0940	TD270K 050-050	24	1,028	3.5	5,886	3.5
25	3.5	K614_0930	TD270K 050-050	25	1,014	3.5	5,803	3.5
24	3.4	K513_0970	TD270K 050-050	24	1,072	3.4	6,138	3.4
21	3.0	K303_1080	TD270K 050-050	21	1,196	8.4	3,100	3.0
21	3.0	K403_1070	TD270K 050-050	21	1,191	4.9	4,872	3.0


1) Speed tolerance at rated load is $\pm 3\%$. At less than rated load, minimum speed may increase 5%.

2) The ComTrac drive operates at constant horsepower above transition values and at constant torque below transition values. Note shaded area.


Engineering advances may cause slight changes to the information shown.

Housing Styles


N – Foot Mounted



F – Round Flange



G – Tapped Holes



These Housing Styles are available as Hollow (A) or Solid (V) Output.

See page 79 for mounting positions.

Output Shaft Diameter and Hollow Output (inches)

See Page 53 for other options.

Base Module	Output Shaft	Hollow Output	Base Module	Output Shaft	Hollow Output
K102	1.000	1.000	K613/K614	1.750	2.000
K202/K203	1.250	1.187	K713/K714	2.375	2.375
K302/K303	1.250	1.375	K813/K814	2.875	2.750
K402/K403	1.375	1.500	K913/K914	3.625	3.250
K513/K514	1.750	2.000			



"K" Series – MGS Adjustable Speed Drive Selection Data



Speed Range		Part Number	Maximum		Transition ⁽²⁾		Minimum	
Output RPM ⁽¹⁾	Max.		RPM	Torque in.lbs.	RPM	Torque in.lbs.	RPM	Torque in.lbs.
.50 HP, 1750 RPM Motor Continued								
20	2.9	K514_1130	TD270K 050-050	20	1,232	2.9	7,054	2.9
20	2.9	K614_1110	TD270K 050-050	20	1,215	2.9	6,955	2.9
20	2.9	K714_1130	TD270K 050-050	20	1,236	2.9	7,079	2.9
18	2.6	K514_1250	TD270K 050-050	18	1,364	2.6	7,810	2.6
18	2.6	K614_1230	TD270K 050-050	18	1,345	2.6	7,700	2.6
18	2.6	K714_1250	TD270K 050-050	18	1,369	2.6	7,837	2.6
17	2.4	K303_1340	TD270K 050-050	17	1,490	8.5	3,100	2.4
17	2.4	K514_1350	TD270K 050-050	17	1,469	2.6	7,972	2.4
17	2.4	K614_1340	TD270K 050-050	17	1,461	2.4	8,366	2.4
17	2.4	K714_1370	TD270K 050-050	17	1,496	2.4	8,566	2.4
15	2.2	K514_1490	TD270K 050-050	15	1,627	2.7	7,972	2.2
15	2.2	K614_1480	TD270K 050-050	15	1,618	2.2	9,263	2.2
15	2.1	K714_1520	TD270K 050-050	15	1,656	2.1	9,484	2.1
14	1.9	K514_1680	TD270K 050-050	14	1,836	2.9	7,972	1.9
14	2.0	K614_1670	TD270K 050-050	14	1,820	2.0	10,421	2.0
13	1.8	K303_1790	TD270K 050-050	13	1,983	8.7	3,048	1.8
13	1.8	K403_1790	TD270K 050-050	13	1,986	5.5	4,737	1.8
13	1.9	K714_1740	TD270K 050-050	13	1,902	1.9	10,891	1.9
12	1.7	K514_1860	TD270K 050-050	12	2,033	3.0	7,972	1.7
12	1.8	K614_1850	TD270K 050-050	12	2,015	1.8	11,537	1.8
12	1.7	K714_1930	TD270K 050-050	12	2,106	1.7	12,058	1.7
11	1.5	K403_2150	TD270K 050-050	11	2,389	7.1	3,752	1.5
10	1.4	K514_2250	TD270K 050-050	10	2,461	3.1	7,972	1.4
10	1.5	K614_2230	TD270K 050-050	10	2,429	1.6	12,844	1.5
10	1.4	K714_2260	TD270K 050-050	10	2,473	1.4	14,158	1.4
9.2	1.3	K614_2460	TD270K 050-050	9.2	2,690	1.7	12,844	1.3
9.1	1.3	K514_2500	TD270K 050-050	9.1	2,725	3.2	7,972	1.3
9.1	1.3	K714_2510	TD270K 050-050	9.1	2,738	1.3	15,675	1.3
8.6	1.2	K614_2660	TD270K 050-050	8.6	2,903	2.0	11,639	1.2
8.4	1.2	K514_2710	TD270K 050-050	8.4	2,959	3.5	7,268	1.2
8.3	1.2	K714_2750	TD270K 050-050	8.3	3,006	1.2	17,212	1.2
7.7	1.1	K614_2940	TD270K 050-050	7.7	3,214	1.8	12,844	1.1
7.6	1.1	K514_3000	TD270K 050-050	7.6	3,276	3.2	7,972	1.1
7.5	1.1	K714_3050	TD270K 050-050	7.5	3,328	1.1	19,056	1.1
6.8	1.0	K614_3330	TD270K 050-050	6.8	3,638	3.0	8,600	1.0
6.7	1.0	K514_3380	TD270K 050-050	6.7	3,685	4.3	6,105	1.0
6.6	0.9	K714_3440	TD270K 050-050	6.6	3,758	1.6	14,803	0.9
6.2	0.9	K614_3690	TD270K 050-050	6.2	4,028	2.7	9,524	0.9
6.1	0.9	K514_3740	TD270K 050-050	6.1	4,080	3.9	6,761	0.9
6.0	0.9	K714_3810	TD270K 050-050	6.0	4,160	1.4	16,394	0.9

Part No. Explanation

K 2 0 2 A F 0230 TD370K140 – 200 W

K 2 0 2 A F 0230 TD370K140 – 200 W
 Housing Style – F (Output Flange)
 Hollow Output Style – A
 No. of Gear Reductions
 Generation No.
 Unit No.
 Right Angle Helical/Bevel

Washdown, when required
 Rated for HP (200 = 2.00)
 Non-gearred TD37 ComTrac Unit, 145TC Input
 Ratio of MGS Unit (0230 = 23.0:1)

Selection Procedure:

- Determine the MGS/ComTrac combination according to the Input HP of the application and the Output RPM nearest the required **maximum speed**.
- Verify that the output torque will sufficiently meet the application requirements.
- Complete the Part No. per the example by adding "A" or "V" for the Output Style and the Housing Style letter ("N", "F", or "G") as required.



"K" Series – MGS Adjustable Speed Drive Selection Data



Speed Range		Part Number	Maximum		Transition (2)		Minimum	
Output RPM (1)	Max.		Min.	RPM	Torque in.lbs.	RPM	Torque in.lbs.	RPM
.75 HP, 1750 RPM Motor Continued on next page								
569	81	K102_0040	TD270K 050-075	569	67	141	258	81
521	74	K202_0044	TD270K 050-075	521	73	129	281	74
409	58	K102_0056	TD270K 050-075	409	93	101	359	58
379	54	K102_0060	TD270K 050-075	379	100	94	387	54
342	49	K102_0066	TD270K 050-075	342	111	85	428	49
340	49	K202_0067	TD270K 050-075	340	112	84	431	49
274	39	K102_0083	TD270K 050-075	274	139	68	535	39
271	39	K202_0084	TD270K 050-075	271	140	67	541	39
246	35	K102_0092	TD270K 050-075	246	155	61	596	35
224	32	K102_0100	TD270K 050-075	224	169	56	653	32
197	28	K102_0115	TD270K 050-075	197	193	49	745	28
180	26	K102_0125	TD270K 050-075	180	211	45	813	26
161	23	K102_0140	TD270K 050-075	161	236	40	910	23
136	19	K102_0165	TD270K 050-075	136	279	38	974	19
135	19	K202_0170	TD270K 050-075	135	282	33	1,086	19
130	19	K102_0175	TD270K 050-075	130	294	35	1,063	19
113	16	K102_0200	TD270K 050-075	113	337	40	974	16
98	14	K102_0230	TD270K 050-075	98	389	37	1,063	14
90	13	K102_0250	TD270K 050-075	90	422	47	851	13
81	12	K102_0280	TD270K 050-075	81	469	37	1,063	12
70	10	K403_0320	TD270K 050-075	70	534	17	2,057	10
70	10	K303_0330	TD270K 050-075	70	538	17	2,074	10
68	10	K202_0340	TD270K 050-075	68	562	29	1,364	10
65	9.3	K102_0350	TD270K 050-075	65	587	38	1,063	9.3
66	9.4	K202_0350	TD270K 050-075	66	578	22	1,772	9.4
63	9.1	K303_0360	TD270K 050-075	63	590	16	2,276	9.1
58	8.3	K303_0390	TD270K 050-075	58	646	14	2,489	8.3
56	8.0	K302_0410	TD270K 050-075	56	677	23	1,705	8.0
51	7.2	K303_0450	TD270K 050-075	51	740	13	2,851	7.2
49	7.0	K202_0460	TD270K 050-075	49	773	22	1,772	7.0
47	6.7	K303_0490	TD270K 050-075	47	801	12	3,089	6.7
45	6.4	K402_0500	TD270K 050-075	45	843	16	2,387	6.4
46	6.6	K403_0490	TD270K 050-075	46	806	12	3,109	6.6
42	6.0	K303_0540	TD270K 050-075	42	888	12	3,100	6.0
41	5.8	K302_0560	TD270K 050-075	41	931	17	2,345	5.8
35	5.0	K303_0650	TD270K 050-075	35	1,079	12	3,100	5.0
34	4.9	K303_0670	TD270K 050-075	34	1,102	12	3,100	4.9
33	4.7	K402_0690	TD270K 050-075	33	1,159	12	3,283	4.7
32	4.6	K513_0700	TD270K 050-075	32	1,155	8.0	4,451	4.6
29	4.1	K303_0780	TD270K 050-075	29	1,292	13	3,100	4.1
27	3.8	K514_0850	TD270K 050-075	27	1,379	6.6	5,316	3.8
27	3.9	K614_0840	TD270K 050-075	27	1,360	6.7	5,241	3.9
26	3.7	K513_0870	TD270K 050-075	26	1,438	6.5	5,544	3.7
25	3.6	K303_0900	TD270K 050-075	25	1,484	13	3,100	3.6
24	3.5	K514_0940	TD270K 050-075	24	1,527	6.0	5,886	3.5
25	3.5	K614_0930	TD270K 050-075	25	1,505	6.1	5,803	3.5
24	3.4	K513_0970	TD270K 050-075	24	1,592	5.8	6,138	3.4
21	3.0	K303_1080	TD270K 050-075	21	1,776	13	3,100	3.0


¹⁾ Speed tolerance at rated load is ±3%. At less than rated load, minimum speed may increase 5%.

²⁾ The ComTrac drive operates at constant horsepower above transition values and at constant torque below transition values. Note shaded area.


Engineering advances may cause slight changes to the information shown.

Housing Styles


N – Foot Mounted



F – Round Flange



G – Tapped Holes



These Housing Styles are available as Hollow (A) or Solid (V) Output.

See page 79 for mounting positions.

Output Shaft Diameter and Hollow Output (inches)

See Page 53 for other options.

Base Module	Output Shaft	Hollow Output	Base Module	Output Shaft	Hollow Output
K102	1.000	1.000	K613/K614	1.750	2.000
K202/K203	1.250	1.187	K713/K714	2.375	2.375
K302/K303	1.250	1.375	K813/K814	2.875	2.750
K402/K403	1.375	1.500	K913/K914	3.625	3.250
K513/K514	1.750	2.000			



"K" Series – MGS Adjustable Speed Drive Selection Data



Speed Range		Part Number	Maximum		Transition ⁽²⁾		Minimum		
Output RPM ⁽¹⁾	Max.		RPM	Torque in.lbs.	RPM	Torque in.lbs.	RPM	Torque in.lbs.	
Max.		Min.							
.75 HP, 1750 RPM Motor Continued									
21	3.0	K403_1070	TD270K 050-075	21	1,769	7.9	4,872	3.0	4,872
20	2.9	K514_1130	TD270K 050-075	20	1,830	5.0	7,054	2.9	7,054
20	2.9	K614_1110	TD270K 050-075	20	1,804	5.1	6,955	2.9	6,955
20	2.9	K714_1130	TD270K 050-075	20	1,836	5.0	7,079	2.9	7,079
18	2.6	K514_1250	TD270K 050-075	18	2,026	4.5	7,810	2.6	7,810
18	2.6	K614_1230	TD270K 050-075	18	1,997	4.6	7,700	2.6	7,700
18	2.6	K714_1250	TD270K 050-075	18	2,033	4.5	7,837	2.6	7,837
17	2.4	K303_1340	TD270K 050-075	17	2,212	13	3,100	2.4	3,100
17	2.4	K403_1340	TD270K 050-075	17	2,214	8.0	4,872	2.4	4,872
17	2.4	K514_1350	TD270K 050-075	17	2,182	4.5	7,972	2.4	7,972
17	2.4	K614_1340	TD270K 050-075	17	2,170	4.2	8,366	2.4	8,366
17	2.4	K714_1370	TD270K 050-075	17	2,222	4.1	8,566	2.4	8,566
15	2.2	K514_1490	TD270K 050-075	15	2,416	4.6	7,972	2.2	7,972
15	2.2	K614_1480	TD270K 050-075	15	2,403	3.8	9,263	2.2	9,263
15	2.1	K714_1520	TD270K 050-075	15	2,460	3.7	9,484	2.1	9,484
14	1.9	K514_1680	TD270K 050-075	14	2,727	4.7	7,972	1.9	7,972
14	2.0	K614_1670	TD270K 050-075	14	2,703	3.4	10,421	2.0	10,421
13	1.8	K303_1790	TD270K 050-075	13	2,945	12	3,048	1.8	3,048
13	1.8	K403_1790	TD270K 050-075	13	2,950	8.3	4,737	1.8	4,737
13	1.9	K714_1740	TD270K 050-075	13	2,825	3.2	10,891	1.9	10,891
12	1.7	K514_1860	TD270K 050-075	12	3,020	4.8	7,972	1.7	7,972
12	1.8	K614_1850	TD270K 050-075	12	2,993	3.1	11,537	1.8	11,537
12	1.7	K714_1930	TD270K 050-075	12	3,128	2.9	12,058	1.7	12,058
11	1.5	K403_2150	TD270K 050-075	11	3,548	10	3,752	1.5	3,752
10	1.4	K514_2250	TD270K 050-075	10	3,655	4.8	7,972	1.4	7,972
10	1.5	K614_2230	TD270K 050-075	10	3,608	2.8	12,844	1.5	12,844
10	1.4	K714_2260	TD270K 050-075	10	3,672	2.5	14,158	1.4	14,158
9.2	1.3	K614_2460	TD270K 050-075	9.2	3,995	2.9	12,844	1.3	12,844
9.1	1.3	K514_2500	TD270K 050-075	9.1	4,047	4.9	7,972	1.3	7,972
9.1	1.3	K714_2510	TD270K 050-075	9.1	4,066	2.2	15,675	1.3	15,675
8.6	1.2	K614_2660	TD270K 050-075	8.6	4,312	3.3	11,639	1.2	11,639
8.4	1.2	K514_2710	TD270K 050-075	8.4	4,394	5.3	7,268	1.2	7,268
8.3	1.2	K714_2750	TD270K 050-075	8.3	4,464	2.0	17,212	1.2	17,212
7.7	1.1	K614_2940	TD270K 050-075	7.7	4,774	3.0	12,844	1.1	12,844
7.6	1.1	K514_3000	TD270K 050-075	7.6	4,865	4.9	7,972	1.1	7,972
7.5	1.1	K714_3050	TD270K 050-075	7.5	4,943	1.8	19,056	1.1	19,056
6.8	1.0	K614_3330	TD270K 050-075	6.8	5,403	4.5	8,600	1.0	8,600
6.7	1.0	K514_3380	TD270K 050-075	6.7	5,473	6.1	6,105	1.0	6,105
6.6	0.9	K714_3440	TD270K 050-075	6.6	5,581	2.6	14,803	0.9	14,803
6.2	0.9	K614_3690	TD270K 050-075	6.2	5,982	4.1	9,524	0.9	9,524
6.1	0.9	K514_3740	TD270K 050-075	6.1	6,059	5.5	6,761	0.9	6,761
6.0	0.9	K714_3810	TD270K 050-075	6.0	6,178	2.3	16,394	0.9	16,394

Part No. Explanation

K 2 0 2 A F 0230 TD370K140 – 200 W

Washdown, when required
 Rated for HP (200 = 2.00)
 Non-gearred TD37 ComTrac Unit, 145TC Input
 Ratio of MGS Unit (0230 = 23.0:1)
 Housing Style – F (Output Flange)
 Hollow Output Style – A
 No. of Gear Reductions
 Generation No.
 Unit No.
 Right Angle Helical/Bevel

Selection Procedure:

- Determine the MGS/ComTrac combination according to the Input HP of the application and the Output RPM nearest the required **maximum speed**.
- Verify that the output torque will sufficiently meet the application requirements.
- Complete the Part No. per the example by adding "A" or "V" for the Output Style and the Housing Style letter ("N", "F", or "G") as required.



"K" Series – MGS Adjustable Speed Drive Selection Data



Speed Range		Part Number	Maximum		Transition (2)		Minimum	
Output RPM (1)			RPM	Torque in.lbs.	RPM	Torque in.lbs.	RPM	Torque in.lbs.
Max.	Min.							

1.0 HP, 1750 RPM Motor

Continued on next page

569	81	K102_0040	TD270K	140-100	569	91	205	258	81	258
521	74	K202_0044	TD270K	140-100	521	99	188	281	74	281
409	58	K102_0056	TD270K	140-100	409	127	147	359	58	359
379	54	K102_0060	TD270K	140-100	379	137	137	387	54	387
342	49	K102_0066	TD270K	140-100	342	151	123	428	49	428
340	49	K202_0067	TD270K	140-100	340	152	123	431	49	431
274	39	K102_0083	TD270K	140-100	274	189	99	535	39	535
271	39	K202_0084	TD270K	140-100	271	191	98	541	39	541
246	35	K102_0092	TD270K	140-100	246	211	89	596	35	596
224	32	K102_0100	TD270K	140-100	224	231	81	653	32	653
197	28	K102_0115	TD270K	140-100	197	264	71	745	28	745
180	26	K102_0125	TD270K	140-100	180	288	65	813	26	813
161	23	K102_0140	TD270K	140-100	161	322	58	910	23	910
136	19	K102_0165	TD270K	140-100	136	381	55	974	19	974
135	19	K202_0170	TD270K	140-100	135	384	49	1,086	19	1,086
130	19	K102_0175	TD270K	140-100	130	400	50	1,063	19	1,063
113	16	K102_0200	TD270K	140-100	113	459	56	974	16	974
112	16	K202_0200	TD270K	140-100	112	463	40	1,310	16	1,310
98	14	K102_0230	TD270K	140-100	98	530	51	1,063	14	1,063
98	14	K202_0230	TD270K	140-100	98	528	35	1,494	14	1,494
90	13	K102_0250	TD270K	140-100	90	575	64	851	13	851
91	13	K202_0250	TD270K	140-100	91	573	33	1,619	13	1,619
81	12	K102_0280	TD270K	140-100	81	639	51	1,063	12	1,063
81	12	K202_0280	TD270K	140-100	81	637	30	1,772	12	1,772
70	10	K403_0320	TD270K	140-100	70	727	25	2,057	10	2,057
70	10	K303_0330	TD270K	140-100	70	733	25	2,074	10	2,074
68	10	K202_0340	TD270K	140-100	68	766	40	1,364	10	1,364
68	10	K302_0340	TD270K	140-100	68	766	24	2,166	10	2,166
65	9.3	K102_0350	TD270K	140-100	65	800	51	1,063	9.3	1,063
66	9.4	K202_0350	TD270K	140-100	66	787	30	1,772	9.4	1,772
63	9.1	K303_0360	TD270K	140-100	63	805	23	2,276	9.1	2,276
58	8.3	K303_0390	TD270K	140-100	58	880	21	2,489	8.3	2,489
56	8.0	K302_0410	TD270K	140-100	56	923	32	1,705	8.0	1,705
56	8.0	K402_0410	TD270K	140-100	56	923	20	2,611	8.0	2,611
51	7.2	K303_0450	TD270K	140-100	51	1,008	18	2,851	7.2	2,851
49	7.0	K202_0460	TD270K	140-100	49	1,053	31	1,772	7.0	1,772
49	7.0	K302_0460	TD270K	140-100	49	1,053	18	2,979	7.0	2,979
47	6.7	K303_0490	TD270K	140-100	47	1,092	17	3,089	6.7	3,089
45	6.4	K402_0500	TD270K	140-100	45	1,149	23	2,387	6.4	2,387
46	6.6	K403_0490	TD270K	140-100	46	1,099	17	3,109	6.6	3,109
42	6.0	K303_0540	TD270K	140-100	42	1,210	17	3,100	6.0	3,100
41	5.8	K302_0560	TD270K	140-100	41	1,269	23	2,345	5.8	2,345
41	5.8	K402_0560	TD270K	140-100	41	1,269	15	3,590	5.8	3,590
35	5.0	K303_0650	TD270K	140-100	35	1,471	17	3,100	5.0	3,100
34	4.9	K303_0670	TD270K	140-100	34	1,502	17	3,100	4.9	3,100
33	4.7	K402_0690	TD270K	140-100	33	1,580	17	3,283	4.7	3,283
32	4.6	K513_0700	TD270K	140-100	32	1,574	12	4,451	4.6	4,451
29	4.1	K303_0780	TD270K	140-100	29	1,761	17	3,100	4.1	3,100
29	4.2	K403_0780	TD270K	140-100	29	1,754	11	4,872	4.2	4,872
27	3.8	K514_0850	TD270K	140-100	27	1,880	10	5,316	3.8	5,316
27	3.9	K614_0840	TD270K	140-100	27	1,854	10	5,241	3.9	5,241


1) Speed tolerance at rated load is $\pm 3\%$. At less than rated load, minimum speed may increase 5%.

2) The ComTrac drive operates at constant horsepower above transition values and at constant torque below transition values. Note shaded area.


Engineering advances may cause slight changes to the information shown.

Housing Styles


N – Foot Mounted



F – Round Flange



G – Tapped Holes



These Housing Styles are available as Hollow (A) or Solid (V) Output.

See page 79 for mounting positions.

Output Shaft Diameter and Hollow Output (inches)

See Page 53 for other options.

Base Module	Output Shaft	Hollow Output	Base Module	Output Shaft	Hollow Output
K102	1.000	1.000	K613/K614	1.750	2.000
K202/K203	1.250	1.187	K713/K714	2.375	2.375
K302/K303	1.250	1.375	K813/K814	2.875	2.750
K402/K403	1.375	1.500	K913/K914	3.625	3.250
K513/K514	1.750	2.000			



"K" Series – MGS Adjustable Speed Drive Selection Data



Speed Range		Part Number	Maximum		Transition ⁽²⁾		Minimum		
Output RPM ⁽¹⁾	Max.		RPM	Torque in.lbs.	RPM	Torque in.lbs.	RPM	Torque in.lbs.	
1.0 HP, 1750 RPM Motor		Continued							
26	3.7	K513_0870	TD270K 140-100	26	1,960	9.4	5,544	3.7	5,544
25	3.6	K303_0900	TD270K 140-100	25	2,023	17	3,100	3.6	3,100
25	3.6	K403_0900	TD270K 140-100	25	2,023	11	4,872	3.6	4,872
24	3.5	K514_0940	TD270K 140-100	24	2,081	8.7	5,886	3.5	5,886
25	3.5	K614_0930	TD270K 140-100	25	2,052	8.8	5,803	3.5	5,803
24	3.4	K513_0970	TD270K 140-100	24	2,171	8.5	6,138	3.4	6,138
21	3.0	K303_1080	TD270K 140-100	21	2,421	17	3,100	3.0	3,100
21	3.0	K403_1070	TD270K 140-100	21	2,412	11	4,872	3.0	4,872
20	2.9	K514_1130	TD270K 140-100	20	2,494	7.3	7,054	2.9	7,054
20	2.9	K614_1110	TD270K 140-100	20	2,460	7.4	6,955	2.9	6,955
20	2.9	K714_1130	TD270K 140-100	20	2,503	7.2	7,079	2.9	7,079
18	2.6	K514_1250	TD270K 140-100	18	2,762	6.6	7,810	2.6	7,810
18	2.6	K614_1230	TD270K 140-100	18	2,723	6.7	7,700	2.6	7,700
18	2.6	K714_1250	TD270K 140-100	18	2,772	6.5	7,837	2.6	7,837
17	2.4	K303_1340	TD270K 140-100	17	3,016	17	3,100	2.4	3,100
17	2.4	K403_1340	TD270K 140-100	17	3,019	11	4,872	2.4	4,872
17	2.4	K514_1350	TD270K 140-100	17	2,975	6.5	7,972	2.4	7,972
17	2.4	K614_1340	TD270K 140-100	17	2,959	6.1	8,366	2.4	8,366
17	2.4	K714_1370	TD270K 140-100	17	3,029	6.0	8,566	2.4	8,566
15	2.2	K514_1490	TD270K 140-100	15	3,293	6.5	7,972	2.2	7,972
15	2.2	K614_1480	TD270K 140-100	15	3,276	5.5	9,263	2.2	9,263
15	2.1	K714_1520	TD270K 140-100	15	3,354	5.4	9,484	2.1	9,484
14	1.9	K514_1680	TD270K 140-100	14	3,718	6.6	7,972	1.9	7,972
14	2.0	K614_1670	TD270K 140-100	14	3,685	4.9	10,421	2.0	10,421
13	1.8	K403_1790	TD270K 140-100	13	4,022	11	4,737	1.8	4,737
13	1.9	K714_1740	TD270K 140-100	13	3,851	4.7	10,891	1.9	10,891
12	1.7	K514_1860	TD270K 140-100	12	4,117	6.6	7,972	1.7	7,972
12	1.8	K614_1850	TD270K 140-100	12	4,080	4.4	11,537	1.8	11,537
12	1.7	K714_1930	TD270K 140-100	12	4,264	4.3	12,058	1.7	12,058
10	1.4	K514_2250	TD270K 140-100	10	4,983	6.6	7,972	1.4	7,972
10	1.5	K614_2230	TD270K 140-100	10	4,919	4.0	12,844	1.5	12,844
10	1.4	K714_2260	TD270K 140-100	10	5,007	3.6	14,158	1.4	14,158
9.2	1.3	K614_2460	TD270K 140-100	9.2	5,446	4.1	12,844	1.3	12,844
9.1	1.3	K514_2500	TD270K 140-100	9.1	5,517	6.6	7,972	1.3	7,972
9.1	1.3	K714_2510	TD270K 140-100	9.1	5,543	3.3	15,675	1.3	15,675
8.6	1.2	K614_2660	TD270K 140-100	8.6	5,879	4.5	11,639	1.2	11,639
8.4	1.2	K514_2710	TD270K 140-100	8.4	5,991	7.1	7,268	1.2	7,268
8.3	1.2	K714_2750	TD270K 140-100	8.3	6,087	3.0	17,212	1.2	17,212
7.7	1.1	K614_2940	TD270K 140-100	7.7	6,509	4.1	12,844	1.1	12,844
7.6	1.1	K514_3000	TD270K 140-100	7.6	6,633	6.5	7,972	1.1	7,972
7.5	1.1	K714_3050	TD270K 140-100	7.5	6,739	2.7	19,056	1.1	19,056
6.8	1.0	K614_3330	TD270K 140-100	6.8	7,367	6.0	8,600	1.0	8,600
6.6	0.9	K714_3440	TD270K 140-100	6.6	7,608	3.6	14,803	0.9	14,803
6.2	0.9	K614_3690	TD270K 140-100	6.2	8,156	5.4	9,524	0.9	9,524
6.0	0.9	K714_3810	TD270K 140-100	6.0	8,423	3.2	16,394	0.9	16,394

Part No. Explanation

K 2 0 2 A F 0230 TD370K140 – 200 W
 Washdown, when required
 Rated for HP (200 = 2.00)
 Non-gearred TD37 ComTrac Unit, 145TC Input
 Ratio of MGS Unit (0230 = 23.0:1)
 Housing Style – F (Output Flange)
 Hollow Output Style – A
 No. of Gear Reductions
 Generation No.
 Unit No.
 Right Angle Helical/Bevel

Selection Procedure:

- Determine the MGS/ComTrac combination according to the Input HP of the application and the Output RPM nearest the required **maximum speed**.
- Verify that the output torque will sufficiently meet the application requirements.
- Complete the Part No. per the example by adding "A" or "V" for the Output Style and the Housing Style letter ("N", "F", or "G") as required.



"K" Series – MGS Adjustable Speed Drive Selection Data



Speed Range		Part Number	Maximum		Transition (2)		Minimum	
Output RPM (1)	Max.		Min.	RPM	Torque in.lbs.	RPM	Torque in.lbs.	RPM
1.50 HP, 1750 RPM Motor Continued on next page								
547	109	K102_0040	TD370K 140-150	547	141	209	378	109
501	100	K202_0044	TD370K 140-150	501	154	192	412	100
423	85	K202_0052	TD370K 140-150	423	182	162	489	85
393	79	K102_0056	TD370K 140-150	393	196	150	526	79
365	73	K102_0060	TD370K 140-150	365	211	139	567	73
329	66	K102_0066	TD370K 140-150	329	234	126	628	66
327	65	K202_0067	TD370K 140-150	327	235	125	632	65
307	61	K202_0071	TD370K 140-150	307	250	117	673	61
263	53	K102_0083	TD370K 140-150	263	292	101	785	53
261	52	K202_0084	TD370K 140-150	261	295	100	794	52
237	47	K102_0092	TD370K 140-150	237	325	90	874	47
236	47	K302_0093	TD370K 140-150	236	326	90	876	47
216	43	K102_0100	TD370K 140-150	216	357	86	920	43
217	43	K202_0100	TD370K 140-150	217	354	83	952	43
189	38	K102_0115	TD370K 140-150	189	407	87	916	38
189	38	K202_0115	TD370K 140-150	189	406	72	1,091	38
173	35	K102_0125	TD370K 140-150	173	444	88	914	35
172	34	K202_0125	TD370K 140-150	172	447	66	1,201	34
155	31	K102_0140	TD370K 140-150	155	497	89	911	31
158	32	K202_0140	TD370K 140-150	158	487	60	1,309	32
130	26	K202_0170	TD370K 140-150	130	593	50	1,593	26
125	25	K102_0175	TD370K 140-150	125	618	88	914	25
125	25	K202_0175	TD370K 140-150	125	615	48	1,651	25
108	22	K202_0200	TD370K 140-150	108	715	45	1,772	22
94	19	K202_0230	TD370K 140-150	94	815	45	1,772	19
94	19	K302_0230	TD370K 140-150	94	819	36	2,201	19
87	17	K202_0250	TD370K 140-150	87	884	46	1,772	17
87	17	K302_0250	TD370K 140-150	87	889	33	2,387	17
78	16	K202_0280	TD370K 140-150	78	983	46	1,772	16
78	16	K302_0280	TD370K 140-150	78	981	30	2,635	16
68	14	K403_0320	TD370K 140-150	68	1,123	26	3,017	14
67	13	K303_0330	TD370K 140-150	67	1,132	26	3,041	13
65	13	K302_0340	TD370K 140-150	65	1,183	37	2,217	13
65	13	K402_0340	TD370K 140-150	65	1,185	25	3,183	13
63	13	K202_0350	TD370K 140-150	63	1,216	45	1,772	13
63	13	K302_0350	TD370K 140-150	63	1,222	26	3,100	13
61	12	K303_0360	TD370K 140-150	61	1,242	25	3,100	12
56	11	K303_0390	TD370K 140-150	56	1,359	25	3,100	11
54	11	K402_0410	TD370K 140-150	54	1,425	30	2,729	11
50	10	K513_0440	TD370K 140-150	50	1,508	19	4,052	10
49	10	K303_0450	TD370K 140-150	49	1,557	26	3,100	10
49	10	K403_0450	TD370K 140-150	49	1,544	19	4,149	10
47	9.5	K302_0460	TD370K 140-150	47	1,626	27	3,048	9.5
47	9.4	K402_0460	TD370K 140-150	47	1,629	18	4,377	9.4
45	9.1	K513_0480	TD370K 140-150	45	1,670	17	4,486	9.1
45	9.0	K303_0490	TD370K 140-150	45	1,686	26	3,100	9.0
45	8.9	K403_0490	TD370K 140-150	45	1,697	17	4,559	8.9
41	8.1	K303_0540	TD370K 140-150	41	1,868	26	3,100	8.1


1) Speed tolerance at rated load is ±3%. At less than rated load, minimum speed may increase 5%.

2) The ComTrac drive operates at constant horsepower above transition values and at constant torque below transition values. Note shaded area.


Engineering advances may cause slight changes to the information shown.

Housing Styles


N – Foot Mounted



F – Round Flange



G – Tapped Holes



These Housing Styles are available as Hollow (A) or Solid (V) Output.

See page 79 for mounting positions.

Output Shaft Diameter and Hollow Output (inches)

See Page 53 for other options.

Base Module	Output Shaft	Hollow Output	Base Module	Output Shaft	Hollow Output
K102	1.000	1.000	K613/K614	1.750	2.000
K202/K203	1.250	1.187	K713/K714	2.375	2.375
K302/K303	1.250	1.375	K813/K814	2.875	2.750
K402/K403	1.375	1.500	K913/K914	3.625	3.250
K513/K514	1.750	2.000			



"K" Series – MGS Adjustable Speed Drive Selection Data



Speed Range		Part Number	Maximum		Transition ⁽²⁾		Minimum	
Output RPM ⁽¹⁾	Max.		RPM	Torque in.lbs.	RPM	Torque in.lbs.	RPM	Torque in.lbs.
1.50 HP, 1750 RPM Motor		Continued on next page						
41	8.1	K403_0540	TD370K 140-150	41	1,862	16	4,872	8.1
39	7.9	K402_0560	TD370K 140-150	39	1,960	22	3,752	7.9
38	7.5	K513_0580	TD370K 140-150	38	2,021	14	5,430	7.5
33	6.7	K303_0650	TD370K 140-150	33	2,271	25	3,100	6.7
33	6.7	K403_0650	TD370K 140-150	33	2,271	16	4,872	6.7
34	6.9	K613_0640	TD370K 140-150	34	2,209	13	5,935	6.9
33	6.5	K303_0670	TD370K 140-150	33	2,318	25	3,100	6.5
33	6.5	K403_0670	TD370K 140-150	33	2,333	16	4,872	6.5
32	6.4	K613_0690	TD370K 140-150	32	2,384	12	6,406	6.4
31	6.2	K513_0700	TD370K 140-150	31	2,430	12	6,528	6.2
29	5.7	K613_0760	TD370K 140-150	29	2,640	11	7,092	5.7
28	5.6	K303_0780	TD370K 140-150	28	2,719	25	3,100	5.6
28	5.6	K403_0780	TD370K 140-150	28	2,708	16	4,872	5.6
28	5.6	K513_0780	TD370K 140-150	28	2,690	11	7,228	5.6
26	5.1	K514_0850	TD370K 140-150	26	2,902	10	7,797	5.1
26	5.2	K614_0840	TD370K 140-150	26	2,861	10	7,687	5.2
25	5.0	K513_0870	TD370K 140-150	25	3,027	13	6,105	5.0
25	5.1	K613_0860	TD370K 140-150	25	2,988	10	8,028	5.1
24	4.9	K403_0900	TD370K 140-150	24	3,123	16	4,872	4.9
24	4.7	K614_0930	TD370K 140-150	24	3,168	9.0	8,511	4.7
23	4.5	K513_0970	TD370K 140-150	23	3,351	12	6,761	4.5
23	4.6	K514_0940	TD370K 140-150	23	3,213	10	7,972	4.6
23	4.6	K613_0950	TD370K 140-150	23	3,308	8.8	8,888	4.6
20	4.1	K403_1070	TD370K 140-150	20	3,723	16	4,872	4.1
20	3.9	K614_1110	TD370K 140-150	20	3,797	7.5	10,201	3.9
19	3.9	K514_1130	TD370K 140-150	19	3,851	10	7,972	3.9
18	3.5	K514_1250	TD370K 140-150	18	4,263	10	7,972	3.5
18	3.6	K614_1230	TD370K 140-150	18	4,204	6.8	11,294	3.6
17	3.5	K714_1250	TD370K 140-150	17	4,279	6.7	11,495	3.5
16	3.3	K403_1340	TD370K 140-150	16	4,660	16	4,872	3.3
16	3.3	K514_1350	TD370K 140-150	16	4,592	10	7,972	3.3
16	3.3	K614_1340	TD370K 140-150	16	4,567	6.2	12,270	3.3
16	3.2	K714_1370	TD370K 140-150	16	4,676	6.1	12,564	3.2
15	2.9	K514_1490	TD370K 140-150	15	5,084	10	7,972	2.9
15	3.0	K614_1480	TD370K 140-150	15	5,057	6.0	12,844	3.0
14	2.9	K714_1520	TD370K 140-150	14	5,177	5.5	13,910	2.9
13	2.6	K514_1680	TD370K 140-150	13	5,740	10	7,972	2.6
13	2.6	K614_1670	TD370K 140-150	13	5,689	6.1	12,844	2.6
13	2.5	K714_1740	TD370K 140-150	13	5,945	4.8	15,973	2.5
12	2.3	K514_1860	TD370K 140-150	12	6,355	10	7,972	2.3
12	2.4	K614_1850	TD370K 140-150	12	6,299	6.1	12,844	2.4
11	2.3	K714_1930	TD370K 140-150	11	6,582	4.3	17,684	2.3
10	2.0	K614_2230	TD370K 140-150	10	7,594	6.1	12,844	2.0
10	1.9	K514_2250	TD370K 140-150	10	7,693	9.4	7,972	1.9
10	1.9	K714_2260	TD370K 140-150	10	7,729	3.7	20,765	1.9
8.9	1.8	K614_2460	TD370K 140-150	9	8,407	6.1	12,844	1.8
8.7	1.7	K714_2510	TD370K 140-150	9	8,557	3.6	21,259	1.7
8.2	1.6	K614_2660	TD370K 140-150	8	9,075	6.6	11,639	1.6
								11,639

Part No. Explanation

K 2 0 2 A F 0230 TD370K140 – 200 W

Washdown, when required
 Rated for HP (200 = 2.00)
 Non-gearred TD37 ComTrac Unit, 145TC Input
 Ratio of MGS Unit (0230 = 23.0:1)
 Housing Style – F (Output Flange)
 Hollow Output Style – A
 No. of Gear Reductions
 Generation No.
 Unit No.
 Right Angle Helical/Bevel

Selection Procedure:

- Determine the MGS/ComTrac combination according to the Input HP of the application and the Output RPM nearest the required **maximum speed**.
- Verify that the output torque will sufficiently meet the application requirements.
- Complete the Part No. per the example by adding "A" or "V" for the Output Style and the Housing Style letter ("N", "F", or "G") as required.



"K" Series – MGS Adjustable Speed Drive Selection Data



Speed Range		Part Number		Maximum		Transition (2)		Minimum	
Output RPM (1)	Max.			Min.	RPM	Torque in.lbs.	RPM	Torque in.lbs.	RPM
1.50 HP, 1750 RPM Motor					Continued				
7.9	1.6	K714_2750	TD370K	140-150	8	9,396	4.1	19,244	1.6
7.4	1.5	K614_2940	TD370K	140-150	7	10,048	6.0	12,844	1.5
7.2	1.4	K714_3050	TD370K	140-150	7	10,403	3.7	21,259	1.4
6.4	1.3	K714_3440	TD370K	140-150	6	11,745	5.2	14,803	1.3
5.7	1.1	K714_3810	TD370K	140-150	6	13,004	4.7	16,394	1.1

2.0 HP, 1750 RPM Motor					Continued on next page				
547	109	K102_0040	TD370K	140-200	547	192	292	378	109
501	100	K202_0044	TD370K	140-200	501	210	267	412	100
423	85	K202_0052	TD370K	140-200	423	249	225	489	85
393	79	K102_0056	TD370K	140-200	393	267	209	526	79
365	73	K102_0060	TD370K	140-200	365	288	194	567	73
329	66	K102_0066	TD370K	140-200	329	319	176	628	66
327	65	K202_0067	TD370K	140-200	327	321	174	632	65
307	61	K202_0071	TD370K	140-200	307	342	164	673	61
263	53	K102_0083	TD370K	140-200	263	399	141	781	53
261	52	K202_0084	TD370K	140-200	261	403	139	794	52
237	47	K102_0092	TD370K	140-200	237	444	142	779	47
238	48	K202_0092	TD370K	140-200	238	441	127	869	48
236	47	K302_0093	TD370K	140-200	236	445	126	876	47
216	43	K102_0100	TD370K	140-200	216	487	141	781	43
217	43	K202_0100	TD370K	140-200	217	484	116	952	43
189	38	K102_0115	TD370K	140-200	189	555	139	784	38
189	38	K202_0115	TD370K	140-200	189	554	101	1,091	38
173	35	K102_0125	TD370K	140-200	173	606	138	787	35
172	34	K202_0125	TD370K	140-200	172	610	92	1,201	34
155	31	K102_0140	TD370K	140-200	155	678	135	792	31
158	32	K202_0140	TD370K	140-200	158	665	84	1,309	32
130	26	K202_0170	TD370K	140-200	130	810	69	1,593	26
129	26	K302_0170	TD370K	140-200	129	813	69	1,601	26
125	25	K202_0175	TD370K	140-200	125	839	67	1,651	25
126	25	K302_0175	TD370K	140-200	126	830	67	1,634	25
108	22	K202_0200	TD370K	140-200	108	976	62	1,772	22
108	22	K302_0200	TD370K	140-200	108	974	58	1,917	22
94	19	K202_0230	TD370K	140-200	94	1,113	62	1,772	19
94	19	K302_0230	TD370K	140-200	94	1,119	50	2,201	19
87	17	K202_0250	TD370K	140-200	87	1,207	62	1,772	17
87	17	K302_0250	TD370K	140-200	87	1,213	46	2,387	17
78	16	K202_0280	TD370K	140-200	78	1,342	61	1,772	16
78	16	K302_0280	TD370K	140-200	78	1,339	42	2,635	16
68	14	K403_0320	TD370K	140-200	68	1,533	36	3,017	14
67	13	K303_0330	TD370K	140-200	67	1,545	36	3,041	13
65	13	K302_0340	TD370K	140-200	65	1,614	49	2,217	13
65	13	K402_0340	TD370K	140-200	65	1,617	35	3,183	13
63	13	K202_0350	TD370K	140-200	63	1,659	60	1,772	13
63	13	K302_0350	TD370K	140-200	63	1,668	36	3,100	13


1) Speed tolerance at rated load is ±3%. At less than rated load, minimum speed may increase 5%.

2) The ComTrac drive operates at constant horsepower above transition values and at constant torque below transition values. Note shaded area.


Engineering advances may cause slight changes to the information shown.

Housing Styles


N – Foot Mounted



F – Round Flange



G – Tapped Holes



These Housing Styles are available as Hollow (A) or Solid (V) Output.

See page 79 for mounting positions.

Output Shaft Diameter and Hollow Output (inches)

See Page 53 for other options.

Base Module	Output Shaft	Hollow Output	Base Module	Output Shaft	Hollow Output
K102	1.000	1.000	K613/K614	1.750	2.000
K202/K203	1.250	1.187	K713/K714	2.375	2.375
K302/K303	1.250	1.375	K813/K814	2.875	2.750
K402/K403	1.375	1.500	K913/K914	3.625	3.250
K513/K514	1.750	2.000			




"K" Series – MGS Adjustable Speed Drive Selection Data



Speed Range		Part Number	Maximum		Transition ⁽²⁾		Minimum		
Output RPM ⁽¹⁾	Max.		RPM	Torque in.lbs.	RPM	Torque in.lbs.	RPM	Torque in.lbs.	
2.0 HP, 1750 RPM Motor		Continued on next page							
63	13	K402_0350	TD370K 140-200	63	1,669	34	3,285	13	3,285
61	12	K303_0360	TD370K 140-200	61	1,696	35	3,100	12	3,100
61	12	K403_0360	TD370K 140-200	61	1,691	33	3,327	12	3,327
56	11	K303_0390	TD370K 140-200	56	1,855	35	3,100	11	3,100
56	11	K403_0390	TD370K 140-200	56	1,848	30	3,637	11	3,637
54	11	K402_0410	TD370K 140-200	54	1,945	40	2,729	11	2,729
50	10	K513_0440	TD370K 140-200	50	2,059	27	4,052	10	4,052
49	10	K303_0450	TD370K 140-200	49	2,125	35	3,100	10	3,100
49	10	K403_0450	TD370K 140-200	49	2,108	26	4,149	10	4,149
47	9.5	K302_0460	TD370K 140-200	47	2,220	36	3,048	9.5	3,048
47	9.4	K402_0460	TD370K 140-200	47	2,224	25	4,377	9.4	4,377
45	9.1	K513_0480	TD370K 140-200	45	2,279	24	4,486	9.1	4,486
45	9.0	K303_0490	TD370K 140-200	45	2,302	35	3,100	9.0	3,100
45	8.9	K403_0490	TD370K 140-200	45	2,316	24	4,559	8.9	4,559
41	8.1	K303_0540	TD370K 140-200	41	2,550	34	3,100	8.1	3,100
41	8.1	K403_0540	TD370K 140-200	41	2,541	22	4,872	8.1	4,872
39	7.9	K402_0560	TD370K 140-200	39	2,675	29	3,752	7.9	3,752
38	7.5	K513_0580	TD370K 140-200	38	2,759	20	5,430	7.5	5,430
33	6.7	K303_0650	TD370K 140-200	33	3,100	33	3,100	6.7	3,100
33	6.7	K403_0650	TD370K 140-200	33	3,100	22	4,872	6.7	4,872
34	6.8	K513_0650	TD370K 140-200	34	3,055	18	6,012	6.8	6,012
34	6.9	K613_0640	TD370K 140-200	34	3,015	18	5,935	6.9	5,935
33	6.5	K403_0670	TD370K 140-200	33	3,185	22	4,872	6.5	4,872
32	6.4	K613_0690	TD370K 140-200	32	3,255	17	6,406	6.4	6,406
31	6.2	K513_0700	TD370K 140-200	31	3,317	17	6,528	6.2	6,528
29	5.7	K613_0760	TD370K 140-200	29	3,604	15	7,092	5.7	7,092
28	5.6	K403_0780	TD370K 140-200	28	3,696	22	4,872	5.6	4,872
28	5.6	K513_0780	TD370K 140-200	28	3,672	15	7,228	5.6	7,228
26	5.1	K514_0850	TD370K 140-200	26	3,961	14	7,797	5.1	7,797
26	5.2	K614_0840	TD370K 140-200	26	3,906	14	7,687	5.2	7,687
25	5.0	K513_0870	TD370K 140-200	25	4,131	18	6,105	5.0	6,105
25	5.1	K613_0860	TD370K 140-200	25	4,079	14	8,028	5.1	8,028
24	4.9	K403_0900	TD370K 140-200	24	4,262	22	4,872	4.9	4,872
24	4.7	K614_0930	TD370K 140-200	24	4,324	13	8,511	4.7	8,511
23	4.5	K513_0970	TD370K 140-200	23	4,574	16	6,761	4.5	6,761
23	4.6	K514_0940	TD370K 140-200	23	4,386	13	7,972	4.6	7,972
23	4.6	K613_0950	TD370K 140-200	23	4,516	12	8,888	4.6	8,888
20	3.9	K614_1110	TD370K 140-200	20	5,183	10	10,201	3.9	10,201
19	3.9	K514_1130	TD370K 140-200	19	5,256	13	7,972	3.9	7,972
19	3.9	K714_1130	TD370K 140-200	19	5,275	10	10,383	3.9	10,383
18	3.5	K514_1250	TD370K 140-200	18	5,820	13	7,972	3.5	7,972
18	3.6	K614_1230	TD370K 140-200	18	5,738	9	11,294	3.6	11,294
17	3.5	K714_1250	TD370K 140-200	17	5,840	9	11,495	3.5	11,495

Part No. Explanation



Selection Procedure:

- Determine the MGS/ComTrac combination according to the Input HP of the application and the Output RPM nearest the required **maximum speed**.
- Verify that the output torque will sufficiently meet the application requirements.
- Complete the Part No. per the example by adding "A" or "V" for the Output Style and the Housing Style letter ("N", "F", or "G") as required.



"K" Series – MGS Adjustable Speed Drive Selection Data



Speed Range		Part Number	Maximum		Transition (2)		Minimum	
Output RPM (1)			RPM	Torque in.lbs.	RPM	Torque in.lbs.	RPM	Torque in.lbs.
Max.	Min.							

2.0 HP, 1750 RPM Motor

Continued

16	3.3	K514_1350	TD370K	140-200	16	6,269	13	7,972	3.3	7,972
16	3.3	K614_1340	TD370K	140-200	16	6,234	9	12,270	3.3	12,270
16	3.2	K714_1370	TD370K	140-200	16	6,383	9	12,564	3.2	12,564
15	2.9	K514_1490	TD370K	140-200	15	6,940	13	7,972	2.9	7,972
15	3.0	K614_1480	TD370K	140-200	15	6,902	8	12,844	3.0	12,844
14	2.9	K714_1520	TD370K	140-200	14	7,067	8	13,910	2.9	13,910
13	2.6	K514_1680	TD370K	140-200	13	7,836	13	7,972	2.6	7,972
13	2.6	K614_1670	TD370K	140-200	13	7,765	8	12,844	2.6	12,844
13	2.5	K714_1740	TD370K	140-200	13	8,116	7	15,973	2.5	15,973
12	2.4	K614_1850	TD370K	140-200	12	8,597	8	12,844	2.4	12,844
11	2.3	K714_1930	TD370K	140-200	11	8,985	6	17,684	2.3	17,684
10	2.0	K614_2230	TD370K	140-200	10	10,366	8	12,844	2.0	12,844
10	1.9	K714_2260	TD370K	140-200	10	10,550	5	20,765	1.9	20,765
8.9	1.8	K614_2460	TD370K	140-200	8.9	11,476	8	12,844	1.8	12,844
8.7	1.7	K714_2510	TD370K	140-200	8.7	11,681	5	21,259	1.7	21,259
7.9	1.6	K714_2750	TD370K	140-200	7.9	12,826	6	19,244	1.6	19,244
7.2	1.4	K714_3050	TD370K	140-200	7.2	14,200	5	21,259	1.4	21,259

3.0 HP, 1750 RPM Motor

Continued on next page

547	109	K202_0040	TD470K	180-300	547	297	237	687	109	687
501	100	K202_0044	TD470K	180-300	501	324	218	750	100	750
423	85	K202_0052	TD470K	180-300	423	384	183	890	85	890
407	81	K302_0054	TD470K	180-300	407	399	177	924	81	924
365	73	K202_0060	TD470K	180-300	365	445	158	1,031	73	1,031
327	65	K202_0067	TD470K	180-300	327	496	142	1,148	65	1,148
307	61	K202_0071	TD470K	180-300	307	528	133	1,223	61	1,223
296	59	K302_0074	TD470K	180-300	296	548	128	1,270	59	1,270
293	59	K402_0075	TD470K	180-300	293	553	127	1,281	59	1,281
261	52	K202_0084	TD470K	180-300	261	623	113	1,443	52	1,443
259	52	K302_0084	TD470K	180-300	259	626	112	1,451	52	1,451
238	48	K202_0092	TD470K	180-300	238	681	107	1,530	48	1,530
237	47	K402_0092	TD470K	180-300	237	685	103	1,588	47	1,588
236	47	K302_0093	TD470K	180-300	236	687	102	1,592	47	1,592
217	43	K202_0100	TD470K	180-300	217	747	108	1,525	43	1,525
216	43	K302_0100	TD470K	180-300	216	752	94	1,742	43	1,742
189	38	K202_0115	TD470K	180-300	189	856	110	1,517	38	1,517
188	38	K302_0115	TD470K	180-300	188	861	82	1,995	38	1,995
172	34	K202_0125	TD470K	180-300	172	942	111	1,513	34	1,513
174	35	K302_0125	TD470K	180-300	174	933	75	2,161	35	2,161
158	32	K202_0140	TD470K	180-300	158	1,027	111	1,511	32	1,511
157	31	K302_0140	TD470K	180-300	157	1,033	68	2,395	31	2,395
150	30	K513_0145	TD470K	180-300	150	1,062	65	2,462	30	2,462
136	27	K513_0160	TD470K	180-300	136	1,176	59	2,726	27	2,726


1) Speed tolerance at rated load is ±3%. At less than rated load, minimum speed may increase 5%.

2) The ComTrac drive operates at constant horsepower above transition values and at constant torque below transition values. Note shaded area.


Engineering advances may cause slight changes to the information shown.

Housing Styles


N – Foot Mounted



F – Round Flange



G – Tapped Holes



These Housing Styles are available as Hollow (A) or Solid (V) Output.

See page 79 for mounting positions.

Output Shaft Diameter and Hollow Output (inches)

See Page 53 for other options.

Base Module	Output Shaft	Hollow Output	Base Module	Output Shaft	Hollow Output
K102	1.000	1.000	K613/K614	1.750	2.000
K202/K203	1.250	1.187	K713/K714	2.375	2.375
K302/K303	1.250	1.375	K813/K814	2.875	2.750
K402/K403	1.375	1.500	K913/K914	3.625	3.250
K513/K514	1.750	2.000			



"K" Series – MGS Adjustable Speed Drive Selection Data



Speed Range		Part Number	Maximum		Transition ⁽²⁾		Minimum		
Output RPM ⁽¹⁾	Max.		RPM	Torque in.lbs.	RPM	Torque in.lbs.	RPM	Torque in.lbs.	
3.0 HP, 1750 RPM Motor		Continued on next page							
130	26	K202_0170	TD470K 180-300	130	1,250	109	1,519	26	1,519
129	26	K302_0170	TD470K 180-300	129	1,256	56	2,911	26	2,911
125	25	K202_0175	TD470K 180-300	125	1,295	109	1,521	25	1,521
126	25	K302_0175	TD470K 180-300	126	1,282	55	2,972	25	2,972
126	25	K402_0175	TD470K 180-300	126	1,291	55	2,991	25	2,991
115	23	K613_0190	TD470K 180-300	115	1,388	50	3,217	23	3,217
113	23	K513_0195	TD470K 180-300	113	1,414	49	3,278	23	3,278
108	22	K302_0200	TD470K 180-300	108	1,504	53	3,100	22	3,100
108	22	K402_0200	TD470K 180-300	108	1,498	47	3,471	22	3,471
99	20	K513_0220	TD470K 180-300	99	1,607	43	3,725	20	3,725
94	19	K302_0230	TD470K 180-300	94	1,727	54	3,100	19	3,100
94	19	K402_0230	TD470K 180-300	94	1,727	41	4,003	19	4,003
90	18	K513_0240	TD470K 180-300	90	1,779	39	4,124	18	4,124
87	17	K402_0250	TD470K 180-300	87	1,875	38	4,344	17	4,344
78	16	K302_0280	TD470K 180-300	78	2,068	54	3,100	16	3,100
79	16	K402_0280	TD470K 180-300	79	2,059	34	4,772	16	4,772
75	15	K513_0290	TD470K 180-300	75	2,133	33	4,942	15	4,942
68	14	K513_0320	TD470K 180-300	68	2,361	29	5,472	14	5,472
63	13	K402_0350	TD470K 180-300	63	2,577	34	4,872	13	4,872
63	13	K513_0350	TD470K 180-300	63	2,543	27	5,894	13	5,894
57	11	K613_0380	TD470K 180-300	57	2,801	25	6,490	11	6,490
57	11	K513_0390	TD470K 180-300	57	2,816	25	6,525	11	6,525
51	10	K613_0430	TD470K 180-300	51	3,151	22	7,301	10	7,301
50	10	K513_0440	TD470K 180-300	50	3,179	22	7,367	10	7,367
49	10	K713_0450	TD470K 180-300	49	3,293	21	7,631	10	7,631
45	9.1	K513_0480	TD470K 180-300	45	3,520	20	7,972	9.1	7,972
45	8.9	K813_0490	TD470K 180-300	45	3,580	19	8,297	8.9	8,297
44	8.8	K713_0500	TD470K 180-300	44	3,646	19	8,448	8.8	8,448
38	7.5	K513_0580	TD470K 180-300	38	4,261	21	7,972	7.5	7,972
38	7.6	K613_0580	TD470K 180-300	38	4,206	16	9,746	7.6	9,746
37	7.5	K713_0590	TD470K 180-300	37	4,281	16	9,920	7.5	9,920
34	6.8	K513_0650	TD470K 180-300	34	4,717	21	7,972	6.8	7,972
34	6.9	K613_0640	TD470K 180-300	34	4,656	15	10,790	6.9	10,790
34	6.7	K713_0650	TD470K 180-300	34	4,739	15	10,983	6.7	10,983
32	6.4	K613_0690	TD470K 180-300	32	5,026	14	11,639	6.4	11,639
31	6.1	K713_0710	TD470K 180-300	31	5,204	13	12,059	6.1	12,059
31	6.1	K813_0720	TD470K 180-300	31	5,240	13	12,144	6.1	12,144
29	5.7	K613_0760	TD470K 180-300	29	5,565	13	12,844	5.7	12,844
28	5.6	K713_0790	TD470K 180-300	28	5,761	12	13,351	5.6	13,351
25	4.9	K713_0890	TD470K 180-300	25	6,505	11	14,803	4.9	14,803
25	5.0	K813_0880	TD470K 180-300	25	6,414	11	14,864	5.0	14,864
23	4.5	K813_0970	TD470K 180-300	23	7,101	10	16,457	4.5	16,457
23	4.7	K914_0940	TD470K 180-300	23	6,746	10	15,633	4.7	15,633
22	4.4	K713_0990	TD470K 180-300	22	7,202	10	16,394	4.4	16,394

Part No. Explanation

K 2 0 2 A F 0230 TD370K140 – 200 W

Washdown, when required
 Rated for HP (200 = 2.00)
 Non-gearred TD37 ComTrac Unit, 145TC Input
 Ratio of MGS Unit (0230 = 23.0:1)
 Housing Style – F (Output Flange)
 Hollow Output Style – A
 No. of Gear Reductions
 Generation No.
 Unit No.
 Right Angle Helical/Bevel

Selection Procedure:

- Determine the MGS/ComTrac combination according to the Input HP of the application and the Output RPM nearest the required **maximum speed**.
- Verify that the output torque will sufficiently meet the application requirements.
- Complete the Part No. per the example by adding "A" or "V" for the Output Style and the Housing Style letter ("N", "F", or "G") as required.



"K" Series – MGS Adjustable Speed Drive Selection Data



Speed Range		Part Number	Maximum		Transition (2)		Minimum	
Output RPM (1)	Max.		Min.	RPM	Torque in.lbs.	RPM	Torque in.lbs.	RPM

3.0 HP, 1750 RPM Motor Continued

19	3.8	K714_1150	TD470K	180-300	19	8,251	8.3	19,121	3.8	19,121
17	3.4	K714_1270	TD470K	180-300	17	9,135	7.5	21,170	3.4	21,170
17	3.5	K914_1260	TD470K	180-300	17	9,049	7.5	20,970	3.5	20,970
16	3.2	K714_1390	TD470K	180-300	16	9,985	7.5	21,259	3.2	21,259
15	3.1	K814_1420	TD470K	180-300	15	10,182	6.7	23,596	3.1	23,596
15	2.9	K914_1490	TD470K	180-300	15	10,718	6.4	24,839	2.9	24,839
14	2.8	K714_1540	TD470K	180-300	14	11,055	7.6	21,259	2.8	21,259
14	2.8	K814_1570	TD470K	180-300	14	11,273	6.1	26,124	2.8	26,124
13	2.5	K814_1730	TD470K	180-300	13	12,468	5.5	28,893	2.5	28,893
12	2.5	K714_1760	TD470K	180-300	12	12,694	7.6	21,259	2.5	21,259
11	2.2	K714_1950	TD470K	180-300	11	14,054	7.7	21,259	2.2	21,259
11	2.3	K814_1920	TD470K	180-300	11	13,804	4.9	31,988	2.3	31,988
10	1.9	K714_2290	TD470K	180-300	10	16,502	7.6	21,259	1.9	21,259
9.5	1.9	K814_2310	TD470K	180-300	9	16,647	4.3	37,204	1.9	37,204
8.9	1.8	K914_2470	TD470K	180-300	9	17,771	3.8	41,182	1.8	41,182
8.6	1.7	K714_2540	TD470K	180-300	9	18,271	7.5	21,259	1.7	21,259
8.5	1.7	K814_2560	TD470K	180-300	9	18,430	4.3	37,204	1.7	37,204
7.8	1.6	K814_2810	TD470K	180-300	8	20,202	5.1	31,935	1.6	31,935
7.4	1.5	K914_2940	TD470K	180-300	7	21,133	3.2	48,973	1.5	48,973
7.0	1.4	K814_3110	TD470K	180-300	7	22,367	4.6	35,365	1.4	35,365
5.9	1.2	K914_3740	TD470K	180-300	6	26,883	3.4	47,620	1.2	47,620

5.0 HP, 1750 RPM Motor

Continued on next page

547	109	K202_0040	TD570K	180-500	547	508	273	1,031	109	1,031
547	109	K302_0040	TD570K	180-500	547	508	273	1,031	109	1,031
501	100	K202_0044	TD570K	180-500	501	554	250	1,125	100	1,125
501	100	K302_0044	TD570K	180-500	501	554	250	1,125	100	1,125
423	85	K202_0052	TD570K	180-500	423	657	244	1,163	85	1,163
407	81	K302_0054	TD570K	180-500	407	683	203	1,386	81	1,386
365	73	K202_0060	TD570K	180-500	365	762	246	1,159	73	1,159
365	73	K302_0060	TD570K	180-500	365	762	182	1,547	73	1,547
327	65	K202_0067	TD570K	180-500	327	849	246	1,160	65	1,160
325	65	K302_0067	TD570K	180-500	325	856	162	1,737	65	1,737
307	61	K202_0071	TD570K	180-500	307	904	244	1,161	61	1,161
296	59	K302_0074	TD570K	180-500	296	939	148	1,905	59	1,905
293	59	K402_0075	TD570K	180-500	293	947	146	1,922	59	1,922
261	52	K202_0084	TD570K	180-500	261	1,066	240	1,168	52	1,168
259	52	K302_0084	TD570K	180-500	259	1,072	129	2,177	52	2,177
261	52	K402_0084	TD570K	180-500	261	1,064	130	2,159	52	2,159
238	48	K202_0092	TD570K	180-500	238	1,167	237	1,174	48	1,174
237	47	K402_0092	TD570K	180-500	237	1,173	118	2,381	47	2,381
236	47	K302_0093	TD570K	180-500	236	1,177	118	2,389	47	2,389
216	43	K302_0100	TD570K	180-500	216	1,287	108	2,612	43	2,612
217	43	K402_0100	TD570K	180-500	217	1,282	108	2,603	43	2,603
188	38	K302_0115	TD570K	180-500	188	1,474	105	2,696	38	2,696


¹⁾ Speed tolerance at rated load is ±3%. At less than rated load, minimum speed may increase 5%.

²⁾ The ComTrac drive operates at constant horsepower above transition values and at constant torque below transition values. Note shaded area.


Engineering advances may cause slight changes to the information shown.

Housing Styles


N – Foot Mounted



F – Round Flange



G – Tapped Holes



These Housing Styles are available as Hollow (A) or Solid (V) Output.

See page 79 for mounting positions.

Output Shaft Diameter and Hollow Output (inches)

See Page 53 for other options.

Base Module	Output Shaft	Hollow Output	Base Module	Output Shaft	Hollow Output
K102	1.000	1.000	K613/K614	1.750	2.000
K202/K203	1.250	1.187	K713/K714	2.375	2.375
K302/K303	1.250	1.375	K813/K814	2.875	2.750
K402/K403	1.375	1.500	K913/K914	3.625	3.250
K513/K514	1.750	2.000			



"K" Series – MGS Adjustable Speed Drive Selection Data



Speed Range		Part Number	Maximum		Transition ⁽²⁾		Minimum		
Output RPM ⁽¹⁾	Max.		RPM	Torque in.lbs.	RPM	Torque in.lbs.	RPM	Torque in.lbs.	
Min.									
5.0 HP, 1750 RPM Motor									
190	38	K402_0115	TD570K 180-500	190	1,463	95	2,969	38	2,969
174	35	K302_0125	TD570K 180-500	174	1,597	106	2,691	35	2,691
173	35	K402_0125	TD570K 180-500	173	1,607	86	3,263	35	3,263
157	31	K302_0140	TD570K 180-500	157	1,770	106	2,686	31	2,686
158	32	K402_0140	TD570K 180-500	158	1,763	79	3,579	32	3,579
150	30	K513_0145	TD570K 180-500	150	1,819	75	3,693	30	3,693
136	27	K513_0160	TD570K 180-500	136	2,014	68	4,088	27	4,088
129	26	K302_0170	TD570K 180-500	129	2,151	105	2,694	26	2,694
129	26	K402_0170	TD570K 180-500	129	2,151	64	4,366	26	4,366
128	26	K613_0170	TD570K 180-500	128	2,147	64	4,358	26	4,358
126	25	K302_0175	TD570K 180-500	126	2,196	105	2,695	25	2,695
126	25	K402_0175	TD570K 180-500	126	2,210	63	4,486	25	4,486
125	25	K513_0175	TD570K 180-500	125	2,188	62	4,441	25	4,441
115	23	K613_0190	TD570K 180-500	115	2,377	57	4,825	23	4,825
113	23	K513_0195	TD570K 180-500	113	2,422	56	4,917	23	4,917
108	22	K302_0200	TD570K 180-500	108	2,575	103	2,714	22	2,714
108	22	K402_0200	TD570K 180-500	108	2,565	58	4,872	22	4,872
99	20	K513_0220	TD570K 180-500	99	2,752	50	5,587	20	5,587
94	19	K402_0230	TD570K 180-500	94	2,958	58	4,872	19	4,872
90	18	K513_0240	TD570K 180-500	90	3,047	45	6,186	18	6,186
87	17	K402_0250	TD570K 180-500	87	3,210	64	4,434	17	4,434
79	16	K402_0280	TD570K 180-500	79	3,527	59	4,872	16	4,872
75	15	K513_0290	TD570K 180-500	75	3,652	37	7,413	15	7,413
68	14	K513_0320	TD570K 180-500	68	4,043	35	7,972	14	7,972
69	14	K613_0320	TD570K 180-500	69	3,987	34	8,093	14	8,093
63	13	K402_0350	TD570K 180-500	63	4,414	58	4,872	13	4,872
63	13	K513_0350	TD570K 180-500	63	4,355	35	7,972	13	7,972
63	13	K613_0350	TD570K 180-500	63	4,332	32	8,793	13	8,793
57	11	K613_0380	TD570K 180-500	57	4,796	28	9,735	11	9,735
57	11	K513_0390	TD570K 180-500	57	4,822	35	7,972	11	7,972
56	11	K713_0390	TD570K 180-500	56	4,910	28	9,967	11	9,967
51	10	K613_0430	TD570K 180-500	51	5,395	25	10,952	10	10,952
50	10	K513_0440	TD570K 180-500	50	5,444	35	7,972	10	7,972
49	10	K813_0440	TD570K 180-500	49	5,538	25	11,242	10	11,242
49	10	K713_0450	TD570K 180-500	49	5,639	24	11,446	10	11,446
45	9.1	K513_0480	TD570K 180-500	45	6,027	35	7,972	9.1	7,972
46	9.2	K613_0480	TD570K 180-500	46	5,974	23	12,126	9.2	12,126
45	8.9	K813_0490	TD570K 180-500	45	6,131	22	12,446	8.9	12,446
44	8.8	K713_0500	TD570K 180-500	44	6,243	22	12,672	8.8	12,672
38	7.5	K513_0580	TD570K 180-500	38	7,296	35	7,972	7.5	7,972
38	7.6	K613_0580	TD570K 180-500	38	7,202	22	12,844	7.6	12,844
37	7.5	K713_0590	TD570K 180-500	37	7,330	19	14,880	7.5	14,880
34	6.9	K613_0640	TD570K 180-500	34	7,973	22	12,844	6.9	12,844
34	6.7	K713_0650	TD570K 180-500	34	8,116	17	16,474	6.7	16,474
32	6.4	K613_0690	TD570K 180-500	32	8,607	24	11,639	6.4	11,639

Part No. Explanation

K 2 0 2 A F 0230 TD370K140 – 200 W

Washdown, when required
 Rated for HP (200 = 2.00)
 Non-gearred TD37 ComTrac Unit, 145TC Input
 Ratio of MGS Unit (0230 = 23.0:1)
 Housing Style – F (Output Flange)
 Hollow Output Style – A
 No. of Gear Reductions
 Generation No.
 Unit No.
 Right Angle Helical/Bevel

Selection Procedure:

- Determine the MGS/ComTrac combination according to the Input HP of the application and the Output RPM nearest the required **maximum speed**.
- Verify that the output torque will sufficiently meet the application requirements.
- Complete the Part No. per the example by adding "A" or "V" for the Output Style and the Housing Style letter ("N", "F", or "G") as required.



"K" Series – MGS Adjustable Speed Drive Selection Data



Speed Range		Part Number		Maximum		Transition (2)		Minimum	
Output RPM (1)	Max.			Min.	RPM	Torque in.lbs.	RPM	Torque in.lbs.	RPM
5.0 HP, 1750 RPM Motor Continued									
31	6.1	K713_0710	TD570K	180-500	31	8,911	15	18,089	6.1
31	6.1	K813_0720	TD570K	180-500	31	8,974	15	18,215	6.1
29	5.7	K613_0760	TD570K	180-500	29	9,529	22	12,844	5.7
28	5.6	K713_0790	TD570K	180-500	28	9,866	14	20,027	5.6
25	4.9	K713_0890	TD570K	180-500	25	11,139	19	14,803	4.9
25	4.9	K714_0890	TD570K	180-500	25	10,971	13	21,259	4.9
25	5.0	K813_0880	TD570K	180-500	25	10,984	12	22,296	5.0
23	4.5	K813_0970	TD570K	180-500	23	12,161	11	24,685	4.5
23	4.7	K914_0940	TD570K	180-500	23	11,552	12	23,450	4.7
22	4.4	K713_0990	TD570K	180-500	22	12,333	17	16,394	4.4
22	4.4	K714_0990	TD570K	180-500	22	12,147	13	21,259	4.4
19	3.8	K714_1150	TD570K	180-500	19	14,130	13	21,259	3.8
19	3.8	K814_1150	TD570K	180-500	19	14,115	10	28,652	3.8
17	3.4	K714_1270	TD570K	180-500	17	15,644	13	21,259	3.4
17	3.4	K814_1270	TD570K	180-500	17	15,627	8.6	31,722	3.4
17	3.5	K914_1260	TD570K	180-500	17	15,496	8.7	31,455	3.5
16	3.2	K714_1390	TD570K	180-500	16	17,098	13	21,259	3.2
15	3.1	K814_1420	TD570K	180-500	15	17,436	7.7	35,393	3.1
15	2.9	K914_1490	TD570K	180-500	15	18,355	7.3	37,258	2.9
14	2.8	K714_1540	TD570K	180-500	14	18,930	13	21,259	2.8
14	2.8	K814_1570	TD570K	180-500	14	19,304	7.4	37,204	2.8
13	2.5	K814_1730	TD570K	180-500	13	21,350	7.4	37,204	2.5
11	2.3	K814_1920	TD570K	180-500	11	23,638	7.4	37,204	2.3
11	2.3	K914_1920	TD570K	180-500	11	23,612	5.7	47,929	2.3
9.5	1.9	K814_2310	TD570K	180-500	9.5	28,506	7.4	37,204	1.9
8.9	1.8	K914_2470	TD570K	180-500	8.9	30,431	5.2	53,194	1.8
8.5	1.7	K814_2560	TD570K	180-500	8.5	31,561	7.4	37,204	1.7
7.4	1.5	K914_2940	TD570K	180-500	7.4	36,189	5.4	51,585	1.5
5.9	1.2	K914_3740	TD570K	180-500	5.9	46,035	5.7	47,620	1.2


¹⁾ Speed tolerance at rated load is $\pm 3\%$. At less than rated load, minimum speed may increase 5%.

²⁾ The ComTrac drive operates at constant horsepower above transition values and at constant torque below transition values. Note shaded area.


Engineering advances may cause slight changes to the information shown.

Housing Styles


N – Foot Mounted



F – Round Flange



G – Tapped Holes



These Housing Styles are available as Hollow (A) or Solid (V) Output.

See page 79 for mounting positions.

Output Shaft Diameter and Hollow Output (inches)

See Page 53 for other options.

Base Module	Output Shaft	Hollow Output	Base Module	Output Shaft	Hollow Output
K102	1.000	1.000	K613/K614	1.750	2.000
K202/K203	1.250	1.187	K713/K714	2.375	2.375
K302/K303	1.250	1.375	K813/K814	2.875	2.750
K402/K403	1.375	1.500	K913/K914	3.625	3.250
K513/K514	1.750	2.000			




Notes



"K" Series – MGS® Adjustable Speed Drives

Dimensional Data



Drawing for Units

K102AG — K403AG

Table No. 1 "K" Series – Tapped Hole Unit Dimensions (Inches) – "G" Housing Style

Base Module	A	B	D	F	G	H	M	Tolerance	P	R	S	Z ₁	BC	BP	FA	GA
K102	4.13	4.72	6.30	3.54	2.76	2.36	2.953	+0.007/-0.005	.12	3.54	2.36	—	3.54	4.41	1.18	1.38
K202/203	4.57	5.83	7.48	4.53	3.54	2.56	3.228	+0.007/-0.005	.12	4.53	2.56	—	3.94	5.28	1.38	1.77
K302/303	5.20	6.30	8.39	5.12	4.13	2.95	3.740	+0.007/-0.005	.12	5.12	2.95	—	4.53	5.75	1.57	2.07
K402/403	5.98	7.40	9.45	6.10	4.72	3.54	4.331	+0.007/-0.005	.14	5.83	3.54	—	5.12	6.81	1.97	2.36
K513/514	5.71	7.87	10.24	5.51	4.92	6.30	4.331	+0.007/-0.005	.14	6.30	3.94	5.98	5.12	7.28	1.57	2.46
K613/614	7.09	8.46	12.20	6.30	5.12	7.48	5.512	+0.008/-0.006	.14	6.61	4.72	6.77	6.50	7.87	1.97	2.56
K713/714	7.68	9.53	13.46	7.09	5.71	8.35	6.102	+0.008/-0.006	.14	7.48	4.92	7.52	7.28	8.90	2.17	2.85
K813/814	8.90	11.81	16.14	9.45	7.28	10.43	7.283	+0.010/-0.007	.16	9.25	5.71	8.11	8.46	11.10	2.95	3.64
K913/914	11.02	13.78	19.49	11.02	8.86	12.40	9.055	+0.010/-0.007	.20	11.22	7.09	9.84	10.43	12.99	3.74	4.43

Table No. 2 "K" Series Bore Dimensions and Mounting Holes (Inches)

Base Module	U	Tolerance	UA	UB	UC	UL	1	J ₁ xDP	J ₂ xDP
K102	1.0000	+0.008/-0.000	.250	1.11	1.57	3.86	1/2-13	4, M8x.51	M8x.51 ¹⁾
K202/203	1.1875	+0.010/-0.000	.250	1.31	1.77	4.78	1/2-13	4, M8x.51	M10x.63
K302/303	1.3750	+0.010/-0.000	.312	1.52	1.97	4.92	5/8-11	4, M8x.51	M10x.63
K402/403	1.5000	+0.010/-0.000	.375	1.67	2.17	6.18	3/4-10	4, M10x.63	M12x.75
K513/514	2.0000	+0.012/-0.000	.500	2.13	2.56	6.46	3/4-10	8, M10x.63	M16x1.02
K613/614	2.0000	+0.012/-0.000	.500	2.23	2.76	7.05	3/4-10	8, M10x.63	M16x1.02
K713/714	2.3750	+0.012/-0.000	.625	2.66	3.35	8.43	1-8	8, M12x.75	M20x1.22
K813/814	2.7500	+0.012/-0.000	.625	3.03	3.94	10.35	1-8	8, M12x.75	M24x1.50
K913/914	3.2500	+0.014/-0.000	.750	3.59	4.33	11.89	1-8	8, M16x1.02	M30x1.89

Table No. 3 "K" Series – Unit Dimensions (Inches)

ComTrac Part No.	NEMA C-Flange	DH	HL	TL	X	Y	Z
TD270K050	56C	4.92	5.67	7.87	2.09	5.55	4.41
TD270K140	143/145TC	4.92	5.67	7.87	2.09	5.55	4.41
TD370K140	143/145TC	4.92	5.91	8.50	2.17	5.67	4.37
TD470K180	182/184TC	6.30	6.81	8.94	2.80	7.20	5.59
TD570K180	182/184TC	7.87	8.31	11.89	3.11	8.11	6.30

(1) Tapped hole are located on Side 2 of K1 units ONLY.

(2) This dimension is a clearance hole. The mounting feet are an integral part of the K10 housing.

Part No. Example

Hollow Output – Tapped Hole Unit with ComTrac

K402AG0350 TD470K180-300



"K" Series – MGS® Adjustable Speed Drives

Dimensional Data




Table No. 4 "K" Series – Tapped Hole Unit Dimensions (Inches) – "G" Housing Style

Base	Module	TD270K050 ⁽³⁾			TD370K140			TD470K180			TD570K180			
		CD	H ₂	I	T	H ₂	I	T	H ₂	I	T	H ₂	I	T
	K102	1.42	2.20	7.87	5.04	1.73	8.50	5.04	—	—	—	—	—	—
	K202	1.81	2.80	11.97	5.79	2.32	12.64	5.79	1.17	12.76	5.87	—	—	—
	K203	1.81	—	—	—	—	—	—	—	—	—	—	—	—
	K302	2.07	3.44	12.76	6.57	2.97	13.43	6.57	2.42	13.54	6.65	1.67	16.18	6.65
	K303	.63	2.01	14.45	8.27	1.54	15.12	8.27	—	—	—	—	—	—
	K402	2.36	—	—	—	3.86	14.21	7.36	3.31	14.33	7.44	2.56	16.97	7.44
	K403	.91	2.87	15.24	9.06	2.40	15.91	9.06	—	—	—	—	—	—
	K513	.59	—	—	—	3.66	13.62	6.77	3.11	13.74	6.85	2.36	16.38	6.85
	K514	.59	4.13	14.65	8.46	3.66	15.31	8.46	—	—	—	—	—	—
	K613	.71	—	—	—	—	—	—	4.17	14.49	7.60	3.43	17.13	7.60
	K614	.71	5.20	15.39	9.21	4.72	16.06	9.21	—	—	—	—	—	—
	K713	.79	—	—	—	—	—	—	4.96	15.59	8.70	4.21	18.23	8.70
	K714	.79	5.98	16.54	10.35	5.51	17.20	10.35	4.96	18.03	11.14	4.21	20.67	11.14
	K813	.94	—	—	—	—	—	—	—	—	—	6.14	19.25	9.72
	K814	.94	—	—	—	—	—	—	6.89	19.02	12.13	6.14	21.65	12.13
	K913	.98	—	—	—	—	—	—	8.82	20.79	13.90	8.07	23.43	13.90
	K914	.98	—	—	—	—	—	—	—	—	—	—	—	—

Table No. 5 "K" Series with ComTrac – Approximate Weight (lbs.)


Part Number	K102	K202	K302	K303	K402	K403	K513	K514	K613	K614	K713	K714	K813	K814	K913	K914
TD270K050⁽³⁾	64	73	100	106	—	133	—	142	—	210	—	267	—	—	—	—
TD370K140	82	91	118	124	144	151	157	160	—	228	—	285	—	—	—	—
TD470K180	—	99	126	—	152	—	165	—	229	—	280	293	—	390	—	589
TD570K180	—	—	155	—	181	—	184	—	258	—	309	322	397	410	—	618

⁽³⁾Also available as TD270K140 for a NEMA 143TC frame motor.



"K" Series – MGS® Adjustable Speed Drives

Dimensional Data



Drawing for Units

K102VN — K403VN

Table No. 1 "K" Series – Foot Mounting Unit Dimensions (Inches) – "N" Housing Style

Base Module	B	D	F	G	H	J	L	M	N	O	P	Q	R	S	Z ₁	BO	FA	N ₁	SN
K102	5.51 ¹⁾	6.97	3.54	4.53	2.95	.35	4.53	1.18	.51	—	2.34	.16	3.54	2.36	—	—	1.18	.59	2.95
K202/203	7.28	8.39	4.53	6.10	3.46	.43	5.31	1.57	.79	—	2.56	.16	4.53	2.56	—	—	1.38	.91	3.46
K302/303	7.87	9.29	5.12	6.69	3.86	.43	5.59	1.77	.79	—	2.60	.16	5.12	2.95	—	—	1.57	.91	3.86
K402/403	9.06	10.43	6.10	7.87	4.53	.55	6.54	1.97	.87	—	3.39	.16	5.83	3.54	—	—	1.97	.98	4.53
K513/514	9.45	11.42	5.51	7.87	7.48	.71	8.74	2.36	1.06	5.10	3.90	.16	6.30	3.94	5.98	7.28	1.57	1.18	5.12
K613/614	9.84	13.39	6.30	8.27	8.66	.71	9.29	2.56	1.06	5.35	4.31	.16	6.61	4.72	6.77	7.87	1.97	1.18	5.91
K713/714	11.42	14.96	7.09	9.45	9.84	.87	10.91	2.76	1.38	6.46	5.14	.16	7.48	4.92	7.52	8.90	2.17	1.50	6.42
K813/814	14.17	17.91	9.45	11.81	12.20	1.02	12.83	3.35	1.61	7.28	5.94	.20	9.25	5.71	8.11	11.10	2.95	1.77	7.48
K913/914	16.93	21.46	11.02	14.17	14.37	1.30	15.16	3.74	1.81	8.66	7.13	.31	11.22	7.09	9.84	12.99	3.74	1.97	9.06

Table No. 2 "K" Series – Shaft Dimensions (Inches)

Base Module	U	Tolerance	V	UA – Key	UB
K102	1.0000	+0.000/-0.006	1.97	1/4 x 1/4 x 1 1/2	1.11
K202/203	1.2500	+0.000/-0.007	2.36	1/4 x 1/4 x 11 ¹⁵ / ₁₆	1.36
K302/303	1.2500	+0.000/-0.007	2.36	1/4 x 1/4 x 11 ¹⁵ / ₁₆	1.36
K402/403	1.3750	+0.000/-0.007	2.76	5/16 x 5/16 x 25 ¹⁵ / ₁₆	1.51
K513/514	1.7500	+0.000/-0.007	3.54	3/8 x 3/8 x 35 ⁵ / ₃₂	1.92
K613/614	1.7500	+0.000/-0.007	3.94	3/8 x 3/8 x 35 ⁵ / ₃₂	1.92
K713/714	2.3750	+0.000/-0.008	4.72	5/8 x 5/8 x 31 ¹⁵ / ₁₆	2.65
K813/814	2.8750	+0.000/-0.008	5.51	3/4 x 3/4 x 45 ⁵ / ₁₆	3.21
K913/914	3.6250	+0.000/-0.009	6.69	7/8 x 7/8 x 5 1/2	4.01

⁽¹⁾ Mounting feet can be bolted to Side 2 of K1 units ONLY.
Mounting feet are an integral part of the K10 housing.

Part No. Example

Foot Mounting Unit with ComTrac

K402VN0350 TD470K180-300

Table No. 3 "K" Series – Unit Dimensions (Inches)

ComTrac Part No.	NEMA C-Flange	DH	HL	TL	X	Y	Z
TD270K050	56C	4.92	5.67	7.87	2.09	5.55	4.41
TD270K140	143/145TC	4.92	5.67	7.87	2.09	5.55	4.41
TD370K140	143/145TC	4.92	5.91	8.50	2.17	5.67	4.37
TD470K180	182/184TC	6.30	6.81	8.94	2.80	7.20	5.59
TD570K180	182/184TC	7.87	8.31	11.89	3.11	8.11	6.30



"K" Series – MGS® Adjustable Speed Drives

Dimensional Data




Table No. 4 "K" Series – Unit Dimensions (Inches) – "N" Housing Style

Base	Module	TD270K050 ⁽³⁾			TD370K140			TD470K180			TD570K180			
		H ₂	I	T	H ₂	I	T	H ₂	I	T	H ₂	I	T	
	K102	1.42	2.20	7.87	5.04	1.73	8.50	5.04	—	—	—	—	—	—
	K202	1.81	2.80	11.97	5.79	2.32	12.64	5.79	1.17	12.76	5.87	—	—	—
	K203	1.81	—	—	—	—	—	—	—	—	—	—	—	—
	K302	2.07	3.44	12.76	6.57	2.97	13.43	6.57	2.42	13.54	6.65	1.67	16.18	6.65
	K303	.63	2.01	14.45	8.27	1.54	15.12	8.27	—	—	—	—	—	—
	K402	2.36	—	—	—	3.86	14.21	7.36	3.31	14.33	7.44	2.56	16.97	7.44
	K403	.91	2.87	15.24	9.06	2.40	15.91	9.06	—	—	—	—	—	—
	K513	.59	—	—	—	3.66	13.62	6.77	3.11	13.74	6.85	2.36	16.38	6.85
	K514	.59	4.13	14.65	8.46	3.66	15.31	8.46	—	—	—	—	—	—
	K613	.71	—	—	—	—	—	—	4.17	14.49	7.60	3.43	17.13	7.60
	K614	.71	5.20	15.39	9.21	4.72	16.06	9.21	—	—	—	—	—	—
	K713	.79	—	—	—	—	—	—	4.96	15.59	8.70	4.21	18.23	8.70
	K714	.79	5.98	16.54	10.35	5.51	17.20	10.35	4.96	18.03	11.14	4.21	20.67	11.14
	K813	.94	—	—	—	—	—	—	—	—	—	6.14	19.25	9.72
	K814	.94	—	—	—	—	—	—	6.89	19.02	12.13	6.14	21.65	12.13
	K913	.98	—	—	—	—	—	—	—	—	—	—	—	—
	K914	.98	—	—	—	—	—	—	8.82	20.79	13.90	8.07	23.43	13.90

⁽³⁾ Also available for a NEMA 143TC frame motor.

Table No. 5 "K" Series with ComTrac – Approximate Weight (lbs.)

Part Number	K102	K202	K302	K303	K402	K403	K513	K514	K613	K614	K713	K714	K813	K814	K913	K914
TD270K050⁽²⁾	64	73	100	106	—	133	—	142	—	210	—	267	—	—	—	—
TD370K140	82	91	118	124	144	151	157	160	—	228	—	285	—	—	—	—
TD470K180	—	99	126	—	152	—	165	—	229	—	280	293	—	390	—	589
TD570K180	—	—	155	—	181	—	184	—	258	—	309	322	397	410	—	618

⁽²⁾Also available as TD270K140 for a NEMA 143TC frame motor.

MGS® Adjustable Speed Drives

Lubrication and Mounting Information




Mounting Hollow Output Reducers

A STOBER hollow output reducer can be mounted from either side. The tolerance for the hollow bore is shown in Table No. 1 and the shaft should be tolerated to fit this bore accordingly.

Table No. 1 Hollow Output Bore Tolerance

Bore Range	Tolerance	Bore Range	Tolerance
.39 — .71	+.0007/-0.0000	1.97 — 3.15	+.0012/-0.0000
.71 — 1.18	+.0008/-0.0000	3.15 & UP	+.0014/-0.0000
1.18 — 1.97	+.0010/-0.0000		

A keeper plate inside the quill is provided with each unit to prevent axial movement. This keeper plate is held in place with snap rings and can be easily removed for location on either end. A spring pin in the keeper plate mounts into the keyway of the quill and prevents rotation. The keeper plate center hole is tapped to fit the removal bolt.



Before installation, brush the inside of the quill with rust inhibiting grease. When mounting the unit onto the shaft, avoid hammering as this may damage the bearings. Do not mount the reducer dry as removal may be impossible.

The drawing above shows a mounting or fixing bolt and a removal bolt. The mounting/fixing bolt should be smaller in size than the removal bolt. See Table No. 4.

To use the keeper plate with a mounting/fixing bolt, drill and tap the end of the shaft that will be mounted into the reducer. Insert the mounting/fixing bolt through the keeper plate and thread into the shaft end. The machine shaft length should not be longer than the "UL" dimension. A shaft length of "UL minus .125" inches will allow the shaft shoulder to pull against the face of the quill of the reducer.

Table No. 2 "UL" Dimension and Removal Bolt Size

Unit	Bore	UL	Bolt	Unit	Bore	UL	Bolt
F1	.750	2.67	3/8-16 NC	K3	1.375	4.92	5/8-11 NC
F2	1.000	3.62	1/2-13 NC	K4	1.500	6.18	3/4-10 NC
F3	1.250	4.06	1/2-13 NC	K5	2.000	6.46	3/4-10 NC
F4	1.500	4.49	3/4-10 NC	K6	2.000	7.05	3/4-10 NC
F6	2.000	5.63	3/4-10 NC	K7	2.375	8.43	1-8 NC
				K8	2.750	10.35	1-8 NC
K1	1.000	3.86	1/2-13 NC	K9	3.250	11.89	1-8 NC
K2	1.187	4.78	1/2-13 NC				

Removal of Hollow Output Reducers

To dismantle the unit from the shaft, remove the mounting bolt. Thread the removal bolt into the keeper plate to press against the shaft and loosen the shaft from the unit. Removal of the reducer will be easier if the quill is greased before installation.

See our web site (www.stober.com) for a parts breakdown of a specific reducer or call STOBER Customer Service.

In order to obtain long life and trouble-free operation from your MGS speed reducer, it is essential that recommended installation and operating procedures be followed.

Included here are directions for mounting and start-up of the MGS unit, as well as lubrication and maintenance instructions. Failure to follow these instructions will void the drive's warranty.

The torque required by the application must not exceed the reducer torque capacity shown on the nameplate. For safety purposes a safety coupling should be installed between the reducer and the driven load. Otherwise, overload may cause damage to the interior parts of the reducer which may result in breaking the reducer housing. As a result, persons could be injured by flying parts or splashing hot gear oil.

If you have questions about the installation, operation or maintenance of your MGS unit, please contact your local Stober distributor for assistance.

WARNING:

Safety is the most important consideration when operating any type of drive. Through proper application, safe handling methods, and wearing appropriate clothing, you can prevent accidents and injury to yourself and fellow workers.

The shafts of MGS speed reducers rotate at very high speeds and can cut off or severely injure hands, fingers, and arms. Use appropriate guards for shafts and other rotating parts at all times. Follow all directions in the service instruction manual. Obey all federal, state and local safety regulations when operating the drive.



- Always be sure electrical power is off while making electrical connections and during installation and maintenance of the unit.
- Keep clothing, hands, and tools away from ventilation openings on motors and from all rotating parts during operation.
- Lift drive with a double rope sling or other proper lifting equipment of adequate strength. Make sure load is secured and balanced to prevent shifting when unit is being moved. Lifting drives by hand may be dangerous and should be avoided.
- The intended use of lifting lugs is to handle the weight of the unit only. Never use a lifting lug to lift attached assemblies.
- Never operate drive at speeds higher than those shown on the nameplate, or personal injury may result. Contact Stober Drives Inc., if there is any change of operating conditions from those for which the unit was originally sold (as stamped on the nameplate). Failure to comply could result in personal injury and/or machinery damage.
- Always follow good safety practices at all times.

Each drive is tested before delivery. Before installation, however, it is advisable to examine the unit for possible damage which might have occurred during transit. If damage is discovered, it should be immediately reported to the transport agent.

If installation is delayed after receipt of the MGS speed reducer, the drive should be stored in a clean, dry place until put into service. Long term storage requires special procedures. If not kept in a heated, dry area, consult Stober Drives, Inc. for storage instructions.

NOTE: If it is necessary to clean drive shafts, take care to protect the oil seals.

IMPORTANT: Do not use any device to hammer the unit onto the output shaft during installation since the bearing races could be damaged.



MGS® Adjustable Speed Drives

Lubrication and Mounting Information

Lubrication and Mounting Position

All STOBER units are shipped filled with the required amount of lubrication. In order to provide the proper lubrication quantity the mounting position required should be specified at the time of order. **No unit will be shipped without the mounting position specified by the customer.**

Vertical mounting may require different seals, bearings, etc. so it is very important to mount the unit in the position for which it was assembled.

Table No. 1 shows standard lubricant characteristics.

Table No. 1

Characteristic of STOBER Standard Lubricants

	Exxon		
	MobilGear XP600	Special Mist EP220 Food Grade	Mobilgear SHC630
Anti-Foaming Additives	4	4	Excellent
Corrosion Protection	4	4	Optimum
Extreme Pressure Additives	4	4	4
Friction and Wear			
Reducing Characteristics	4	4	Superior
Oxidation Protection	4	4	Enhanced
Wide Temperature Range			4

If food grade or synthetic oil is requested, it will be Mobilgear Special Mist EP220 food grade or Mobilgear SHC630 synthetic.

Maintenance

With STOBER reducers very little maintenance is required under normal operating conditions.

Breathers are provided on the following units:

C612 through C913

K513 through K914

See Table No. 2 and 3 for location of drain and vent for each series and mounting position.

We recommend that the lubrication be changed in units supplied with breathers according to the following schedule:

Normal Operating Conditions after 5000 Hours

Wet Operating Conditions after 2000 Hours.

Units supplied without breathers are lubricated for life.

Some motor manufacturers provide a drain hole in the mounting face of washdown motors. Be sure this hole is covered during washing or when the unit is used in a wet environment.




Table No. 2

Drain Plug and Vent Location

Mounting Position	1	2	2a	3	4
EL1	Vent				
EL2	Drain				
EL3		Vent			
EL4		Drain	Vent		
EL5(C612-C912)				Vent	
EL5(C613-C913)					Vent
EL6				Drain	

Position 2a is on the opposite side of 2.




Table No. 3

Drain Plug and Vent Location

Mounting Position	1	2	2a	3	4
EL1	Vent				
EL2	Drain				
EL3		Vent			
EL4		Drain	Vent		
EL5(K513/K913)				Vent	
EL5(K514/K914)					Vent
EL6(K513/K913)				Drain	
EL6(K513/K914)					Drain

Position 2a is on the opposite side of 2.

MGS® Adjustable Speed Drives

Mounting Information

Mounting position must be specified when the order is placed.



ComTrac Location

The position of the ComTrac and the handwheel location can be specified at the time of assembly.

Specify by ComTrac position I thru IV with handwheel L (left) or R (right).

IV is the standard position — with the handwheel on the left (L) as shown.

If no specification is made, units will be shipped with the standard position.

Table No. 1

"C" Series – Mounting Position

EL1	EL2	EL3	EL4	EL5	EL6
Side 1	Side 2	Side 3	Side 4	Side 5	Side 6





Table No. 2

"F" Series – Mounting Position

EL1	EL2	EL3	EL4	EL5	EL6
Side 1	Side 2	Side 3	Side 4	Side 5	Side 6





MGS® Adjustable Speed Drives

Mounting Information

Mounting position must be specified when the order is placed.

Table No. 3

"K1-K4" Series – Mounting Position

EL1	EL2	EL3	EL4	EL5	EL6
Side 1	Side 2	Side 3	Side 4	Side 5	Side 6




Table No. 4

"K5-K9" Series – Mounting Position

EL1	EL2	EL3	EL4	EL5	EL6
Side 1	Side 2	Side 3	Side 4	Side 5	Side 6

Terms and Conditions of Sale



1. GENERAL. All orders for products supplied by STOBER DRIVES INC. ("STOBER") shall be subject to these terms and conditions of sales. All transactions shall be governed by the laws of the Commonwealth of Kentucky. No modifications hereto will be binding unless agreed to in writing by STOBER.

2. CUSTOMER. The term "Customer," as used herein, means the distributor, resale dealer, original equipment manufacturer or first end-user customer that purchases the STOBER products.

3. WARRANTY. STOBER products shall be free from defects in material and workmanship for a maximum of 5-years (single shift operation or 30 months multiple shift operation) for ServoFit products and MGS *Long Life* products; 3-years (single shift operation or 18 months multiple shift operation) for MGS products; 2-years (single shift operation or 12 months multiple shift operation) for TD products, from the date of shipment to the Customer. For ServoFit products, all normal wear items, including oil seals and bearings, shall be covered for a period of 2-years (single shift operation or 12 months multiple shift operation). In the event that a product proves to be defective, STOBER's sole obligation shall be, at its option, to repair or replace the product. The repaired or replacement product will be shipped F.O.B. STOBER's facilities, freight prepaid by STOBER.

No employee, agent or representative of STOBER has the authority to waive, alter, vary or add to the terms hereof without the prior written approval of an officer of STOBER. It is expressly agreed that (a) this section constitutes the final expression of the parties' understanding with respect to the warranty and (b) this section is a complete and exclusive statement of the terms of the warranty.

STOBER shall have no obligation under the warranty set forth above in the event that:

- (a) The Customer fails, within the warranty period to notify STOBER in writing and provide STOBER with evidence satisfactory to STOBER of the alleged defect within five (5) days after it becomes known to the customer;
- (b) After inspection of a product, STOBER determines, in its sole discretion, that it is not defective in material or workmanship;
- (c) Repair or replacement of a product is required through normal wear and tear;
- (d) Any part in a product or any ingredient contained in a product requires replacement or repair through routine usage or normal wear and tear;
- (e) A product is not maintained or used in accordance with STOBER's applicable operating and/or maintenance manuals, whether by the Customer or any third party;
- (f) A product has been subject to misuse, misapplication, negligence, neglect (including, but not limited to, improper maintenance or storage), accident, catastrophe, improper installation, modification, adjustment, repair or lubrication, whether by the Customer or any third party, without the prior written consent of STOBER. Misuse shall include, but not be limited to, deterioration in a product due to chemical action and wear caused by the presence of abrasive materials;
- (g) The system of connected rotating parts into which the product becomes incorporated is not compatible with the product, or it is not free from critical speed or torsional or other type of vibration within the specified operating range, no matter how induced; or
- (h) The transmitted load and imposed torsional thrust and overhung loads are not within the published capacity limits for the unit sold.

Items manufactured by other parties but installed in or affixed to STOBER's products are not warranted by STOBER and bear only those warranties, express or implied, which are given by the manufacturer of such items, if any.

THE WARRANTY SET FORTH ABOVE IS INTENDED SOLELY FOR THE BENEFIT OF THE Customer

AND DOES NOT APPLY TO ANY THIRD PARTY. ALL CLAIMS MUST BE MADE BY THE Customer AND MAY NOT BE MADE BY ANY THIRD PARTY. THIS WARRANTY MAY NOT BE TRANSFERRED OR ASSIGNED, IN WHOLE OR IN PART, BY THE Customer FOR ANY REASON WHATSOEVER. ANY SUCH ATTEMPTED TRANSFER OR ASSIGNMENT SHALL BE NULL AND VOID.

THIS WARRANTY TAKES THE PLACE OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, WHICH ARE HEREBY DISCLAIMED AND EXCLUDED BY STOBER, INCLUDING WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OF USE AND ALL OBLIGATIONS OR LIABILITIES ON THE PART OF STOBER FOR DAMAGES ARISING OUT OF OR IN CONNECTION WITH THE USE, REPAIR OR PERFORMANCE OF THE PRODUCTS.

4. MODIFICATIONS. STOBER reserves the right, without notice to the Customer, to (a) change the specifications of any product, (b) improve a product in any manner that STOBER deems necessary or appropriate and (c) discontinue the manufacture of any product.

5. PURCHASE ORDERS. The Customer will submit purchase orders for the products to STOBER in writing, whether by mail or telefax, which shall set forth, at a minimum: (a) an identification of the products ordered, (b) prices for such products, (c) quantities, (d) requested delivery dates and (e) shipping instructions and shipping addresses.

6. ACCEPTANCE OF ORDERS. All purchase orders received from the Customer are subject to acceptance by STOBER in writing.

7. MODIFICATION OF ORDERS. No accepted purchase order shall be modified or canceled except upon the written agreement of STOBER and the Customer. Mutually agreed cancellations shall be subject to reasonable charges based upon expenses already incurred by STOBER and commitments made by STOBER. Mutually agreed change orders shall be subject to all provisions of these Terms and Conditions of Sale.

8. PRICE INCREASES. STOBER may increase its prices for the products by providing the original purchaser of the products with at least thirty (30) days' prior written notice. Increased prices for products shall not apply to purchase orders accepted prior to the effective date of the price increase unless such orders provide for delivery more than thirty (30) days after the date of acceptance of the order.

9. PRICING AND DELIVERY TERMS. In accordance with KRS 355.2-319(1)(b), all products are delivered F.O.B. STOBER's warehouse facility in Maysville, Kentucky, or such other facility as STOBER may designate. Orders are then shipped per Customer's shipping instructions as set forth in Customer's purchase order. **CATALOG PRICING DOES NOT INCLUDE SHIPPING, HANDLING AND TAXES.** Once delivered to a common carrier of the Customer's choosing [or of STOBER's choosing if Customer has failed to specify a common carrier on or before five (5) days prior to the requested delivery date] STOBER shall have no further responsibility for the products and all risk of damage, loss or delay shall pass to the Customer. A handling fee is added to freight costs by STOBER to cover the cost of having to pay the carrier within seven (7) days when the terms with the Customer are net 30. The Customer has the option of shipping collect with our carrier or the carrier of choice.

10. PAYMENT TERMS. Net 30 days. All orders will be shipped either prepaid by the Customer or C.O.D., at STOBER's option, unless the Customer has established a previously approved credit line. If STOBER approves a credit line for the Customer, all payments shall be due within thirty (30) days of the date of the invoice. If any invoice is not paid in full within such thirty (30) day period, then finance charges shall be assessed at the rate of one and one-half percent (1½%) per month (eighteen percent (18%) per year).

If such rate is deemed to be usurious at any time, it shall be reduced to the maximum rate permitted by applicable law. STOBER may stop or withhold shipment of products if the Customer does not fulfill its payment obligations. If STOBER is insecure about payment for any reason, STOBER may require full or partial payment in advance and as a condition to the continuation of its delivery of products.

11. SECURITY INTEREST. Unless and until the products are paid for in full, STOBER reserves a security interest in them to secure the unpaid balance of the purchase price. The Customer hereby grants to STOBER a power of attorney, coupled with an interest, to execute and file on behalf of the Customer all necessary financing statements and other documents required or appropriate to protect the security interest granted herein.

12. ACCEPTANCE OF PRODUCTS. The Customer will conduct any incoming inspection tests as soon as possible upon arrival of the products, but in no event later than ten (10) days after the date of receipt. Any products not rejected by written notice to STOBER within such period shall be deemed accepted by the Customer. STOBER shall not be liable for any additional costs, expenses or damages incurred by the Customer, directly or indirectly, as a result of any shortage, damage or discrepancy in a shipment.

13. LIMITATION OF REMEDIES.

(a) STOBER SHALL NOT BE LIABLE FOR ANY LOSS OR DAMAGE CAUSED BY DELAY IN FURNISHING THE CUSTOMER WITH PRODUCTS.

(b) IN NO EVENT SHALL STOBER'S LIABILITY INCLUDE ANY SPECIAL, INDIRECT, INCIDENTAL OR CONSEQUENTIAL LOSSES OR DAMAGES, EVEN IF STOBER HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH POTENTIAL LOSS OR DAMAGE.

14. MADE-TO-ORDER PRODUCTS. STOBER reserves the right to revoke and amend any price quotations offered to the Customer for made-to-order products, provided that such price quotations have not been accepted by the Customer prior to the date of revocation or amendment.


15. DIES, TOOLS AND EQUIPMENT. Charges incurred by the Customer for dies, tools and other equipment shall not confer ownership or the right to possession therein by the Customer. All such dies, tools and equipment shall remain the property of STOBER, and STOBER shall have the exclusive right to possession thereof. STOBER shall maintain such tools and equipment in good working order.

16. REGULATORY LAWS AND STANDARDS. STOBER makes no representation that its products conform to state or local laws, ordinances, regulations, codes or standards except as may be otherwise agreed to in writing by STOBER.

17. SIZES AND WEIGHTS. STOBER's products are made only in the sizes and to the specifications set forth in its catalogs and other literature. If any alteration is requested, such altered product will be treated as a made-to-order item. STOBER assumes no responsibility for typographical errors which may appear in its catalogs or literature, and cannot accept alteration charges caused by such errors. Since weights shown in STOBER's catalogs are approximate, they cannot be used in determining freight allowances set forth in its catalogs and other literature. Freight allowances will be determined at the time of shipment and shall be based on actual shipping weight.

18. SYSTEM DESIGN. Responsibility for system design to ensure proper use and application of STOBER's products within their published specifications and ratings rests solely with the Customer. This includes, but is not limited to, an analysis of loads created by torsional vibrations within the entire system, regardless of how induced.





ServoFit Modular System - SMS Gearheads



STOBER Drives Inc.
Maysville, Kentucky



MGS Speed Reducers

STÖBER Antriebstechnik
Pforzheim, Germany



SPG - ServoFit Precision Planetary Gearheads

STOBER Drives, Inc.

1781 Downing Drive, Maysville KY 41056

Phone: 606 759-5090, FAX: 606 759-5045, Toll Free: 800 711-3588

Web: www.stober.com, E-mail: sales@stober.com

ComTrac™, MGS™, Stober™, and ServoFit™ are registered trademarks of STOBER Drives, Inc.
TD, Copyright August 2012, Printed in U.S.A.

